

4-5

Go Go Elite Traveller® 2 Platinum / Victory® Platinum

6-7

Go Go Elite Traveller® 2

8-9

Pursuit 2

12-13

Zero Turn 10 / i-Go™

14-15

Go Go® Carbon / Go Go Elite Traveller®

16-17

Go Go® Sport / Go Go® Endurance Li

18-19

Go Go® Ultra X / Maxima

20-21

Revo® 2.0 / Victory® LX Sport

22-23

Victory® 10 / Victory® 10.2

24 Victory® 9



MY PRIDE SCOOTER HAS BEEN A LIFESAVER FOR ME. I COULD NOT DO LIFE WITHOUT IT.

— Etta G., White Plains, NY



Go Go Elite Traveller® 2 Platinum

With premium features galore, the Go Go Elite Traveller® 2 Platinum is a next-generation mobility solution. EZ Turn technology, Charge 360 magnetic charging, feather-touch disassembly, a convenient adjustable tiller mechanism, and much more define this luxurious, high-performing travel scooter that's made in the U.S.A.



Up To

B

Miles Per Charge at 220 lbs.

37 Turning Radius

Up To

L23mph

Maximum Speed

BOOIDS.

Weight Capacity



Up To 15.5 Miles Per Charge

45.5" **Turning Radius**

Up To

6mph

Maximum Speed

400lbs. Weight Capacity





Victory® Platinum

Proudly assembled in the U.S., the Victory® Platinum 4-wheel scooter offers a premium mobility experience. Patented EZ Turn technology helps you navigate tight spaces with 3-wheel precision. Exclusive Charge360 technology keeps you powered up with magnetic charging. With full front and rear suspension, take on uneven terrain with confidence.

FDA Class II Medical Device





Go Go Elite Traveller® 2

No four-wheel scooter can turn like the 4-wheel Go Go Elite Traveller® 2. Thanks to Pride's patented, intelligent-turning EZ Turn Technology, it boasts the tightest turning radius of any available 4-wheel scooter at just 37", which means you have 3-wheel scooter agility without compromising 4-wheel scooter stability.

GOOGO ELITE TRAVELLER® 2



Up To

IB.

Miles Per Charge
with 18Ah battery at 200 lbs.

37"
Turning Radius

Up To **4.2mph**Maximum Speed

300lbs. Weight Capacity





PX4

The PX4 features an impressive 500-lb. weight capacity, a top speed of 9.3 mph, water-resistant user interface, enhanced lighting package, and a remarkable 23.4 mile battery range.

The ignition system also offers an extra layer of security with its innovative NFC technology. Simply tap or place the NFC key fob near the receiver to start the scooter.



Miles per Charge

82.3

Turning Radius

Up To

Seed

Waximum Speed

500lbs.

Weight Capacity





Pursuit 2

Built to thrill and designed to go the distance, the Pursuit 2 never backs down from an off-road detour or long-distance excursion. With a fast top cruising speed of 9.3 mph and the ability to make it 40 miles on a single charge, this agile unit offers swift, efficient transport and endurance you can count on.

You were born to roam. The Pursuit 2 was built to ride.

PURSUIT²



69.3"

9.3mph

* Requires dual lithium battery upgrade







ZERO TurniO

Up To

Classification

Miles Per Charge at 200 lbs.


H3"
Turning Radius

Up To

7.3mph

Maximum Speed

Weight Capacity



The Zero Turn 10 can traverse the most beautiful, out-of-reach places and move seamlessly through doors and hallways in your home. This scooter combines powerful dual motors and two-wheel drive with revolutionary turning technology. Let the Zero Turn 10 carry you to places unknown.





Up To

Signature

Wiles Per Charge at 220 lbs.

Turning Radius

Up To

Hmph

Maximum Speed

2751bs.
Weight Capacity



i-Go™

The i-Go™ Folding Scooter supports you when you refuse to compromise. So, when you're dreaming of a cruise vacation, know that i-Go™ comes with the all-day power, speed and versatility to take you there and back again. When disassembled, the heaviest piece weighs less than 32 lbs. and has a height of less than 12" for easy storage.

Non-Medical Device



Go Go® Carbon

Harnessing the power of its full carbon fiber frame, the Go Go® Carbon offers exceptional portability in a fourwheel scooter. It weighs just **35 pounds** without its lithium battery, folds down in seconds for convenient transport and storage, and can be towed like luggage through airports and other environments.



Up To

Miles Per Charge

53"
Turning Radius

Up To

Imph

Maximum Speed

BOOIDS.

Weight Capacity





Up To

S

Miles Per Charge

Turning Radius

Up To

Up To

Maximum Speed

BOOLS.
Weight Capacity



Go Go Elite Traveller®

Every day is a new adventure with the Go Go Elite Traveller®, an exceptionally stable and maneuverable travel scooter.

With easy disassembly and a convenient storage basket, the Go Go Elite Traveller keeps up with your active life!





Up To Miles Per Charge

Turning Radius

4.7mph Maximum Speed

Up To

325lbs. Weight Capacity



It's time to make your mark on this world! The Go Go® Sport offers simple disassembly and an ergonomic delta tiller, perfect for one-handed operation. Enjoy the versatility of this sporty scooter, as well as bright LED lighting.



FDA Class II Medical Device¹

Also available in 3-wheel (EZ Turn only available on 4-wheel). Please see back of catalog for specifications.



Up To 14.4 Miles Per Charge (16AH* MAXX Battery Pack)

48.25" Turning Radius

4.2mph Maximum Speed

325lbs. Weight Capacity

*16 AH battery pack does not meet airline requirements.



Go Go® Endurance Li

With the Go Go® Endurance Li, traveling has never been easier! This 4-wheel scooter has everything you need for a safe and convenient trip. With the standard 8AH airlinecompliant lithium battery pack, the Go Go Endurance is perfect for air travel. Feathertouch disassembly provides the portability you need.



Go Go® Ultra X

Enjoy worry-free travel with the Go Go® Ultra X, an ultracompact scooter that is simple to disassemble. Ride in comfort and style with the foldable swivel seat and keep your personal items handy with the front basket.





Up To 19.5 Miles Per Charge

53" **Turning Radius**

Up To **5.8**mph Maximum Speed

500lbs. Weight Capacity

MAXIMA



Maxima

Experience the comfort of a new high-back, depth adjustable limited recline seat that swivels for easier access. The Maxima scooter comes standard with front and side bumpers, a USB charger and full LED lighting!

Also available in 3-wheel. Please see back of catalog for specifications.



REVO 2.0

Revo® 2.0

Robustly rugged meets brilliant convenience. With the Revo® 2.0, there is nothing you can't handle! This tough and dependable scooter has powerful suspension for a smooth ride, yet easily disassembles for full portability.



Up To **78**Miles Per Charge at 200 lbs.

52 Turning Radius

Up To

Seed

Maximum Speed

ЧООIbs. Weight Capacity

FDA Class II Medical Device¹

Also available in 3-wheel. Please see back of catalog for specifications.



VIETORY LX SPORT

Up To 19.7 Miles Per Charge at 200 lbs.

61.25" **Turning Radius**

Up To 8.6mph Maximum Speed

400lbs. Weight Capacity



Victory® LX Sport

You're active and always on the go. You need a scooter that is up to the task! Appeal to your sporty side with the Victory® LX Sport. Enjoy premium suspension, bright lighting and other sophisticated features, all in one sporty package.







Up To 15.5 Miles Per Charge

24" Turning Radius

5.3mph Maximum Speed

Up To

HOOIbs. Weight Capacity

Victory® 10

Versatility knows no bounds with the Victory® 10. Enjoy simple disassembly with one hand and drive up to 16 miles on a single charge. You won't miss a beat with this scooter, which includes a bright LED headlight. Anything is possible with the Victory 10!



FDA Class II Medical Device¹

Also available in 3-wheel (EZ Turn only available on 4-wheel). Please see back of catalog for specifications.





45" **Turning Radius**

Up To 5.2mph Maximum Speed

400lbs. Weight Capacity



Victory® 10.2

Embrace your potential! The Victory® 10.2 is fully loaded with style and advanced features, including frosted LED headlights and an integrated storage space with cup holder. Drive at speeds up to 5.2 mph and see what life has in store for you!

ONLY available in 3-wheel. Please see back of catalog for specifications.



VICTORY"/9/

Victory® 9

Sophisticated and stylish, the Victory® 9 is everything you could want in a scooter. The delta tiller lets you operate the scooter with a single hand. Enjoy easy disassembly and plenty of lighting with the LED headlight.



Up To

Miles Per Charge

51.5

Up To

Samph

Maximum Speed

300lbs. Weight Capacity

FDA Class II Medical Device¹

Also available in 3-wheel. Please see back of catalog for specifications.



2B. 10. 13. 14. 15. 16. 17.

1. Cane Clip Attachment | 2A. Pride® Cup Holder | 2B. Cup Holder | 3. Under Seat Storage | 4. Single or Double Cane Holder | 5. XLR USB CHarger | 6. Rear Basket | 7. Oxygen Holder | 8. New Cell Phone Holder | 9. Wishbone Crutch Holder | 10. Lap Belt 11. Saddlebag | 12. Walker Holder | 13. Rearview Mirror | 14. Weather Cover | 15. Military Patches | 16. Safety Flag | 17. Storage Pod

Note: Not all accessories are available for all products. Please speak with your Provider for details and availability.

| MODEL NAME / NUMBER | VICTORY® PLATINUM SC710PLA | GO GO ELITE TRAVELLER® 2 PLATINUM SC442EMS | GO GO® CARBON SC25 | GO GO ELITE TRAVELLER® 2 SC442E (4W) | PX4 SC134 |
|-------------------------------|---|--|--|--|--|
| WEIGHT CAPACITY | 400 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 500 lbs. |
| MAXIMUM SPEED ² | Up to 6 mph | Up to 4.23 mph | Up to 3.7 mph | Up to 4.23 mph | Up to 9.2 mph |
| GROUND CLEARANCE 3,8,9 | 2.75" at motor & transaxle | 1.34" at motor 3.15" at mid-deck | 1.5" at motor | 1.34" at motor, 3.15" at mid-deck | 3.5" at motor frame, 4.4" at mid-frame |
| TURNING RADIUS 3 | 45.5" | 37" | 53" | 37" | 82.3" |
| LENGTH/ WIDTH 3,7 | 47" / 24" | 39.37" / 19.45" | 40.3" / 17.5" | 39.37" / 19.45" | 56" / 27-27.8" |
| SEAT-TO-GROUND HEIGHT | 23.5"-25" | 18.25"-20.25" | 21.75" | 18.25"-20.25" | 24.17-25.29" |
| SEAT-TO-DECK HEIGHT | 17.5"-19" | 16.38"-17.83" | 16.14" | 16.38"-17.83" | 16.54-18.39" |
| FRONT WHEELS (TIRES) | 3.5" x 10.4" solid | 2" x 7" solid | 7" solid | 2" x 7" solid | 13" pneumatic |
| REAR WHEELS (TIRES) | 3.5" x 11" solid | 2.5" x 8" solid | 8" solid | 2.5" x 8" solid | 13" pneumatic |
| SUSPENSION | Front and Rear Suspension | N/A | N/A | N/A | Front & Rear |
| RANGE PER CHARGE ⁵ | Up to 15.5 miles at 400 lbs. | 12 Ah Battery Pack: Up to 6.6 miles at 300 lbs.; Up to 8.8 miles at 220 lbs. 18 Ah Battery Pack: Up to 10.4 miles at 300 lbs.; Up to 13.8 miles at 220 lbs. | Up to 10 miles | 12 Ah Battery Pack: Up to 6.6 miles at 300 lbs.; Up to 8.8 miles at 220 lbs. 18 Ah Battery Pack: Up to 10.4 miles at 300 lbs.; Up to 13.8 miles at 220 lbs. | Up to 23.4 miles (220 lbs.) Up to 14 miles at (500 lbs.) |
| HEAVIEST PIECE ³ | 67 lbs. (front section) | 39 lbs. (front section) | 35 lbs. (unit does not disassemble) | 35 lbs. (front section) | 201.2 lbs. (base) |
| STANDARD SEATING | Type: Compact, folding Weight: 30.4 lbs. Material: Black Vinyl Dimensions: 18" (W) x 17" (D) | Type: Mesh Back Weight: 23 lbs. Material: Black Vinyl Dimensions: 17" (W) x 17" (D) | Type: Compact, folding Material: Molded plastic Dimensions: 14" (W) x 11.4" (D) | Type: Mesh Back Weight: 23 lbs. Material: Black Vinyl Dimensions: 17" (W) x 17" (D) | Limited Recline High Back Dimensions: 18" (W) x 18" (D) |
| BATTERIES 4,13 | (Two) 12-volt, sealed lead-acid, non-spillable deep cycle | (Two) 12-volt, sealed lead-acid, non-spillable deep cycle | 24V, 12Ah lithium battery ¹³ | (Two) 12-volt, sealed lead-acid, non-spillable deep-cycle | (2) 12V 75Ah (SLA/AGM) |
| BATTERY WEIGHT 5,6 | 21.6 lbs. each | 12 Ah: 19.5 lbs. (standard) 18 Ah: 29.6 lbs. | 4 lbs. | 12 Ah: 19.5 lbs. (standard) 18 Ah: 29.6 lbs. | 48.8 lbs. each |
| BATTERY CHARGER | 3.5 amp magnetic charger | Off-board, 2A | 24V, 2A | Off-board, 2A | Off-board, 8A |
| HCPCS CODES | K0899* | K0899* | K0800 (Group 1, Standard) | K0800 (Group 1, Standard) | K0899* |
| WARRANTY | Lifetime Limited on Frame; 2-year limited on electronics; 2-year limited on drivetrain | Lifetime limited on frame; 2-year limited on Electronics; 2-year limited on Drivetrain | Frame: lifetime limited Drivetrain: 1-year Electronics: 1-year Battery: 1-year | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-month limited | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-month limited |

| MODEL NAME / NUMBER | PURSUIT 2 SC7132 | ZERO TURN 10 S710ZT | i-GO™ SC20 | GO GO ELITE TRAVELLER® SC40E (3W) | GO GO® ENDURANCE LI S54LXLIT |
|-------------------------------|---|--|---|--|---|
| WEIGHT CAPACITY | 400 lbs. | 400 lbs. | 275 lbs. | 300 lbs. | 325 lbs. |
| MAXIMUM SPEED ² | Up to 9.3 mph | Up to 7.3 mph | Up to 4 mph | Up to 4 mph | Up to 4.2 mph |
| GROUND CLEARANCE 3.8,9 | 3.78" at transaxle, 4.6" at mid-frame | 2" at motor 3" at mid-frame | 4.2" at mid-frame | 1.38" at motor, 0.75" at anti-tip, 2.25" at mid frame | 1.5" at motor 3.23" at deck |
| TURNING RADIUS ³ | 69.3" | 43" | 45.9" | 33" | 48.25" |
| LENGTH / WIDTH 3,7 | 57.5" / 29.7" | 48" / 24.25" | 44"/ 20.3" | 37" | 42"/20.5" |
| SEAT-TO-GROUND HEIGHT | 28.74" | 23.25" - 24.75" | 22.25" | 18.25"-20.25" | 21.25"-22.75" |
| SEAT-TO-DECK HEIGHT | 176.9-20.9" | 17.75"-19.25" | 14.6" | 15.75"-17.25" | 16.25"-17.75" |
| FRONT WHEELS (TIRES) | 13" pneumatic | 9" solid | 8" hub motor | 2" x 8" solid | 2" x 8" solid |
| REAR WHEELS (TIRES) | 13" pneumatic | 10.75" solid | 9" perforated | 2.5" x 8" solid | 2" x 8" solid |
| SUSPENSION | Front & Rear | Front and rear (CTS) | N/A | N/A | Front and rear (CTS) |
| RANGE PER CHARGE ⁵ | Single Battery: Up to 17.4 miles (220 lbs.) Up to 13.8 miles (400 lbs.) Dual Battery: Up to 34.8 miles (220 lbs.) Up to 30.9 miles (350 lbs.) | Up to 15.9 miles (at 400 lbs.) Up to 21.2 miles (at 200 lbs.) | Up to 7 miles at 275 lbs. Up to 9.3 miles at 220 lbs. | Up to 7.25 miles (12 AH) Up to 10.5 miles (18 AH) | 8 AH: Up to 7.2 miles 16 AH: Up to 14.4 miles at 200 lbs. |
| HEAVIEST PIECE ³ | 163 lbs. (base) | 75 lbs. (front section) | 32.8 lbs. (rear base with seat back) | 29.5 lbs. (front section) | 40.75 lbs. (front section) |
| STANDARD SEATING | Limited Recline High Back with Sliders Dimensions: 18" (W) x 18" (D) | Type: Foldable, deluxe contour Weight: 34 lbs. or Foldable, compact Weight: 30 lbs. Material: Black vinyl Dimensions: 18" (W) x 17" (D) | Type: Compact, folding (back is removable) Material: Molded plastic Dimensions: 16" x 16" | Type: Compact, foldable Weight: 23 lbs. Material: Black vinyl Dimensions: Width: 17", Depth: 17" | Type: Compact, mesh, foldable Weight: 23 lbs. Material: Black vinyl Dimensions: 17"x17", 20"x18" |
| BATTERIES 4,13 | (1) or (2) 24V, 50Ah Lithium-ion | (2) 40 AH | (1) 25.2V 9.6 Ah Rechargeable Lithium-Ion | (2) 12 AH (standard) or (2) 18 AH (optional) | 8 AH ¹³ lithium ion battery pack or 16 AH ¹² lithium ion battery pack (optional) |
| BATTERY WEIGHT 5.6 | 23.8 lbs. each | 30.25 lbs. each | 4.8 lbs. | 9 lbs. each (12 AH), 20 lbs. per battery pack 14 lbs. each (18 AH), 29.5 lbs. per battery pack | 8 lbs. (8 AH); 12 lbs. (16 AH) |
| BATTERY CHARGER | Off-board, 8A | Off-board, 3.5A | Off-board, 3.5 amp (lithium-ion) | Off-board, 2 amp | Off-board, 3.5 amp (lithium ion) ¹³ |
| HCPCS CODES | K0899* | K0899* | N/M (non-medical) | K0800 (Group 1, Standard) | K0899* |
| WARRANTY | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 3-year limited | Frame: Lifetime limited Drive motors: 2-year limited Electronics: 2-year limited Batteries: 6-month limited | Frame: 3 years Electronics: 2 years (does not include charger) 1 year on motor, battery and charger | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-month limited | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 2-year limited |

| MODEL NAME / NUMBER | GO GO® SPORT S73 (3W), S74 (4W) | GO GO® ULTRA X¹ S39 (3W), S49 (4W) | REVO® 2.0¹ S66 (3W), S67 (4W) | VICTORY® LX SPORT¹ S710LXW |
|-----------------------------------|--|--|---|--|
| WEIGHT CAPACITY | 325 lbs. | 300 lbs. | 400 lbs. | 400 lbs. |
| MAXIMUM SPEED ² | Up to 4.7 mph | 3W: Up to 4.3 mph 4W: Up to 4.1 mph | Up to 5.2 mph | Up to 8.6 mph at 200 lbs. |
| GROUND CLEARANCE ^{3,8,9} | 1.5" at motor, 0.75" at anti-tip | 1.25" at motor 3.23" at deck | 3W: 3.25" at side deck 4W: 3.5" at side deck | 2.2" at motor 3.15" at mid-frame |
| TURNING RADIUS ³ | 3W: 36" 4W: 41.5" | 3W: 36.5" 4W: 52.25" | 3W: 40" 4W: 52" | 61.25" |
| LENGTH / WIDTH ^{3,7} | 3W: 42" 4W: 43" / 21.25" | 40.25"/ 19.25" | 3W: 46" 4W: 47" / 20.75" | 47" / 25.5" |
| SEAT-TO-GROUND HEIGHT | 20.5" - 22" | 21.5 -23" | 22"- 23.5" | 23" - 25" |
| SEAT-TO-DECK HEIGHT | 17" - 18" | 16.5"-18" | 15"-16.5" | 16.5" -18.5" |
| FRONT WHEELS (TIRES) | 3W: 3" x 8" (4W: 3" x 9") solid | 2" x 8" solid | 3W: 3" x 8" solid 4W: 3" x 9" solid | 3.5" x 10" solid |
| REAR WHEELS (TIRES) | 3" x 9" solid | 2.5" x 8" solid | 3" x 9" solid | 3.5" x 10" solid |
| SUSPENSION | N/A | N/A | Front and rear (CTS) | Front and rear (CTS) |
| RANGE PER CHARGE⁵ | 3W: Up to 12.75 miles 4W: Up to 12 miles | 3W: Up to 8 miles (200 lbs.) 3W: Up to 6.2 miles (300 lbs.) 4W: Up to 8.9 miles (200 lbs.) 4W: Up to 6.6 miles (300 lbs.) | 3-Wheel: Up to 17.4 miles (at 200 lbs.) Up to 12.8 miles (at 400 lbs.) 4-Wheel: Up to 17.8 miles (200 lbs.) Up to 14.8 miles (at 400 lbs.) | Up to 19.7 miles (at 200 lbs.) Up to 13 miles (at 400 lbs.) |
| HEAVIEST PIECE ³ | 3W: 35.75 lbs.(front section) 4W: 44 lbs. (front section) | 3W: 29.5 lbs. (front section) 4W: 34.5 lbs. (front section) | 3W: 48 lbs. (rear section) 4W: 57 lbs. (front section) | 77 lbs. (front section) |
| STANDARD SEATING | Type: Compact, foldable Weight: 23 lbs. Material: Black vinyl Dimensions: Width: 17", Depth: 17" | Type: Compact, foldable Weight: 23 lbs. Material: Black vinyl Dimensions: 17" (W) x 17" (D) | Type: Compact, foldable Material: Black vinyl Dimensions: 20" (W) x 18" (D) | Type: Limited reclining high-back Weight: 43 lbs. Material: Black vinyl Dimensions: 18" (W) x 18" (D) |
| BATTERIES⁴ | (2) 18 AH | (2) 12 AH | (2) U-1 | (2) 50 AH |
| BATTERY WEIGHT ^{5,6} | 14 lbs. each 29.5 lbs. per battery pack | 9 lbs. each 20 lbs. per battery pack | 25 lbs. each | 30.2 lbs. each |
| BATTERY CHARGER | Off-board, 2 amp | Off-board, 2 amp | Off-board, 3.5-amp | Off-board, 5 amp |
| HCPCS CODES | K0801 (Group 1, Heavy Duty) | K0800 (Group 1, Standard) | K0899* | K0899* |
| WARRANTY | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-month limited | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-month limited | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months |

| MODEL NAME / NUMBER | VICTORY® 10.21 S6102 | VICTORY® 10 ¹ SC610 (3W), SC710 (4W) | VICTORY® 9¹ SC609 (3W), SC709 (4W) | MAXIMA ¹ SC901 (3W), SC941 (4W) |
|--------------------------------------|--|--|--|---|
| WEIGHT CAPACITY | 400 lbs. | 400 lbs. | 300 lbs. | 500 lbs. |
| MAXIMUM SPEED ² | Up to 5.2 mph | Up to 5.3 mph | Up to 5.3 mph | Up to 5.8 mph |
| GROUND CLEARANCE ^{3,8,9} | 2.4" at transaxle, 2.1" at anti-tip, 3" at side deck | 3W: 2.2" at motor, 1.26" at anti-tip 4W: 2" at motor, 1.5" at anti-tip | 3W: 1.8" at transaxle, 1.4" at anti-tip 4W: 1.8" at transaxle, 1.4" at anti-tip | 3W: 2.5" at motor, 3" at mid-frame 4W: 2.25" at motor |
| TURNING RADIUS ³ | 42" | 3W: 42" 4W: 24" | 3W: 40.25" 4W: 51.5" | 3W: 49" 4W: 53" |
| LENGTH/ WIDTH ^{3,7} | 45" | 3W: 45.25" 4W: 47" / 22.5" | 3W: 43.5" 4W: 45.5" / 22.5" | 3W: 47.5" 4W: 47.5" / 27" |
| SEAT-TO-GROUND HEIGHT | 22" – 24" | 23.5"-25" | 22.5"-24" | 22.1" - 24.1" 22.32"-28.57" (with power elevating seat) |
| SEAT-TO-DECK HEIGHT | 15.25" – 17.25" | 17.5"-19" | 17.25"-18.75" | 17.13" - 19.13" 17.36"- 23.61" (with power elevating seat) |
| FRONT WHEELS (TIRES) | 3.5" x 10" solid | 3.5" x 10" solid | 3W: 3" x 8" solid 4W: 3" x 9" solid | 3W: 10.5"x 3.6" solid 4W: 10"x 3.6" solid |
| REAR WHEELS (TIRES) | 3.5" x 10" solid | 3.5" x 10" solid | 3" x 9" solid | 10.75"x 3.6" solid |
| SUSPENSION | N/A | N/A | N/A | N/A |
| RANGE PER CHARGE ⁵ | Up to 11 miles (U-1) Up to 13 miles (40 AH) | Up to 15.5 miles | Up to 13 miles | 3W: Up to 19.8 miles 4W: Up to 19.5 miles |
| HEAVIEST PIECE ³ | 3W: 56.5 lbs. (front section) | 3W: 54 lbs. (front section) 4W: 63 lbs. (front section) | 3W: 48.5 lbs. (front section) 4W: 59 lbs. (front section) | N/A (unit does not disassemble) |
| STANDARD SEATING | Type: Compact, foldable Weight: 28.5 lbs. Material: Black vinyl Dimensions: Width: 18", Depth: 17" | Type: Compact, foldable Weight: 28 lbs. Material: Black vinyl Dimensions: Width: 18", Depth: 17" | Type: Compact, foldable Weight: 28 lbs. Material: Black vinyl Dimensions: Width: 18", Depth: 17" | Type: Depth-adjustable, limited recline high back Weight: 53.2 lbs. Material: Black vinyl Dimensions: 22" x 18"-20" |
| BATTERIES ⁴ | (2) U-1 (standard) (2) 40 AH (optional) | (2) U-1 (standard) (2) 40 AH (optional) | (2) U-1 | (2) GEL, 58AH, NF-22 |
| BATTERY WEIGHT ^{5,6} | 24 lbs. each (standard) 32 lbs. each (optional) | 24.5 lbs. each (standard) 32.5 lbs. each (optional) | 24 lbs. each | 36.5 lbs. each |
| BATTERY CHARGER | Off-board, 3.5 amp (U-1) Off-board, 5 amp (40 AH) | Off-board, 3.5 amp (U-1) Off-board, 5 amp (40 AH) | Off-board, 3.5 amp | Off-board, 5 amp |
| HCPCS CODES | K0801 (Group 1, Heavy Duty) | K0801 (Group 1, Heavy Duty) | K0800 (Group 1, Standard) | 3W: K0802 (Group 1; Very Heavy Duty) 4W: K0808 (Group 2; Very Heavy Duty) |
| WARRANTY | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months | Frame: Lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Batteries: 6-months |



(US) 800-800-8586 | (CAN) 888-570-1113 | pridemobility.com | 🚯 🕲 🖸 🕡

- 1. Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition.
 This specification can be subject to a variance of (+ or -) 10%.
- 3. Varies with user weight, terrain type, battery amp- hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 4. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or 3%.
- 5. Deep cycle (AGM or gel cell type recommended).
- 6. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 7. Battery weight may vary based on manufacturer.
- 8. Width of base (not including seat).
- 9. Does not account for anti-tip clearance.
- 10. At midframe.
- 11. Product is available exclusively to Authorized Pride Brick & Mortar Providers. No internet sales are permitted. Available in store only. Other conditions apply.
- 12. Does not meet airline requirements.
- 13. Transport of this item on commercial aircraft is subject to federal regulations and airline policy. Please consult your airline prior to your flight to ensure your item and its lithium ion battery are permitted.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

N/M: This product is not a medical device and is not intended to assist, treat, diagnose, or alleviate any medical condition or disability.

*K0899 – power mobility device, not coded by DME PDAC.

**Not all accessories are available for all products. Please speak with your Provider for details and availability.

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

