RESULTS EVERY TIME WITH THE AITCHISON® AIRPRO SERIES





enquire now from your authorised dealer

AITCHISON


QUALITY PRODUCTS BUILT TO LAST

www.aitchisonagri.com

NEW ZEALAND

41 Kelvin Grove Road, P.O. Box 5056, Palmerston North New Zealand. Tel: +64 6 357 9323 Fax: +64 6 354 3155 AIRPRO

AITCHISON



A PRODUCT OF NEW ZEALAND

AITCHISON

Combining three proven technologies - a European Seed and Fertiliser air distribution system, over 5 decades of proven Aitchison® seeding experience and Aitchison's Electronic computerised drive and monitoring system.

The 8000 Series Airpro zero tillage air seeder continues to build on the Aitchison legacy of soil preservation through environmentally sustainable zero tillage equipment. Aitchison seed drills are synonymous with building soil organic matter, and creating an optimal environment for trouble free seed germination, and the AirPro is no exception.

The AirPro utilises the well proven Aitchison inverted "T" boot mounted on the same coil spring as the hugely successful Seedmatic seed drill. Designed to cut through residual plant matter ahead of the inverted "T" boot, the disc coulter undercarriage assembly is standard equipment on all Airpros. And with up to 40 rows spaced at 150mm gaps and a 400mm stagger of seeding rows gives this drill superior residual matter clearance.

Floating three-piece chassis design creates great contour following abilities unmatched by any other large drill on the market today. With a sowing width of up to 6 metres and a transport width of 2.9 metres this machine can be moved very easily.

Airpros are equipped with a proven European air distribution system for consistent and accurate seed placement. Independent hydraulic fan drives ensure the right air pressure for seed or fertiliser, and the European Accord-style dispensing system is simple and sowing rates can be set very accurately, ideal for small seeds.

With this versatile, larger coverage and higher capacity machine, you will be able to continue to sow the seeds of success the Aitchison zero-tillage way.

With the new Electronic drive system, calibration is a breeze and the application rate can be altered on the move. The monitor shows area covered, Kg's/ha, Load on the motors, Ground speed, Ha/hour, Low bin level, Fan RPM, Seed rate range, Alarms, Downloadable records of past jobs.

Job 1	nfe:	Res	sse Eng	inneri	ng LTD.	Alteh	isan		
Run	0	km	νħ	0	ha/h	1.473	ha	0	
ψ	Runr	aing	SEE	D				ø	
٠	50			0 Rai		kg/ħa	0 Shaft		
	kg/ha					ate		0	
50 100 Rate1 Rate2			0	1.77 ha		ha	Fan		
			1,11		1104	Enter			
0.597 to 9.553 km/h			Area				4		
ψ	Stop	ped	FER	т				ø	
	50			0			Т	0	
						kg/ha	5	Shaft	
	kg/h	kg/ha		Rate				0	
25 50			1.77		ha	Fan			
Rate1 Rat					. 1151		Enter		
0.597 to 9.553 km/h				Area				4	

AIRPRO 3, 4.8 & 6MTR

SPECIFICATIONS	AIRPRO 8124E	AIRPRO 8132E	AIRPRO 8140E			
No of Rows & Tines	24	32	40			
Sowing Width	3.0m	4.8m	6.0m			
Row Spacing	125mm (5")	mm (6")				
Overall Width - sowing (S) transport (T)	3.30m (S & T)	4.95m (S) / 2.9m (T)	6.15m (S) / 2.90m (T)			
Overall Height - sowing (S) transport (T)	2.5m (S) / 2.80m (T)	2.2m (S) / 3.53m (T)	2.20m (S) / 4.0m (T)			
Overall Length - sowing (S) transport (T)	5.12m (S & T)	8.15m (S) / 6.80m (T)	8.15m (S) / 6.80m (T)			
Weight empty	2150kg	3950kg	4400kg			
Fertiliser Box Capacity	700ltr	1500ltr				
Seed Box Capacity	700ltr	1000ltr				
Working Speed	6 - 15 km/hr					
Tractor HP (min)	100 hp	130 hp	140 hp			
Opener Stagger	500 mm	400 mm				
Aitchsion® Electronic Drive System	✓	✓	✓			
Coulter Disc Bar Assembly	✓	✓	✓			
Rear Rubber tyre rollers	Not Included	✓	✓			
Hiab Mount Point	Not Included	Optional (factory fitted)	Optional (factory fitted)			

SOW YOUR SEEDS IN ANY CONDITION WITH THE WORLD'S MOST VERSATILE RANGE OF AIR SEEDERS

