

ROTOFLO HAS BEEN USED FOR

Activated carbon	Granulated Sugar	Recycled plasterboard
Adipic Acid	Gypsum Powder	Rice bran concentrate
Air Filter Dust	Hydroxy Ethyl Cellulose (Calcium Hydroxide)	Salt
Aluminium Silicate	Hydrated Lime	Sand
Andracite	Kaolin - Anhydrous	Sewage Sludge Pellets
Artificial Gypsum	Kaolin - Hydrous	Silica - Powder
Astaxin	Lead Oxide	Silica - Precipitated
Barium Sulphate	Magnesium Oxide	Sodium Bi Carbonate
Bentonite	Magnesium Silicate	Sodium Carbonate (Soda Ash)
Blast-furnace Slag Powder	Magnesium Sulphate	Sodium Chloride
Boric Acid	Maize	Soya Bean Feed
Caster Sugar	Maize Starch	Spanish Gypsum
Calcium Carbonate	Marble Powder	Starch
Calumite	Microdol	Steatite
CEM11	Milled Biomass	Stucco Plaster
China Clay	Milled Coal	Super Absorbent Polymer (SAP)
Chocolate Crumb	Modified Corn Starch	Titanium Dioxide
Chromium Oxide	Oat bran Concentrate	Urea Prill
Diuron	Opacilite	Wheat fibre
Dolomite	Ordinary Portland Cement	Wheat Flour
Dried Sewage Granulate Pellets	Pulverised Activated Carbon	Corn Meal
Ferrous Sulphate Heptahydrate	Pulverised Fuel Ash	Wood flour
Ferrous Sulphate Monohydrate	Polyelectrolyte Polymer	Zeocros
Fillite	Potato Starch	Zeodent
Flour	Precipitated Calcium Carbonate	Zeolex
Fumed Silica	PVC resin	Zinc Oxide
Glass	Quicklime (Calcium Oxide)	Zinc Phosphate

TO FIND OUT MORE ABOUT ROTOFLO SILO DISCHARGER, PLEASE CONTACT US OR VISIT OUR WEBSITE AT:

www.severfield.com/products/material-handling/rotoflo

Severfield Modular Solutions Limited
Severs House
Dalton Airfield Industrial Estate
Dalton, Thirsk
North Yorkshire
YO7 3JN
United Kingdom

Telephone
Steve Kennedy: +44 (0) 7817 538523
Rocco Mastrodonardo: +44 (0) 7803625361
Office: +44 (0) 1845 577896

Email
rotoflo@severfield.com

 www.severfield.com

 Severfield
Rotoflo
Silo Discharger



SCAN THE QR
CODE FOR OUR
ROTOFLO
WEBPAGE

 Severfield
Rotoflo
Silo Discharger



**ROTOFLO SILO
DISCHARGE UNITS**
VERSATILE, CONTROLLED, VIBRATION-FREE

INTRODUCTION

Severfield Modular Solutions Limited is part of Severfield plc - the UK's market-leading structural steel company. Its success is built on its commitment to delivering outstanding customer service, being responsive, dependable, and flexible, ensuring it meets all your project needs on time and in full.



SCAN THE QR CODE
FOR THE ROTOFLO
ANIMATION



A REVOLUTION IN MATERIALS HANDLING

Since its inception at Portasil, the Rotoflo Silo Discharger has been continuously developed to ensure it meets the most demanding of applications. As a result, Rotoflo remains at the forefront of material handling technology.

We purchased the patent and Intellectual Property for Rotoflo from Portasil in 2020, and it is now our role to produce and develop these units for our global customer base.

By working closely with our customers, we ensure we understand their specific needs and requirements, helping increase manufacturing efficiency, increase productivity, reduce downtime, and reduce maintenance costs.

With an impressive track record across multiple industry sectors, we aim to consolidate and build on Rotoflo's reputation, making it the universal first choice for silo discharging applications.

UNIQUE VIBRATION-FREE SYSTEM DESIGN

The Rotoflo discharger provides a highly efficient, reliable, and controlled flow of even the most challenging materials, without incurring the complications, costs, or side effects associated with vibration or aeration. Rotoflo represents a cost-effective solution to the common challenges of discharging difficult materials from storage vessels, such as bridging, rat-holing, and stagnant zones.

BUILT-IN VERSATILITY

The Rotoflo is available in a range of sizes and materials construction to meet your specific application and feed rates. These versatile units can be manufactured from mild steel, stainless steel, or mild steel combined with a stainless-steel cladding. We can also provide food-safe finishes and ATEX-rated equipment to suit your requirements.

Rotoflo can be mounted in new-build and retro-fit silo applications and achieves complete, controlled, and pulse-free discharge on vessels ranging from 20m³ to 600m³ storage capacity.

Rotoflo units can be supplied with multiple outlets for simultaneous or alternate material feeding of up to four discharge points. There are also alternative drive options available, including dual and variable speed for weighing and process control applications.

LOW-PROFILE, EASY MAINTENANCE DESIGN


All maintainable items can be easily serviced without the need to empty the storage vessel. This includes the externally mounted gearbox. The low-profile design makes the Rotoflo discharger an ideal solution for plants and operations where headroom is at a premium.

THE COST-EFFECTIVE SOLUTION

- Reduces capex
- Increasing live storage volume in your vessels
- Multiple discharging points from the same silo
- Reducing the need for downstream equipment
- Lowering power consumption
- Allowing maintenance access, without the need to empty your vessel

TECHNICAL DATA

The Rotoflo offers a range of options tailored to suit various industrial needs. Available in four sizes the Rotoflo caters to a broad spectrum of silo capacities, spanning from 20m³ to 600m³. Each model of the Rotoflo is available in both carbon steel and stainless steel. This flexibility ensures compatibility with diverse operational environments and material handling requirements.



Rotoflo	A (mm)	B (mm)	C (mm)	Through-put*
LP 1200	1200	200	250	1.5 - 60m ³ /hr
LP 1500	1500	250	300	2.4 - 80m ³ /hr
LP 1800	1800	300	350	4.8 - 120 m ³ /hr
LP 2400	2400	350	450	8 - 160 m ³ /hr

*Low speed gear box option or frequency inverter can be used to achieve lower throughputs

ROTOFLO® BENEFITS

- Controlled discharge – consistent feeding over a wide range of throughputs.
- Multiple outlets – feeds up to four process streams from the same silo.
- Totally sealed and dust free – fixed, flanged connections with no flexible joints.
- First-In, First-Out discharge – can be achieved for better inventory control.
- Complete silo emptying – eliminates dead storage and increases effective storage capacity.
- Suitable for a diverse range of materials – from fine powders and particulates to granular products.
- Low power consumption – high torque, low speed rotation requires (typically) 0.2kW per hour, per tonne discharged.
- Easy to retrofit – to existing silos and vessels.
- No vibration – avoids product compaction and eliminates vessel fatigue failures.
- ATEX certified – units are available certified ATEX 1D for use in potentially explosive atmospheres.
- Robust construction – pressure shock resistant design, ideal with explosive materials.
- Positive shut-off – reversing the drive closes the scoops, enabling positive shut off with the silo full.
- Minimal maintenance requirements – increased productivity and lower running costs.
- Industry leading reliability – 20+ years of trouble-free operation.