
Brighten Every Moment

LumiFit Series

Outdoor





Front & Rear Maintenance



Energy Saving



Aluminum Profile

Robust and Stable Performance

• Stronger & Lighter Structure

Aluminum profile achieves a stronger and lighter structure and flatter splicing, further improved by open rear design

Higher Protection Level


Fully enclosed in an aluminum shell, with IP67 front protection and IP66 rear protection



Aluminum Profile Aluminum Shell

Excellent Heat Dissipation

- Capable of operating below 60°C without air conditioning
- PCB directly connected to aluminum bottom shell with thermal grease
- $\boldsymbol{\cdot}$ Enhanced heat dissipation through $\boldsymbol{\mathsf{numerous}}$ fins and open rear design



Versatile Cabinet Sizes

- Both **500 × 500 mm** and **500 × 1,000 mm** models available, with the same pixel pitch
- Seamlessly integrated to form a unified video wall



Easier Installation

- Supports **cordless and waterproof** connection
- Aviation plugs ensure easier installation

Application Scenarios







Vertical Billboard

Bus Stop Sign

Gas Station

Key Spec

	DS-D4239CD-1AAB	DS-D4248CD-1AAB	DS-D4239CF-1AAB	DS-D4248CF-1AAB
Pixel Structure	SMD Triad LED			
Pixel Pitch (mm)	3.91	4.81	3.91	4.81
Module Composition (W × H)	1×2	1×2	1 × 4	1 × 4
Module Structure	Aluminum Shell			
Cabinet Dimension (W × H × D, mm)	500 × 500 × 97 (19.69" × 19.69" × 3.82")		500 × 1,000 × 97 (19.69" × 39.37" × 3.82")	
Cabinet Resolution (W × H)	128×128	104 × 104	128×256	104 × 208
Cabinet Weight	9.12 Kg(20.11 lb)	9.12 Kg (20.11 lb)	17 Kg(37.48 lb)	17 Kg(37.48 lb)
Pixel Density (dots/m²)	65536	43264	65536	43264
Cabinet Material	Aluminum profile			
Maintenance Method	Front and back maintenance	Both front and rear maintenance	Front and back maintenance	Both front and rear maintenance
Protection Level	Front IP67 and rear IP66			
Brightness (nits)	4500-5000			
Viewing Angle	160°(H)/80°(V)			
Contrast Ratio	≥ 5000:1			
Peak Consumption (W/m²)	≤ 650			
Average Consumption (W/m²)	≤ 210			
Refresh Rate (Hz)	Up to 3840			













