

SLA MAX

READY TO START
MAXIMUM POWER

Ready to use, SLA MAX batteries (AGM technology) are **Factory Activated, completely spill-proof**, and require **no maintenance**. Specially developed to meet the **superior needs of big-engine bikes** offering **maximum performance, maximum reliability and extended life**.



FACTORY ACTIVATED

AGM (Absorbent Glass Mat) technology.



READY TO USE

Just plug & play.



NO MAINTENANCE

VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN

Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING

Very safe.



EXTREME VIBRATION RESISTANCE

Reinforced battery case.



MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE

20% higher than SLA CCA.




SUPERIOR CAPACITY

20% higher than SLA capacity.

MOUNTING ANGLES

HIGH INCLINATION
NON-SPILLABLE



COMPATIBLE CHARGERS

BS 10 Battery size up to 20Ah	BS 15 Battery size up to 30Ah
BS 30 Battery size up to 60Ah	BS 30 MAX Battery size up to 60Ah
BS 60 Battery size up to 120Ah	BK 20 Battery size up to 40Ah

DID YOU KNOW?

SLA MAX range is a perfect solution for ATV, UTV, SSV, watercraft & snowmobile too!

SLA MAX batteries are non-spillable, so they're safe to ship and e-commerce ready!

FOR HARLEY DAVIDSON - BGZ SERIES

Developed to fit Harley Davidson bikes, the SLA MAX BGZ series thus offer maximum performance to big-engine vehicles with demanding requirements and extensive electronic equipment.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL	REPLACEMENT - MOST POPULAR MODELS	
					L	W	H			SLA / SLA MAX	MF / DRY
BGZ16H	300931	16	16.8	240	150	88.5	145	+		BTX14H BTX14	BTX14-BS
BGZ16HL	300932	16	16.8	240	150	88.5	145	-		BTX14HL BTX14L	BTX14L-BS
BGZ20H	300938	20	21.1	360	176	89	157	+		BTX20H	BTX20-BS
BGZ20HL	300939	20	21.1	360	176	89	154	-		BTX20HL	BTX20L-BS BTX20HL-BS BB18L-A
BGZ32HL	300935	32	33.7	500	170	132	175	-		BIX30HL BIX30L	BIX30L-BS BB30L-B




BUILT-IN COPPER NUTS

Enhanced conductivity (up to 50% more than standard terminal) & improved max torque strength (up to 13N.m).



FRONT & TOP CONNECTIONS

Designed to facilitate the mounting on Heavy Duty motorcycles.



TALLER PLATES

For enhanced CCA & Capacity.

FOR BMW

Developed to fit BMW's latest bikes, these SLA MAX models are designed to offer maximum performance with increased capacity and high starting power.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BTX14H*	300887	14	14.7	220	150	87	145	+	
BTX16H*	300896	14	16	250	150	87	161	+	
51913	300860	21	22	275	186	82	171	-	

FOR POLARIS & INDIAN

Developed to fit Indian's latest bikes, SLA MAX BTX14AH provides increased power, extended life and maximum reliability.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BTX14AH*	300863	13	13.7	240	134	89	164	+	

* Models manufactured and designed according to OEM specifications

SLA MAX U1-500 GR26-620

READY TO START
MAXIMUM POWER

Ready to use, these SLA MAX batteries (AGM technology) are **Factory Activated**, **completely spill-proof**, and **maintenance-free**. Specially engineered for ATV and UTV applications, they deliver reliable starting power, exceptional vibration resistance, and long-lasting performance even in the toughest off-road conditions.



FACTORY ACTIVATED

AGM (Absorbent Glass Mat) technology.



READY TO USE

Just plug & play.



NO MAINTENANCE

VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN

Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING

Very safe.



EXTREME VIBRATION RESISTANCE

Reinforced battery case.



MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE

20% higher than SLA CCA.




SUPERIOR CAPACITY

20% higher than SLA capacity.

MOUNTING ANGLES

HIGH INCLINATION
NON-SPILLABLE



COMPATIBLE CHARGERS

BS 10 Battery size up to 20Ah	BS 15 Battery size up to 30Ah
BS 30 Battery size up to 60Ah	BS 30 MAX Battery size up to 60Ah
BS 60 Battery size up to 120Ah	BK 20 Battery size up to 40Ah

DID YOU KNOW?

Built to handle extreme terrain, mud, and weather, U1-500 and GR26-620 ensure maximum reliability and superior endurance.

FOR POLARIS, YAMAHA & KAWASAKI


Built with a reinforced casing and powerful starting capabilities, the U1-500 and GR26-620 deliver reliability and performance for latest ATVs, SSVs and UTVs.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
U1-500	300899	30	31.6	500	195	125	176		
GR26-620	300692	51	53	620	220	172	199		




REINFORCED CASING WITH GRID FRAMEWORK

For a maximum vibration
resistance.



8,8 MM TERMINALS*

specially designed for large
SSV/UTV screws.



TALLER PLATES

For enhanced CCA
& Capacity.

* U1-500 only



BATTERY RANGE OVERVIEW



DRY BATTERY

CONVENTIONAL



Entry-level bikers with standards requirement.

MF BATTERY

MAINTENANCE FREE



Entry-level bikers seeking easiness.

TECHNOLOGY

Flooded dry

AGM/VRLA

FACTORY ACTIVATED READY TO USE

—

—

NO ACID HANDLING

—

—

NO MAINTENANCE

—





NON-SPILLABLE

—

—

INCLINATION LEVEL



OEM APPROVED

—



SUITABLE FOR E-COMMERCE

COMPLIANT WITH EU REGULATION 2019/1148
(FOR THE SALE OF ACID FOR BATTERIES)

—

—

EASY TO SHIP

—

—

TRANSPORT TYPE



SLA
FACTORY ACTIVATED

READY TO START



Budget-conscious riders looking for performance and time-saving.

SLA
FACTORY ACTIVATED **MAX**

READY TO START
MAXIMUM POWER



Adventure riders with big engines seeking robust performance and durability.

LITHIUM
LiFePO4

INNOVATION FOR
HIGH PERFORMANCE



Demanding riders seeking for peak performance, lightweight and advanced technology.

LITHIUM
LiFePO4 **MAX**

INNOVATION FOR
MAXIMUM PERFORMANCE






Selective riders aiming to meet the latest standards of modern vehicles.

AGM/VRLA

AGM/VRLA

LiFePO4

LiFePO4



(1) Once activated | (2) According to ADR, IMDG & IATA regulations

UPGRADE CROSS REFERENCE CHART

DRY	MF	SLA	SLA MAX	LITHIUM
	BTZ5S/BTX4L-BS+	BTZ5S/BTX4L+		BSLi-02 ; BSLi-02 MAX
		BTZ6S/BTX5L		BSLi-02 ; BSLi-02 MAX
	BTZ7S-BS	BTZ7S		BSLi-02 ; BSLi-02 MAX
	BT7B-BS	BT7B-4		BSLi-03
		BTZ7V		BSLi-02 ; BSLi-02 MAX
		BTZ8V		BSLi-02 ; BSLi-02 MAX
	BT9B-BS	BT9B-4		BSLi-03
	BTZ10S-BS	BTZ10S		BSLi-04/06
	BTZ12S-BS	BTZ12S		BSLi-04/06 ; BSLi-09
	BT12B-BS	BT12B-4		BSLi-04/06
	BTZ14S-BS	BTZ14S		BSLi-04/06 ; BSLi-09
	BT14B-BS	BT14B-4		BSLi-04/06
51814 ; 51913			51913 MAX	BSLi-12
	BT12-10Z-BS	BT12-10Z		
	BT4B-BS	BT4B-5		
	BTR4A-BS	BTR4A-5		
	BTX4L-BS+/BTZ5S-BS	BTX4L+/BTZ5S		BSLi-02 ; BSLi-02 MAX
	BTX5L-BS	BTX5L/BTZ6S		BSLi-02 ; BSLi-02 MAX
		BTX6.5L		BSLi-02 ; BSLi-02 MAX
	BTX7L-BS	BTX7L		BSLi-02 ; BSLi-02 MAX
	BTX7A-BS	BTX7A		BSLi-03
	BTX9-BS	BTX9		BSLi-03
	BT12A-BS	BT12A		BSLi-04/06
	BTX12-BS	BTX12		BSLi-04/06
	BTX14-BS	BTX14	BTX14H MAX ; BGZ16H MAX	BSLi-04/06
	BTX14L-BS	BTX14L	BGZ16HL MAX	BSLi-08
BB14-A2 (12N14-4A) ; BB14-B2	BTX14AH-BS	BTX14AH/BB14-A2/B2	BTX14AH MAX	BSLi-04/06
BB14L-A2 (12N14-3A) ; BB14L-B2	BTX14AHL-BS	BTX14AHL/BB14L-A2/B2		BSLi-05
	BTX16-BS	BTX16	BTX16H MAX	BSLi-09
	BTX20-BS	BTX20H	BGZ20H MAX	BSLi-09
	BTX20CH-BS ; BTX20A-BS	BTX20CH		BSLi-09
BB18L-A	BTX20L-BS ; BTX20HL-BS	BTX20HL	BGZ20HL MAX	BSLi-10 ; BSLi-10 MAX
B50-N18L-A/A2/A3	BTX24HL-BS	BTX24HL/B50-N18L-A/A2/A3		BSLi-10 ; BSLi-10 MAX
BB30L-B	BIX30L-BS	BIX30L	BGZ3ZHL MAX	BSLi-10 ; BSLi-10 MAX
6N11A-1B ; 6N11A-3A		6N11A-1B/3A		
6N4-2A ; 6N4-2A-4		6N4-2A/A-4		
6N6-3B ; 6N6-3B-1		6N6-3B/B-1		
6N11A-4 ; 6N11A-4A		6N11A-4A		
B49-6		B49-6		
B38-6A		B38-6A		
12N5.5-3B		12N5.5-3B		BSLi-02 ; BSLi-02 MAX
12N5.5-4A ; 12N5.5-4B		12N5.5-4A/4B		
12N7A-3A		12N7A-3A/B		
BB3L-A ; BB3L-B		BB3L-A/B		BSLi-01
BB4L-B		BB4L-B		BSLi-02 ; BSLi-02 MAX
BB5L-B (12N5-3B)		BB5L-B		BSLi-02
BB7-A (12N7-4A)		BB7-A		BSLi-03
BB7C-A		BB7C-A		BSLi-02 ; BSLi-02 MAX
BB7B-B		12N7A-3A/B		
BB7L-B (12N7-3B) ; BB7L-B2		BB7L-B2		BSLi-02 ; BSLi-02 MAX
BB9-B (12N9-4B-1)	BT9A-BS	BB9-B		BSLi-03
BB10L-A2 ; BB10L-B2 ; BB10L-BP		BB10L-A2/B2		BSLi-05
BB12AL-A/A2		BB12AL-A2		BSLi-05
BB12A-A (12N12A-4A-1) ; BB12A-B		BB12A-A/B		BSLi-04/06
BB14A-A2 ; BB14A-A1		BB14A-A2		BSLi-04/06
BB14-A2 (12N14-4A) ; BB14-B2	BTX14AH-BS	BB14-A2/B2/BTX14AH	BTX14AH MAX	BSLi-04/06
BB14L-A2 (12N14-3A) ; BB14L-B2	BTX14AHL-BS	BB14L-A2/B2/BTX14AHL		BSLi-05
BB16AL-A2		BB16AL-A2		BSLi-05
BB16CL-B		BB16CL-B		BSLi-10 ; BSLi-10 MAX
B50-N18L-A/A2/A3	BTX24HL-BS	B50-N18L-A/A2/A3/BTX24HL		BSLi-10 ; BSLi-10 MAX
53030		53030		BSLi-12 ; BSLi-12 MAX