



产品简介
PRODUCT INTRODUCTION


JQX-15F/T90 Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 32.4x27.5x19.5 Electric contact 1C.1H.1D Electric load 30A, 40A Switching Voltage 277VAC/30VDC contact Silver alloy Coil power DC 0.93W AC 1.2VA Coil voltage DC 3V~110V, AC 6V~240V Electrical life ≥10 ⁵ Installation PCB printing plate Certification 	

JQX-15F/T91 Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 32.4x27.4x28.6 Electric contact 1C.1H.1D Electric load 30A, 40A Switching Voltage 277VAC/30VDC contact Silver alloy Coil power DC 0.93W AC 1.2VA Coil voltage DC 3V~110V, AC 6V~240V Electrical life ≥10 ⁵ Installation PCB printing plate Certification 	

JQX-15F/T93 Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 32.4x27.4x21 Electric contact 1C.1H.1D Electric load 30A, 40A Switching Voltage 277VAC/30VDC contact Silver alloy Coil power DC 0.93W AC 1.2VA Coil voltage DC 3V~110V, AC 6V~240V Electrical life ≥10 ⁵ Installation PCB printing plate Certification 	

PYF11A Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current 7A Load voltage 300V Medium pressure 2500VAC/S Applicable relay JQX-18F-3Z, HH53P, MY3

产品简介
PRODUCT INTRODUCTION

PYF08A1、PYF08A-E1、PYF08A2 Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current 7A Load voltage 300V Medium pressure 2500VAC/S Applicable relay JQX-18F-2Z, HH52P, MY2

PYF14A1、PYF14A-E1 Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current 7A Load voltage 300V Medium pressure 2500VAC/S Applicable relay JQX-18F-4Z, HH54P, MY4

PTF08A Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current 12A Load voltage 300V Medium pressure 2500VAC/S Applicable relay JQX-13F-1Z, JQX-13F-2Z, HH61P, HH62P, LY1, LY2

产品简介
PRODUCT INTRODUCTION
致力于未来
FOCUS ON THE FUTURE

※由于标准和材料的变更，文中所述特征和本资料中的图像仅供参考，一切以实物为准，我公司保留最终解释权。


公司简介
COMPANY PROFILE

浙江格亚电气有限公司是一家引进国内外先进的生产设备和技 术，专业从事继电器的研发、生产、销售、服务为一体的综合性企业 座落于中国电器之都 柳市。为能在日益激烈的全球化市场竞争中实现公司的可持续发展，格亚电器将继续秉承 诚信、超越 的经营理念、以高性价比的产品、快速的交货期和优越的售后服务来满足全球客户的需求。




产品简介
PRODUCT INTRODUCTION

JQX-13F/2Z Electromagnetic relay series


产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x21x35 Electric contact 2C.2H.2D Electric load 12A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 0.9W AC 1.2VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	

产品简介
PRODUCT INTRODUCTION


HH52P Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x21x35 Electric contact 2C.2H.2D Electric load 6.5A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 0.9W AC 1.2VA Coil voltage DC 3V~220V, AC 3V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	


HH53P Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x21x35 Electric contact 3C.3H.3D Electric load 6.5A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 0.9W AC 1.2VA Coil voltage DC 3V~220V, AC 3V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	

HH54P Electromagnetic relay series


产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x21x35 Electric contact 4C.4H.4D Electric load 5A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 0.9W AC 1.2VA Coil voltage DC 3V~220V, AC 3V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	

JQX-13F/3Z Electromagnetic relay series


产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x31x35 Electric contact 3C.3H.3D Electric load 12A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 1.5W AC 2.5VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	

产品简介
PRODUCT INTRODUCTION


JQX-38F Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 55.5x30x37.5 Electric contact 2C.2H.2D.3C.3H.3D Electric load 40A, 50A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 2.5W AC 6VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation Base Bolt type Certification 	

JQX-40F Electromagnetic relayseries

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 60x46x46 Electric contact 1C.1H.1D Electric load 40A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 2.0W AC 8.6VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation Bolt type Certification 	

JQX-60F Electromagnetic relayseries

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 60x46x46 Electric contact 1C.1H.1D Electric load 50A, 60A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 2.0W AC 8.6VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation Bolt type Certification 	

JQX-13F/4Z 电磁继电器系列

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension 27.3x41x35 Electric contact 4C.4H.4D Electric load 12A Switching Voltage 240VAC/28VDC contact Silver alloy Coil power DC 1.5W AC 3VA Coil voltage DC 6V~220V, AC 6V~380V Electrical life ≥10 ⁵ Installation PCB printing plate, base Certification 	