



SAFETY DATA SHEET

R-426A (RS-24)

Issue: June 2024 Version 2.3

Date: 4.06.2024

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: **R-426A (RS-24)**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Refrigerant

Restrictions on use: For professional use only.

1.3. Details of the supplier of the safety data sheet

Name of supplier: GAS SERVEI S.A.
Address: C/ Motors, 151-155 nave nº 9
08038 Barcelona
SPAIN
Telephone: +34 (93) 2231377
Telefax: +34 (93) 2231479
www.gas-servei.com

E-mail address
of person responsible
for the SDS: gas-servei@gas-servei.com

1.4. Emergency telephone number

Gas-servei: + 34 619373605
(CHEMTREC – Recommended): +(44)-870-8200418

SECTION 2. Hazard identification

2.1. Classification of the substance or mixture

Criteria Regulation EC 1272/2008 (Classification, Labelling and Packaging):

Gases under pressure,
Liquefied gas H280: Contains gas under pressure; may explode if heated.

2.2. Label elements

Hazard pictograms: Symbols: GHS04



Signal word: Warning

Hazard statements: H280: Contains gas under pressure; may explode if heated.

Precautionary statements: Storage:
P410+P403: Protect from sunlight. Store in a well-ventilated place.

Additional labelling: Contains fluorinated greenhouse gases (HFC-125, HFC-134a).

2.3. Other hazards

This substance/mixture does not contain components that are considered to be bioaccumulative and persistent toxic (PBT) or very bioaccumulative and very persistent (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components that have endocrine disrupting properties based on Article 57(f) of REACH or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components that have endocrine disrupting properties based on Article 57(f) of REACH or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air and can cause asphyxiation by reducing oxygen in the air breathed.

Misuse or intentional inhalation abuse can cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause freezing.

Can displace oxygen and cause rapid asphyxiation.









SECTION 3. Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Components

Chemical name	Concentration (% by weight)	CAS No	EC No	REACH Registration No	Ranking
					EC Regulation No 1272/2008
1,1,1,2-Tetrafluoroethane (HFC 134a)	93.0	811-97-2	212-377-0	01-2119459374-33-XXXX	 2.5 Press. Gas H280
1,1,1,2,2-Pentafluoroethane (HFC 125)	5.1	354-33-6	206-557-8	01-2119485636-25-XXXX	 2.5 Press. Gas H280
N-butane (R-600)	1.3	106-97-8	203-448-7	01-2119474691-32-XXXX	 2.2/1 Flam. Gas1 H220  2.5 Press. Gas H280
Isopentane (R-601a)	0.6	78-78-4	201-142-8	01-2119475602-38-XXXX	 2.6/1 Flam. Liq. 1 H224  3.10/1 Asp. Tox. 1 H304  3.8/3 STOT SE 3 H336  4.1/C2 Aquatic Chronic 2 H411

SECTION 4. First aid measures

4.1. Description of first aid measures



General recommendations: In case of accident or if you feel unwell, seek medical advice immediately. If symptoms persist or if in doubt, seek medical advice.

Protection of first-aiders: No special precautions are required for lifeguards.

In case of inhalation: If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Consult a doctor immediately.

In case of skin contact:	Thaw frozen parts with lukewarm water. Do not rub the affected part. Consult a doctor immediately.
In case of eyes contact:	Consult a doctor immediately.
In case of ingestion:	Ingestion shall not be considered as a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

May cause cardiac arrhythmia.

Other symptoms potentially related to inhalation misuse or abuse include:

Cardiac sensitisation	Anaesthetic effects
Mild dizziness	Dizziness
Confusion	Lack of coordination
Drowsiness	Unconsciousness

Gas reduces oxygen available for breathing.

Contact with liquid or refrigerated gas may cause cold burns and frostbite.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:	Symptomatic treatment and supportive therapy as indicated. Because of possible heart rhythm disturbances, catecholamines such as epinephrine, which may be used in emergency life support situations, should be used with special caution.
------------	---

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:	Not applicable Will not burn.
Unsuitable extinguishing media:	Not applicable Will not burn.

5.2. Specific hazards arising from the substance or mixture

Specific hazards during the firefighting:	Exposure to combustion products may be a health hazard. Do not inhale fumes produced. Due to the high vapour pressure, there is a danger that the containers may burst if the temperature rises.
Hazardous combustion products:	Hydrogen fluoride Carbonyl fluoride Carbon oxides Fluorinated compounds

5.3. Advice for firefighters

Special protective equipment for firefighters:	If necessary, wear self-contained breathing apparatus for fire-fighting. Use personal protective equipment.
Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fight the fire from a distance due to the risk of explosion. Use water spray to cool closed containers. Remove undamaged containers from fire area if safe to do so. Evacuate the area.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Evacuate personnel to safe areas.
- Use self-contained breathing apparatus and appropriate personal protection during spill removal.
- Avoid skin contact with leaking liquid (danger of frostbite).
- Ventilate the area.
- Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2. Environmental Precautions

- Do not release into the environment.
- Prevent the product from entering the soil/subsoil.
- Do not allow to enter surface water or sewage system.
- Prevent further leakage or spillage safely.
- Retain and dispose of contaminated water.
- In case of gas leakage or penetration into watercourses, soil or sewage system, inform the responsible authorities.

6.3. Methods and materials for containment and cleaning up

- | | |
|--------------------------|----------------------------|
| Methods for cleaning up: | Ventilate the area. |
| | Wash with plenty of water. |

- | | |
|---|---|
| Materials of
containment and clean-up: | Appropriate material for collection: absorbent material, organic, sand. |
|---|---|

Local or national regulations may apply to the release and disposal of this material, and to the materials and items used in cleaning up the releases. You will need to determine which regulations apply.
Sections 13 and 15 of this safety data sheet provide information on certain local or national requirements.

6.4. Reference to other sections

See also paragraphs 7, 8, 11, 12 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

- | | |
|---------------------------|---|
| Technical measures: | Use equipment rated for the cylinder pressure. Use a backflow prevention device in the pipeline. Close the valve after each use and after emptying. |
| Local/Total Ventilation: | Use only with adequate ventilation. |
| Tips for a safe handling: | <p>Avoid contact with skin and eyes.</p> <p>Avoid inhalation of fluid vapours and mists.</p> <p>Do not use empty containers that have not been previously cleaned.</p> <p>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment.</p> <p>Wear insulated gloves against cold and face/eye protection.</p> <p>Valve protection caps and valve outlet screw caps must remain in place unless the container is secured with the valve outlet connected to the point of use.</p> <p>Use a check valve or trap (exhaust, siphon trap interceptor) in the discharge line to prevent dangerous reverse flow into the cylinder.</p> <p>Before transfer operations, ensure that there are no incompatible materials and/or waste in the containers.</p> <p>Prevent gas from flowing back into the gas container.</p> <p>Use a pressure regulator when connecting the cylinder to lower pressure systems or piping.</p> <p>Close the valve after each use and after emptying.</p> <p>DO NOT change or force connections.</p> |

Prevent water from infiltrating into the gas container.
Never attempt to lift the cylinder by its cap.
Do not drag, slide or roll the cylinders.
Use a suitable hand truck to move the cylinder.
Keep away from heat and sources of ignition.
Transfer of liquid refrigerant from refrigerant containers to and from systems can result in the generation of static electricity.
Ensure that proper grounding is in place.
Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions. Avoid electrostatic charge build-up.
Pay attention to mitigating the risk of developing high pressures in systems, caused by temperature rise when liquid is trapped between closed valves or when containers have been overfilled.
Prevent spillage, disposal. Minimise release to the environment.

Hygiene measures:

If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Technical requirements for
storage areas and containers:

Keep cylinders in a well-ventilated place away from fire hazards.
Cylinders must be stored upright and securely fixed to prevent them from falling or being knocked over.
Separate full containers from empty containers.
Do not store near combustible materials.
Avoid areas where salt and other corrosive materials are present.
Store in properly labelled containers.
Keep in a cool, well-ventilated place.
Keep out of direct sunlight.
Store in accordance with particular national regulations.

Advice on
common storage:

Do not store with the following types of products:
Self-reactive substances and mixtures
Organic peroxides
Oxidants
Flammable liquids
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Substances and mixtures undergoing spontaneous heating.
Substances and mixtures which, in contact with water, give off flammable gases.
Explosives
Highly toxic mixtures and substances.
Highly toxic mixtures and substances.
Mixtures and substances with chronic toxicity

Recommended
storage temperature:

< 50 °C

Storage period:

> 10 years

Further information
on storage stability:

The product has an indefinite shelf life when properly stored.

7.3. Specific end use(s)

Subject to Member State regulations, applicable uses are:
Refrigerant.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Substance name	CAS No.	VLE-ED (8h ppm)	VLE-ED (8h mg/m ³)
N-Butane	106-97-8	1.000	2.377

Derived no-effect level (DNEL) based on Regulation (EC) No. 1907/2006:

Substance name	CAS No.	End Use	Exposure routes	Potential health effects	Value (mg/m ³)
1,1,1,1,2-Tetrafluoroethane	811-97-2	Workers	Inhalation	Long-term - systemic effects	13,936 mg/m ³
		Consumers	Inhalation		2,476 mg/m ³
1,1,1,1,2,2-Pentafluoroethane	354-33-6	Workers	Inhalation	Long-term - systemic effects	16,444 mg/m ³
		Consumers	Inhalation		1,753
Isopentano	78-78-4	Workers	Dermal	Long-term - systemic effects	432 mg/kg/day
		Consumers	Dermal		214 mg/kg/day
		Workers	Inhalation		3,000 mg/m ³
		Consumers	Inhalation		643 mg/m ³
		Consumers	Ingestion		214 mg/kg/day

Predicted no effect concentration (PNEC) based on Regulation (EC) No. 1907/2006:

Substance name	CAS No.	Environmental Compartment	Value
1,1,1,1,2,2-Pentafluoroethane	354-33-6	Freshwater	0.1 mg/l
		Freshwater - Intermittent	1 mg/l
		Freshwater sediment (dry weight)	0.6 mg/kg
1,1,1,1,2-Tetrafluoroethane	811-97-2	Freshwater	0.1 mg/l
		Seawater	0.01 mg/l
		Discontinued release/use	1 mg/l
		Freshwater sediment (dry weight)	0.75mg/kg
		Wastewater treatment plant	73 mg/l
Isopentane	78-78-4	Technically unfeasible tests	-

8.2. Exposure controls

Occupational exposure controls

Personal protective equipment must comply with current UNE standards: Respiratory protection UNE 136, 140, 149; Protective goggles/eye protection UNE 166; Protective clothing UNE 340, 463, 469, 943-1, 943-2; Protective gloves ISO 374, 511; Protective shoes ISO 20345.

Do not breathe vapours.

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimise exposure concentrations in the workplace.

Personal protection



Respiratory protection:

If adequate exhaust ventilation is not available or exposure assessment shows exposure outside recommended limits, self-contained breathing apparatus or positive pressure airline and mask.
The equipment shall comply with UNE 14387.

Filter type:

Organic gas and low boiling vapour (AX) type.

Skin protection and body:

Wash skin after all contact with the product.
Protective shoes should be worn when handling containers.



Hand protection:

Material:
Remarks:

Low temperature resistant gloves
Choose chemical protective gloves taking into account the quantity and concentration of the hazardous substances to be handled at the workplace.
It is recommended to clarify with the manufacturer of the above-mentioned protective gloves whether they have the necessary resistance for applications with special chemicals.
Wash hands before breaks and after the end of the working day.
The breakthrough time is not determined for the product.
Change gloves often.



Eye protection:

Wear the following personal protective equipment:
Chemical resistant goggles should be worn.
Face shield.
The equipment must comply with UNE 166.

SECTION 9. Physical and chemical properties

Appearance:	Liquefied gas
Colour:	Colourless
Odour:	Light, ether like
Odour threshold:	No data available
pH:	No data available
Melting/freezing point:	No data available
Initial boiling point and boiling range:	-28,5 °C
Flash point:	Not applicable
Evaporation rate:	Not applicable
Flammability (solid, gas):	Will not burn
Upper explosive limit /Upper flammability limit:	Upper flammability limit Method: ASTM E681 None.
Lower explosion limit /Lower flammability limit:	Lower flammability limit Method: ASTM E681 None.
Vapour pressure:	7,070 hPa (25 °C).
Relative density:	1.18 (25 °C) (as a liquid)
Density:	1.184 g/cm ³ (25 °C) (as a liquid).
Solubility	
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not applicable
Auto-ignition temperature:	No data available

Temperature of decomposition:	Not applicable
Viscosity:	Not applicable
Explosive properties:	Non-explosive
Oxidising properties:	The substance or mixture is not classified as an oxidiser.
Particle size:	Not applicable

Other information

Critical temperature:	101 °C
Critical pressure:	41 bar

SECTION 10. Stability and reactivity

10.1. Reactivity

Not classified as a reactivity hazard.

10.2. Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

10.3. Possibility of hazardous reactions

Certain HFC mixtures may be flammable or reactive under certain conditions.
May react with strong oxidising agents.

10.4. Conditions to avoid

This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature may become combustible in the presence of an ignition source.

This substance can also become combustible in an oxygen-enriched environment (oxygen concentrations higher than those in air). Therefore, if a mixture containing air and this substance, or if this substance is in an oxygen-enriched environment, it can become combustible. This will depend on the relationship between 1) the temperature, 2) the pressure and 3) the proportion of oxygen in the mixture. In general, this substance should not be mixed with air at pressures above atmospheric or at high temperatures; or in an oxygen-enriched environment. For example, this substance should NOT be mixed with air under pressure for leak testing or other purposes.

Avoid heat, flames and sparks.

10.5. Incompatible materials

Strong oxidising agents, alkali and alkaline earth metals, other metals and transition metals, aluminium powder, zinc, etc...

10.6. Hazardous decomposition products

Halogen compounds, hydrogen fluoride by thermal decomposition and hydrolysis.

SECTION 11. Toxicological information

11.1. Information on toxicological effects as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure:	Inhalation
	Skin contact
	Eye contact

a. Acute toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Acute oral toxicity: Assessment: The substance or mixture does not exhibit acute oral toxicity.

Acute inhalation toxicity: LC50 (Rat): > 567,000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD 403 Test Guidelines
No Observed Adverse Effect Concentration (Dog): 40,000 ppm
Test atmosphere: gas
Remarks: Cardiac sensitisation
Low Observed Adverse Effect Concentration (Dog): 80,000 ppm
Test atmosphere: gas
Symptoms: May cause cardiac arrhythmia.
Threshold limit for cardiac sensitisation (Dog): 334,000 mg/m³.
Test atmosphere: gas
Symptoms: May cause cardiac arrhythmia.

Acute dermal toxicity: Assessment: The substance or mixture does not exhibit any acute dermal toxicity.

1,1,1,2,2-Pentafluoroethane:

Acute inhalation toxicity: LC50 (Rat): > 800,000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD 403 Test Guidelines
No observed Adverse Effect Concentration (Dog): 75,000 ppm
Remarks: Cardiac sensitisation
Threshold limit for cardiac sensitisation (Dog): 368,160 mg/m³.
Remarks: Cardiac sensitisation

Isopentane:

Acute oral toxicity: LC50 (Rat): > 25.300 mg/m³
Exposure time: 4 h
Test atmosphere: gas
Remarks: Basado en datos de materiales similares.

Acute dermal toxicity: LD50: (Rabbit): 3.000 ppm

N-butane:

Acute inhalation toxicity: LC50 (Rat): > 570,000 ppm
Exposure time: 15 min
Test atmosphere: gas

b. Skin corrosion/irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane: Result: Non-irritating to skin.

1,1,1,2-Pentafluoroethane: Result: Non-irritating to skin.

Isopentane:

The study is not technically feasible.

N-butane:

The study is not technically feasible.

c. Serious eye damage/irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane: Species: Rabbit
Classification: Not classified as irritant.
Result: Non-irritating to the eyes.

1,1,1,2,2-Pentafluoroethane:

Not tested on animals.

Classification: Not classified as irritant.

Result: Non-irritating to the eyes.

Isopentane:

Species: Rabbit

Method: OECD 405 Test Guidelines

Result: Non-irritating to the eyes.

N-butane:

The study is not technically feasible.

d. Respiratory or skin sensitisation
Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:
1,1,1,2-Tetrafluoroethane:

Routes of exposure: Skin contact

Result: Negative

Routes of exposure: Inhalation

Species: Rat

Result: Negative

Routes of exposure: Inhalation

Species: Human

Result: Negative

1,1,1,2,2-Pentafluoroethane:

Not tested on animals.

Classification: Not a skin sensitiser.

Result: Does not cause skin sensitisation.

No reports of respiratory sensitisation in humans.

Isopentane:

Not classified based on available information.

N-butane:

Not classified based on available information.

e. Germ cell mutagenicity

Not classified based on available information.

Components:
1,1,1,2-Tetrafluoroethane:

In vitro genotoxicity:

Test type: Bacterial reverse mutation assay (Ames test)

Method: OECD Test Guidelines 471

Result: Negative

Test Type: In vitro chromosomal aberration test

Method: OECD Test Guidelines 473

Result: Negative

Genotoxicity in vivo:

Test type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Route of application: inhalation (gas)

Method: OECD Test Guidelines 474

Result: Negative

Test type: Unscheduled DNA synthesis test (UDS) with cells from mammalian liver in vivo.

Species: Rat

Route of application: inhalation (gas)

Method: OECD Test Guidelines 486

Result: Negative

1,1,1,2,2-Pentafluoroethane:

In vitro genotoxicity:

Test type: Bacterial reverse mutation assay (Ames test).

Method: OECD Test Guidelines 471

Result: Negative

Remarks: Based on data from similar materials.

Type of test: In vitro chromosome aberration test

Method: OECD Test Guidelines 473

Result: Negative

Genotoxicity in vivo:

Test type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay).

Species: Mouse

Route of application: inhalation (gas)

Method: OECD 474 Test Guidelines

Result: Negative

Isopentane:

Not classified based on available information.

Mutagenicity in
germ cells:

Assessment: The weight of evidence does not support classification as a germ cell mutagen.

N-butane:

In vitro genotoxicity:

Test type: Bacterial reverse mutation assay (Ames test).

Method: OECD Test Guidelines 471

Result: Negative

Type of test: In vitro chromosome aberration test

Method: OECD Test Guidelines 473

Result: Negative

Genotoxicity in vivo:

Test type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay).

Species: Mouse

Route of application: inhalation (gas)

Method: OECD 474 Test Guidelines

Result: Negative

Remarks: Based on data from similar materials.

Mutagenicity in
germ cells:

Assessment: The weight of evidence does not support classification as a germ cell mutagen.

f. Carcinogenicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Species: Rat

Route of application: Inhalation (gas)

Exposure time: 2 years

Method: OECD 453 Test Guidelines

Result: Negative

g. Reproductive toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Effects on fertility:

Species: Mouse

Route of application: Inhalation

Result: Negative

Foetal developmental effects:

Test Type: Repeated dose toxicity study combined with reproductive/developmental toxicity screening test.

Species: Rabbit

Route of application: inhalation (gas)

Method: OECD Test Guidelines OECD 414

Result: Negative

1,1,1,2,2-Pentafluoroethane:

Effects on fertility:

Type of test: One-generation reproductive toxicity study.

Species: Rat

Route of application: inhalation (vapour)

Result: Negative

Remarks: Based on data from similar materials.

Effects on foetal development:

Type of evidence: Embryonic and foetal development.

Species: Rat

Route of application: inhalation (gas)

Method: OECD 414 Test Guidelines

Result: Negative

Isopentane:

Not classified based on available information.

Reproductive toxicity:

Assessment: The weight of evidence does not support classification as a reproductive toxicant.

N-butane:

Effects on fertility:

Test Type: Repeated dose toxicity study combined with reproductive /developmental toxicity screening test.

Species: Rat

Route of application: Inhalation (gas)

Method: OECD 422 Test Guidelines

Result: Negative

Effects on foetal development:

Test Type: Repeated dose toxicity study combined with reproductive /developmental toxicity screening test.

Species: Rat

Route of application: Inhalation (gas)

Method: OECD 422 Test Guidelines

Result: Negative

h. Specific target organ toxicity (STOT) - single exposure

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Routes of exposure: inhalation (gas)

Assessment: No significant health effects were observed in animals at concentrations of 20,000 ppmV/4h or less.

1,1,1,2,2-Pentafluoroethane:

Not classified based on available information.

Isobutane:

Assessment: May cause drowsiness or dizziness.

N-Butano:

Assessment: May cause drowsiness or dizziness.

Remarks: Based on data from similar materials.

i. Specific target organ toxicity (STOT) - repeated exposures

Not classified based on available information.

1,1,1,2-Tetrafluoroethane:

Routes of exposure: inhalation (gas)

Assessment: No significant health effects were observed in animals at concentrations of 250 ppmV/6h/d or less.

Isopentane:

Routes of exposure: inhalation (gas)

Assessment: There are health effects although not sufficient for classification.

N-Butane:

Routes of exposure: inhalation (gas)

Assessment: There are health effects although not sufficient for classification.

j. Aspiration toxicity

Not classified based on available information.

11.2. Information concerning other hazards

a. Endocrine disrupting properties

Assessment:

The mixture does not contain components that have endocrine disrupting properties based on Article 57(f) of REACH or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1 % or higher.

SECTION 12. Ecological information

12.1. Toxicity

Components:

1,1,1,2-Tetrafluoroethane:

Toxicity to fish:

LC50 (Oncorhynchus mykiss (rainbow trout): 450 mg/l

Exposure time: 96 h

Method: Standard (EC) No 440/2008, Annex, C.1

Toxicity to daphnia

and other aquatic invertebrates:

EC50 (Daphnia magna (large sea flea): 980 mg/l

Exposure time: 48 h

Method: Standard (EC) No 440/2008, annex, C.2

Toxicity to

algae/aquatic plants:

ErC50 (green algae): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials.

1,1,1,2-Pentafluoroethane:

Toxicity to fish:

LC50 (Oncorhynchus mykiss (rainbow trout): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia

and other aquatic invertebrates:

EC50 (Daphnia magna (large sea flea): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to

algae/aquatic plants:

ErC50 (Pseudokirchneriella subcapitata (green algae): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae): > 1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Isopentane:

Toxicity to fish:

LC50 (Oncorhynchus mykiss (Rainbow trout): > 34.05 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia

and other aquatic invertebrates:

EC50 (Daphnia magna (Big sea flea)): > 59.44 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

	Remarks: Based on data from similar materials NOAEL (Daphnia magna): 13.29 mg/l NOEC (Pseudokirchneriella subcapitata (green algae): > 1 mg/l Exposure time: 21 d Method: OECD Test Guideline
Toxicity to algae/aquatic plants:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 10.7 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
N-Butane:	
Not classified based on available information.	

12.2. Persistence and degradability

Components:

1,1,1,2-Tetrafluoroethane:

Biodegradability:	Result: Not readily biodegradable. Method: OECD Test Guidelines 301D
-------------------	---

1,1,1,2,2-Pentafluoroethane:

Biodegradability:	Result: Not readily biodegradable. Biodegradation: 5 % Exposure time: 28 d Method: OECD Test Guidelines 301D
-------------------	---

Isopentane:

Biodegradability:	Result: Not readily biodegradable. Method: OECD Test Guidelines 301D
-------------------	---

N-butane:

Biodegradability:	Result (in water): Readily biodegradable. Remarks: Based on data from similar materials.
-------------------	---

12.3. Bioaccumulative potential

Components:

1,1,1,2-Tetrafluoroethane:

Bioaccumulation :	Remarks: Bioaccumulation is unlikely. Partition coefficient (n-octanol/water): log Pow: 1.06
-------------------	--

1,1,1,2,2-Pentafluoroethane:

Partition coefficient (n-octanol/water): Pow: 1.48 Method: OECD 107 Test Guidelines

Isopentane:

Partition coefficient (n-octanol/water): Pow: 3.45 Remarks: Based on data from similar materials.

N-butane:

Partition coefficient (n-octanol/water): log Pow: 2.89

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvBm assessment

Assessment:	This mixture does not contain components considered to be either bioaccumulative, persistent and toxic (PBT) or very bioaccumulative and very persistent (vPvB) at levels of 0.1% or higher.
-------------	--

12.6. Endocrine disrupting properties

Assessment:

The mixture does not contain components considered to have endocrine disrupting properties according to Article 57(f) of REACH or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

Global Warming Potential

Regulation (EU) 2024/573 on fluorinated greenhouse gases

Product:

100-year global warming potential: 1.508

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Product:

Dispose of in accordance with local regulations. However, this product should be recycled or reclaimed whenever possible.

Contaminated packaging:

Empty containers should be returned to the supplier. Operate in accordance with local and national regulations.

13.2. Other information

Waste-related provisions:

Directive 2006/12/EC; Directive 2008/98/EC
EC Regulation No. 1013/2006

Personal protective equipment, see section 8.

SECTION 14. Transport information

14.1. UN number

DNA:	1078
ADR:	1078
RID:	1078
IATA:	1078
IMDG:	1078

14.2. United Nations proper shipping name

ADR/ADN/RID:	REFRIGERANT GAS, N.O.S. R-426A (RS-24) (1,1,1,2-TRETRAFLUOROETHANE/ 1,1,1,2,2-PENTAFLUOROETHANE/ N-BUTANE/ ISOPENTANE)
IMDG:	REFRIGERANT GAS, N.O.S. R-426A (RS-24) (1,1,1,2-TRETRAFLUOROETHANE/ 1,1,1,2,2-PENTAFLUOROETHANE/ N-BUTANE/ ISOPENTANE)
IATA:	Refrigerant gas, N.O.S. R-426A (RS-24) (1,1,1,2-Tetrafluoroethane/ Pentafluoroethane/ N-butane/ Isopentane)

14.3. Transport hazard class(es)

	<u>Class</u>	<u>Subsidiary risks</u>	<u>Clasificación code</u>	<u>Hazard identification no.</u>	<u>Tunnel restric. code</u>
ADR:	2	2.2	2A	20	(C/E)
ADN:	2	2.2	2A	20	
RID:	2	2.2, (13)	2A	20	
IMDG:	2.2				
IATA:	2.2				

14.4. Packing group

Not assigned by regulation.

Labels

ADR/ADN/RID/IMDG: 2.2



IMDG / IATA: Non-flammable. Non-toxic Gas

Packaging instruction

IATA (Cargo): 200

IATA (Passenger): 200

EmS Code

IMDG: F-C, S-V

14.5. Environmental hazards

No : (ADR/ADN/RID/IMDG)

14.6. Special precautions for users

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH-Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII):

Not applicable

REACH-Candidate list of substances of particular concern for Authorisation (Article 59):

This product does not contain substances of very high concern above the relevant legal concentration limit (≥ 0.1 % w/w).

Regulation (EC) 1005/2009 on substances that deplete the ozone layer:

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast):

Not applicable

Regulation (EC) 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals:

Not applicable

REACH-List of substances subject to authorisation (Annex XIV):

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances:

Not applicable

Regulation (EC) 2024/573 of the European Parliament and of the Council on certain fluorinated greenhouse gases: Fluorinated greenhouse gas R-426A (RS-24) must be supplied in returnable containers (drums/cylinders).

The container contains fluorinated greenhouse gases regulated under the Kyoto Protocol. Fluorinated greenhouse gases in containers or cylinders may not be vented to the atmosphere.

15.2. Chemical safety assessment

A chemical safety assessment has not been conducted for this product.

SECTION 16. Other information

This sheet cancels and replaces all previous editions.

Date of issue : June 4, 2024

Version: 2.3

This Safety Data Sheet has been prepared in accordance with:

Regulation (EC) No 1907/2006 and its subsequent amendments: Regulation (EU) No 2015/830 and Regulation (EU) No 2020/878.

Text of phrases used in section 3:

H220: Extremely flammable gas.

H221: Flammable gas.

H224: Extremely flammable liquid and vapours.

H280: Contains gas under pressure; danger of explosion if heated.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H411: Hazardous to the aquatic environment.

This document has been prepared by a competent person who has received appropriate training.

The information given here is based on our knowledge up to the date stated above. It refers exclusively to the product indicated and does not constitute a guarantee of particular qualities.

The user must satisfy himself as to the suitability and accuracy of such information in relation to his specific use of the product.

The information is believed to be correct, but is not exhaustive and shall be used only as guidance, which is based on current knowledge of the chemical or mixture and is applicable to the appropriate safety precautions for the product.

The list of risks, legal, regulatory and administrative texts are not exhaustive, and it is the sole responsibility of the recipient or user of the product to refer to the official regulations for storage, handling and use of these products.

Glossary of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CMR: Carcinogenic, mutagenic or toxic for reproduction.

DIN: Standard of the German standardisation institute.

ECx: Concentration associated with x% response.

EmS: Emergency procedure.

GHS: Globally Harmonised System of Classification and Labelling of Chemicals.

IATA: International Air Transport Association.

IBC: International Code for the Construction and Equipment of Ships Carrying Goods.
Hazardous Chemicals in bulk.

IMDG: International Maritime Dangerous Goods Code.

LC50: Lethal concentration in 50% of a test population.

NOAEL: No Observed Adverse Effect Level.

NOEL: No Observable Effect Level.

NOELR: No Observable Effect Loading Ratio.

IMO: International Maritime Organisation.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail (COTIF).

UN: United Nations.

ELV: Environmental Limit Values.

UNRTDG: United Nations Recommendations on the Transport of Dangerous Goods.