

SELECT PRO BOLT-ON DEADLOCK

Specification Sheet
SBD

FEATURES

- Built to last: Stainless steel deadbolt which moves 30mm with one turn of a key.
- Adjustable: Deadbolt is adjustable on length for precise fitting on site.
- Convenient access: Key operation on both sides with simple unlocking via one turn of the key.

PRODUCT DETAILS

Product code	Description
SBD1601	To fit flat bar and up to 30mm (1/2" - 1 1/4") box section
SBD1602	To fit 40-60mm (1/2" - 1 1/4") box section
Can be used for both left and right handed gates	



INCLUDED IN THE BOX

- 1x3mm hex key
- M8 fixing bolts
- Face plate
- Deadbolt
- Strike plate (self-drilling fasteners)
- A set of keys (3)

INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 92mm (3 2/3") centres for fixing bolts provided.
2. Drill a 18mm (3/4") clearance hole for the latchbolt at 22mm (7/8") centres down from the top fixing hole.
3. Fix lock in place using stainless steel clamp plate, bolt support plate and 2 stainless steel countersunk fixing bolts supplied.
4. Drill clearance hole in keep or outer frame to receive the deadbolt/latchbolt. Slot this hole vertically to allow for the gate sag. Fit strike plate and bend back so the latchbolt slides smoothly.
5. Ensure latchbolt moves freely without binding on gate or frame.
6. **Maintenance:** Every 2 months, lubricate the latchbolt/deadbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.

