






# Product Showcase

## ③ Value Series DVR

DS-7100HGHI-K1(/M1)	DS-7200HGHI-K1(/M1)	iDS-7100HQHI-M1/S
		
4/8/16-Channel DVR with 1 HDD	4/8/16-Channel DVR with 1 HDD	4/8/16-Channel DVR with 1 HDD
Up to 4 TB capacity for each HDD Up to 10 TB capacity for 16 channels	Up to 4 TB capacity for each HDD Up to 10 TB capacity for 16 channels	Up to 10 TB capacity for each disk
Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264	Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264	Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264
1080p Lite/720p @ 15 fps (DS-7104HGHI-K1(/M1) supports 30 fps)	1080p Lite/720p @ 15 fps (DS-7204HGHI-K1(/M1) supports 30 fps)	1080p/720p @ 15 fps/ 4 MP Lite @ 15 fps
Deep learning-based Motion Detection 2.0 for all analog channels with human/vehicle classification	Deep learning-based Motion Detection 2.0 for all analog channels with human/vehicle classification	Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels

iDS-7100HUHI-M1/S	iDS-7200HQHI-M/E	iDS-7200HUHI-M/E
		
4/8/16-Channel DVR with 1 HDD	4/8/16-Channel DVR with 1 HDD	4/8/16-Channel DVR with 1 HDD
Up to 10 TB capacity for each disk	Up to 10 TB capacity for each disk	Up to 10 TB capacity for each disk
Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264	Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264	Video Compression: H.265 Pro+ /H.265 Pro/H.265/ H.264+ /H.264
8 MP@ 8 fps / 5 MP @ 12 fps	1080p/720p @ 15 fps / 4 MP Lite @ 15 fps	8 MP@ 8 fps / 5 MP @ 12 fps
Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels	Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels	Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels

#### 4 Pro Series DVR

iDS-7200HQHI-M1(2)/S	iDS-7200HUHI-M1(2)/S	iDS-7200HTHI-M1(2)/S
		
4/8/16/32-Channel DVR with 1 or 2 HDDs	4/8/16-Channel DVR with 1 or 2 HDDs	4/8-Channel DVR with 1 or 2 HDDs
Up to 10 TB capacity for each disk	Up to 10 TB capacity for each disk	Up to 10 TB capacity for each disk
Video Compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	Video Compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	Video Compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
1080p/720p @ 15 fps/4 MP Lite @ 15 fps	8 MP@ 8 fps / 5 MP @ 12 fps/3K @ 12 fps	8 MP@ 15 fps / 5 MP @ 20 fps/3K @ 20fps
Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels	Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 channels	Deep learning-based Motion Detection 2.0 for all analog channels, Perimeter-Protection Analytics for up to 4 or 8 channels



#### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com



# Motion Detection 2.0

## Smart Motion Capture — Boosted Accuracy and Efficiency



### Focused

Get notified of human and/or vehicle events



### Convenient

This configuration-free function is ON by default



### Efficient

Search footage by human or vehicle event type



The Motion Detection 2.0 function is available on select models of:

- Value Series Network Cameras
- Pro Series NVRs
- Value and Pro Series DVRs

Enjoy the familiar agility of motion detection while getting the upgraded accuracy. Motion Detection 2.0 features:



### Humans & Vehicle Target Classification

Deep-learning algorithms are trained to classify objects in videos into three categories - Humans, Vehicles, and Other.




### Easy Configuration

The configuration-free function is ON by default and generates much fewer false alarms than conventional motion detection.



### Efficient Playback

Through sorting video clips into "Person Files" and "Vehicle Files", homeowners and businesses can quickly locate the clip that they want.



Get instant detection notifications on the Hik-Connect app, wherever you are.



Hik-Connect



Scan and Download the Hik-Connect APP

## Application Scenarios



Residences



Warehouses



Parking lots







Buildings




# Product Showcase

## 1 Value Series Network Cameras

DS-2CD104762-L(UF)	DS-2CD114762-L(UF)	DS-2CD134762-L(UF)	DS-2CD1T4762-L(UF)
 <b>NEW</b>	 <b>NEW</b>	 <b>NEW</b>	 <b>NEW</b>
Bullet Network Camera	Dome Network Camera	Turret Network Camera	Bullet Network Camera
1/3" CMOS sensor	1/3" CMOS sensor	1/3" CMOS sensor	1/3" CMOS sensor
0.001 lux @ F1.0	0.001 lux @ F1.0	0.001 lux @ F1.0	0.001 lux @ F1.0
2.8/4 mm lens	2.8/4 mm lens	2.8/4 mm lens	2.8/4 mm lens
H.265+/H.265	H.265+/H.265	H.265+/H.265	H.265+/H.265
120 dB WDR	120 dB WDR	120 dB WDR	120 dB WDR
- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot
Up to 30 m warm light range	Up to 30 m warm light range	Up to 30 m warm light range	Up to 50 m warm light range
IP67	IP67	IP67	IP67

DS-2CD102762-L(UF)	DS-2CD112762-L(UF)	DS-2CD132762-L(UF)	DS-2CD1T2762-L(UF)
 <b>NEW</b>	 <b>NEW</b>	 <b>NEW</b>	 <b>NEW</b>
Bullet Network Camera	Dome Network Camera	Turret Network Camera	Bullet Network Camera
1/2.8" CMOS sensor	1/2.8" CMOS sensor	1/2.8" CMOS sensor	1/2.8" CMOS sensor
0.001 lux @ F1.0	0.001 lux @ F1.0	0.001 lux @ F1.0	0.001 lux @ F1.0
2.8/4 mm lens	2.8/4 mm lens	2.8/4 mm lens	2.8/4 mm lens
H.265+/H.265	H.265+/H.265	H.265+/H.265	H.265+/H.265
DWDR	DWDR	DWDR	DWDR
- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot	- UF: built-in microphone, SD card slot
Up to 30 m warm light range	Up to 30 m warm light range	Up to 30 m warm light range	Up to 50 m warm light range
IP67	IP67	IP67	IP67

## 2 Pro Series NVR

DS-7616NI-Q2(/16P) (D)	DS-7608NI-Q2(/8P) (D)	DS-7616NI-Q1(/16P) (D)
		
16-Channel NVR with 2 HDDs	8-Channel NVR with 2 HDDs	16-Channel NVR with 1 HDD
Up to 8 TB capacity for each HDD	Up to 8 TB capacity for each HDD	Up to 8 TB capacity for each HDD
Decoding formats: supporting H.265/H.265+/H.264/H.264+/MPEG4	Decoding formats: supporting H.265/H.265+/H.264/H.264+/MPEG4	Decoding formats: supporting H.265/H.265+/H.264/H.264+/MPEG4
Bandwidth: 160 Mbps incoming, 256 Mbps outgoing	Bandwidth: 80 Mbps incoming, 80 Mbps outgoing	Bandwidth: 160 Mbps incoming, 256 Mbps outgoing
1-ch 8 MP or 5-ch 1080p decoding	1-ch 8 MP or 5-ch 1080p decoding	1-ch 8 MP or 5-ch 1080p decoding
1 HDMI, 1 VGA output	1 HDMI, 1 VGA output	1 HDMI, 1 VGA output
1 SATA interface	1 SATA interface	1 SATA interface
1U chassis	1U chassis	1U chassis
16 PoE interfaces	8 PoE interfaces	16 PoE interfaces

DS-7608NI-Q1(/8P) (D)	DS-7604NI-Q1(/4P) (D)
	
8-Channel NVR with 1 HDD	4-Channel NVR with 1 HDD
Up to 8 TB capacity for each HDD	Up to 8 TB capacity for each HDD
Decoding formats: supporting H.265/H.265+/H.264/H.264+/MPEG4	Decoding formats: supporting H.265/H.265+/H.264/H.264+/MPEG4
Bandwidth: 80 Mbps incoming, 80 Mbps outgoing	Bandwidth: 40 Mbps incoming, 80 Mbps outgoing
1-ch 8 MP or 5-ch 1080p decoding	1-ch 8 MP or 5-ch 1080p decoding
1 HDMI, 1 VGA output	1 HDMI, 1 VGA output
1 SATA interface	1 SATA interface
1U chassis	1U chassis
8 PoE interfaces	4 PoE interfaces