

# SELECT PRO BOLT-ON LATCH

Specification Sheet  
**SBL**

## FEATURES

- Dependable hold: Stainless steel latchbolt which springs 13mm into the gate post to hold the gate closed.
- Adjustable: Latchbolt is adjustable on length for precise fitting on site. Easy to rotate for left handed and right handed gates.
- Stylish options: Supplied with handles, 2 different styles available.

## PRODUCT DETAILS

Product code	Description
SBL1601	To fit flat bar and up to 30mm (1/2" - 1 1/4") box section
SBL1602	To fit 40-60mm (1/2" - 1 1/4") box section
SBL1601AH	10mm to 30mm gate frames, AH Handle
SBL1601TDH	10mm to 30mm gate frames, TDH Handle
SBL1602AH	40mm to 60mm gate frames, AH Handle
SBL1602TDH	40mm to 60mm gate frames, TDH Handle



## INCLUDED IN THE BOX

- 1x3mm hex key
- M8 fixing bolts
- Face plate
- Latchbolt
- Strike plate (self-drilling fasteners)
- A set of keys (3)
- Set of handles

## INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 92mm (3 2/3") centres for fixing bolts provided.
2. Drill a 18mm (3/4") clearance hole for the latchbolt at 22mm (7/8") centres down from the top fixing hole.
3. Fix lock in place using stainless steel clamp plate, bolt support plate and 2 stainless steel countersunk fixing bolts supplied.
4. Drill clearance hole in keep or outer frame to receive the latchbolt. Slot this hole vertically to allow for the gate sag. Fit strike plate and bend back so the latchbolt slides smoothly.
5. Ensure latchbolt moves freely without binding on gate or frame.
6. **Maintenance:** Every 2 months, lubricate the latchbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.

