



PRIDE[®]
MOBILITY

GROUP 2 POWER CHAIR COLLECTION

TABLE OF CONTENTS

		DRIVE DESIGN	WEIGHT CAPACITY	STANDOUT FEATURES
4	JAZZY AIR® MED	Mid-wheel Drive	300 lbs.	Power Seat Elevation 
5	JAZZY® 600 ES	Mid-wheel Drive	300 lbs.	
6	JAZZY® SELECT	Mid-wheel Drive	300 lbs.	
7	JAZZY® EVO 613	Mid-wheel Drive	300 lbs.	Ultra Narrow 
8	JAZZY® EVO 614	Mid-wheel Drive	300 lbs.	
9	JAZZY® EVO 614HD	Rear-wheel Drive	450 lbs.	450-lb. capacity 
10	JAZZY® ELITE HD	Front-wheel Drive	450 lbs.	450-lb. capacity 
11	JAZZY® 1450	Front-wheel Drive	600 lbs.	600-lb. capacity 
12	JAZZY® ELITE 14	Front-wheel Drive	300 lbs.	
13	JAZZY® ELITE ES	Front-wheel Drive	300 lbs.	
14	GO CHAIR® MED	Rear-wheel Drive	300 lbs.	Feather-touch Disassembly 
15	ACCESSORIES			
16	SPECIFICATIONS			

Group 2 Power Chair Requirements

If an individual requires a medium duty use power chair and is able to safely operate the power chair in all areas of anticipated use, then a Group 2 power chair is reasonable and necessary. All Group 2 power chairs must meet the following requirements:

- Includes integrated or remote-proportional joystick
- Accommodates seating and positioning items
- Length less than or equal to 48 inches
- Width less than or equal to 34 inches
- Minimum top speed of 3 mph
- Minimum range of 7 miles
- Minimum obstacle climb of 40mm
- Dynamic stability incline of 6 degrees
- No single component weighing over 55 lbs.

JAZZY® POWER CHAIRS offer a wide range of mobility solutions that are built for the real world. From easily portable power chairs, to robust models with enhanced suspension, there is a Jazzy Power Chair to suit anyone’s needs. With its superb construction, unparalleled maneuverability and ease of operation, it’s no wonder the Jazzy Power Chair is America’s #1 Group 2 power chair.



PHYSICIAN RECOMMENDED

The Jazzy is America’s number one physician recommended power chair, offering innovative technology and proven quality.




ACCESSORIES

From cup holders to flags, a wide array of accessories are available to customize the Jazzy® to the client’s personal preferences.




15% OF AMERICANS
are currently enrolled in Medicare.

18% OF AMERICANS
will be over 65 by the year 2029.



OVER 60 MILLION AMERICANS
are currently beneficiaries of Medicare parts A and B.

■ Top 10 Medicare Beneficiary States



10,000 Baby Boomers

turn 65 every day. With that increase in Medicare beneficiaries comes the increasing demand for more Group 2 powered mobility. Pride is perfectly positioned to offer a premiere product and service to this rapidly expanding market with the Jazzy® Power Chair.

JAZZY AIR® MED

HCPCS Code: **K0830/K0831**
Group 2 Standard, Seat Elevator

MID-WHEEL DRIVE



SPECIFICATIONS

Top Speed: 3.7 mph

Turning Radius: 24.4"

Weight Capacity: 300 lbs.

Range: Up to 14.1 miles at 220 lbs.
and up to 13 miles at 300 lbs.

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 6" solid casters
Drive Wheels: 10" solid
Rear Wheels: 6" solid casters

Ground Clearance: 1" (at motor bracket)

Product Weight: 197.2 lbs. (241.6 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



12" power elevation while driving up to 3.7 mph improves activities of daily living.



Active-Trac® Suspension with Mid-Wheel 6® technology delivers a smooth and stable ride.



Memory foam seating keeps your client comfortable for long rides.

COLOR OPTIONS



Black

JAZZY® 600 ES

HCPCS Code: Group 2: Standard
(K0822/K0823)

SPECIFICATIONS

Top Speed: 4 mph

Turning Radius: 20.5"

Weight Capacity: 300 lbs.

Range: Up to 29.5 miles at 200 lbs.
and up to 24.8 miles at 300 lbs.

Seat Sizes: 18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 6" solid OMNI-Casters

Drive Wheels: 14" foam-filled

Rear Wheels: 6" solid OMNI-Casters

Ground Clearance: 2.75"

Product Weight: 124 lbs. (198 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



50A Dynamic LiNX adjustable speed dial enables the client to adjust speed comfort level.



Active-Trac® ATX Suspension for enhanced performance over more varied terrain.



The Jazzy® 600 ES features a turning radius of 20.5" for superior maneuverability in tight areas.

COLOR OPTIONS



Cardinal Red

JAZZY SELECT®

MID-WHEEL DRIVE



HCPCS Code: Group 2: Standard
(K0822/K0823)

SPECIFICATIONS

Top Speed: 4.3 mph

Turning Radius: 22.5"

Weight Capacity: 300 lbs.

Range: Up to 19.4 miles

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 5" solid casters

Drive Wheels: 10" solid

Rear Wheels: 6" solid casters

Ground Clearance: 0.75" (at motor bracket)

Product Weight: 144.2 lbs. (194.6 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



Batteries can be easily accessed from the side.



Active-Trac® Suspension ensures a smooth ride experience over uneven surfaces.



Flip-up foot platform is height and depth adjustable.

COLOR OPTIONS



Jazzy Red

JAZZY® EVO 613

MID-WHEEL DRIVE



HCPCS Code: Group 2: Standard
(K0822/K0823)

SPECIFICATIONS

Top Speed: 5.1 mph

Turning Radius: 22"

Weight Capacity: 300 lbs.

Range: Up to 17.1 miles at 200 lbs.
and up to 14 miles at 300 lbs.

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 5" solid casters
Drive Wheels: 13" solid
Rear Wheels: 5" solid casters

Ground Clearance: 3" (at motor bracket)

Product Weight: 142 lbs. (189 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



Ultra-narrow base width of only 22" makes navigating small spaces and tight corners a breeze.



Active-Trac® Suspension with Mid-Wheel 6® technology delivers a smooth and stable ride.



Comfort-style memory foam seat with single seat post allows the client to swivel.

COLOR OPTIONS



Black (matte)

Iceberg Blue
(matte)

Red (matte)

Robin's Egg Blue
(matte)

Sugar Plum
(matte)

White (matte)



JAZZY® EVO 614

MID-WHEEL DRIVE



HCPCS Code: Group 2: Standard
(K0822/K0823)

SPECIFICATIONS

Top Speed: 4.4 mph

Turning Radius: 22"

Weight Capacity: 300 lbs.

Range: Up to 21.5 miles at 200 lbs.
and up to 19 miles at 300 lbs.

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 6" solid casters
Drive Wheels: 13.75" perforated
Rear Wheels: 6" solid casters

Ground Clearance: 3" (at motor bracket)

Product Weight: 183.5 lbs. (255.5 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



60A Dynamic LiNX adjustable speed dial enables the client to adjust speed comfort level.



Active-Trac® Suspension with Mid-Wheel 6® technology delivers a smooth and stable ride.



13.75" perforated drive tires

COLOR OPTIONS



Black (matte)



Iceberg Blue (matte)



Red (matte)



Robin's Egg Blue (matte)



Sugar Plum (matte)



White (matte)

JAZZY® EVO 614HD

HCPCS Code: Group 2: Heavy Duty
(K0824/K0825)

MID-WHEEL DRIVE



HEAVY DUTY



SPECIFICATIONS

Top Speed: 4.8 mph

Turning Radius: 22"

Weight Capacity: 450 lbs.

Range: Up to 21.5 miles at 200 lbs.
and up to 13 miles at 450 lbs.

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 6" solid casters
Drive Wheels: 13.75" perforated
Rear Wheels: 6" solid casters

Ground Clearance: 3" (at motor bracket)

Product Weight: 183.5 lbs. (255.5 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



60A Dynamic LiNX adjustable speed dial enables the client to adjust speed comfort level.



Active-Trac® Suspension with Mid-Wheel 6® technology delivers a smooth and stable ride.



13.75" perforated drive tires

COLOR OPTIONS



Black (matte)

Iceberg Blue (matte)

Red (matte)

Robin's Egg Blue (matte)

Sugar Plum (matte)

White (matte)

JAZZY® ELITE HD

HCPCS Code: Group 2: Heavy Duty
(K0824/K0825)

FRONT-WHEEL DRIVE

FWD

HEAVY DUTY



SPECIFICATIONS

Top Speed: 4 mph

Turning Radius: 24"

Weight Capacity: 450 lbs.

Range: Up to 14.4 miles

Seat Sizes: 18"W x 18-20"D
20"W x 18-20"D
22"W x 20-22"D

Front Wheels: 3" solid anti-tips

Drive Wheels: 14" foam-filled

Rear Wheels: 6" solid casters

Ground Clearance: 3" at battery tray

Product Weight: 151 lbs. (225 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



40A Dynamic LiNX adjustable speed dial enables the client to adjust speed comfort level.



14" knobby tires and optimum weight distribution provide superior traction.



Easy rear access to batteries.

COLOR OPTIONS



Jazzy Red



JAZZY® 1450

HCPCS Code: Group 2: Very Heavy Duty (K0826/K0827);
Single Power Very Heavy Duty (K0839)

FRONT-WHEEL DRIVE

FWD

HEAVY DUTY



SPECIFICATIONS

Top Speed: 4.9 mph

Turning Radius: 26.5"

Weight Capacity: 600 lbs.

Range: Up to 16.5 miles

Seat Sizes: 22"W x 20"D
24"W x 20-24"D

Front Wheels: 4" solid anti-tips

Drive Wheels: 14" solid

Rear Wheels: 9" solid casters

Ground Clearance: 1.5" (at anti-tips)

Product Weight: 247 lbs. (351 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



Large flat-free 14" knobby drive tires provide superb traction.



Contoured, black vinyl high-back seat with headrest



Large 17" x 13" foot platform

COLOR OPTIONS



Candy Apple Red

Viper Blue



JAZZY® ELITE 14

HCPCS Code: Group 2: Standard
(K0822/K0823)

SPECIFICATIONS

Top Speed: 4 mph

Turning Radius: 24"

Weight Capacity: 300 lbs.

Range: Up to 21 miles at 200 lbs.
and up to 18 miles at 300 lbs.

Seat Sizes: 18"W x 18-20"D
20"W x 18-20"D
22"W x 20-22"D

Front Wheels: 3" solid anti-tips
Drive Wheels: 14" foam-filled
Rear Wheels: 6" solid casters

Ground Clearance: 3" at battery tray

Product Weight: 151 lbs. (225 lbs. with batteries)



FDA Class II
Medical Device *

HIGHLIGHTS



40A Dynamic LiNX adjustable speed dial enables the client to adjust speed comfort level.



14" knobby tires and optimum weight distribution provide superior traction.



Easy rear access to batteries.

COLOR OPTIONS



Jazzy Red

JAZZY® ELITE ES

HCPCS Code: Group 2: Standard
(K0822/K0823)

FRONT-WHEEL DRIVE

FWD

SPECIFICATIONS

Top Speed: 4 mph

Turning Radius: 24.75"

Weight Capacity: 300 lbs.

Range: Up to 15 miles

Seat Sizes: 16"W x 16-18"D
18"W x 18-20"D
20"W x 18-20"D

Front Wheels: 3" solid anti-tips

Drive Wheels: 9" solid

Rear Wheels: 6" solid casters

Ground Clearance: 1.85" (at motor bracket)


Product Weight: 119 lbs. (169 lbs. with batteries)



HIGHLIGHTS



Flip-up, height adjustable
foot platform



Depth-adjustable, limited recline,
black vinyl high-back seat



Black, flat-free, non-marking tires

COLOR OPTIONS



Candy Apple Red

GO CHAIR® MED

HCPCS Code: Group 2: Standard, Portable
(K0821)

REAR-WHEEL DRIVE

RWD

FEATHER-TOUCH
DISASSEMBLY



SPECIFICATIONS

Top Speed: 3.7 mph

Turning Radius: 25.5"

Weight Capacity: 300 lbs.

Range: Up to 9.4 miles

Seat Sizes: 18"W x 17"D or 20"W x 18"D

Front Wheels: 6" solid casters

Drive Wheels: 9" solid

Rear Wheels: 3" solid anti-tips

Ground Clearance: 1.75" (at motor bracket)

Heaviest Piece: 36 lbs. (rear section)



FDA Class II
Medical Device *

HIGHLIGHTS



One-hand feather-touch disassembly
for quick transport or storage



GC3 controller with
quick disconnect



Large foot platform for
added comfort

COLOR OPTIONS



Black



POWER CHAIR® ACCESSORIES



Cup Holder



Swing-Away Joystick



Rear Basket



Walker Holder



Cell Phone Holder



Cane/Crutch Holder



Lap Belt



Elevating Legrests



Oxygen Tank Holder



Military Patches



Weather Cover



Cushions



Heel Loops



Saddle Bag



XLR USB Charger



Safety Flag



	JAZZY AIR® MED	JAZZY® 600 ES	JAZZY® SELECT	JAZZY® EVO 613
WEIGHT CAPACITY	300 lbs.	300 lbs.	300 lbs.	300 lbs.
TURNING RADIUS³	24.25"	20.5"	22.5"	22"
LENGTH /WIDTH³	42" / 23.25"	35.5" / 24.5"	32.99" / 23.75"	35" / 22"
MAXIMUM SPEED⁸	Up to 4 mph	Up to 4 mph	Up to 4.3 mph	Up to 5.1 mph
GROUND CLEARANCE³	1" at motor bracket	2.75"	0.75" at motor bracket	3" at motor bracket
FRONT WHEELS	6" solid casters	6" solid OMNI-casters	5" solid anti-tips	5" solid casters
DRIVE WHEELS	10" solid	14" foam filled	10" solid	13" solid
REAR WHEELS	6" solid casters	6" solid OMNI-casters	6" solid casters	5" solid
DRIVETRAIN	Two-motor, Mid-Wheel 6®	Two-motor, mid-wheel drive	Two-motor, mid-wheel drive	Two-motor, in-line, mid-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical
SUSPENSION	Active-Trac® (ATX) with Mid-Wheel 6® Technology	Active-Trac® (ATX) Mid-Wheel 6® Technology	Active-Trac® (ATX)	Active-Trac® (ATX)
HIGH-BACK SEAT (max size)	20"W x 20"-22"D	20" W x 20" D	20"W x 20"D	20"W x 18-20"D
HIGH-BACK SEAT-TO-FLOOR RANGE	21.25" - 33"	20.5" - 22.5"	21" - 22"	19.75" - 21.25"
SYNERGY® SEATING	N/A	20"W x 20"D	20"W x 20"D	N/A
SYNERGY® SEAT SEAT-TO-FLOOR RANGE	N/A	15.875" - 17.875"	17.25" - 19.25"	N/A
POWER ELEVATING SEAT⁶	Standard	N/A	N/A	N/A
STANDARD ELECTRONICS	40A, PG VR2	50A, Dynamic LiNX	40A, PG GC3	40A, PG GC3
BATTERY SIZE⁵	(2) 12 volt, U-1 (std.), 40 AH (optional)	(2) 12 volt, NF-22	(2) 12 volt, U-1	EVO 613: (2) 12 volt, U-1 EVO 613 Li: (1) 25.6V, 32.4 Ah lithium iron phosphate
BATTERY CHARGER	Off-board, 5 amp	Off-board, 5 amp	Off-board, 3.5 amp	Off-board, 3.5 amp
RANGE PER CHARGE^{2,8}	Up to 15 miles at 300 lbs. Up to 16.6 miles at 220 lbs.	Up to 29.5 miles @ 200 lbs. Up to 24.8 miles @ 300 lbs.	Up to 19.4 miles	EVO 613 Li: 21 miles @ 200 lbs. EVO 613 Li: 17.6 miles @ 300 lbs. EVO 613: 17.1 miles @ 200 lbs. EVO 613: 14 miles @ 300 lbs.
BATTERY WEIGHT⁴	24.5 lbs. each (U-1) 32.5 lbs. each (40 AH)	37 lbs. each	25.2 lbs. each	EVO 613 Li: 18.5 lbs. EVO 613: 23.5 lbs.
HEAVIEST PIECE WEIGHT³	202 lbs.	124 lbs.	94 lbs.	94 lbs.
STANDARD SEAT WEIGHT	41 lbs.	51.8 lbs.	50.2 lbs.	48 lbs.
STANDARD SEAT SIZE	16"x16-18", 18"x18-20", 20"x20-22"	18"x18-20", 20"x18-20"	16"x16-18", 18"x18-20", 20"x18-20"	16" x 16-18", 18" x 18-20", 20" x 18-20"
HCPCS CODES	K0899*	Group 2: Standard (K0822/K0823)	Group 2: Standard (K0822/K0823)	Group 2: Standard (K0822/K0823)
WARRANTY	Frame: 5-year limited Drive motor: 13-month Electronics: 13-month Batteries: 13-month	Frame: 5-year limited Drive motor: 13-month Electronics: 13-month Batteries: 13-month	Frame: 5-year limited Drive motor: 13-month Electronics: 13-month Batteries: 13-month	Frame: 5-year limited Drive motor: 24-month limited Electronics: 24-month limited Lithium battery: 3-year limited SLA battery: 13-month limited



	JAZZY® EVO 614	JAZZY® EVO 614HD	JAZZY® ELITE HD	JAZZY® 1450
WEIGHT CAPACITY	300 lbs.	450 lbs.	450 lbs.	600 lbs.
TURNING RADIUS³	22"	22"	24"	26.5"
LENGTH /WIDTH³	40.5" / 25.4"	40.5" / 25.4"	35.5" / 24.25"	38.25" / 29.25"
MAXIMUM SPEED⁸	Up to 4.4 mph	4.8 mph)	Up to 4 mph	Up to 4.9 mph
GROUND CLEARANCE³	3"	3"	3" at battery tray	1.5" at anti-tips
FRONT WHEELS	6"	6"	3" solid anti-tips	4" solid anti-tips
DRIVE WHEELS	13.75" perforated	13.75" perforated	14" foam filled	14" solid
REAR WHEELS	6"	6"	6" solid casters	9" solid casters
DRIVETRAIN	Two in-line HD motors	Two in-line HD motors	Two-motor, in-line, front-wheel drive	Two-motor, front-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical
SUSPENSION	Full independent front & rear Active-Trac® ATX Suspension	Full independent front & rear Active-Trac® ATX Suspension	Limited	Swing Arm
HIGH-BACK SEAT (max size)	20"x18-20" (HD: 24"x22-24")	20"x18-20" (HD: 24"x22-24")	22" W x 22" D	32" W x 28" D
HIGH-BACK SEAT-TO-FLOOR RANGE	22" - 24"	22" - 24"	20" - 22"	20.5" - 22.5"
SYNERGY® SEATING	N/A	N/A	24"W x 24"D	32" W x 28" D
SYNERGY® SEAT SEAT-TO-FLOOR RANGE	N/A	N/A	15.75" - 17.75"	17.25" - 19.25"
POWER ELEVATING SEAT⁶	N/A	N/A	N/A	N/A
STANDARD ELECTRONICS	60A Dynamic Linx	60A Dynamic Linx	50A, Dynamic LiNX	90A, PG VR2
BATTERY SIZE⁵	(2) NF-22	(2) NF-22	(2) 12 volt NF-22	(2) 12 volt, Group 24
BATTERY CHARGER	Off-board, 5 amp	Off-board, 5 amp	Off-board, 5 amp	Off-board, 8 amp
RANGE PER CHARGE^{2,8}	Up to 19 miles at 300 lbs. Up to 21.5 miles at 200 lbs. (HD: Up to 13 miles at 450 lbs. Up to 21.5 miles at 200 lbs.)	Up to 19 miles at 300 lbs. Up to 21.5 miles at 200 lbs. (HD: Up to 13 miles at 450 lbs. Up to 21.5 miles at 200 lbs.)	Up to 14.4 miles	Up to 16.5 miles
BATTERY WEIGHT⁴	36 lbs. each	36 lbs. each	37 lbs. each	52 lbs. each
HEAVIEST PIECE WEIGHT³	125.7 lbs.	125.7 lbs.	99 lbs.	195 lbs.
STANDARD SEAT WEIGHT	57.8 lbs.	57.8 lbs.	51.8 lbs.	52 lbs.
STANDARD SEAT SIZE	16"x16-18", 18"x18-20", 20"x18-20"; (HD: 18"x18-20", 20"x18-20", 22"x20-22", 24"x22-24")	16"x16-18", 18"x18-20", 20"x18-20"; (HD: 18"x18-20", 20"x18-20", 22"x20-22", 24"x22-24")	18"x18-20", 20"x18-20", 24"x24"	22"x20"- 24"x24"
HCPCS CODES	Group 2: Standard (K0822/K0823); (614HD: Group 2: Heavy Duty (K0824/K0825)	Group 2: Standard (K0822/K0823); (614HD: Group 2: Heavy Duty (K0824/K0825)	Group 2: Heavy Duty (K0824/K0825)	Group 2: Very Heavy Duty (K0826/K0827), Single Power Very Heavy Duty (K0839)
WARRANTY	Frame: 5-year limited Drive motor: 13-month limited Electronics: 13-month limited Batteries: 13-month limited	Frame: 5-year limited; Drive motor: 13-month limited Electronics: 13-month limited Batteries: 13-month limited	Frame: 5-year limited Drive motor: 13-month Electronics: 13-month Batteries: 13-month	See footnote 9



	JAZZY® ELITE 14	JAZZY® ELITE ES	GO CHAIR® MED
WEIGHT CAPACITY	300 lbs.	300 lbs.	300 lbs.
TURNING RADIUS³	24"	24.75"	25.5"
LENGTH /WIDTH³	35.5" / 24.25"	34.75" / 22.75"	28.5" / 22.5"
MAXIMUM SPEED⁸	Up to 4 mph	Up to 4 mph	Up to 3.7 mph
GROUND CLEARANCE³	3" at battery tray	1.85" at motors	1.75" at motor
FRONT WHEELS	3" solid anti-tips	3" solid anti-tips	6" solid casters
DRIVE WHEELS	14" foam filled	9" solid	9" solid
REAR WHEELS	6" solid casters	6" solid casters	3" solid anti-tips
DRIVETRAIN	Two-motor, front-wheel drive	Two-motor, in-line, front-wheel drive	Two-motor, rear-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical
SUSPENSION	Limited	Limited	Limited
HIGH-BACK SEAT (max size)	20"W x 20"D	20" W x 20" D	N/A
HIGH-BACK SEAT-TO-FLOOR RANGE	20" - 22"	21.5" - 23.5"	N/A
SYNERGY® SEATING	20"W x 20"D	N/A	N/A
SYNERGY® SEAT SEAT-TO-FLOOR RANGE	15.75" - 17.75"	N/A	N/A
POWER ELEVATING SEAT⁶	N/A	N/A	N/A
STANDARD ELECTRONICS	50A, Dynamic Linx	40A, PG GC3	40A, PG GC3
BATTERY SIZE⁵	(2) 12 volt, NF-22	(2) U-1	(2) 18 AH, 12 volt, deep-cycle
BATTERY CHARGER	Off-board, 5 amp	Off-board, 3.5 amp	Off-board, 2 amp
RANGE PER CHARGE ^{2,8}	Up to 21 miles @ 200 lbs. Up to 18 miles @ 300 lbs.	Up to 15 miles	Up to 8.6 miles
BATTERY WEIGHT⁴	37 lbs. each	25 lbs. each	14 lbs. each
HEAVIEST PIECE WEIGHT³	99 lbs.	69 lbs.	36 lbs.
STANDARD SEAT WEIGHT	51.8 lbs.	50.2 lbs.	29 lbs. (18" compact foldable)
STANDARD SEAT SIZE	18"x18- 20", 20"x18-20", 22"x20-22"	16"x16-18", 18"x18-20", 20"x18-20"	18"x17", 20" x 18"
HCPCS CODES	Group 2: Standard (K0822/K0823)	Group 2: Standard (K0822/K0823)	Group 2: Standard, Portable (K0821)
WARRANTY	Frame: 5-year limited Drive motors: 13-month Electronics: 13-month Batteries: 13-month	Frame: 5-year limited Drive motors: 13-month Electronics: 13-month Batteries: 13-month	Frame: 5-year limited Drive motors: 13-month Electronics: 13-month Batteries: 13-month

LEARN MORE ABOUT OUR EXCITING RETAIL OPTIONS AT PRIDEMOBILITY.COM



JAZZY® ULTRA LIGHT

Weighing only 33 lbs. without the battery, folds and unfolds in just seconds and features a programmable joystick.

1 Color Option:



GO CHAIR®

Features one-hand feather-touch disassembly for quick transport or storage.

6 Color Options:



JAZZY® AIR® 2

Safely elevates up to 12" (while driving up to 4 mph) for improved face-to-face social engagement.

8 Color Options:



JAZZY® CARBON

Quickly folds flat for transport or storage, with a weight of only 39 lbs. without battery.

2 Color Options:





800.800.8586

| pridemobility.com



-
- 1 Pride® Power Chairs are FDA Class II Medical Devices designed to aid individuals with mobility impairments.
 - 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
 - 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
 - 4 Battery weight may vary based on battery manufacturer.
 - 5 AGM or gel cell type required.

- 6 Maximum weight capacity is reduced to 400 lbs. (181 kg) on 18" deep seat configurations.
- 7 Seat weight included. Unit does not disassemble.
- 8 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 9 K0826/K0827 Models: Lifetime limited on frame; 13-month limited on electronics; 13-month limited on drive motors; 13-month on batteries. K0839 Model: Lifetime limited on frame; 2-year limited on electronics; 18-month limited on drive motors; 13-month on batteries.
- 10 Not all accessories are available for all products. Please speak with your Provider for details and availability.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for power chair only. Overall measurements will vary based on seating and accessory selections.

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

* K0899 - power mobility device, not coded by DME PDAC.