


Specifications



Model	GS-3384 RT	
Measurements	US	Metric
Working height maximum ¹	39 ft	12.06 m
▲ Platform height maximum	33 ft	10.06 m
▲ Platform height - stowed ²	5 ft 1 in	1.55 m
▲ Platform length:		
outside, extended - single deck	12 ft 11.25 in	3.94 m
outside, extended - dual deck	17 ft 6.25 in	5.34 m
▲ Slide-out platform extension deck - front	5 ft	1.52 m
▲ Slide-out platform extension deck - rear	4 ft	1.22 m
▲ Platform width - outside	6 ft	1.83 m
▲ Height - stowed: folding rails	8 ft 9.5 in	2.68 m
rails lowered	6 ft 6.75 in	2.0 m
▲ Length - stowed: single deck	12 ft 11.25 in	3.94 m
dual deck	13 ft 0.5 in	3.98 m
with outriggers	16 ft	4.88 m
▲ Width: standard tires	7 ft	2.13 m
high flotation tires	7 ft 11 in	2.41 m
▲ Wheelbase	9 ft 4 in	2.84 m
▲ Ground clearance - center	13 in	.33 m

Productivity

Maximum platform occupancy	7	7
Lift capacity	2,500 lbs	1,134 kg
Lift capacity - extension deck	500 lbs	227 kg
Drive height	full height	
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised	0.7 mph	1.1 km/h
Gradeability - stowed ³	50%	
Maximum outrigger leveling: front to back	7°	
side to side	12°	
Turning radius - inside	10 ft 1.5 in	3.09 m
Turning radius - outside	19 ft 6 in	5.94 m
Raise/lower speed	45/29 sec	
Controls	proportional	
Drive	four wheel	
Tires - foam-filled rough terrain	10 x 31 in	25 x 79 cm

Power

Power source	Ford MSG-425 4 cylinder gas/LPG 75 hp (56 kW) Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW) air cooled	
Auxiliary Power unit	12 V DC	
Fuel tank capacity	30 gal	113.6 L
Hydraulic system capacity	30 gal	113.6 L

Weight⁴ / Floor Loading⁵

Weight - ANSI/CSA	11,825 lbs	5,364 kg
- with outriggers	13,500 lbs	6,124 kg
Tire load, maximum	4,689 lb	2,127 kg
Tire contact pressure	129 psi	886 kPa
Occupied floor pressure	177 psf	8.49 kPa

Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

¹ The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

² Based on RT tires; deduct 2 in (5.8 cm) for turf and non-marking tires.

³ Gradeability applies to driving on slopes. Gradeability may vary depending on the weight of options installed on machine. See operator's manual for details regarding slope ratings.

⁴ Weight varies depending on options and country standards.

⁵ Note: Floor loading information is approximate and does not incorporate different option configurations. It should be used only with adequate safety factors.

Features

Standard Features

Measurements

- 39 ft (12.06 m) working height
- Up to 2,500 lbs (1,134 kg) lift capacity

Productivity

- 156.5 x 72 in (3.98 x 1.83 m) steel frame platform
- 60 in (1.52 m) extension deck
- Replaceable aluminum diamond plate deck
- Drive at full height
- Folding rails
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Full height swing gate
- Two self-closing gates
- 4WD
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires
- Tilt level sensor with audible alarm
- Dual flashing LED beacons
- Descent alarm
- Horn
- Hour meter
- Motion alarm

Power

- 48 hp (36 kW) Deutz D2.9L4 diesel, Tier 4f


Options & Accessories

Productivity Options

- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Automatic leveling hydraulic outriggers
- Air line to platform
- Foam filled non-marking rough terrain tires
- High flotation air-filled tires
- High flotation foam-filled tires
- Biodegradable hydraulic oil
- Platform control guard

Power Options

- 75 hp (56 kW) Ford MSG 425 gas/LPG
- AC, 2000 Watt generator (120 V / 60 Hz), (includes hydraulic oil cooler)
- Cold weather package
- Hydraulic oil cooler
- Diesel catalytic scrubber muffler
- LPG steel tank only, 33.5 lb capacity



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By: