



## SYNCHRONIZED VIBRANT COLOR

## **Apelo Light Controller**

Transform your space into a stunning visual display, with unified control of all Apelo RGB/W Underwater, Interior, Flood, and Courtesy lamps; plus a selection of universal RGB products.

Effortlessly group and intelligently network multiple sets of lights and controllers wirelessly over Bluetooth® Mesh. Then show your true colors with fully synchronized, completely customizable lighting throughout your vessel.



## Apelo Light Controller App

Pair the Apelo App with the Apelo Light Controller for infinite creativity and control of all compatible connected RGB/W lighting.

Enjoy the convenience of centralized control in the palm of your hand. Whether you have a smaller pleasure craft, or large luxury vessel, Bluetooth® Mesh ensures easy, wireless control from anywhere on board.

Use the intuitive Apelo App to easily manage multiple controllers and light groups, access built-in presets, and express yourself with vivid colors and vibrant custom lighting sequences throughout your craft.

#### No Phone? No Worries...

Directly wired Switch control allows for simple cycling through color modes; press and hold, and the lights will dim or brighten. Switch control can be used alongside the Apelo Light Controller and Apelo App.

### Control more than just RGB

Apelo Light Controller is also able to manage single color, dual color, dual function, and dual intensity lights such as EuroLED 75/95, dual intensity Sea Hawk XLR floodlights, and Sea Hawk Light bars.







iPhone and App Store are registered trademarks of Apple Inc. Google Play is a registered trademark of Google Inc.



Scan or Click for more info

# APELO CONTROLLER BRINGS IT ALL TOGETHER

## Control


Connect Apelo Light Controllers to any combination of compatible Apelo RGB and RGB/W Underwater, Interior, Flood, and Courtesy lamps for individual and/or synchronized control. Easily adjust a single light or trigger a color pattern throughout an entire grouping.

## Group

Use the intuitive Apelo App to easily group multiple lights and manage multiple controllers (individually, or groups containing multiple controllers and lights), to create areas of unique colors and functions throughout your vessel. All without additional wiring.

## Create

Make it as simple or as advanced as you like: from basic colored mood and safety lighting, to a multicolor, animating entertainment area synced with underwater lights, while also preserving the captain's night vision with red downlighting at the controls.





Enhance your marine entertainment lighting with the most powerful light in its class, the Apelo A1. Delivering vibrant blue or intense white, or full spectrum RGB color experiences, the A1 uses intelligent optical design to get impressive illumination levels that outshine the competition.

The A1 RGB light gives you complete control to choose any color you wish, with Apelo's optical intelligence creating an even distribution of color across the transom.

A completely sealed, corrosion resistant, thermal polymer housing ensures ongoing protection against the harshest environments. The A1 is suitable for mounting to any hull material. All Apelo models are equipped with an advanced thermal management system to allow operation in or out of the water.

Apelo Underwater Lights are made in New Zealand, and built to last.





Scan or Click for more info



#### Thermal Polymer Housing

Function	Lens	Part Number
Dual Blue / White	White	016145011
Dual Blue / White	Charcoal	016145001
RGB	White	016146011
RGB	Charcoal	016146001

See page 10-11 for full specifications.



The Apelo A2 offers bright 3000-lumen light output, plus additional features including a stylish Edge Light.

Available in Blue / White or full-spectrum RGB, the A2's Blue / White version includes a 'Fish mode' strobe function that's sure to attract attention, including from your next big catch. RGB allows for any color selection.

The corrosion-resistant, anodized aluminum housing is designed for aluminum hulls, boats that aren't permanently submerged, or vessels at mooring.

For permanent submersion, the marine-grade bronze housing option provides superior durability and thermal management, and is suitable for fiberglass, timber, steel, and composite hulls.

† Marine grade bronze models should only be used on aluminum hulls with an Apelo Surface Mount Spacer, or suitable isolation spacer.

Apelo Underwater Lights are made in New Zealand, and built to last.





Scan or Click for more info











#### Hard Anodized Aluminum Housing

Function	Lens	Part Number
Dual Blue / White	Charcoal	016147001
RGB	Charcoal	016148001

#### Marine Grade Bronze Housing

Lens	Part Number
White	016147101
White	016148101
	White

See page 10-11 for full specifications.



The ultimate in the Apelo Underwater Light range is the A3 Bronze. Supercharged with 6000 lumen light output, and a larger overall size than the Apelo A2 Bronze.

The A3 model has an improved formula with double the light output, maximizing the vibrant blue or intense white, or full spectrum RGB/W color. The blue or white model retains the strobe functionality, the RGB/W version includes dedicated white light emitting LEDs, adding brighter and more intense white light to your RGB underwater lighting. Both versions offer the Edge Light function.

Intelligent optics spread light across the water without losing light to the depths, projecting wide across the transom. With the addition of Nickelsilver to the extremely corrosion resistant housing, the Apelo A3 is perfect for permanently submerged installations on larger boats or yachts. Suitable for fiberglass, timber, steel, and composite hulls. Only mount on aluminum hulled vessels with a suitable isolation spacer.

Apelo Underwater Lights are made in New Zealand, and built to last.





Scan or Click for more info











Function	Lens	Part Number
Dual Blue / White	White	016830001
RGB/W	White	016831001

See page 10-11 for full specifications.



A downlight with no compromise to form or function, the Apelo EuroLED 75 RGB/W delivers full spectrum color, plus bright, even, broad illumination of 150 lumens from dedicated White LED's. Whether you're setting the mood with vivid colors, or preserving your sensitive night vision with illuminating red, the Apelo EuroLED 75 RGB/W is a powerfully flexible lighting solution.

Single and dual color models also available.





Scan or Click for more info













#### **Round Lights**

Function	Trim	Connector	Pack Qty	Part Number
RGB/W	White	Tinned marine cable	Single	017884001
RGB/W	White	Tinned marine cable	Bulk (20)	017884007
RGB/W	White	4 Pin + 2 Pin DT	Bulk (18)	017884207
RGB/W	Stainless	Tinned marine cable	Single	017884011
RGB/W	Stainless	Tinned marine cable	Bulk (20)	017884017
RGB/W	Stainless	4 Pin + 2 Pin DT	Bulk (18)	017884217

#### **Square Lights**

Function	Connector	Pack Qty	Part Number
RGB/W	4 Pin + 2 Pin DT	Bulk (18)	015072607

EuroLED 75 RGB/W Square downlights are only available in Bulk packs, and are supplied without trims. Please also include compatible square trims when ordering. See page 10-11 for full specifications.

#### **Square Trims**

Function	Trim	Pack Qty	Part Number
Accessory	Matte Black	Bulk (30)	241487107
Accessory	Brushed Chrome	Bulk (30)	241487217



## Apelo RGB Step Lamp

Apelo RGB Step lamps offer a vibrant way to highlight and accent your steps and gangways. Dynamic, synchronized colors will transform your space into a stunning visual display.

Apelo RGB Step Lamps use a simple, 4-wire connection for power and control. Labor saving installation is via a 25mm hole, also allowing for DT connector use. Available with chrome, white or stainless steel trim.





Scan or Click for more info











Function	Trim	Connector	Pack Qty	Part Number
RGB	White	Tinned marine cable	Single	958126531
RGB	White	Tinned marine cable	Bulk (54)	958126537
RGB	White	4 pin DT Connector	Bulk (54)	958126507
RGB	Chrome	Tinned marine cable	Single	958126541
RGB	Chrome	Tinned marine cable	Bulk (54)	958126547
RGB	Chrome	4 pin DT Connector	Bulk (54)	958126517
RGB	Stainless	Tinned marine cable	Single	958126551
RGB	Stainless	Tinned marine cable	Bulk (54)	958126557
RGB	Stainless	4 pin DT Connector	Bulk (54)	958126527

See page 10-11 for full specifications.

## **Apelo Ecosystem Specifications**









		Apelo Light Controller	Euro	EuroLED 75 RGB/W Downlight (Round & Square)			Apelo RGB Step Lamp	
ESCRIPTION	White Plastic	<b>285814001</b> Single Pack	017884001 017884007 017884207		NA	958126531 958126537 958126507	Bulk Pack	
	Chrome Plated Plastic	NA		NA	NA	958126541 958126547 958126517	Single Pack Bulk Pack Bulk Pack - DT	
TRIM DESCRI	Stainless Steel	NA	017884011 017884017 017884217		NA	958126551 958126557 958126527	Bulk Pack	
	No Bezel	NA		NA	<b>015072607</b> Bulk Pack - DT <sup>‡</sup>		NA	
Bul	k Pack Quantity	30		Bulk: 20 / Bu	lk DT: 18	54		
Мо	unting	Surface Mount		Recess	ed	Recessed		
Voltage Multivolt™		Multivolt™ 12 / 24V DC Nominal	12V DC only (9-16V)		Multivolt™ 12 / 24V DC Nominal			
Power Handling (		150W / 13A @ 12V DC (6.5A @ 24V DC) (3A Per channel)	NA		NA			
Pov	wer Consumption	1W	3W RGB (0.25A @ 12V DC) 3W White (0.25A @ 12V DC)		1W / 0	0.03A (30 mA) MAX		
Lur	men Light Output	NA	150 lumen measured output (White)		NA			
Bea	am Angle	NA		90° spread		30° downward lighting angle		
Pro	tection	IP67 (Completely sealed)	IP6K7 & IP6K9K (Completely sealed)		IP67 (Completely sealed)			
Cal	ole Length	140mm tinned marine cable	120mm tinned marine cable		100mm tinned marine cable			
Connector NA (DT Models)		4 Pin + 2 Pin DT Connector (Applicable Models)			n DT Connector olicable Models)			
Lens Material NA		NA	PC		UV resistant enhanced impact acrylic			
Bas	se Material	V0 Rated Plastic	UV resistant enhanced impact acrylic			NA		
Cor	Compliance F© C € ĽK 👂 🙆 C € ĽK 💩			C	€ EK 💩			

<sup>‡</sup> Euro LED 75 RGB/W Square lamps are only available as a Bulk packs, and are supplied without trims. Please also include compatible square trims when ordering. See Page 9 for trim options.

#### EuroLED 75 RGB/W Light Controller RGB Step Lamp (Diagrams not to scale) Dimensions Round Square (with Trim) a = 60 mm (2.4") a = 63mm (2.5")a = Ø75mm (3.0") Dia a = 45mm (1.8") b = 129mm (5.1")b = Ø54mm (2.2") Dia b = 16 mm (0.7")b = 31.5mm (1.3")c = 117mm (4.6")c = 21mm (0.9")c = Ø50 mm (2.0") Dia c = 25.4mm (1.0")d = 7.4mm (0.3") d = 14mm (0.6")d = 30mm (1.2")d = 22mm (0.9")e = 22.7mm (0.9")












	Apelo A1 Polymer	Apelo A2 Aluminum Apelo A2 Bronze		Apelo A3 Bronze	
Blue / White - White Lens	016145011	NA	016147101	016830001	
Blue / White - Charcoal Lens	0141/5001		NA	NA	
RGB - White Lens	016146011	NA	016148101	<b>016831001</b> (A3 models are RGB/W)	
RGB - Charcoal Lens	016146001	016148001	016148001 NA		
Mounting		Surface /	Transom		
Voltage		Multivolt™ 12 /	24V DC Nominal		
Power Consumption† Blue / White RGB / RGB/W* Edge Light	20W / 1.7A @ 12V, 0.9A @ 24V 15W / 1.25A @ 12V, 0.7A @ 24V NA	30W / 2.5A @ 12V, 1.3A @ 24V 30W / 2.5A @ 12V, 1.3A @ 24V <2W / <0.2A@12V, <0.1A @ 24V	70W / 5.9A @ 12V, 2.9A @ 24V 70W / 5.9A @ 12V, 2.9A @ 24V <5W / 0.37A @12V, 0.2A @ 24V 6000 lumen (White only)		
Lumen Light Output	Lumen Light Output 1800 lumen (White only) 3000 lumen (White only)				3000 lumen (White only)
Beam Angle		90° :	x 24°		
Protection	Spike protected to +500 volts, Reverse polarity protected to -700 volts.  IP68 / IP69: Suitable for submersion in operation and high pressure water jet cleaning  High temperature electrical thermal cutout for out of water operation or use				
Cable Length		2.5m / 8.2ft, tinn	ned marine cable		
Lens Material	Grilamid® (Premium grade, UV stable, impact resistant Nylon)				
Base Material	Corrosion proof advanced thermal polymer	Hard anodized aluminum	Marine grade bronze	Marine grade bronze	
Compliance		C€ E	K A		

 $<sup>\</sup>dagger$  Allow up to 200% of power consumption to account for momentary peak.

#### Apelo Surface Mount Spacer




Dimensions a = Ø125mm (5.0") Dia b = 45mm (1.8") c = Ø95mm (3.8") Dia d = Ø83.5mm (3.4") PCD e = 35mm (1.4")

 $f = \emptyset 5.5 mm (0.3")$ 



#### Apelo A1 / A2




(Diagrams not to scale)

a = 23.5mm (0.9")b = Ø95mm (3.8") Dia

c = Ø16mm (0.7") Cable Hole Dia d = 83.5mm (3.3") Mounting PCD

#### Apelo A3



a = 23.5mm (0.9")

 $b = \emptyset 130 \text{mm} (5.1") \text{ Dia}$   $c = \emptyset 16 \text{mm} (0.7") \text{ Cable Hole Dia}$ 

d = 117.5mm (4.6") Mounting PCD

#### **Surface Mount Spacer Accessory**

#### 280801001

Note: Apelo Surface mount spacer only fits Apelo A1 & A2 lamps.





Hella marine USA

Phone (770) 631-7500 Email gary.stidham@forvia.com For Distributors in other regions, please visit hellamarine.com

See the Apelo Ecosystem









