

# TIP SHEET


For Jambette spray paint touch-ups.

Here are a few rules to follow to ensure the success of your paint touch-up repair job.

## Weather conditions


They will be decisive for the longevity and proper execution of your work.

### DO NOT PAINT:



**If it's too hot,**  
*(above 30 degrees Celsius or 86 degrees Fahrenheit) the paint will dry too quickly.*

**If it's too cold,**  
*(below 10 degrees Celsius or 50 degrees Fahrenheit) the paint won't dry fast enough.*



**If it rains,**  
the paint won't dry.

In all 3 cases, you run the risk of cracks, blisters, etc. appearing.

## Execution

Prep your parts. Using masking tape (usually green or white), newspaper, old rags or such, protect any areas that may be exposed to unintended spray during painting.

## Metal pickling

Using a wire brush or mechanical tool, vigorously scrub rusted metal to get rid of corrosion. Grind the part with a fine abrasive such as steel wool or emery cloth to help adhesion.

## Cleaning

Remove sanding dust with a soft-bristled brush, vacuum cleaner or soft cloth before painting.

## Primer application

Primer is usually grey or white. As an undercoat, it provides better protection against rust (stir well to ensure correct mixing).

## Paint application

Once all is dry and after shaking your spray can, apply successive thin coats of paint, generally between three and five times, depending on the colour and quality of the post, until it is covered.

## Lastly

Make sure that children do not have access to the play area while it is drying, and that staff are notified beforehand.