

# HYOSUNG

# MX7600XLD

## Hyosung's proven, reliable, full-function ATM.

Designed to provide unprecedented reliability, the **7600** series is unparalleled in the market. The **MX7600XLD** through-the-wall drive-up ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. It's high uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company.

## Features

---

### Highest Availability

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime. The **MX7600XLD** is designed to provide reliability that is unequalled in the market, with minimum maintenance and maximum up time.

### Flexibility

The **7600** series can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

### Capacity

High capacity, cash dispense capability and the ability to support large volume transactions, makes the **MX7600XLD** a high capacity machine.

### Security Options

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, anti-skimming, white-listing, and encryption.



# HYOSUNG

# MX7600XLD

## Specifications

### Dimensions

- Height: 1574mm (54.4")
- Width: 1058mm (28.4")
- Depth: 990mm (40.6")
- Weight: 1299kg (1978lbs)

### Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 25% – 85%

### System Platform

- Microsoft Windows® 10

### Customer Interface

- 15" TFT LCD
- Input method – touch screen
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – EMV compliant, DIP

### Media Handling

- **Cash Dispenser**
  - Configurable denominations up to 4 cassettes
  - 3,000 notes per cassette
  - Bundle present, bundle retract
- **Cash & Check In Module (CCIM)**
  - Maximum capacity 50 checks/cash per bundle per transaction
  - Check cassette capacity 2000 note (CCIM)
  - Cash cassette capacity 2000 note (CCIM)
  - Reject and retract capability

### Security

- Safe – UL291 Level-1
- Alarm – Seismic + Heat
- Locking Device – Electronic, mechanical combination lock, KABA Mas Cencon
- Security camera

### Printer

- 3.1" graphical thermal receipt printer

### Servicing

- Rear access
- State of health indicators for all modules

### Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

### Additional Features

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.