



CONSTRUCTION & INDUSTRIAL



LentusLLC.com

Sales@LentusLLC.com

+1-270-765-2212

400 Ring Road, Suite 101
Elizabethtown, KY 42701

Table Of Contents

Lentus History	3
DOWSIL™ Sealants	4
DOWSIL™ Fluid	7
Dow Propylene Glycols	8
LENTEK™ Sealants	9
GREAT STUFF™ Foams	10
GREAT STUFF™ Work Wipes & Gloves	11
GREAT STUFF™ Dispensing Guns	12
FROTH-PAK™ Foams	12
Lucas Oil	13




Lentus History

1965

Jim Hartlage (Lentus Founder) began working as a Lab Technician for Dow Corning in Elizabethtown, KY

1970

Jim founded Accumetric, the first authorized repackager of Dow Corning Silicone Sealants



2011

Dow Corning approached Jim and Jud Hartlage (Lentus President) to become Master Distributor for Dow Corning Silicones

2012

Lentus is founded on July 1



DOWSIL™ 732 Multi-Purpose Sealant

One-component, acetoxy-cure adhesive sealant engineered for general industrial sealing and bonding applications. Features extensive technical specifications for more-regulated applications.

- Non-sag, paste consistency
- Easy to apply
- Cures to a tough, flexible rubber
- Good adhesion to many substrates
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, NSF 51, and NSF 61 requirements
- UL Listed
- Available in 90 mL, 139 mL, 300 mL, 17.7 KG, and 205 KG

PART N°	SIZE	COLOR	CASE / PALLET
1891961	90 mL	Aluminum	12 / 3,000
99179259	300 mL	Aluminum	12 / 1,296
2112531	90 mL	Black	12 / 3,000
99179209	300 mL	Black	12 / 1,296
3138356	90 mL	Clear	12 / 3,000
99179271	300 mL	Clear	12 / 1,296
3140717	90 mL	White	12 / 3,000
99179246	300 mL	White	12 / 1,296



DOWSIL™ 700 Industrial Grade Silicone Sealant

Designed for general industrial sealing and adhesive applications. Cost-effective alternative to DOWSIL™ 732 for less regulated applications.

- One-part room temperature cure
- 100% silicone, free of any petroleum distillates
- Resistant to weathering and adverse conditions
- Ideal for caulking, bonding, adhering, and formed-in-place gasketing
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 food contact requirements
- UL 94 HB Compliant (low-flammability)

PART N°	SIZE	COLOR	CASE / PALLET
4060123	300 mL	Aluminum	12 / 1,296
4060067	300 mL	Clear	12 / 1,296
4060071	17.4 KG	Clear	1 / 24
4060070	205 KG	Clear	1 / 4
4060069	300 mL	Black	12 / 1,296
4060122	17.4 KG	Black	1 / 24
4063559	205 KG	Black	1 / 4
4060068	300 mL	White	12 / 1,296
4066044	205 KG	Red	1 / 4



DOWSIL™ 733 Glass & Metal Sealant

Conventional one-part, acetoxy RTV designed for use in OEM bonding and sealing applications, including appliances, heavy equipment, recreational vehicles, and marine equipment. Also excels in general industrial sealing and bonding applications.

- Enhanced unprimed adhesion to cleaned substrates including glass, metals, and plastics
- Good resistance to weathering, vibration, moisture, ozone, and extreme temperatures
- Easy to apply
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, NSF 51, and NSF 61 requirements
- UL Listed

PART N°	SIZE	COLOR	CASE / PALLET
99179264	300 mL	Aluminum	12 / 1,296
99179189	300 mL	Black	12 / 1,296
99179322	300 mL	Clear	12 / 1,296
2468379	17.7 KG	Clear	1 / 24
99179245	300 mL	White	12 / 1,296
2468336	17.7 KG	White	1 / 24



DOWSIL™ 734 Flowable Sealant

Designed for general industrial sealing and bonding applications requiring a flowable, self-leveling product. Particularly suitable for sealing assemblies with fine joints as well as cable entries and connectors to ensure they remain watertight.

- Flowable and self-leveling
- Cures to a tough, flexible rubber at room temperature
- Easy to apply, one-part acetoxy cure
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, and NSF 51 requirements
- UL Listed

PART N°	SIZE	COLOR	CASE / PALLET
4102963	90 mL	Clear	12 / 3,000
99179310	300 mL	Clear	12 / 1,296
4102353	18.1 KG	Clear	1 / 24
4101950	204.1 KG	Clear	1 / 4
4102964	90 mL	White	12 / 3,000
99179270	300 mL	White	12 / 1,296
4102341	18.1 KG	White	1 / 24



DOWSIL™ 736 Heat Resistant Sealant

Non-slumping sealant designed for sealing and bonding applications exposed to temperatures as high as 600° F. Ideal for sealing and encapsulating heating elements in appliances, aerospace gasketing, moving oven belts, and bag filters on smoke stacks.

- One-component silicone that will not sag or run
- May be applied overhead or on side walls
- Designed to meet MIL-A-46106 Rev. B Spec
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 requirements
- UL 94 HB Compliant (low-flammability)

PART N°	SIZE	COLOR	CASE / PALLET
2423472	90 mL	Red	12 / 3,000
99179248	300 mL	Red	12 / 1,296
3145824	17.7 KG	Red	1 / 24
4023912	205 KG	Red	1 / 4



DOWSIL™ 786 Silicone Sealant

Silicone rubber sealant for nonporous surfaces, showers, tubs, sinks, and plumbing fixtures where conditions of high humidity and temperature extremes exist. Excellent as ceramic tile grouting.

- Cured sealant is mildew-resistant
- Remains permanently flexible without shrinking, cracking, crumbling, or drying out
- Resists staining, spotting, or color changes
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 requirements

PART N°	SIZE	COLOR	CASE / PALLET
99179247	300 mL	Clear	12 / 1,296
99179249	300 mL	Trans White	12 / 1,296
99179321	300 mL	White	12 / 1,296
4011651	17.7 KG	White	1 / 24



DOWSIL™ Hi-Temp Sealant Red

High temperature, acetoxy cure silicone sealant with iron oxide to resist extreme heat exposure. Sealing fired heaters, access doors and flanged pipe joints, flues on gas appliances, heating elements in appliances, plywood drying oven doors, and windows in oven doors.

- Cures to 100% silicone rubber
- Resistant to sunlight and weather extremes
- Fast cure, high strength
- Performs in high temperatures applications, up to 500° F (260° C) continuously, and 550° F (288° C) intermittently

PART N°	SIZE	COLOR	CASE / PALLET
99150445	90 mL	Red	12 / 3,000
4045040	305 mL	Red	12 / 1,296



DOWSIL™ Tub/Tile/Ceramic Sealant

Silicone rubber sealant for nonporous surfaces, showers, tubs, sinks, and plumbing fixtures. Can be used where conditions of high humidity and temperature extremes exist.

- Cured sealant is mildew resistant
- Resists staining, spotting, and color changes
- Meets FDA Reg 21 CFR 177.2600 requirements
- Remains permanently flexible without shrinking, cracking, crumbling, or dying out

PART N°	SIZE	COLOR	CASE / PALLET
4045034	305 mL	Almond	12 / 1,296
99150433	90 mL	Clear	12 / 3,000
4045036	305 mL	Clear	12 / 1,296
4045038	305 mL	Trans White	12 / 1,296
99150434	90 mL	White	12 / 3,000
4045039	305 mL	White	12 / 1,296



DOWSIL™ 730 FS Solvent Resistant Sealant

Solvent resistant silicone adhesive/sealant. For bonding and sealing applications where resistance to the swelling effects of fuels, solvents, and oils is required.

- One-component fluorosilicone adhesive/sealant
- Cures at room temperature when exposed to moisture in the air
- Non-sag, paste consistency
- Easy to apply
- Cures to a tough, flexible rubber

PART N°	SIZE	COLOR	CASE
4097353	90 mL	White	12
4097354	170 mL	White	12
4095684	23 KG	White	1



Neutral Cure

DOWSIL™ 832 Multi-Surface Adhesive Sealant

Neutral-cure RTV adhesive sealant featuring an adhesion promoter that provides excellent adhesion to many substrates.

- Superior unprimed adhesion to a wide variety of substrates, including glass, metal, masonry, concrete, and most rubber and plastics
- Low odor
- Non-corrosive to metals and other corrosion-sensitive materials
- UL Listed

PART N°	SIZE	COLOR	CASE
99180523	300 mL	Black	12
4059470	22.7 KG	Black	1
99180620	300 mL	Gray	12
2654580	22.7 KG	Gray	1
2823501	228.1 KG	Gray	1
99180648	300 mL	Off-White	12
4031452	22.7 KG	Off-White	1



DOWSIL™ Sealants

Neutral Cure



DOWSIL™ 737 Neutral Cure Sealant

Neutral, oxime-cure RTV adhesive/sealant with primerless adhesion to most substrates. In addition to typical bonding/sealing applications, can also be used to replace mechanical fasteners and waterproof electrical components.

- Oxime cure (neutral)
- Primerless adhesion to a wide variety of substrates
- UV and weather-resistant
- Low odor and non-corrosive to metals and alkalines when compared to alkoxy-based RTVs
- UL 94 HB Compliant (low-flammability)

PART N°	SIZE	COLOR	CASE / PALLET
99180484	300 mL	Black	12 / 1,296
4099910	17.6 KG	Black	1 / 24
4098499	90 mL	Clear	12 / 3,000
99180483	300 mL	Clear	12 / 1,296
4098497	17.6 KG	Clear	1 / 24
4098496	205 KG	Clear	1 / 4
99180646	300 mL	White	12 / 1,296
4099876	17.6 KG	White	1 / 24



DOWSIL™ 738 Electrical Sealant

One-part, white, non-flowing RTV designed for the bonding and sealing of electrical assemblies.

- Room temperature cure when exposed to moisture
- High elongation for added stress relief
- Faster in-line processing with optional heat acceleration
- Non-flowing
- UL Listed

PART N°	SIZE	COLOR	CASE / PALLET
1949101	90 mL	White	12
99180508	300 mL	White	12
1907824	17.6 KG	White	1



DOWSIL™ Specialty Fluid



DOWSIL™ 550 Fluid

100% actives, polyphenylmethylidimethylsiloxane polymer fluid. Useful as a heat transfer fluid, in thermostat systems and as a base oil for high temperature lubricants

- Low volatility
- Serviceable in temperature range of -40° C up to 230° C in open systems, and up to 315° C in closed systems
- High flash point and viscosity index
- Excellent heat transfer characteristics
- Good compressibility
- Good oxidation and thermal stability

PART N°	SIZE	COLOR	CASE
2288494	500 mL Bottle	Colorless	1
2076641	4 KG Pail	Colorless	1
4019093	20 KG Pail	Colorless	1
2639203	220 KG Drum	Colorless	1



DOWFROST™ Heat Transfer Fluid

- Industrially inhibited heat transfer fluid with an operating range of -50° F to 250° F (-46° C to 121° C)
- Made with pharmaceutical grade DOW PuraGuard™ Propylene Glycol USP/EP
- Provides freeze protection to below -60° F (-51° C) and burst protection to below -100° F (-73° C), depending on concentration
- NSF Registered for use where there is possibility of incidental food contact
- Clear DOWFROST is Generally Regarded As Safe (GRAS) by the FDA
- Available in blue and clear in 1 gal bottles, 5 gal pails, 55 gal drums, and 275 gal totes

Applications

- HVAC
- Chill water and hydronic heating loops
- Geothermal
- Snow melt, defrosting, and turf heating
- Solar hot water heating
- Fire water sprinkler systems
- Food processing
- Chilling of dairy products and beverages
- Cold room dehumidifying
- Beer and wine (fermentation cooling)
- Refrigeration and freezing
- Ice skating rinks
- Secondary heat transfer loops



DOWFROST™ HD Heat Transfer Fluid

- Engineered for closed loop HVAC systems with operating range of -50° F to 325° F (-46° C to 163° C)
- Made with pharmaceutical grade DOW PuraGuard™ Propylene Glycol USP/EP
- Provides freeze protection to below -60° F (-51° C) and burst protection to below -100° F (-73° C), depending on concentration
- Contains industrial corrosion inhibitors and yellow dye for leak detection
- Available in 1 gal bottles, 5 gal pails, 55 gal drums, and 275 gal totes

Applications

- HVAC
- Chill water and hydronic heating loops
- Geothermal
- Snow melt and turf heating systems
- Solar hot water heating
- Fire water sprinkler systems
- Refrigeration
- Ice skating rinks
- Large-scale chiller systems
- Cold storage, refrigerated warehouses, and supermarkets (secondary loop)
- Thermal Energy Storage (TES)



DOWCAL™ 200 Heat Transfer Fluid

- Provides long lasting and efficient corrosion protection, particularly for aluminum alloys
- Low acute oral toxicity
- Free of nitrite, borax and CMR (carcinogenic, mutagenic and reprotoxic)
- Recommended operating temperature range between -50° F to 350° F (-46° C to 121° C)
- Long fluid lifetime, lowering maintenance cost
- Available in 1 gal bottles, 5 gal pails, 55 gal drums, and 275 gal totes

Applications

- Solar heating
- Floor heating
- Snow melting systems
- Process heating
- Heat recovery
- Cooling of electronic systems and components
- Wind turbine systems
- Photo-voltaic (PV) inverters
- Data center cooling
- Ice skating rinks



LENTEK™ 172 Hybrid Sealant

One-part, moisture-cure RTV with silane-terminated polymer chemistry that features the weather-resistance of a silicone, the paintability of a polyurethane, and the increased adhesion of hybrid sealant technology.

- Paintable within 24 hours
- Increased adhesion compared to non-hybrid sealants
- Eco-friendly and VOC compliant
- Excellent UV and weather-resistance
- Cost-effective
- Conforms to USDA Requirements for non-food contact

PART N°	SIZE	COLOR	CASE / PALLET
7300001	300 mL	Black	12 / 1,296
7300002	300 mL	Bronze	12 / 1,296
7300003	300 mL	Gray	12 / 1,296
7300004	300 mL	White	12 / 1,296



LENTEK™ Insulating Foam Sealant

Fills and insulates gaps efficiently with the power of long-lasting, water-resistant, expanding foam. Provides a simple, cost-effective solution to eliminate unwanted airflow and improve energy efficiency.

- Triple expanding
- Cost-effective polyurethane foam sealant
- UL Listed
- Interior/exterior use
- Long-lasting, airtight, and weather-resistant seals
- Adheres to wood, metal, masonry, glass, and most common building materials

PART N°	SIZE	COLOR	CASE / PALLET
2299120	12 OZ Straw Can	Tan	76 / 912



LENTEK™ Fireblock Foam Sealant

Fills and insulates gaps efficiently with the power of long-lasting, water-resistant, expanding foam. Orange-colored foam for easy identification and inspection. Also comes in 24 oz gun foam can.

- Impedes spread of fire and smoke through service penetrations
- Cost-effective polyurethane foam sealants
- UL Listed
- B2 Fire Rating
- Seals service penetrations between floors and electrical runs through wall studs
- Adheres to wood, metal, masonry, glass, and most common building materials

PART N°	SIZE	COLOR	CASE / PALLET
2299121	12 OZ Straw Can	Orange	76 / 912
2299200	24 OZ Can	Orange	76 / 912



Gaps & Cracks

- Expands to fill, seal, and insulate gaps up to 1" (25mm)
- Helps keep insects, moisture, condensation and allergens out
- Adheres to wood, metal, masonry, glass, and most plastics



Big Gap Filler

- Expands to fill, seal, and insulate gaps up to 3" (76mm)
- Forms a long-lasting, airtight, weather-resistant seal
- Adheres to wood, metal, masonry, glass, and most plastics



Fireblock

- Impedes spread of fire and smoke through service penetrations
- Colored orange for easy identification
- Tested according to ASTM E84, ASTM E814 (modified), UL 1715
- Seals service penetration between floors and electrical runs through wall studs



Multipurpose Black

- Black color blends naturally into the surrounding environment
- Expands to fill, seal, and insulate gaps up to 1" (25mm)
- Specifically formulated for both indoor and outdoor use



Window & Door

- Minimally expanding foam with a low-pressure build that remains soft and flexible after curing
- Formed without trimming to create long-lasting, airtight and water-resistant seal proven not to bow window or door frames



Pro Pestblock

- Reusable for 30 days when left attached to GREAT STUFF PRO™ Dispensing Gun
- Blocks critters, bugs and other pests
- Expands to fill, seal, and insulate gaps up to 1" (25mm)
- Pesticide-free
- Grey-colored foam for easy identification



GUN

PART N°	PRODUCT	COLOR	CASE / PALLET
00341557	PRO Gaps & Cracks	24 OZ	12 / 768
00341558	PRO Gaps & Cracks	30 OZ	12 / 768
00187273	PRO Window & Door	20 OZ	12 / 768
11073754	PRO Pestblock	20 OZ	12 / 768

SMART DISPENSER

PART N°	PRODUCT	COLOR	CASE / PALLET
99108824	Gaps & Cracks	12 OZ	12 / 768
99108860	Big Gap Filler	12 OZ	12 / 768
99108862	Window & Door	12 OZ	12 / 768
99112876	Multipurpose Black	12 OZ	12 / 768
99112831	Fireblock	12 OZ	12 / 768

STRAW

PART N°	PRODUCT	COLOR	CASE / PALLET
00157901	Gaps & Cracks	12 OZ	12 / 768
00157906	Big Gap Filler	12 OZ	12 / 768
00157911	Gaps & Cracks	20 OZ	12 / 768
00157913	Big Gap Filler	20 OZ	12 / 768
00197711	PRO Window & Door	20 OZ	12 / 768
00341553	PRO Gaps & Cracks	24 OZ	12 / 768

GREAT STUFF™ Heavy Duty Bamboo Work Wipes

GREAT STUFF™ Heavy Duty Bamboo Work Wipes' durable and strong scrub removes uncured GREAT STUFF™ and more. The 100% natural bamboo wipes clean up paint, oil, grease, and other messes.

- Removes uncured GREAT STUFF™
- Large sized 9.8 in by 7.9 in
- Removes oil, paint, grease, grime, and more
- Automotive, industrial, work, and household use
- 30 wet wipes per reusable package
- Made with 100% natural bamboo

Order by the case.

PART N°	SIZE	CASE
--	Shelf Ready Box	12 Packs / 2 Boxes Per Case
7500104	Case	24 Packs
5900004	1/4 Pallet Display	8 Cases / 4 Displays Per Pallet



GREAT STUFF™ Gloves

GREAT STUFF™ Latex / Nitrile Blend Disposable Gloves

The 7.5 mil thick GREAT STUFF™ Latex / Nitrile Blend Disposable Gloves have the comfort and dexterity of latex and the durability and strength of nitrile. 100 pairs of gloves per box.

- 7.5 mil thickness provides industrial strength
- Puncture resistant
- Nitrile and latex blend blue disposable gloves
- Powder-free and polymer-coated

PART N°	SIZE	EACH	CASE
5000089	L 100 Shelf Ready Case	100 Gloves	10 Boxes
5000090	XL 100 Shelf Ready Case	100 Gloves	10 Boxes
5900005	L 10 Shelf Ready Case	10 Gloves	20 Packs
5900002	1/4 Pallet Display	80 Boxes	8 Cases



GREAT STUFF PRO™ Dispensing Guns

GREAT STUFF

GREAT STUFF PRO™ Dispensing Guns

No-drip precision application, Great Stuff Pro™ Dispensing Gun provides total control over every seal, ensuring professionals get the maximum yield out of every can.

- Lightweight, high-strength aluminum body with a metal trigger
- Flow-control mechanism dispenses beads from 1/8" to 3"
- Provides greater precision and access to hard-to-reach areas
- Non-stick coated can adapter and needle
- Large flow control knob with a secured back-crew system
- Replaceable smooth dispensing nozzle

PART N°	PRODUCT	CASE / PALLET
00230408	13" Gun	1
99046685	14" Gun Blister Pack	3



FROTH-PAK™ Foams

FROTH-PAK™

FROTH-PAK™ Foam Sealants

Two-component, chemically-cured polyurethane foam that seals cavities penetrations, and cracks up to 4" wide. Best for common building materials, rim joists, basements, crawl spaces, and attics.

- Helps improve the comfort, health, performance, and energy efficiency of any building
- Lower long-term cost of ownership compared to drum and rig systems
- Blocks air infiltration and seals out moisture, dust, pests, and smoke
- Quick setup and 30 second cure time

FROTH-PAK 12 Sealant: Covers 12 board feet

FROTH-PAK 120 Sealant: Covers 120 board feet

FROTH-PAK 200 Sealant: Covers 200 board feet

FROTH-PAK 210 Insulation: Class A Fire Rated insulation, covers 210 board feet

FROTH-PAK 620 Sealant: Covers 620 board feet

FROTH-PAK 650 Insulation: Class A Fire Rated insulation, covers 650 board feet

PART N°	PRODUCT	SIZE	CASE / PALLET
12030014	Froth-Pak 12	Kit	1 / 144
12031891	Froth-Pak 120	Kit	1 / 26
12031949	Froth-Pak 200	Kit	1 / 26
12031897	Froth-Pak 210	Kit	1 / 26
12031879	Froth-Pak 620	A-ISO	1 / 12
12031900	Froth-Pak 620	B-POLYOL	1 / 12
12031908	Froth-Pak 620	Kit	1 / 12
12031896	Froth-Pak 650	A-ISO	1 / 12
12031877	Froth-Pak 650	B-POLYOL	1 / 12
12031907	Froth-Pak 650	Kit	1 / 12



Lucas Oil Red “N” Tacky Grease

Smooth, tacky, red lithium complex grease fortified with rust and oxidation inhibitors. Can be used in many general agricultural, automotive, and industrial applications.

- NLGI #2
- Water-resistant
- Excellent mechanical stability
- Long storage life
- Fortified with rust and oxidation inhibitors
- Enhanced tackiness enables longer performance

PART N°	SIZE	COLOR	CASE
11025	11 OZ Aerosol	Clear	12
10005-30	14 OZ Cartridge	Red	30
10574	1 LB Tub	Red	12
10027	35 LB Pail	Red	1
10028	120 LB Keg	Red	1
10029	400 LB Drum	Red	1



Lucas Oil X-TRA Heavy Duty Grease

EP fortified grease that exceeds OEM specifications and is virtually wash-out-proof. Formulated for automotive, agricultural, heavy-duty, and industrial applications.

- NLGI #2
- Enhanced stability compared to conventional lithium grease
- Last four times longer than regular grease
- The ultimate grease for high-speed bearings
- Fortified with an extreme pressure additive package

PART N°	SIZE	COLOR	CASE
10330	1 LB Tub	Green	12
10301-30	14.5 OZ Cartridge	Green	30
10305	35 LB Pail	Green	1
10316	120 LB Keg	Green	1
10335	400 LB Drum	Green	1



Lucas Oil Marine Grease

Premium, multi-purpose, OBCS grease containing unique polymers, anti-wear agents, and tackifiers with inherent rust and oxidation resistance to provide the highest-performance properties.

- NLGI #2
- Excellent fresh water and salt water corrosion protection
- Extreme pressure properties, water-resistance, and shock-loading protection
- Applications include trailer wheel bearing, trailer chassis lubrication, and outboards
- Crossover applications in automotive wheel bearing and chassis lubrication
- Overbased Calcium Sulfonate (OBCS)

PART N°	SIZE	COLOR	CASE
11148	1 LB Tub	Blue	12
10320-30	14.5 OZ Cartridge	Blue	30
10321	35 LB Pail	Blue	1
10322	120 LB Keg	Blue	1
10660	400 LB Drum	Blue	1



Lucas Oil White Lithium Grease

Multi-purpose, high-quality NLGI #2 formulation. Recommended for use in household applications including garage doors, hinges, openers, and springs.

- NLGI #2
- White and creamy in appearance
- Long-lasting and reduces wear
- Extreme friction reducer

PART N°	SIZE	COLOR	CASE
10533	8 OZ Tube	White	12
10535	35 LB Pail	White	1



Lucas Oil Heavy Duty Mining & Construction Grease

Lithium complex grease fortified with 5% molybdenum disulfide to provide excellent shock loading protection in the most adverse operating conditions.

- Provides excellent shock loading protection
- Extends equipment life

PART Nº	SIZE	CASE
10881-30	14 OZ Cartridge	30
10881-60	14 OZ Cartridge	60
10597	35 LB Pail	1
10922	120 LB Keg	1
10598	400 LB Drum	1



Lucas Oil Hydraulic Oil Booster & Stop Leak

One-of-a-kind, long-lasting blend of oils and petroleum extracted additives that add lubricity and thermal stability to any hydraulic oil. Excellent preventative maintenance product, adding life to pumps, rams, seals, and the treated hydraulic fluid.

- Designed for and unsurpassed at correcting existing problems
- Treat rate for preventative maintenance is only 5-10%
- Anti-foam agents present

PART Nº	SIZE	CASE
10019	1 Quart	12
10018	1 Gal	4
10039	5 Gal Pail	12
10040	55 Gal Drum	1
11123	330 Gal Tote	1



Lucas Oil Industrial Gear Oils

Blended with the highest-quality base oils and additives to provide extreme pressure protection, resistance to foam, and excellent rust, corrosion, and oxidation protection.

- Excellent shock-loading properties
- Designed to withstand heavy loads
- Non-corrosive to brass, bronze, steel, and other copper alloys
- Recommended for use in bevel, spur, herringbone, planetary, worm, and industrial hypoid gears
- Available in gallon bottles, 5 gal pails, 6 gal boxes, 55 gal drums, and totes

PART Nº	PRODUCT	SIZE	CASE
10673	ISO 150	55 Gal Drum	1
10590	ISO 220	55 Gal Drum	1
10592	ISO 320	55 Gal Drum	1
10806	ISO 460	55 Gal Drum	1
10496	ISO 680	55 Gal Drum	1



Lucas Oil Penetrating Oil

Designed to loosen rusted-on nuts and bolts, finding its way between the tiniest of crevices between metal parts and lubricating them.

- Fortified with powerful corrosion inhibitors and wetting agents
- Slow evaporation that leaves a tenacious film that fights water and corrosion
- Use in any position, even upside down
- Use on: nuts, bolts, hinges, bearings, sliding doors, bicycle chains and a million other uses around the home, garage, shop, and office

PART Nº	SIZE	CASE
11043	11 OZ Aerosol	12
11103	5 Gal Pail	1
11104	55 Gal Drum	1



Lucas Oil Multi Purpose Parts Cleaner & Degreaser

Made with advanced Polyetheramine (PEA) detergents to help clean and degrease carburetors, chokes, brake calipers, rotors, air intakes, throttle bodies, and unpainted metal parts.

- Removes build-up that can cause loss of power, rough idle, high emissions, and hard starting
- Fast-drying and helps remove unwanted deposits such as gum, varnish, oil, brake fluid, grease, dirt, and sludge
- Cleans brakes for better performance and smoother operations
- 50 state VOC compliance

PART N°	SIZE	CASE
11115	16 OZ Aerosol	12
11115-6	16 OZ Aerosol	6



Lucas Oil Bag in Box

Lucas Oil's "Bag in a Box" oil program is specifically designed to be used by dealerships, auto repair shops, and quick lubes for their ability to carry multiple oil grades and specialty items for faster lube servicing and dispensing. Lucas Oil's most common motor oils are available.

- Designed to carry multiple oil grades and specialty items for a faster lube service/dispensing
- Minimal floor space needed (2 ft x 2 ft)
- Eco-friendly design, less waste of oil and plastic
- Outer cardboard box is 100% recyclable
- Holds 6, six gallon containers at a time and 6 jugs with lids (wrap-around display panel included)
- Easy to assemble
- Optimized storage

PART N°	PRODUCT	SIZE	CASE
18057	AW ISO 32 Hydraulic Oil	6 Gal Bag In Box	1
18058	AW ISO 46 Hydraulic Oil	6 Gal Bag In Box	1
18059	AW ISO 68 Hydraulic Oil	6 Gal Bag In Box	1
18004	Synthetic SAE 5W-20 API SN Plus Motor Oil	6 Gal Bag In Box	1
18005	Synthetic SAE 5W-30 API SN Plus Motor Oil/Dexos	6 Gal Bag In Box	1
18012	Synthetic SAE 5W-40 API SN Plus Motor Oil	6 Gal Bag In Box	1
18011	Synthetic SAE 5W-40 CK-4 Truck Oil	6 Gal Bag In Box	1
18065	Synthetic SAE 15W-40 CK-4 Truck Oil	6 Gal Bag In Box	1
18017	Synthetic Blend SAE 10W-30 CK-4 Truck Oil	6 Gal Bag In Box	1
18060	Industrial Gear Oil ISO 220	6 Gal Bag In Box	1
18061	Industrial Gear Oil ISO 320	6 Gal Bag In Box	1
18064	Industrial Gear Oil ISO 680	6 Gal Bag In Box	1





LENTUS



2/2024



DUPONT

DOWSIL™

DOWFROST™

FROTH-PAK™

GREAT STUFF™

LUCAS OIL™



LentusLLC.com

Sales@LentusLLC.com

+1-270-765-2212

400 Ring Road, Suite 101
Elizabethtown, KY 42701