

🚺 bestrongworld 🌐 global.bestrong.com 🖸 info@bestrong.com

Muscle Groups Focus





1-1-126-02

EN 16630

14 + years

1 person

99 kg

Fitness Medium

Multifunctional Trainer On Pillar

f bestrongworld

The multifunctional trainer is a versatile piece of workout equipment that allows for leg raises, knee raises, and dips with the front handles of the element. This versatility makes this element the perfect choice for those people who are looking for complex outdoor training equipment for the home. Two multifunctional trainers may be combined on one column.

Attributes

Product code
Certificate
Age group
Capacity
Max. weight load
Гуре
Difficulty level





Side View



Plan View



Installation information

Number of installers (concrete)	At least 2 people
Total installation time (concrete)	45-90 min.
Number of installers (equipment)	At least 2 people
Total installation time (equipment)	46-60 min.
Excavation volume	0.5 m ³
Concrete volume	0.5 m ³
Size of the base structure	0,8 x 1,2 x 0,08 m
Anchoring options In combined structures, the volume of concrete required	In-ground or surface

Technical specification

Safety surfice area	Around 1,5 m ra
Net weight	
Material	
Critic fall height	1380
Color options	
For more color options, discuss with your sales representa	

Warranty

n rediue	Ctructure	10 1/00/00
m radius	Structure	10 years
29 kg	Steel	5-10 years
S235	Paint	2 years
380 mm	Plastic	5-10 years
	Rubber	1-3 years
	Moving parts Detailed information in the warranty document	2 years
	Detailed information in the warranty document	

Material specification



7'BESTRONG

🖪 bestrongworld 🚺 bestrongworld 🌐 global.bestrong.com 🖻 info@bestrong.com



The element is made of high quality S235 steel, which has been cleaned via sandblasting. A corrosion resistant powder coating finish is then applied. Also available with galvanized surface for even greater protection and longevity!



The clamp system allows for easy assembly and extreme stability.



The seats and backrests are

made of strong HDPE ma-

terial. Which is fully heat,

moisture and UV resistant.



The connecting elements are fastened with vandal-proof stainless steel screws and nuts.



The ends of the bars and posts are sealed with injection-moulded plastic caps.



