

HYOSUNG

Full-Function Island Drive-Up ATM

MX7600XLI

Hyosung's proven reliable full function ATM.

Designed to provide unprecedented reliability, the **MX7600XLI** is unparalleled in the market. This island drive-up ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. It's high uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company.

Features

Highest Availability

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime. The **MX7600XLI** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

Flexibility

The **MX7600** series can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

Capacity

High capacity, cash dispense capability and the ability to support large volume transactions, makes the **MX7600XLI** a high capacity machine.

Security Options

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, anti-skimming, white-listing, and encryption.



Specifications

Dimensions

- Height: 1574mm (62.9")
- Width: 1058mm (41.3")
- Depth: 990mm (39.5")
- Weight: 1299kg (2,866lbs)

Environmental Conditions

- Temperature: 32°F – 104°F
(0°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10

Customer Interface

- 15" TFT LCD
- Input method – touch screen
- Privacy filter
- Tilt screen monitor
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant

Media Handling

- **Cash Dispenser**
 - Configurable denominations up to 4 cassettes
 - 3,000 notes per cassette
 - Bundle present, bundle retract
- **Single Slot Mixed Media Deposit**
 - 50 item deposit
 - Option for up to 2000 checks
 - Option for up to 2000 notes
 - Reject and retract capability

Security

- Safe – UL291 Level-1
- Alarm – Seismic + Heat
- Locking Device – Electronic, mechanical combination lock, KABA Mas Cencon (optional)
- Security camera

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Front Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%,
200V ~ 240V±10% 50/60Hz

Additional Features

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.