

Real-Time Multi-Person Recognition

Powered by Deep-learning Algorithm





673 / 673T Series



Multi-person recognition

Accurate recognition of single or up to 5 persons



Flexible modular design

Module combinations including fingerprint, Bluetooth, and QR codes



Advertisement auto-display

Up to 8 customizable photos or headlines for digital advertisement



Privacy protection

Photo not stored by default







Flexible Modules Satisfy a Diverse Set of Needs





PRODUCT SHOWCASE

Model	DS-K1T673 Series	DS-K1T673T Series
Maximum face images	10,000	100,000
Fingerprint capacity	10,000 with fingerprint module	10,000 with fingerprint module
Card capacity	50,000	100,000
Card types	Felica, DESfire, M1	Felica, DESfire, M1
Event capacity	150,000	150,000
Mask detection	Support	Support
Communication protocols	Ethernet, Wi-Fi (optional) RS-485, Wiegand USB, Bluetooth (optional)	Ethernet, Wi-Fi (optional) RS-485, Wiegand USB, Bluetooth (optional)
Voltage input	DC 12 V ~ DC 24 V, 2A	DC 12 V ~ DC 24 V, 2A
Protective level	IP65	IP65

7" screen



Note:

This series supports both on-premises deployments as well as cloud-based deployment.

Learn more about > Hikvision's Cloud-based Attendance Solution























