



Illuminated Signals

ROADWORKS

VEHICLE

ON-BOARD

PERMANENT

Your contacts :

our team answers your daily inquiries... +33(0)4 92 08 29 99



Yannick CHIAVELLI
Department manager
y.chiavelli@ttsys.fr



Bianca VAMVU
Sales Assistant
b.vamvu@ttsys.fr



Maxime DASPRE
Technical sales representative
m.daspre@ttsys.fr



Valentin MINIERE
After-Sales services
v.miniere@ttsys.fr



Rémo CHIAVELLI
Chief Executive Officer

The world changes, TTS innovates

Committed for over 30 years to the development of new solutions for safety and signage, we maintain a high level of standards in which innovation plays a key role.

We are able to provide innovative, tried and tested solutions for traffic management, with over 90% added value generated by our workshops in France.



Made in France



Environmentally friendly

Setting up system for collection, transport and recycling system for Waste Electrical and Electronic Equipment is a legal obligation (European WEEE Directive) for all producers who place this type of equipment on the market.

A part of our commitment is to be a responsible player and in order to meet this legal obligation, we have registered with Ecosystem as an EEE producer, so that our customers can benefit from a free collection and recycling service for our end-of life products. Catalogue prices exclude Eco Participation. For any information for waste collection points or collecting methods, please visit : www.ecosystem.eco.



ROADWORKS P 6-23



VEHICLES P 24-39



ON-BOARD P 40-53



PERMANENT P 54-70



Design
Office



Integrated
Welding
Workshop



Digital Graphic
Design
Workshop



Assembly
Workshop

THE DESIGN BEHIND YOUR SAFETY

The human resources, the means and the technology to ensure your safety

Mechanical
Fabrication Unit



Electronics
Boards
Manufacturing
Unit



Digital Machining
Centre for Plastic
and Metal Sheets.



Commissioning
and After-Sales
Unit



Our range of optics to suit all configurations...



Optic Ø 300 mm - The large size :

Made up of 225 high light intensity yellow LEDs. Polycarbonate protective lens. Integrated contrast screen (500 x 500 mm / polyester powder coated paint).



Optic Ø 200 mm - High safety :

Made up of 80 high light intensity yellow LEDs. The electronic CPU can be integrated into the optic. Polycarbonate protective lens.



Optic Ø 130 mm - The perfect format :

Made up of 30 high light intensity yellow LEDs. Especially thin designed. Polycarbonate protective lens.



Optic Ø 70 mm - The small systems :

Composed of 30 or 12 high and very high light intensity yellow LEDs. The 30 LED version is cast in a black polymerized polyurethane resin. The 12 LED version is protected by a lens.

NEW

■ New 2 battery case New design


+ compact
+ resistant

The case profile protects the connectors.



■ New optic Ø 70 mm for triangle 700 ultra-thin (12 mm)

The optic is fully integrated into the panel profile.



■ New optic Ø 130 mm ultra-thin (25 mm) + resistente

The optics are fully integrated into the panel profil.



These products allow optimized loading in the racks of panel trailers, without risk of damage.



Illuminated Signals

ROADWORKS

Tempo mobile traffic light range ■ p. 8 - 15

Illuminated sign equipment ■ p. 16 - 17

Traffic guidance ■ p. 18 - 19

Site lighting ■ p. 20

Work on site equipments ■ p. 21

Power supplies ■ p. 22 - 23



TRAFFIC LIGHTS P 8-13



NEW

**ILLUMINATED SIGN
EQUIPMENT** P 16-17



TRAFFIC GUIDANCE P 18-19



WORKS ON SITE EQUIPMENTS P 21

Tempo Mobile Traffic Light

tempo

THE MARKET
BENCHMARK

CERTIFIÉ PAR ASCQUER

NF

IK10

IP55



Waiting time
display in **minutes**
and **secondes**



High Autonomy
2 month with a 200 Ah battery.
1 month with a 100 Ah battery.



Easy to program



Easy Handling



Low price and
reactivity on the spare parts



Economic
The lowest operating
cost on the market



 Choice of optional box

TEMPO range : Specialist's expertise result !

tempo STANDARD

page 10



Up to
1,5 months*
of autonomy
⚡
(*) with a 200 Ah battery

tempo SOLAR

page 12



Up to
1 year*
of autonomy
⚡
(*) with a 200 Ah battery


tempo RÉGULATION

page 13



tempo OPTIONS

page 14-15



Usable on all your sites

7 built-in programmable configurations on standard version.

The key word is flexibility. The Tempo traffic lights standard version can also manage alternating traffic at 3 and 4 branches junction. It supports the management of cross-cycles and changeover cycles on green.



↔ Alternating



↔ 3 branches junction




↔ 4 branches junction

Specific protection solutions

more details page 10


Theft delay arm tube

↔ 47110



Protection cage

↔ 41186



Tempo Mobile Traffic Light



ASCQUER CERTIFICATION
Admission n° : KR11 01
www.ascquer.fr



tempo STANDARD

Reliability, technology, and unique know how.

The electronics :

- Programming and management interface via infrared link with mobile synchronisation case.
- Module and all the optics protected by a polycarbonate face.
- Display on a 2 x 16 character alphanumeric LCD screen of all cycle information, programming, and control information.
- Waiting time display.

The structure :


- Wheelbarrow box with ABS cover.
- Handling handles.
- Telescopic mast : closed 1.55 m, open 2.50 m.

Up to
1,5 months*
of autonomy
(*) with a 200 Ah battery

→ 21698



→ 41186



→ 47110

Tempo Mobile Traffic Light

21698 Set of 2 Tempo temporary traffic lights with remote control

22563 Single Tempo temporary traffic light (without remote control)

Power Supplies

The range of 100 Ah battery makes **handling easier** while maintaining one month's autonomy.

1992 Rechargeable battery 12 V 100 Ah
Plan for one rechargeable battery per light

The range of 200 Ah battery gives the tempo 2 months **autonomy**. Perfectly suited to long term worksites.

376 Rechargeable battery 12 V 200 Ah
Plan for one rechargeable battery per light

Battery fixing straps :

9322 Set of 2 straps
Two straps per battery are required

Battery charger from 100 Ah to 250 Ah :

21551 Battery charger range 300 W / 12 V

Battery charger from 50 Ah to 100 Ah :

26758 Battery charger range 100 W / 12 V

230 V power supply :

1522 Power supply 230 /12 V
Allow for one power supply per light

Protection Accessories

Protection structure for Tempo casing :

41186 Protection structure for Tempo casing
(Padlock nnot included)

Theft delay arm tube :

47110 Theft delay arm tube
(Padlock nnot included)

Padlock :

12257 Brass padlock

Tempo Mobile Traffic Light & Tempo Solar

11



**Sent within
48 hours !**

Electrical Components For Connection Box

460

3-pin XLR female base socket

**1521**

Spiral cable + 3-pin XLR socket

**477**

Red battery terminal

**478**


Green battery terminal



Tempo Solar Specific Spare Parts

42359

Solar panel 12 V 20 W

**31125**

Solar housing cover 12 V 20 W

**1164**

Tempo Solar wheel

**31036**

Solar battery holder case 12 V 20 W

**31119**

Charge regulator



Steel Metal Options

43753

OPTIMO battery casing

**44429**

Casing cover Partial opening before October 2019

**49678**

Casing cover Total opening from October 2019



From 2018 :



44426
Connection box

Before 2018 :



21753
Connection box

27645
Wheel axle

**22832**

Left cover tab

27647

Elastic washer with cap

22833

Right cover tab

22385

unpuncturable wheel

27646

Wheel spacer

Solar Tempo Mobile Traffic Lights



Intertraffic
INNOVATION AWARD



Reinforced impact protection
with polycarbonate
and steel casing.



tempo 
SOLAR

eco-efficient



Tempo changes to Green !

Always looking for innovation, we adapt our know-how in photovoltaic energy for the benefit of work site traffic light.

Unrivalled autonomy

The solar panel allows you to increase your battery's autonomy safely and free of charge. So you make a considerable maintenance savings.

The technique :

- The 20 W photovoltaic panel supplies the battery via a charge regulator.
- Photovoltaic module unit protected by polycarbonate.

The structure :

- Painted steel casing.
- Handling handles.
- Telescopic mast.

Solar Tempo Traffic Lights

31175

Set of 2 solar Tempo traffic lights
with remote control

30878

Single solar Tempo traffic light
(without remote control)

Rechargeable battery

The use of 200 Ah battery provides optimum traffic light ballasting. It also enables available power levels to be smoothed during less sunny periods.

376

Rechargeable battery 12 V 200 Ah
Allow for one rechargeable battery per light


Specific Spare Parts

Tempo solar traffic light spare parts are available on page 11.

Traffic Regulation Tempo Mobile Traffic Light

13

tempo 
REGULATION



Discover how

Watch the video

It automatically regulates traffic

→ priority to the most congested axis

Traffic Regulation Tempo Traffic Lights

35375

Set of 2 Tempo regulation traffic light
with remote control

41855

1 Tempo regulation traffic light
(without remote control)

Power Supplies

The 100 Ah battery range makes **handing easier** while maintaining good autonomy.

1992

Rechargeable battery 12 V 100 Ah
Plan for one rechargeable battery per light

The 200 Ah battery range gives the Tempo Regulation optimum **autonomy** perfectly suited to long term work sites.

376

Rechargeable battery 12 V 200 Ah
Plan for one rechargeable battery per light

Battery fixing straps :

9322

Set of 2 fixing straps
Two straps per battery are required

Batteries charger from 100 Ah to 250 Ah :

21551

Battery charger range 300 W / 12 V

Batteries charger from 50 Ah to 100 Ah :

26758

Battery charger range 100 W / 12 V

Protection Accessories

Specific protection solutions can be found on page 10.



Easier to program.
Easier to force all lights to red.




Less traffic jams.
Less waiting at red lights.



Less incivility.
Less stress on sites.
Less risk of accident.



Less pollution.
Less energy consumed.



Tempo Mobile Traffic Lights - Options

**Control Options**

Radio remote control
Remote control case
Call push button
GSM/SMS

**Detections Options**

Motion detection radar
Regulation radar
Speed detection radar
Magnetic loop detector

**Communications Options**

Wireless link
Wired link
Dry contact

**Software Development Options**

Non-standard cycles
Customized function...

**Specific Optics Options**


Cross, arrow, repeater, green, white, blue optics...

**Power Supply Options**

Battery, Solar, 230 V,
Public Lighting Source

tempo 
OPTIONS

For all your configuration
we have the solution !



N°1 on Modularity

Options to match every site configuration.

Contact us  

Tempo Mobile Traffic Lights - Options

Some examples of specific configurations :

tempo
OPTIONS

Exit from site
priority



Watch the video

tempo
OPTIONS

Manual remote -
controlled alternate
Independent



Watch the video

tempo
OPTIONS

Manual remote -
controlled alternate
Synchronized



Watch the video

tempo
OPTIONS

Green traffic
light reward

Excessive Speed :
the light stays red



Watch the video

tempo
OPTIONS

Intermediate arrows traffic light

Inform of the active direction of traffic, for a traffic light alternate



Watch the video

For 20 years we've been ensuring that our lights meet your specific requirements.

...we have been entrusted with carrying out their projects : Atlante construction, Demathieu et Bard, Dodin Campenon, DTP Terrassement, Eiffage TP, Entreprise Girard, GTS Guintoli, Razel Bec, Roessel, SFTRF, Sobeca, Spie Fondations, Vinci Construction Terrassement, Loxam etc...

Illuminated Sign Equipment

NEW

 Triangle 700

 Up to
3 months
of autonomy
(*) with a 75-Ah battery


(*) with a 75-Ah battery

 Up to
3 months
of autonomy
(*) with a 75-Ah battery

 Triangle 1000
Other symbols :
contact us.

Tri-flash set autonomy * :

Optic	2 Battery Case		4 Battery Case		Battery 75 Ah
	7 Ah	45 Ah	7 Ah	45 Ah	
70 mm 30 LEDs	390 h	2 510 h	781 h	5 020 h	4 183 h
70 mm 12 LEDs 130 mm 30 LEDs	207 h	1 329 h	413 h	2 658 h	2 215 h

* 24 hours working with 7 hours of night and at 20°C

Site Light Triangle

Lighting equipment composed of :
3 optics of Ø 130mm/30 LEDs or Ø 70 mm/12 LEDs and a control unit. The length of the optics leads are 1.5 m. Extensions of 5m are possible. Activated by a 3-position waterproof switch (24-hours, off, night).

1000 or 700 mm triangle sign, class 2 symbol of your choice, fitted with an integral stand completely foldable.

Power supply using 2-battery case (type 4R25) :

58800	Triangle 700 Ø 70/12 LEDs - classe 2 2-battery case (batteries not included)
17836	Triangle 1000 Ø 130/30 LEDs - classe 2 2-battery case (batteries not included)

Power supply using rechargeable battery :

60087	Triangle 700 Ø 70/12 LEDs - classe 2 Rechargeable battery (Rechargeable battery not included)
20238	Triangle AK5 1000 Ø 130/30 LEDs - classe 2 Rechargeable battery (Rechargeable battery not included)
49962	Additional sign 700 x 200 - classe 2

4 batteries case option

→ **57270**

NEW

 Up to
55 days
of autonomy
(*) with 2 x 45-Ah batteries


(*) with 2 x 45-Ah batteries

→ **55236**

2 batteries case option

→ **15702**

BATTERY

 Up to
3 months
of autonomy
(*) with a 75-Ah battery


(*) with a 75-Ah battery

→ **16891**

RECHARGEABLE BATTERY

→ **29815**→ **22279**

Lighting kit

Power supply using a 2-battery case (type 4R25) :

19601	3 optics Ø 70mm/30 LEDs set 2-battery case (batteries not included)
15702	3 optics Ø 130mm/30 LEDs set 2-battery case (batteries not included)

Rechargeable battery power supply :

19602	3 optics Ø 70mm/30 LEDs set Rechargeable battery (Rechargeable battery not included)
16891	3 optics Ø 130mm/30 LEDs set Rechargeable battery (Rechargeable battery not included)

Options


Universal fixing clamp option : the option includes 3 pre fitted clamps on diameter 130 mm optics.

29815	option 3 clamps for universal mounting.
--------------	---

Jack lead extension :

22279	For optics Ø 70, Ø 130 ou Ø 200 Length : 5 m
--------------	---

Illuminated Sign Equipment



Bi-flash set autonomy * :

Optic	2 Battery Case		4 Battery Case		Battery
	7 Ah	45 Ah	7 Ah	45 Ah	75 Ah
130 mm 30 LEDs	301 h	1 936 h	602 h	3 873 h	3 227 h
200 mm 80 LEDs	119 h	767 h	239 h	1 535 h	1 279 h

* 24 hours operation with 7 hours of night and at 20°C

Pre-Equipped Bar For Panel Signs

Lighting equipment composed of 2 LED optics a control panel. Activated by a 3-position waterproof switch (24-hours, off, night).

Bar length 1500 mm

Power supply using 2-battery case (type 4R25) :

14004	Fast-fit bar bi-flash optic Ø 130-30 2-battery case (batteries not included)
1532	Fast-fit bar bi-flash optic Ø 200-80 2-battery case (batteries not included)

Power supply using rechargeable battery :

57703	Fast-fit bar bi-flash optic Ø 130-30 Rechargeable battery (Rechargeable battery not included)
23659	Fast-fit bar bi-flash optic Ø 200-80 Rechargeable battery (Rechargeable battery not included)

Bi-Flash Set For Panel Signs

Lighting equipment composed of 2 LED optics a control panel. Activated by a 3-position waterproof switch (24-hours, off, night).

The length of the optics lead is 1.5 m. Extension option available.

2 battery case power supply (4R25 type) :

26906	bi flash optics Ø 130mm/30 LEDs set 2-battery case (batteries not included)
16893	bi flash optics Ø 200mm/80 LEDs set 2-battery case (batteries not included)

Rechargeable battery power supply:

24856	bi flash optics Ø 130mm/30 LEDs set Rechargeable battery (Rechargeable battery not included)
16894	bi flash optics Ø 200mm/80 LEDs set Rechargeable battery (Rechargeable battery not included)

Traffic Guidance



→ 1547



→ 37121

Scrolling Lighting Bar 5 Optics

Length 1,3 m, with 5 optics Ø 200/80 LEDs.
Scrolling direction (right, left or double flash) is controlled by a switch.
3m power supply cable with XLR plug.

1547

Bar with 5 optics Ø 200/80 LEDs

37121

Clamp option for universal fixing

Accessories

XLR extension :

12018

XLR extension - 16 m

Day/night control unit:

Allows night-time only power-up to be achieved.

1556

Day/night control panel

Mobile battery case Option :

45801

Mobile battery case option

Protection cage for mobile battery case :

41186

Protection cage for mobile battery case
(Padlock nnot included)

Theft delay arm tube:

47110

Anti-theft arm
(Padlock nnot included)

Padlock :

12257

Brass padlock



→ 12018



→ 1556



→ 45801



→ 41186



→ 47110

Exclusive :

The scrolling mode is preceded by a **double synchronised flash** on all optics.

This method helps to guide drivers !



Scrolling Ø 200 Optic with theft-prevention attachment

Auto-synchronizable lamps via wired connections. Each optic connects behind the previous light. Power on the first fire.

LED optics Ø 200/80 with secondary lens.

Consumption at 12 V in flash mode : 0,06 A.

Operating mode for better security :

Double control of the light source. Synchronous flash of all optics to promote spatial identification of the bend in all its depth.

Superimposed scrolling sequence with drag effect to mark the curve.

Wiring mode :

Supplied with an independent cable equipped with two XLR plugs, length 16 m.

Easy storage and quick implementation.

11400

Optic Ø 200/80 LEDs wired connection
Anti-theft device

5 optics storage container :

37192

Storage container for 5 optics & cables

Mobile VMS

The Variable Message Panel on a mobile trolley precisely informs and signals the road user. Its flexibility of implementation and its small footprint on the roadway make it possible to adapt to all scenarios. Supplied with its control case and a complete library of messages, it can easily be supplemented with the messages of your choice.

Variable Message Sign specifications:

- 140 mm matrix display, for up to 10 characters.
- Yellow LEDs.
- Polycarbonate UV-resistant protection.
- Standard RAL matte black colored.
- Enclosure fitted with toggle locks.
- Fixing gear included.

Control unit specification:

- Backlighting.
- Direct short keys (auxiliary, triangle, VMS).
- 99 preprogrammed messages.
- Editable text messages with the programming software (included).
- Connection with USB port for message modification.
- Rear ball joint fixing.

VMS general specifications :

- Voltage: 12 V.
- Dimensions: 1210 x 295 x 220 mm.
- Overall height: 1533 mm.

The mast can be detached from the battery compartment for transport means

40099

Site mobile VMS
H140 matrix, 10 characters



Site Lighting



1535



Light With Optic Ø 180 mm

Double-face light with transportation handle.
LED optic with Ø 180 mm (1 LED per face).
Power-up using a protected switch.

Power supply using 2-battery case 6V 4R25.
(batteries not included).

Standard model :

Operational autonomy in flashing mode : 250 hours.

Night operation only.

Theft prevention fixing.

One lock key supplied for the purchase of 4 lights.

1535

Light Ø 180/2 LEDs

Light With Optic Ø 210

Single-face light with transportation handle, LED optic diameter 210 mm. Activated by a 3-position waterproof switch (24-hours, off, night).

Power supply using a 4-battery case 6 V 4R25.
(batteries not included).

Operational autonomy in double flash mode : 255 hours.

One lock key supplied for the purchase of 2 lights.

14386

Light Ø 210/80 LEDs



14386

Work On Site Equipments

21

Intervention Triangle

700 mm Triangle equipped with 3 LED optics with Ø 70 mm.
Folding front/rear stand.
Stands locked using self-tightening strap.
Choice of symbol.

Power supply using rechargeable battery built into box.
Supplied with mains-charger power supply.
Operational autonomy in double flash mode: 35 hours.

26386 Intervention triangle 700 - class 2
With built-in rechargeable battery

6035 Class 2 - road sign 400 x 150
Single sided

35265 Class 2 - road sign 400 x 150
Double sided



❖ 26386

❖ 6035



Symbol of
your choice



Tripod

700 mm tripod to place on the ground with 3 faces AK5 retro class 2 fluorescent prismatic.
Other symbol, Contact us.
Delivered with its storage bag.

36446 3-sided tripod 700 AK5 T2 prismatic fluo
+ PVC case



❖ 36446



Emergency Traffic Guidance Kit

Set of **6 LEDs lights** (for emergency marking) in their own **storage and re-charging case.**

Mains and cigarette-lighter recharge included
Each lamp also has a magnetic attachment.
9 operating modes (fixed, flashing, rotating...).

30096 Blue Emergency Traffic Guidance Kit
Rechargeable

30107 Amber Emergency Traffic Guidance Kit
Rechargeable



❖ 30107

High Strength




230 V



Cigarette-Lighter

Power Supplies



→ 376

→ 1992

→ 1953

→ 393



→ 1555



→ 21551



→ 26758



Rechargeable Battery

376	Rechargeable battery 12 V 200 Ah range
1992	Rechargeable battery 12 V 100 Ah range
1953	Rechargeable battery 12 V 75 Ah range
393	Rechargeable battery 12 V 40 Ah range
56356	Rechargeable battery 12 V 3 Ah range

Battery Holder Box

Polypropylène battery holder box allowing the integration of a battery up to 75 Ah. External connection via 3-point XLR socket.

1555	Battery holder box
------	--------------------

Battery Charger

Charge your batteries safely.

For each battery technology, there is a suitable charging curve.

Our chargers can recharge your batteries in accordance with manufacturers' recommendations.

Restore the initial capacity of your batteries while preserving them.

BOOST/rapid charge - ABSORPTION/égalisation - FLOATING/maintenance. These three curves are applied automatically in turn.


Our battery chargers provide high quality charge regulation which guarantees protection and a long battery operating life.

Charger for batteries from 100 Ah to 250 Ah :

21551	Battery charger range 300 W / 12 V
-------	------------------------------------

Charger for batteries from 50 Ah to 100 Ah :

26758	Battery charger range 100 W / 12 V
-------	------------------------------------




385

36029

Batteries 6 V 4R25

Carbon-zinc battery 6 V 4R25 7 Ah :

385

Battery 6 V 4R25 7 Ah range

Pile alcaline 6 V 4R25 45 Ah :

36029

Battery 6 V 4R25 45 Ah range


15700

17129
NEW

4R25 Battery Power Box

6 V 4R25 battery power supply box: (batteries not included). Equipped with a dual flash mode electronics. Activated by a 3-position waterproof switch (24-hours, off, night). Connection via 3 jack sockets.

17129

2-battery power supply case jack
Double flash mode

15700

2-battery power supply case jack
Double flash mode

Mains Supply

Power supply 230 V / 12 V - 3 A in PVC housing. This housing is compatible with all safety equipment.

1522

Alimentation secteur 230/12 V
Connexion par fiche XLR


230 V
1522


Supply Using Public Lighting Source

Box allowing connection to the public lighting network.

34577

Public Lighting Source case 7 Ah
Rechargeable battery included

1694

Public Lighting Source case 17 Ah
Rechargeable battery included


P.L.S
34577


Solar Power Site Supply

Set consisting of a solar panel and an accumulator box, including the regulation electronics and the battery.

29577

Solar power kit 20 W
Connection via XLR plug

29578

Tri-flash control panel for solar power kit
17 Ah


SOLAR
29577


Intégral™

Pre-equipped, ready to install.

The **Intégral™** system is a concept : the idea of developing a coherent **customised ready-made assembly**.

Our **Intégral™** design concept will ensure that we produce the equipment that you require.



Our human/equipment interface

The control of the equipment is based on ergonomic elements, offering real comfort of use.

Our control panels, are compact and fully configurable according to requests; they allow the integration of all functions.

Illuminated Signals

VEHICLES

Control panels ■ p. 26

Searchlights & work lights ■ p. 27

Rotating beacons ■ p. 28 - 29

Light Heads ■ p. 28

Mini lightbars ■ p. 29

Lightbars ■ p. 30 - 31

Scrolling lightbars ■ p. 32

Directional light arrows ■ p. 33

Light triangle ■ p. 34

The Integral Classic ■ p. 35

The streamlined Integral Classic ■ p. 36 - 37

Fittings ■ p. 38

Vehicle screen printing ■ p. 39



CONTROL PANELS P 26



NEW

ROTATING BEACONS P 28 - 29



LIGHTBARS P 30 - 31



**STREAMLINED
INTEGRAL CLASSIC** P 36 - 37

Control Panels



Configure your Intégral™ system to meet your needs : A control panel is available



Our Switches

In individual modular formats, up to «n» switch elements can be assembled together. They offer two outputs protected by a 15 A fuse. In the simplest solution the switch allows equipment to be controlled individually (one switch = one item of equipment). The switch is illuminated when the equipment is in operation. Set of pictograms provided.

30216	1 Switch pack Supplied with base and set of pictograms
30217	2 Switch pack Supplied with base and set of pictograms
30218	3 Switch pack Supplied with base and set of pictograms

MEZZO 8 ECO our all-in-one control unit

MEZZO 8 ÉCO is a control panel very compact and ergonomic, fully configurable. The keys are customisable and backlit depending on the active equipment. It is designed to ensure complete control of a bidirectional ramp. It also includes 3 positive outputs for controlling additional equipment (rotating beacons, siren, triangle, spotlights, etc.).

The 12/24 V dual-voltage power module allows you to control up to three 10 A on-off auxiliary outputs protected by fuse. It also allows the control of a scrolling ramp.

43385 MEZZO 8 ECO control panel + power module + cable



USB
Connection




BUS single
cable only



Quick
setup



Adjustable
stand



LED
backlight



No
relays



Pictograms
collection



➔ **37852**



➔ **55754**

Sound Management Modules

37852	Sound generator - siren 12/24 V 100 W
55754	Kit Public adress For siren HP micro

Search Lights

27

Search Lights

To efficiently light up a working zone with the possibility of remotely directing the light beam in various directions (from a distance of more than 25m). Our searchlights are studied to be able to give you a large use and installation flexibility.

Wireless remote control included.

41414

LED search lights
30 W / 12 V

33898

Halogen searchlights
65 W / 12 V



Work Lights

LEDs Work Lights

This range of work lights will guarantee low energy consumption with high light intensity (on average: 80 Lumens / 1 Watt).

Professional model suitable for extreme conditions.



30164

30162

30174

30167

Voltage	Power	Brightness	Work lights	Magnetic fixing kits
			Reference	Reference
12/24 V	18 Watts	1260 Lumens	30162	30633
	24 Watts	2000 Lumens	30164	30633
	36 Watts	2520 Lumens	30174	30633
	72 Watts	5040 Lumens	30167	30681

All our LEDs work lights are also available with magnetic fixings



Magnetic
fixing kit



Cigarette
lighter plug



12V - 24 V

Move your lights, not your vehicle !

Thanks to our magnetic kit, you can position the work light anywhere on your vehicle.
5m extension included.



30633

30681

Rotating Beacons

HOMOLOGATION
R10HOMOLOGATION
R65

❖ 23392



❖ 35785

Wireless beacon



❖ 52547

LED Range

Available in flat base, tube or magnetic mounting (supplied with spiral cable and cigarette lighter socket), our LEDs rotating beacons have all the current advantages of the market :

- Dual voltage 12/24 V.
- Robust (polycarbonate dome).
- To be used with engine off.
- Very long lifetime.
- No maintenance (no bulb, no belt, no motor...).
- Ultra quiet.

CLASSIC Range

Voltage	Fixing	Mode	Colour	Reference
12/24 V	Flat	Rotating	Amber	35785
			Blue	contact us
		Flash	Amber	23391
			Blue	contact us
	Tube	Rotating	Amber	23392
			Blue	contact us
		Flash	Amber	23393
			Blue	24058
	Magnetic	Rotating	Amber	contact us
			Blue	
		Flash	Amber	
			Blue	

Amber **wireless rotating beacon** in flash and rotating mode. Operates on 2.6 Ah battery, autonomy of 6 hours (depending on the mode and state of charge of the battery). Easy charging using a spiral cord with cigarette lighter plug (provided), charging time 4 hours. Double magnetic and suction cup fixing system. Battery charge status indicator.

❖ 52547

Rechargeable wireless LED flash/rotating beacon
Amber - magnetic & suction mount

Light Heads

Light Heads

LEDs penetration light, dual voltage 12/24 V:

21149 Light head 113 x 28 amber
12/24 V

43398 Light head 113 x 28 blue
12/24 V

43397 light head 133 x 45 bicolor amber/blue



❖ 21149



❖ 43398



Ultra thin



❖ 43397

Bicolor - amber / blue



Bicolor LED

ACCESS Range

Optimized to meet the essentials



→ 30302



→ 30634



→ 34855

NEW

ACCESS Range

Voltage	Fixing	Mode	Colour	Reference
12/24 V	Flat	Rotating	Amber	30302
	Tube		Amber	30634
	Magnetic		Amber	34855

ACCES range blue : contact us

Connection Tube

- 1595 Screw-on tube
- 1597 Vertical fixing tube
- 1598 Horizontal fixing tube



→ 1598



→ 1597



→ 1595

Mini Lightbars

Ultra-Flat Lightbars : ALPHA

- 36593 Amber ultra-flat lightbar 12/24 V, 24 LEDs, 355 mm
Magnetic + Cigarette lighter plug
- 36294 Amber ultra-flat lightbar 12/24 V, 24 LEDs, 355 mm
Fixing by central bolt

Control panel not included (to be select from page 26)



→ 36593



→ 36294

Lightbars

HOMOLOGATION
R10

HOMOLOGATION
R65



LEDs Lightbars



Multifunction streamlined signal lightbar Height 135 mm.
LED lights. Central module with back-lit text (double sided).

Voltage	Length	Number of lights	Colour of lights	Text	Reference
12/24 V	970 mm	2	Amber	Yes	35594
		4	Amber	Yes	35598
				No	35592
	1400 mm	2	Amber	Yes	35596
		4	Amber	Yes	35600
			Amber / Blue	Yes	35604



→ **35594**



→ **35604**

Halogen Lightbars



Multifunction streamlined signal lightbar Height 135 mm.
Halogen lights. Central module with back-lit text (double sided).

Voltage	Length	Number of lights	Colour of lights	Text	Reference
12 V *	970 mm	2	Amber	Yes	35593
		4	Amber	Yes	35597
				No	35590
	1400 mm	2	Amber	Yes	35595
		4	Amber	Yes	35599
			Amber / Blue	Yes	35603

* For 24 Volts: please contact us



→ **35597**



→ **35603**



Magnetic option
& customised lightbars :
Contact us  





Standard Flat Lightbars : EPSILON

This ultra low profile lightbar, length 1080mm, is composed of 36 yellow power LEDs. A blank central text space (448mm), on both sides, with a text of your choice.

39953

Flat lightbars 59 mm
36 LEDs length 1080 mm



→ 39953

Synchronized flash :

12 blocks of 3 yellow LEDs, 18 LEDs on the front panel and 18 yellow LEDs on the rear panel. As well as 4 blocks of 6 wide-angle yellow LEDs (2 on each side).

42121

Flat lightbars 59 mm
60 LEDs length 1252 mm



→ 42121

Also available in blue

Bicolore LED amber & blue :

4 blocks of 3 yellow LEDs, 6 LEDs on the front panel and 6 yellow LEDs on the rear panel. 4 blocks of 3 blue LEDs, 6 LEDs on the front panel and 6 LEDs on the rear panel. Central white module with free text.

45591

Flat lightbars 59 mm
48 LEDs length 1252 mm



→ 45591

Control panel not included (to be select from page 26)

Operating mode
Flash, Scrolling, Alternative mode

Color
Led, Lens

Size



Bicolore LED

2 in 1 : scrolling & illuminated ramp



→ 39954

N°1 on modularity
Options to fit your needs

Contact us  



Special Flat Lightbars

We can modulate our lightbars to your needs.
Consult us for specific requirements.

We can adapt the size of our lightbars for a better fit into the vehicle, and offers you specific functioning mode, colors and polycarbonate lenses that suits your requests.

Example :

2 in 1 : a scrolling bar at the rear of the vehicle, **a lightbar** on the front and on the sides. 12 blocks of 3 yellow LEDs, 18 LEDs on the front and 18 LEDs on the back. 2 blocks of 6 wide-angle yellow LEDs on each side.

39954

Flat lightbar 59 mm
60 LEDs length 1252 mm

Scrolling Lightbar



Scrolling Lightbar

2 in 1 : a scrolling bar at the rear of the vehicle, **a lightbar** on the front and on the sides. 12 blocks of 3 yellow LEDs, 18 LEDs on the front and 18 LEDs on the back. 2 blocks of 6 wide-angle yellow LEDs on each side.

39954

Flat lightbar 59 mm
60 LEDs length 1252 mm

Ultra-flat scrolling lightbar:

37866

Scrolling lightbar 8 LEDs lights
Control panels below

43385

MEZZO 8 ECO control panel + power module + cable

2 in 1 : scrolling & illuminated ramp



➡ **39954**



➡ **37866**

➡ **43385**



➡ **30222**

Streamlined scrolling lightbar :

30222

LEDs scrolling lightbar 5 lights
and 2 LEDs rotating beacons



➡ **27473**

With triangle AK5 500 or 700 class 2, with electrical lifting system, and 2 LEDs rotating beacons.

27473

LEDs scrolling lightbar
Triangle 500 class 2

21968

LEDs scrolling lightbar
Triangle 700 class 2

Control panel not included (to be select page 26)
(switches not compatible)

Lighted Directional Traffic Arrows

33

These arrows are composed of 2 aluminum panels, assembled with a rubber watertight gasket. Fixing with back rails. Magnetic fixture is optional.

Control panel is not included (to be select page 26) :
The arrows can be controlled by the 2 switch pack (reference 30217, not included).
Contact us when a complete solution is required, with added triangles and rotating lights.



➡ 38789

Lighted Directional Traffic Arrows (16 optics)

Blinking arrow (1000 x 400 x 50 mm), 16 lights Ø 70 :
Arrow with low consumption LEDs, single sided.

38789

LEDs blinking arrow



➡ 1585



Lighted Directional Traffic Arrows (14 optics)

Blinking arrow (720 x 720 x 50 mm), 14 lights Ø 70 :
Arrow with low consumption LEDs, single sided.

1585

LEDs blinking arrow



➡ 24006

Directional Light Arrow Flashing and Magnetic (8 optics)

Directional light flashing 8 lights Ø 70 :
The traffic direction, right or left, is determined by the direction of installation of the luminous arrow.
Supplied with 10m cable and cigarette lighter plug.

Warning, this product cannot be used on a driving vehicle.

24006

LEDs flashing arrow
12V power supply

Light Triangle

- Ultra-flat optics.
- 8 power LEDs.
- Protected by polycarbonate lenses.

➡ 1566



500 mm Triangle Range with LED Optics

- Dimensions : 500 mm.
- Anodized aluminium box.
- The light element is composed of three optics of Ø 70 mm on each side
- Dual voltage without bulb change (12 or 24 V).
- Supplied with 10 m power cord.

Double sided 500 mm :

Mounting on double-acting hinge, for a forward or backward tilt of the box.

1566

Light triangle AK5 500 - double sided
Class 2

Single sided 500 mm :

With rails fixed on the back.

1570

Light triangle AK5 500 - single side
Class 2 - With rails fixed on the back



➡ 1570



➡ 1567



700 mm Triangle Range with LED Optics

- Dimensions : 700 mm.
- Anodized aluminium box.
- The light element is composed of three optics of Ø 70 mm on each side
- Dual voltage without bulb change (12 or 24 V).
- Supplied with 10 m power cord.

Double sided 700 mm :

Mounting on two double-acting hinges, for a forwards or backwards tilt of the box.

1567

Light triangle AK5 500 - double sided
Class 2

Single sided 500 mm :

With rails fixed on the back.

1571

Light triangle AK5 700 - single side
Class 2 - With rails fixed on the back

Option

Manual folding kit :

1576

Manual folding kit

➡ 1576



Create your own **Intégral™**
or select a standard configuration :



→ 1956 Triangle 500



2 Elements Configuration

Pre-equipped assembly including :

1 roof rack.
1 amber LEDs beacons.
1 LEDs triangle 500 mm or 700 mm.

1956	Configuration n°2 Triangle 500 class 2
1957	Configuration n°3 Triangle 700 class 2

Control panel not included (to be select page 26).

→ 1959 Triangle 700



3 Elements Configuration

Pre-equipped assembly including :

1 roof rack.
1 amber LEDs beacons.
1 LEDs triangle 500 mm or 700 mm.
2 LEDs work lights.

1958	Configuration n°4 Triangle 500 class 2
1959	Configuration n°5 Triangle 700 class 2

Control panel not included (to be select page 26).

→ 35341



→ 37866

Options **Intégral™** Classic

Manual folding kit :

1576	Manual folding kit
------	--------------------

8 lights LEDs scrolling lightbar :

37866	8 lights LEDs scrolling lightbar (control panel ref 43385 not included)
-------	--

Intégral™ Streamlined Classic



Reinforced durability

Triangle anodized aluminum /
LEDs / aluminum chassis



➡ 29112



➡ 29963

Intégral™ Streamlined Classic

Manual Lift :

1 LEDs triangle 500 mm or 700 mm. 1 power supply cable length 10 m with cigarette-lighter plug 1 magnetic fixing kit.

« The all-in-one » removable or fixed.
Universal system, without roof rack
it is immediately suitable for all vehicles.



Delivered assembled
ready to operate



Only
10 kg



Cigarette lighter
power supply
12/24V

29112

With triangle AK5 500 mm
Class 2

29113

With triangle AK5 700 mm
Class 2

Electrical Lifting System :

1 LEDs triangle 500 mm or 700 mm. 1 power supply cable length 10 m. 1 magnetic fixing kit.
Supplied with a 1 switch pack.

29963

With triangle AK5 500 mm class 2
Electric Lift

29964

With triangle AK5 700 mm class 2
Electric Lift

It is necessary to add a fixing option to your electrical lifting system fairing :

Roof rack fixings option :

38492

Optional roof rack fixings

Adhesive fixings kit :

29053

Optional adhesive fixings

Removable : Magnetic
Fixed : Adhesive



➡ 29053

Intégral™ Streamlined Classic

37

Options



Create your own **Intégral™**

Beacons, scrolling lightbar,
work lights, paint...



OPTIONS

Tell us your requirements,
we have the solution!

Intégral™ Streamlined Classic Options

2 LEDs beacons kit :

29030 Optional two rotating beacons with amber LEDs.
(For other beacons please contact us)

2 LEDs work lights kit

30223 Optional two LEDs 18 W work lights
(For other work lights please contact us)

8 lights LEDs scrolling lightbar :

37866 8 lights LEDs scrolling lightbar

Manual folding kit :

1576 Manual folding kit

RAL color of your choice !

All our fairings have a professional level of powder-coating finish.

The use of a polyester powder paint guarantees the best paint resistance.

By default the fairing is white.



Fixings



→ 38410

Universal adhesive system



→ 4765

Universal Fixing Kits

System without need of drilling :

Fits all brands and types of vehicles.

38410

Adhesive fixing kit for Integral Classic
3M adhesive tape

System requiring drilling

Roof bar with drilled fixing system.

4765

Drilled fixing kit
K1P1 rack

Whatever your vehicle, a suitable system is available



Contact us  

Roof Rack For Vehicles

Complete kit (pair of fastenings + roof bar)

Please specify the correct vehicle type and its year of manufacture (fixings may vary from one year to another).



1614 Renault Master / Mascotte

1615 Renault Clio

1616 Renault Kangoo

2232 Renault Master Mascotte (Benne)

5283 Renault Trafic / Opel Vivaro

1617 Peugeot Boxer / Citroën Jumper

1618 Peugeot Expert / Citroën Jumpy

1620 Peugeot Partner / Citroën Berlingo

24568 Fiat Doblo

20998 Fiat Fiorino

2231 Mercedes Vito

23077 Mercedes Sprinter / VW Crafter

14301 Opel Combo

1622 Iveco Daily

24436 Nissan Cabstar / Renault Maxity

Vehicles with roof gutters :

Complete kit for vehicles equipped with roof gutters.
1 pair of adapters and a roof rack.

1607

Standard gutter-system roof-rack



→ 1616



→ 1614



→ 1612



→ 2232



→ 1618



→ 1620





→ 1607

Vehicle Screen Printing

39

A cut perfectly adapted to the vehicle



Minimum lateral



Maximum lateral



→ 1972

→ 1973



→ 12866

Order of 6 November 1992 published in the journal officiel of 3 January 1993

Article 2 : approves the new requirements in book 1 of the inter-ministerial instructions on road signals shown under the heading «Part 8»: temporary signals.

Article 122C booklet part 8e : mobile equipment.

Mobile equipment forms an obstacle which must be made particularly obvious. Vehicles which regularly work on the roadway must carry signals in accordance with the requirements of the order of 20 January 1987.

Requirements of the Order of 20 January 1987 :

Minimum surface area per vehicle, 0.80 m².

Front : 0,16 m² - **Rear :** 0,32 m².

Right side +left side : 0,32 m².

Homologated by DSCR, under the TPESC number shown on each white stripe.

Pre-Cut Kit

Appropriate for the vehicle, available in class 1 and class 2. Minimum front and rear + side kit or maximum front and rear + side kit. **Contact us.**

Box Of 2 Rolls

Includes the left side and right side roll. Red and white traffic guidance.

1966

Rolls Class1

2 rolls 9 m / width 0.14 m

1967

Rolls Class 2

2 rolls 9 m / width 0.14 m

Magnetic Strip

1972

Magnetic «service» strip Class 1
50x15 cm

1973

Magnetic «service» strip Class 2
50x15 cm

Municipal Police Vehicle Screen-Print

Decree no.2005-425 of 28 April 2005 (published in the journal officiel of 7 May 2005).

- **Front :** 800 x 400 mm 'Police Municipale' with red margin and blue text screen printed on 2 lines.
- **Rear :** 3-colour badge 96 x 120 mm. Strip 720 x 90 mm 'Police Municipale' with red margin and blue text screen printed on 1 line, class 2.
- **Side :** Blue strip 14 x 120 mm.
Triple 'Gitane' stripe 120 x 14 mm.
Triple 'Gitane' stripe with red 'Z' 14 x 120 mm.
3-colour badge 240 x 300 mm.

12866

VL Kit 'Police municipale'

**Screen printing for other types of vehicles available :
Contact us.**

Intégral™ Dynamic

The **Intégral™** concept : all our safety equipment are integrated in a coherent and customized signaling device.

The **Intégral™** Dynamic, it is the insurance to get the equipment you need. Our control units and our interfaces will allow you to easily integrate all of your vehicle and on-board signaling projects.



Our **compact** and **ergonomic control panels** are fully configurable. The keys are backlit. Two sizes of control units: 4,3" and 7" in diagonal, suitable for light or heavy duty vehicles.



NEW

**Micro-lift
VMS 1 + 3 lines**



A new addition to our on-board range, here is a compact lift, capable of relaying messages of 1 to 4 lines.



Illuminated signals

ON-BOARD

General description ■ p. 42

Control panels ■ p. 43

On-board range ■ p. 44 - 47

FLR trailers ■ p. 48 - 49

VMS trailers ■ p. 50 - 51

Pictogram trailers ■ p. 52 - 53



CONTROL PANELS P 43



ON-BOARD RANGE P 44 - 47



EMERGENCY LIGHT ARROW P 47



TRAILERS P 48 - 53

General Description



VMS for light utility vehicles

For the equipment of your light utility vehicles, we recommend the character heights : **H160** and **H200** mm of 8 to 10 characters with spacing or 12 characters in a **continuous matrix**.



CE certified to EN12966 standard

Visit the site : www.ascquer.fr



VMS for heavy duty vehicles

For the equipment of your heavy utility vehicles, we recommend the character heights : **H200** and **H250** mm in 9 to 10 characters with spacing or 12 characters in a **continuous matrix**.

Our **Intégral™** Dynamic concept integrates our entire range of **certified** displays in 7 x 5 matrix or continuous matrix.

Certification requires complete control of photometric and heat resistance parameters, making our displays **the most efficient displays** on the market .



**Fast
maintenance**



BUS 80 A & Control Electronics Cards Reliability / Modularity

The **Intégral™** Dynamic it is the first signaling system to have a complete modular BUS with electrical and data connection. With no more hard-to-extract cables, the BUS 80A provides guaranteed reliability and ease of maintenance. This expandable BUS on one hand distributes electrical supplies of up to 80A and on the other hand high flow CAN. It incorporates a general cut-out relay.

There are two configurations available: 2 slots and 4 slots.



The **Intégral™** Dynamic is the first signaling system to have a set of control electronics cards allowing it to respond to all applications in a standard and modular manner.

Functions relating to VMS, lifting, auxiliary, scrolling light bars, emergency light arrow, analog and digital inputs functions can all be combined using the 3 Integral Dynamic base cards.

Modular chassis

The chassis of the **Intégral™** Dynamic are mechanically assembled using stainless steel screws, from a library of standard parts common to all equipment. The screw assembly technique and the standardization of parts allow unrivaled maintenance comfort, within the reach of all maintenance workshops without any particular qualification, without delay !

All our frames benefit from a professional powder-coating finish. The use of a polyester powder paint makes it possible to guarantee the best paint resistance.





ALTO 4.3"

The **ALTO 4.3"**, 11 cm diagonal control panel is particularly suitable for light goods vehicles: Kangoo, Nemo, Berlingo, Jumpy, Partner, Expert, Doblo, Fiorino, Scudo etc. It has a 16/9 screen - 480 x 272 pixels - high luminosity 400 cd/m², +/-60° angle for unmatched ease of use. Guaranteed to operate between -30°C and +75°C.

The **ALTO 4.3"** is made for use in all difficult environments. It includes all commands for VMS, triangles, lifting, beacon auxiliaries, working lights, scrolling lightbars etc. Update by USB key.

32702

Control panels
ALTO 4.3"USB
ConnectionBUS single
cable onlyQuick
setupPC
setupAdjustable
standÉcran
LCDLED
backlight

USB Connection



Dual pivot mount

ALTO 7"

The **ALTO 7"** 18 cm diagonal control panel is suitable for all types of vehicles. It has a 16:9 screen - 800 x 480 pixels high brightness 400 cd/m², +/-60° angle for unrivaled comfort of use. Guaranteed to operate between -30°C and +75°C.

The **ALTO 7"**, is made for all difficult environments. It integrates all VMS controls, triangles, lifts, gyro auxiliaries, work lights, scrolling ramps, emergency light arrow, etc.

The **ALTO 7"** has a dual port for front and rear cameras as standard. With a GSM modem, you will be able to transmit images in real time to your control PC. Updated control box by USB key.

34023

Control panels
ALTO 7"

Wide angle camera

On-Board Range



VMS - Variable Message Sign

Our variable message signs installed directly on the vehicle are equipped with high light intensity LED displays. Created for temporary mobile signaling on roads and highways, they inform users of traffic conditions.

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera etc.).



VMS 1 + 3 Lines

- VMS : new generation energy-saving displays, H125 mm (2 LEDs per point) 12 characters..
- Automatic brightness switching thanks to a day and night cell.
- Lifting system using electrically operated cylinder, equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera etc.).

Safety auxiliaries available as options

A wide range of additional accessories allowing you to create equipment that fully meets your requirements: Beacons, spotlights, anemometer, rearview camera, siren etc.

Please contact us to configure your on-board equipment.



VMS + Triangle 500 / 700

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Double sided triangle 500 or 700 mm :
 - Aluminum sheet with flanged edges.
 - Class 2 adhesive, symbol of your choice.
 - Equipped with 6 Ø 70 mm optics with 30 LEDs.
- Lifting system using electrically operated cylinder, equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).



VMS + Triangle 1000 / 1250

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Double sided triangle 1200 mm :
 - Aluminum sheet with flanged edges.
 - Class 2 adhesive, symbol of your choice.
 - Equipped with 6 Ø 200 mm optics with 80 LEDs, protection by polycarbonate lens.
- Lifting system using electrically operated cylinder equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).



On-Board Range



VMS + Triangle 1250 Pictogram

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Triangle 1250 mm :
 - Two-colour graphic matrix.
 - Allows the display of "large" type A range panels.
- Lifting system using electrically operated cylinder equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).



VMS + 16 optics Arrow (KR42)

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Double sided triangle 500 or 700 mm :
 - Aluminum sheet with flanged edges.
 - Class 2 adhesive, symbol of your choice.
 - Equipped with 6 Ø 70 mm optics with 30 LEDs.
- KR42 type arrow: 16 optics Ø 70 mm with 30 LEDs.
- Lifting system using electrically operated cylinder equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).

Safety auxiliaries available as options

A wide range of additional accessories allowing you to create equipment that fully meets your requirements: Beacons, spotlights, anemometer, rearview camera, siren etc.

Please contact us to configure your on-board equipment.



Illuminated Emergency Arrow

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Illuminated Emergency Arrow type KR43 : 23 optics Ø 200 with 80 LEDs, protection by polycarbonate lens.
- Lifting using electrically operated cylinder equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).



Illuminated Emergency Arrow + Triangle 1250 - Foldable System

- VMS : new generation energy-saving displays, different sizes to choose from H160, 200, 250 mm (3 to 4 LEDs per point) ranging from 8 to 12 characters.
- Automatic brightness switching thanks to a day and night cell.
- Triangle 1250 mm single or double sided :
 - Aluminum sheet with flanged edges.
 - Class 2 adhesive, symbol of your choice.
 - Equipped with 3 optics for the single-sided triangle or 6 optics for the double-sided triangle.
- Illuminated Emergency Arrow type KR43 : 23 optics Ø 200 with 80 LEDs, protection by polycarbonate lens.
- Dual independent lifting using electrically operated cylinder equipped with a limit switch.
- Standard RAL paint of your choice.
- Latest generation ALTO control panel with update by USB key.
- Options available on request (beacon, spotlight, rearview camera, anemometer etc.).



FLR Trailers

Long operational autonomy

With its 2 batteries each of 200 Ah, the FLR Trailer can achieve a record operational autonomy of 180 hours



180 hours of autonomy

Galvanised 750 kg chassis

The 750 kg chassis made entirely of galvanised steel can be towed by a light vehicle with no special licence required.

It is equipped as standard with an adjustable height drawbar and a self-braking system.



Towable by a light vehicle
without a specific licence



100% LEDs Technology

The optics of diameter 200 mm are made up of a lighting element with 80 high-luminosity yellow SMC 5 mm LEDs. This lighting element is integrated in a ABS dome.

The front part is protected by a transparent lens made of polycarbonate (high impact resistance). There is guaranteed water-tightness between the polycarbonate lens and the dome, provided by a circular seal.

The assembly is fully dismountable.

Adjustable
Drawbar



Self
Braked



100%
LED

Easy to use

Simple and user-friendly, our FLR trailer facilitates the work of operators, both on the road and in the workshop. A 230 V cord winder ensures permanent storage of the charging cable. A simple, lockable box that holds all of the power supplies.

The deployment of the FLR is carried out from a local command or from a remote box.

Local control cabinet

Our local control cabinet. A digital display enables a clear real time communication between the user and the equipment.

LED indicators are displaying the actual message at the back of the trailer, even from long distance



Protected





FLR Trailer

New generation trailer with LED optics, specifically designed for traffic guidance of mobile sites and urgent work on roads and motorways.

Structure :

- Single axle chassis 750 kg.
- Manual stabilisers.
- Parking brake.
- Adjustable draw-bar.
- Large capacity service chest.
- 25 flashing optics Ø 200 mm.
- 2 flash optics Ø 300.
- 1 B21 sign of diam 1250 class 2, motorised and disengageable.
- Red and white chevrons class 2.

Operational autonomy :

- Long operational endurance :
180 hours with 2 batteries 12 V - 200 Ah.

Low maintenance costs :

Due to LEDs optics, no bulbs to change.

Simplified controls :

The control module provides one-touch control of your signals.

Modular design :

- Generator set.
- Charger for 12 V batteries.
- Control panel on unit or remote operation using a radio or cable link.
- Inertial braking.

Power :

Batteries / charger for 12 V batteries / mains lead reel / generator set available as option.

25878

Single axle trailer

Remote Control Device

The trailer is equipped with a remote-control box (IP67), cable, (15m) and / or radio. It takes the functionality of the local console, while adding new functions :

- Faithful view of the FLR.
- Scenario mode (single command for FLR and B21).
- Fine-tune fault management.
- A 4-indicator battery gauge.

The repeaters remain active on the local console in case of control by the remote console.

The remote control unit allows you to manage FLR commands remotely, safely from the cabin of the towing vehicle or near the trailer.

35514

Radio control panel



35514

RADIO or WIRED
remote control



VMS Trailers



Selectable power supply



Towable by a light vehicle
without a specific license



Power supply

The electrical modularity of the VMS trailer allows it to be powered by different energy sources : batteries, 230 V, generator, solar energy.

Galvanised 750 kg chassis

The 750 kg chassis made entirely of galvanised steel can be towed by a light vehicle with no special licence required. It is equipped as standard with an adjustable height drawbar and a self-braking system.

Ease of use and maintenance

Easy to use, our VMS trailer makes the work of operators easier, both on the road and in the workshop. A simple, lockable box brings together all the power supplies. Access to the displays is by opening the rear door of the box.

100% LEDs Technology

200 mm H displays composed of a 7x5 matrix with 3 LEDs per pixel, for a total of 105 high brightness 5 mm yellow SMD LEDs. This light element is integrated into a one-piece box made of mechanically welded TTS aluminum profile. It is covered with a black oven-baked epoxy paint. The front panel is made of 4 mm anti-UV polycarbonate for maximum protection.

The assembly is completely removable for simplified maintenance.
Our displays are CE EN12966 certified

Control unit

The modularity of the VMS trailer allows control by different systems locally or remotely: encoder wheel, local control box with LCD screen, updates via USB key, remote control via 4G modem, supervision software, etc.



Control panel ALTO
See page 43.





VMS Trailers

This variable message sign on-board a trailer is equipped with high light intensity LED displays. Created to provide temporary mobile signaling on roads and motorways, they provide road users with information on traffic conditions.

Structure :

- Self-braking chassis / single axle 750 kg (Towable weight 830 kg) • Made of galvanised steel • Manual stabilisers • Parking brake • Adjustable drawbar.

Display :

- 1, 2, 3 or 4 lines of 12 characters. • Characters Hc200-4, matrix 7 x 5 • 3 yellow LEDs per point • Red and White chevrons class 2.

Simplified controls :

- In local mode messages are selected using the ALTO 4.3" control panel or encoder wheel or via PC connection.
- In remote mode, communication using GSM network, radio etc.
- Automatic luminosity management.

Programming :

- Programming using a laptop PC / Software and linking cable provided.
- Messages are updated via USB key or connection cable between the PC and the trailer.

Modular design :

- Generator set • Charger for 12 V batteries • Electrically operated stabilisers • Inertial braking • GSM modem.


Power supply :

- Batteries • Charger for 12 V batteries • Mains lead reel • Generator set available as option.

32775

Single axle trailer 750 kg

Single axle trailer, 4 lines of 12 characters, character height 200 mm, 3 LEDs per point.



NEW

SOLAR

Solar power supply option :
600 W photovoltaic panel.

54595

Photovoltaic option for VMS trailer



Picto Trailers



Two-Color Picto. Trailer

Assembly of a fixed part (A14 steel panel with warning arrows, and a matrix panel with a high intensity LED display), on-board a trailer.

Structure : single axle chassis of 750 kg.
Manual stabilizers / Parking brakes / Inertial breaking / Adjustable height drawbar.
4 stands for manual stabilization.
Hot-galvanized steel structure, chassis and mechanisms.
Semi-automated jockey wheel lifting, spring blocking, and reinforced tyre wheel.

Picto Bichrome display : Bichrome matrix display box, size 1550x1550 mm.
56x56 points resolution (3136 yellow LEDs and 3136 red high intensity LEDs).
Display of panel codes A, B and KD in 1250 mm.

Energy : 12 V operation.
Electricity generators. Plug for charging on mains voltage.
Electricity distribution panel with circuit breaker and fuse.

Control electronics : Coating protected control board, mounted in waterproof cabinet.

Control unit : Message selection with the encoder.
Automatic light intensity adjustment (day/night cell).

Programming : With portable computer (not included).
Software and linking cable provided.

39767

Pictogram Bichrome trailer, single axle

Matrix Display Trailer

Assembly of 2 variable message signs, equipped with high light intensity LEDs, on-board a trailer.

Structure : Single axle chassis 1300 kg.
Manual stabilisers / Parking brake / Inertial braking / Adjustable height drawbar.

Fixed lower part display : Monochrome graphic 128 x 96 point matrix. Used to display text, KD signs, animations.

Moving upper part display : Two-colour graphic 48 x 48 point to 64 x 64 point matrix. Used to display «normal to very large» range signs of type A, B and KD.

Control : On site, by laptop PC or encoder. Remotely, by GSM link, radio etc

Programming from a PC : Software provided. Files backed-up on hard disk. Programming of messages, animations, signs from a library.
Multi-level access code for security of programming.

Modular design : Generator set / batteries charger / electrically operated stabilisers / GSM modem.

Energy : 230 V.

13763

Pictographic single axis trailer

Full-Color Picto. Display URBAN Trailer

Set composed of a folding panel equipped with high light intensity Full-Color LED matrix displays and a fixed part (sheet metal panel composed of warning chevrons), loaded on a trailer.

Small trailer 2370 x 1294 mm (dimensions excluding drawbar), which can be installed in a standard parking space.

Structure : Single axle chassis 1300 kg.

Manual stabilizers / Parking brake / Inertia braking / Height-adjustable drawbar.

4 crutches with manual stabilization.

Structure, chassis and mechanisms in hot galvanized steel. Jockey wheel with semi-automatic lifting and spring locking, reinforced tire.

Powder-coated steel panel support structure. Foldable using an electric cylinder for deployment assistance. Locks in folded and unfolded position.

Picto Full-Color Display : Full-Color matrix graphics box with 16 million shades.

Display dimension 1024 x 1280 mm.

Definition 64 x 80 points (i.e. 5120 high light intensity Full-Color LEDs).

Text only display :

- 7 lines of 9 characters character height 112 mm.

Pictogram + text display :

- Pictogram range 700 + 3 lines of 9 characters character height 112 mm.
- Pictogram range 1000 + 2 lines of characters character height 112 mm.

Pictures:

- Any type of image of 64 x 80 pixels max.

Energy : 12 V operation. Generator. Power socket for mains charging. Distribution panel with circuit breaker and fuse.

Control :

Remote control: Slot + power supply for Cisco 4G router (router not supplied)

Local control: IP socket on Cisco router / basic local control software for PC compatible computer.

Automatic brightness management (day/night cell).

NEW



55078

Full-Color urban pictogram micro trailer



Even more economical and environmental friendly equipment & power supplies

Stand-alone photovoltaic power supply :

This is an independent and low-cost method of power supply.

No civil engineering, connection or subscription costs.

Example of economic and environmental summary for two 1000 mm LED triangles over 10 years :



850 KW/h saved,
5000 € saving on electricity consumption and subscription costs.



390 Kg of CO²
not emitted.



Supply using public lighting :

Connection to a public lighting pylon with differential protection.

Low civil engineering cost.

eco-efficient



Illuminated Signals

PERMANENT

Sign lighting equipment ■ p. 56

Curve light-signaling ■ p. 57

Enhanced signaling ■ p. 58 - 59

Dynamic enhanced signaling ■ p. 60 - 61

Permanent signal options ■ p. 62 - 63

Power supplies ■ p. 64 - 65

Green-reward traffic lights ■ p. 66 - 67

Radar speed sign ■ p. 68

Short stop terminal ■ p. 69

Traffic control lights ■ p. 70

Island point warning lights : Eclipse ■ p. 70



**SIGN LIGHTING
EQUIPMENT** P 56



CURVE LIGHT-SIGNALING P 57



ENHANCED SIGNALING P 58-59



**GREEN-REWARD
TRAFFIC LIGHTS** P 66-67

Sign Lighting Equipment



→ 5559

→ 1684
→ 1686
→ 3156


→ 879

→ 1665
→ 1666
→ 1660

→ 35629

Reinforcing all Danger, Prohibition and Information signs

Static signals are not always enough for passing on information to road users. Increasingly either illuminated enhancements, or one or more «flashing» lights are used in association with these signals **in order to attract the attention of road-users.**

Optic Ø300

Optic Ø300 mm with 225 yellow LEDs, (others colors on-demand). Fixing on double rail on the rear side. Polycarbonate protection lens. Integrated contrast screen (500x500 mm / epoxy powder coated paint).

1684	Optic Ø300/225 LEDs 230 V Flashing mode
1686	Optic Ø300/225 LEDs 230 V Double-flash mode
3156	Optic Ø300/225 LEDs 12 V Model for Public Lighting Source or solar power supply
5559	Shield for Ø300mm optic

Optic Ø200

Optic Ø200 mm with 80 yellow LEDs. Fixing using rear plate (most of 60 to 168 mm diameter).

1665	Optic Ø200/80 LEDs 230 V Flashing mode
1666	Optic Ø200/80 LEDs 230 V Double-flash mode
1660	Optic Ø200/80 LEDs 12 V Model for Public Lighting Source or solar power supply
879	Shield for Ø200 mm optic
35629	Contrast screen for Ø200 mm optic 350 x 350 mm

Optic Ø130

Kit with 2 optics Ø130 mm with 30 yellow LEDs (other colors available). Double-flash operating mode.

2306	Kit Biflash Ø130/30 LEDs 230 V Equipped with a control / 230/12V power supply box.
35837	Kit Biflash Ø130/30 LEDs 12 V Model for Public Lighting Source or solar power supply



→ 2306

Options

Speed or presence detection radar, timer etc.

Adapt equipment to meet your requirements, options on pages 62 and 63

No need to connect the equipment together :

NEW



All these products can be equipped with our **GPS synchronization option !**

No more interconnecting equipment; this option, combined with a viable solar power supply, results in a completely autonomous product, thereby significantly reducing installation constraints and costs (civil engineering/road closures) as well as operational expenses (electricity subscription).

Contact us


Scrolling Optic

Optic Ø 200 mm with 80 yellow LEDs.

Functioning mode for a better safety :

Running sequence overlaid with drag effect to mark the curve.

35932

Optic Ø 200/80 LEDs scrolling 230 V
Wired connection

3511

Optic Ø 200/80 LEDs scrolling 12 V
Wired connection

Alternative power supply solutions: Contact-us.

37259

Automatic day/night dimming cell option

Chevron PPRF BTR synchro

The Reinforced Police Panel (PPRF) BTR series, with a low thickness, see pages 58-59.

Contact us :

All sizes (600x600 / 800x800/...).

Different power supplies (230 V, Public lighting, Solar power).

Communication of your choice (wireline, radio, GPS).

Enhanced Signaling J4 + Optic Ø 200

Scrolling light signals for turns, from 5 to 32 sets.

The reinforced panel J4 400x400mm is composed of a thin aluminium box (70mm).

Epoxy paint finish, silver grey color (metal).

Rear fixing by double rail.

The front face is protected by a 3mm polycarbonate.

The adhesive is in class 2.

Optional: Ø 200 mm optic.

The scrolling synchro control unit is attached to the back of the J4 panel.

Contact us :

Other sizes (600x600 / 800x800...).

Different power sources (230V, SEP, Solar).

Communication of your choice (wired, radio, GPS).



Power supplies

To power your equipment see the various power supplies available on pages 64 and 65.

Enhanced Signaling



Gamme PPRF BTR

The enhanced Police sign (PPRF) in the BTR range, has a low thickness and is made up of two aluminium signs with folded dropped edges, assembled using an elastomer seal.

Epoxy paint finish, silver-grey colour RAL 9006.
It is equipped with 3 m of cable.
Rear fixing using double rail.

The border is enhanced by two rows of red LEDs (for C signs: one row of blue LEDs).
The symbol is enhanced by yellow LEDs on the border (for C signs: one row of white LEDs).

The panel must be connected to a power source: 230 V, on public lighting, or solar.

Electronics fully encapsulated in resin

electronic
IP68

Qualified & sorted LEDs

(High intensity & high efficiency)

- High luminous efficiency.
- Reduced consumption.
- Lifespan +50%.



Small Normal Large

△ A Category	700	1000	1250
○ B Category	650	850	1050
□ C Category	500	700	900

All sizes and formats:

Contact us



Options

Speed or presence detection radar, timer etc.

Adapt equipment to meet your requirements, options on pages 62 and 63





Advantages :

- Thanks to their NF058 certification, our panels replace their non-reinforced equivalents.
- Low-thickness box (5 cm) in the shape of the sign.
- No savings on the number of LEDs.
Border formed of 2 rows of LEDs.
The symbol is enhanced as standard by LEDs.
- 3M certified class 2 film.
- Optional extras may be added at any time.
- High output 5 mm LEDs.
- Less and simpler maintenance required.
- No more rivets, only the message on the front.
- Visible: Prevents familiarisation effects.
- Reliable: Operational life in excess of 100,000 hours.

NEW



Power Supply 230 V PPRF BTR

38312

Power supply 230 V double flash mode
For PPRF BTR

Power supplies

To power your equipment see the various power supplies available on pages 64 and 65.



Dynamic Enhanced Signaling



1 panel 1 symbol

Flashing mode



1 panel 2 symbols

Alternating Operating mode

We ensure that the information displayed to road users is the most accurate, while optimizing visual impact thanks to a continuous alternance of symbols.



Symbol sign	Dimensions (mm)	△ and/or	○ and/or	□	Text
	700 x 700	700	650	700	-
	900 x 900	1000	850	900	-
	700 x 900	700	650	700	1 line (8 letters)
	900 x 1150	700	650	700	2 lines (2 x 8 letters)
	900 x 1150	1000	850	900	1 line (8 letters)
	700 x 350	-	-	-	2 lines

All sizes and formats:

Contact us



PPDY BTR Range

The Dynamic sign (PPDY) in the BTR range, has a low thickness and is made up of two aluminium signs with folded dropped edges, assembled using an elastomer seal.

Front finish: Polyester powder powder coating, black color RAL 9005.

Rear surface finish: Polyester powder powder coating, silver gray color RAL 9006.

It is equipped with 3 m of cable.
Rear fixing using double rail.

The symbol is outlined with red LEDs on the outside and yellow LEDs on the inside.

The lifetime of a LED is greater than 100 000 hours.
Red and yellow LEDs are connected in networks of 5 LEDs, ensuring continuous operation of the lighting element.

The panel must be connected to a power source: 230 V, on public lighting, or solar.

This type of sign can be manufactured with the road symbol of your choice, and can be supplied with 2 alternating symbols.

Flash mode operation.

Options

Speed or presence detection radar, timer etc.

Adapt equipment to meet your requirements, options on pages 62 and 63





Advantages :

■ Thin box (5 cm).

Designed to offer better integration in urban environments. The listel and the symbol are materialized by high brightness LEDs on a matt black background.

■ Single or double symbols.

This type of sign is entirely adaptable to your needs. Up to 2 alternating symbols of your choice.

■ Superior visual impact

The reinforcement of the symbol by LEDs, and its square / rectangular shape on a black background allow for a better visual impact of the symbol.

No more rivets, only the message on the front.

■ Qualified & sorted LEDs (High intensity & high efficiency)

- High luminous efficiency.
- Reduced consumption.
- Lifespan +50%.

electronic
IP68

NEW



Power Supply 230 V PPDY BTR

42581

Power supply 230 V flashing mode
for PPDY BTR

Power supplies

To power your equipment see the various
power supplies available on pages 64 and 65.



Permanent Signal Options

**Command Options**

Radio remote control
Remote control box
Call push button
GSM/SMS

**Détections Options**

Motion detection radar
Radar regulation
Radar speed detection
Magnetic loop detector

**Clock Options**

Weekly
Annual

**Power Supply Options**

Battery, Solar, 230 V,
Public Lighting Source

**Software Development Options**

Non-standard cycles
Customized function...

**Synchronization Options**

Radio synchronization, GPS



Options

Tell us your requirement,
we have the solution !



N°1 in terms of Modular design
Options for creating special signals

Contact us  

Some examples of specific configurations :



Options

Speed Detection Radar



Radar detects an approaching vehicle. Detection of excessive speed triggers operation of the sign.

Common application :
Urban area entrance.



Options

Remote control start-up



Operation of the sign is initiated manually using a remote control. This system results in optimum impact of the sign when it is of greatest use.

Common application :
School areas.



Options

Securing pedestrian crossings



Activation of the pedestrian control initiates the illuminated enhancement on both signs.

Pedestrians are therefore safe to move, safe in both directions of traffic.

Radars

Speed detection radar

35485

Low power consumption radar 230 V
Max range 80 m

24221

Low power consumption radar 12 V
Max range 80 m

Movement Detection Radar

29395

Movement Detection Radar 12 V
Max range 40 m

36391

Movement Detection Radar 230 V
Max range 40 m

Clocks

22018

Weekly NFC timer 230 V 

445

Weekly NFC timer 12 V 

On quotation

(to be adapted to the power supply) + programming kit

Annual timer



Options

Height sensor



A profile detector is positioned on the side of the road, upstream of the sign. If the height limit is reached, the light reinforcement on the profile indication panel is activated

Common application :
Tunnel.

We have been adapting our illuminated signals to meet your specific needs for 25 years

Our design bureau monitors the latest technological developments daily so that we can create the best signal systems to meet your requirements.

Power Supplies Using Public Lighting



eco-efficient

Alternative power supply solutions

No heavy civil engineering, no administrative procedures, no meter connection fees, and more respect for the environment.

Supply Using Public Lighting

The SEP power supply is a box for charging at night (when public lighting is active) the battery which powers the equipment 24 hours a day.

34577	Public Lighting Source Box 15 W 7 Ah - 12 V Rechargeable battery included
1694	Public Lighting Source Box 60 W 17 Ah - 12 V Rechargeable battery included
1695	Public Lighting Source Box 60 W 34 Ah - 12 V Rechargeable battery included

Differential Circuit Breaker

3117	30 mA differential circuit breaker
------	------------------------------------

Find the right power supply for your product :

	Public Lighting Source Power (for a lighting time of 7 hours per night*)			
	Standard	Weekly clock**	Speed radar	Motion radar
Permanent optics				
Biflash kit 130/30 (réf.35837)	7 Ah (réf. 34577)			
Optic 200/80 (réf.1660)				
Optic 300/225 (réf. 3156)				
Enhanced Signaling				
Triangle 700	7 Ah (réf. 34577)			
Triangle 1000				
Rond 650				
Rond 850				
C20 500				
C20 700				
C20 900				
Dynamic Enhanced Signaling				
Contact us				

* **Please note** that some municipalities, in order to save energy, turn off public lighting for several hours at night. In this case the SEP sizing must be the subject of a specific study.

** Operation 4 hours per day.

Solar Power Supplies (photovoltaic)

65

Solar Power Supply (photovoltaic)

The solar panel is used to charge a battery which powers the equipment 24h/24. The solar power kit includes the solar panel and the rechargeable battery housing.


35637	Solar Power Kit 10 W 7 Ah Battery supplied
23278	Solar Power Kit 0 W 17 Ah Battery supplied
28616	Solar Power Kit 40 W 34 Ah Battery supplied
28664	Solar Power Kit 60 W 60 Ah Battery supplied
32692	Solar Power Kit 100 W 60 Ah Battery supplied
48101	Solar Power Kit 120 W 60 Ah Battery supplied
33402	Solar Power Kit 165 W 120 Ah Battery supplied
47909	Solar Power Kit 200 W 120 Ah Battery supplied



The golden rules for setting up :



**SOUTH
FACING**



**CLEAR
ORIENTATION**



**NOT EXPOSED
TO FOULING**



**CLEANED TWICE
PER YEAR**

Find the right power supply for your product :

	Solar power supply					
	Standard	Weekly clock*	Speed radar	Motion radar		
Permanent optics						
kit Biflash 130/30 (réf.35837)	10 W 7 Ah (réf. 35637)		10 W 7 Ah (réf. 35637)	20 W 17 Ah (réf. 23278)		
Optique 200/80 (réf.1660)						
Optique 300/225 (réf. 3156)	20 W 17 Ah (réf. 23278)	10 W 7 Ah (réf. 35637)	20 W 17 Ah (réf. 23278)			
Enhanced Signaling						
Triangle 700	20 W 17 Ah (réf. 23278)	10 W 7 Ah (réf. 35637)	20 W 17 Ah (réf. 23278)	20 W 17 Ah (réf. 23278)		
Triangle 1000						
Rond 650						
Rond 850	10 W 7 Ah (réf. 35637)		10 W 7 Ah (réf. 35637)			
C20 500						
C20 700						
C20 900	20 W 17 Ah (réf. 23278)		20 W 17 Ah (réf. 23278)			
Dynamic Enhanced Signaling						
Contact us						

* Operation 4 hours per day.

Green-Reward Traffic Lights

Limit road abuses and encourage good behaviour on sensitive routes

PERMANENT

230V



TEMPORARY

Solar or Public Lighting



MOBILE

Rechargeable battery



Green-Reward Traffic Lights

Includes: a Ø 200 three-colour traffic light, a radar, a control cabinet, a power supply, a mast with accessories.

PERMANENT 230 V :

54865

Green-reward traffic lights 230 V

TEMPORARY Using Public Lighting:

32406

Green-reward traffic lights - using public lighting

TEMPORARY Solar power

32407

Green-reward traffic lights - solar power

MOBILE version :

This model uses the operating principle of the green-reward traffic lights: autonomous and delivered ready to use* !

Ideal for :



Events



Site



School security



Implementation study

38512

Green-reward mobile traffic lights
Battery operation*

37744

KC700 Class 1 panel
«SPEED RESPECTED = GREEN LIGHT»

* (battery not included)



Configure your equipment.

Contact us  

Repeater, information panel, red cross optics, loop detector...



Green-Reward Traffic Lights

67

Implementation rules :



Only in urban areas



Speed threshold : 30Km/h or 50Km/h



main road section



Excluding Intersection



Excluding pedestrian crossing



Excluding town entrance sign



Watch the video

How it works ?

When stationary, the traffic light is red.
It turns green when a vehicle approaches the authorized speed.



And where there is a pedestrian crossing

Facilitate the flow of traffic while favoring pedestrians.



Approaching vehicle detected: the light turns green if there is no pedestrian.

Micro-Regulated Traffic Lights Pedestrian Crossing

Motion detection: the light turns green

This device makes a pedestrian crossing safer and slows down approaching vehicles.

When idle, the lights are red, they turn green when a vehicle is detected nearby.

Includes: two Ø 200 three-colour traffic light, two Ø 100 three-colour traffic light, two pedestrian call blocks, two pedestrian figurines, two radars, a control cabinet, two masts.

25009

230 V micro-regulated traffic lights with pedestrian crossing

Radar Speed Sign

EASY

simple & compact



Easy Radar Speed Sign

Display of the speed detected in "fixed" mode, by two 250 mm characters with red and green LEDs.
Possible display of speeds from 1 to 99 km/h.
Front face protected by polycarbonate.
Rear fixing by rails for masts of maximum Ø140 mm (clamps not supplied).
Dimensions: 425 x 380 x 127 mm.

The panel can be powered by 230 V, public lighting or solar power.

43415

Radar speed sign 2H250 12V Easy
LEDs Red/Green - box 425 x 380 x 127 mm

43662

Radar speed sign Easy option 230 V power supply

43663

Radar speed sign Easy option using public lighting
Battery included

43665

Solar kit 40 W 34 Ah frozen mode
Battery included

45801

Mobile box option

9317

Mobile box option with reinforcement feet

➔ **43415**

➔ **45801**



For any other need for educational radar panels with options (data collection, matrix text, etc.)

Contact us 📞 ✉️

Power supplies

To power your equipment see the various power supplies available on pages 64 and 65.



Short Stop Terminal

69

The Short Stop Terminal is **the ideal solution** for the management of limited-time parking places.

- **Supports local businesses.**
- **Perfectly identified.**
- **Very visible due to its big size.**
- **Simple installation without significant civil engineering.**
- **In the colors of your city.**

TTS Short Stop Terminal

This device allows a large number of vehicles «rotation» on the same parking place. Short stop terminals contribute to reduce the traffic of vehicles searching for a place, which also reduces noise and pollution.

Our terminals authorize the parking for a limited time, ranging from 10 to 40 minutes.

They can be with or without count down time, manage a simple or a double place, and function on 230 V ou public lighting system.

These terminals can be equipped with an optional clock, or with an «SMS sending» option (after the authorized parking times is exceeded).

Our minute short stop terminals are customized with the logo, the text and the town chosen colors.

The **detection and management system** does not require complex programming. With a single setting requiring no adjustments, the desired parking time is easily set either in the factory or by the client themselves.

Our short stop terminal is equipped with the latest design of electromagnetic detector.

Voltage	Number of places	With time count-down	Single-sided	Reference
230 V	1	No	Yes	23372
230 V	2	No		38336
230 V	1	Yes		31330
230 V	2	Yes		31331
12 V*	1	No		24458
12 V*	2	No		36124
12 V*	1	Yes		40932
12 V*	2	Yes		40933

* It is necessary to add the adequate power supply to the terminal.



**Standard version
or with count down**

**Single or
double places**

Optional



Our minute stop terminals can be integrated into our Smart City parking supervision solutions.



Traffic Control Lights



Traffic Control Lights Ø 200

Polycarbonate assembly equipped with 2 optics Ø200 mm : one red, one green.

Crossing traffic light - LEDs light :

1706 Crossing traffic light Ø 200 LEDs
12 V

2329 Crossing traffic light Ø 200 LEDs
230 V

Crossing traffic light - E27 Light bulb :

2331 Crossing traffic light Ø 200 - E27 Light bulb
12 V

2330 Crossing traffic light Ø 200 - E27 Light bulb
230 V

38525 E27 Light bulb LEDs 230 V

Traffic Control Lights Ø 100

Polycarbonate assembly equipped with 2 optics of diameter 100 mm: one red, one green. LED light source, E27 230V bulb. Fixing system using inserts.

42531 Crossing traffic light Ø 100 LEDs
12 V

15856 Crossing traffic light Ø 100 LEDs
230 V

Specifics Crossing Traffic Lights

Bicolor crossing traffic light :

ABS optic Ø 210 mm. Optic built of 80 red LEDs and 81 green LEDs.

33950 Bicolor optic Ø 210/12 V
Red / Green

30915 Bicolor optic Ø 210/230 V
Red / Green

Red cross / green arrow :

ABS optic Ø 210 mm. Cross built of 53 red LEDs. Arrow built of 60 green LEDs.

37679 Optic Ø 210/12 V
Red cross / Green arrow

24718 Optic Ø 210/230 V
Red cross / Green arrow

1678 Optic Ø 210/230 V
Red cross

1677 Optic Ø 210/230 V
Green arrow

Eclipse



Road Island Edge Warning Lights

The rows of LEDs on the circumference operate as fixed locating lights. The central part operates as a flashing light during bad weather.

Bowl Ø 250 mm made of grey-painted aluminium, IP55. 300 yellow LEDs arranged in 2 parts (crown ring and central part)

1707 Eclipse lights

GENERAL SALES CONDITIONS

Section 1 - General points

The present sales conditions apply to all our sales except for public contracts and sales to local authorities, which, due to their nature or measures that are in force, are the subject of specific conditions

Section 2 - Orders

All orders must be confirmed in writing (letter, email or fax). Confirmed orders cannot be subsequently modified. Any later modification will be invoiced as an addition. Duly recorded orders can only be cancelled with our written agreement.

Section 3 - Prices - Lead-times and delivery

- Our reference prices are set each year in our catalogue.
 - Our lead-times are given for indication only. Delays which might occur will not give rise to any indemnity on our part, nor will they be the motive to refuse goods.
 - Unless otherwise stated, our tariffs are excluding departure taxes, packaging and transport
- invoiced as additions. Goods are dispatched in accordance with the standard conditions of the transport service providers. Urgent or special deliveries are to be the subject of a specific agreement and the purchaser will be invoiced for these as an additional service.
- Our goods, even those dispatched «free», whether delivered by ourselves or third parties, always travel at the risk and peril of the receiving party to whom they belong. In the event of apparent defects or missing items, make all necessary observations, check the consignments on arrival and if necessary take recourse against the transport service provider who alone has responsibility.
 - As a result, the consignee must, at the time of acceptance, check the products and formulate precisely on the carrier's voucher any defects or deficiencies found and, if necessary, refuse the goods.
- Any unspecified reserves such as «Subject to unpacking, damaged boxes, or damaged goods» will not be accepted.
- The recipient must also confirm by registered mail these reservations to the carrier no later than 48 business hours after receipt of the goods, and send a copy of this letter to: Traffic Technologie Système, Quality Department, ZI 1 avenue 2ème Rue BP594 06516 Carros Cedex, recalling the references on the delivery note.

Section 4 - Conditions for settlement

- For all our «account» client, the payment deadlines are set at 45 days from the invoicing date.
- No discount for early payment.
- During the completion of an order or contract, we reserve the right to demand any guarantee of payment in the event of new information about the situation of our client being brought to our attention (non-payment by due date to ourselves or to a third party, negative opinion following an examination of financial documentation etc.).
- All sales to clients without an account with us are payable with the order.
- Catalog prices are exclusive of Eco-Participation.

Section 5 - Penalties

- Late payment interest equal to the official lending rate plus 7 points will be applied as a penalty once the due payment date has passed. This will apply to the full amount remaining due.
- In the event of failure to pay on one or more of the due instalments, bills of exchange, promissory notes, the other instalments will become immediately payable, even if they have given rise to bills of exchange.
- One-off indemnity for recovery costs 40 € (ART D441-5 of the French Commercial Code).

Section 6 - Warranty

- Before installation or use, the delivered product must be stored in their original packaging under cover, protected from water or humidity, corrosive products, excessive heat or cold temperatures.
- Our clients expressly agree to scrupulously follow the advice for use provided for each type of product in our catalogue. We will not accept any responsibility and will not implement any warranty in the event of the advice for use not being followed.
- The warranty commences on the day of delivery. Equipment must be returned carriage paid, with all references relating to the fault as well as the invoice number. The re-dispatch of equipment after repair is made carriage-paid for equipment under warranty. The warranty ceases to be applicable if the equipment has undergone any non-authorized intervention, or if elements disturb the normal operation of the equipment.
- The standard warranty is for 12 months.
- Our warranty is strictly limited to the replacement of equipment deemed to be defective.

Section 7 - Retention of title

- Products are sold with retention of title.
- The seller retains title to the products until the payment of the purchase price made effectively and in full by the purchaser.

In the event of default of payment at the due date, the seller may reclaim the products and cancel the sale. Cheques and bills of exchange are only considered to be payments once they have been effectively deposited. Until that time the retention of title clause is to apply in full. These arrangements are not to be an obstacle to the transfer, on delivery, of the risk to the products that are sold. The purchaser agrees not to transform or incorporate the said products or re-sell them, or use them as collateral, until the purchase price is paid in full, on pain of immediate reclamation of the products by the seller.

Section 8 - Derogations

No derogation to the general sales conditions may be made without written confirmation on our company's headed paper.

Section 9 - Disputes

All disputes relating to our sales, even in the case of warranty related claims or multiple defendants, are to come under the exclusive competence of the French Commercial Court within whose jurisdiction the registered office of Traffic Technologie System falls.

Section 10 - EEE

The unique identifier FR025658_05T0SA attesting to registration in the register of producers in the EEE sector, in accordance with section L.541-10-13 of the Environmental Code, has been awarded by the ADEME to the company TTS (Siret: 398 379 214 00065). This identifier certifies its conformity with regard to its registration requirement in the register of producers of Electrical and Electronic Equipment and the declaration of its product market launch to ecosystem.



Other Activites



Intelligent Transport Systems



Parking Systems Signalling



Digital Display Systems



Download this document



ROADWORKS



VEHICLE



ON-BOARD



PERMANENT

TTS (Trafic Technologie Système) S.A au capital de 1 088 000 Euros - RC Grasse B 398 379 214 - Siret 398 379 214 00065

Headquarters and manufacturing center : ZI Carros - 1^{ère} avenue, 2^{ème} rue - BP 594 - 06516 Carros

Tél. +33 (0)4 92 08 29 99 Fax +33 (0)4 92 08 29 90

Email : info@ttsys.fr - Human ressources: rh@ttsys.fr

Paris office : ZAC des Forboeufs - 8 rue Denis Papin - 95280 Jouy le Moutier

