

LITHIUM MAX

INNOVATION FOR MAXIMUM PERFORMANCE

Designed to offer maximum performance thanks to highly reduced weight, low self-discharge, much longer battery life. The Lithium Max battery range is specially developed to meet the superior needs of off-road motorcycles, V-Twins, ATVs, UTVs and SSVs. The ideal solution for riders aiming to meet the latest standards of modern vehicles.



READY TO USE

Just plug & play.



LIGHTER WEIGHT

Up to 70% lighter than Lead Acid batteries.



EXTENSIVE CYCLE LIFE

Over 2 000 cycles.



HEAT RESISTANCE

Up to 230°C.



ROBUST BRASS TERMINALS

To enhance electrical performance.



STATE OF CHARGE INDICATOR

Monitor the state of charge with the indicator screen on the top.



HIGHEST STARTING POWER

Up to 900A.




HIGHEST CAPACITY

Up to 2 times that of the Lithium range.

Note: lithium motorcycle batteries can't be charged over 15V and require a specific charger for lithium technology.

MOUNTING ANGLES

HIGH INCLINATION



COMPATIBLE CHARGERS

BS 10
Battery size up to 20Ah

BS 30
Battery size up to 60Ah

BS 30 MAX
Battery size up to 60Ah

BK 20
Battery size up to 40Ah

DID YOU KNOW?

Our BSLi-10 Max & BSLi-12 Max battery casings are designed to fit with original Lead Acid batteries no spacers are required.

Lithium batteries exceeding 100Wh must be shipped as dangerous goods. Our Lithium Max batteries are packaged in UN mastercarton in compliance with international transportation standards.

BS BATTERY TYPE	BS CODE	POWER (Wh)	CCA (A)	CAPACITY AH (10Hr)	DIMENSIONS (±2mm)			POLARITY	TERMINAL	REPLACEMENT - MOST POPULAR MODELS	
					L	W	H			LITHIUM	SLA/SLA MAX
BSLi-02 MAX	360115	36	180	3	114	70	85		 M5	BSLi-02	12N5.5-3B BB4L-B BB5L-B BB7C-A BB7L-B2 BTX4L+/BTZ5S BTX5L/BTZ6S BTZ7S BTX7L BTZ7V BTZ8V
BSLi-10 MAX	360116	180	750	15	175	87	155		 M6	BSLi-10	BGZ20HL BTX20HL BTX24HL/ B50N18L-A/A2/A BTX20L-BS BTX20HL-BS BTX24HL-BS BB18L-A
BSLi-12 MAX	360117	216	900	18	166	127	175		 M6	BSLi-12	BGZ32HL BIX30L BIX30HL BIX30L-BS BB30L-B 53030



BATTERY RANGE OVERVIEW



DRY BATTERY

CONVENTIONAL



Entry-level bikers with standards requirement.

MF BATTERY

MAINTENANCE FREE



Entry-level bikers seeking easiness.

TECHNOLOGY

Flooded dry

AGM/VRLA

FACTORY ACTIVATED READY TO USE

—

—

NO ACID HANDLING

—

—

NO MAINTENANCE

—





NON-SPILLABLE

—

—

INCLINATION LEVEL



OEM APPROVED

—



SUITABLE FOR E-COMMERCE

COMPLIANT WITH EU REGULATION 2019/1148
(FOR THE SALE OF ACID FOR BATTERIES)

—

—

EASY TO SHIP

—

—

TRANSPORT TYPE



SLA
FACTORY ACTIVATED

READY TO START



Budget-conscious riders looking for performance and time-saving.

SLA
FACTORY ACTIVATED **MAX**

READY TO START
MAXIMUM POWER



Adventure riders with big engines seeking robust performance and durability.

LITHIUM
LiFePO4

INNOVATION FOR
HIGH PERFORMANCE



Demanding riders seeking for peak performance, lightweight and advanced technology.

LITHIUM
LiFePO4 **MAX**

INNOVATION FOR
MAXIMUM PERFORMANCE





Selective riders aiming to meet the latest standards of modern vehicles.

AGM/VRLA

AGM/VRLA

LiFePO4

LiFePO4



(1) Once activated | (2) According to ADR, IMDG & IATA regulations

UPGRADE CROSS REFERENCE CHART

DRY	MF	SLA	SLA MAX	LITHIUM
	BTZ5S/BTX4L-BS+	BTZ5S/BTX4L+		BSLi-02 ; BSLi-02 MAX
		BTZ6S/BTX5L		BSLi-02 ; BSLi-02 MAX
	BTZ7S-BS	BTZ7S		BSLi-02 ; BSLi-02 MAX
	BT7B-BS	BT7B-4		BSLi-03
		BTZ7V		BSLi-02 ; BSLi-02 MAX
		BTZ8V		BSLi-02 ; BSLi-02 MAX
	BT9B-BS	BT9B-4		BSLi-03
	BTZ10S-BS	BTZ10S		BSLi-04/06
	BTZ12S-BS	BTZ12S		BSLi-04/06 ; BSLi-09
	BT12B-BS	BT12B-4		BSLi-04/06
	BTZ14S-BS	BTZ14S		BSLi-04/06 ; BSLi-09
	BT14B-BS	BT14B-4		BSLi-04/06
51814 ; 51913			51913 MAX	BSLi-12
	BT12-10Z-BS	BT12-10Z		
	BT4B-BS	BT4B-5		
	BTR4A-BS	BTR4A-5		
	BTX4L-BS+/BTZ5S-BS	BTX4L+/BTZ5S		BSLi-02 ; BSLi-02 MAX
	BTX5L-BS	BTX5L/BTZ6S		BSLi-02 ; BSLi-02 MAX
		BTX6.5L		BSLi-02 ; BSLi-02 MAX
	BTX7L-BS	BTX7L		BSLi-02 ; BSLi-02 MAX
	BTX7A-BS	BTX7A		BSLi-03
	BTX9-BS	BTX9		BSLi-03
	BT12A-BS	BT12A		BSLi-04/06
	BTX12-BS	BTX12		BSLi-04/06
	BTX14-BS	BTX14	BTX14H MAX ; BGZ16H MAX	BSLi-04/06
	BTX14L-BS	BTX14L	BGZ16HL MAX	BSLi-08
BB14-A2 (12N14-4A) ; BB14-B2	BTX14AH-BS	BTX14AH/BB14-A2/B2	BTX14AH MAX	BSLi-04/06
BB14L-A2 (12N14-3A) ; BB14L-B2	BTX14AHL-BS	BTX14AHL/BB14L-A2/B2		BSLi-05
	BTX16-BS	BTX16	BTX16H MAX	BSLi-09
	BTX20-BS	BTX20H	BGZ20H MAX	BSLi-09
	BTX20CH-BS ; BTX20A-BS	BTX20CH		BSLi-09
BB18L-A	BTX20L-BS ; BTX20HL-BS	BTX20HL	BGZ20HL MAX	BSLi-10 ; BSLi-10 MAX
B50-N18L-A/A2/A3	BTX24HL-BS	BTX24HL/B50-N18L-A/A2/A3		BSLi-10 ; BSLi-10 MAX
BB30L-B	BIX30L-BS	BIX30L	BGZ3ZHL MAX	BSLi-10 ; BSLi-10 MAX
6N11A-1B ; 6N11A-3A		6N11A-1B/3A		
6N4-2A ; 6N4-2A-4		6N4-2A/A-4		
6N6-3B ; 6N6-3B-1		6N6-3B/B-1		
6N11A-4 ; 6N11A-4A		6N11A-4A		
B49-6		B49-6		
B38-6A		B38-6A		
12N5.5-3B		12N5.5-3B		BSLi-02 ; BSLi-02 MAX
12N5.5-4A ; 12N5.5-4B		12N5.5-4A/4B		
12N7A-3A		12N7A-3A/B		
BB3L-A ; BB3L-B		BB3L-A/B		BSLi-01
BB4L-B		BB4L-B		BSLi-02 ; BSLi-02 MAX
BB5L-B (12N5-3B)		BB5L-B		BSLi-02
BB7-A (12N7-4A)		BB7-A		BSLi-03
BB7C-A		BB7C-A		BSLi-02 ; BSLi-02 MAX
BB7B-B		12N7A-3A/B		
BB7L-B (12N7-3B) ; BB7L-B2		BB7L-B2		BSLi-02 ; BSLi-02 MAX
BB9-B (12N9-4B-1)	BT9A-BS	BB9-B		BSLi-03
BB10L-A2 ; BB10L-B2 ; BB10L-BP		BB10L-A2/B2		BSLi-05
BB12AL-A/A2		BB12AL-A2		BSLi-05
BB12A-A (12N12A-4A-1) ; BB12A-B		BB12A-A/B		BSLi-04/06
BB14A-A2 ; BB14A-A1		BB14A-A2		BSLi-04/06
BB14-A2 (12N14-4A) ; BB14-B2	BTX14AH-BS	BB14-A2/B2/BTX14AH	BTX14AH MAX	BSLi-04/06
BB14L-A2 (12N14-3A) ; BB14L-B2	BTX14AHL-BS	BB14L-A2/B2/BTX14AHL		BSLi-05
BB16AL-A2		BB16AL-A2		BSLi-05
BB16CL-B		BB16CL-B		BSLi-10 ; BSLi-10 MAX
B50-N18L-A/A2/A3	BTX24HL-BS	B50-N18L-A/A2/A3/BTX24HL		BSLi-10 ; BSLi-10 MAX
53030		53030		BSLi-12 ; BSLi-12 MAX