## PURA



# PERCHING, ILLUMINATING

Pura series is originally designed by npk design, Along with its beautiful design and fine finishing, the luminaires of Pura series offer a unique mechanism for easy installation. Offering even distributed light on its surface, high efficiency of light output and non flickering feature. With a specific built-in driver and different dimming functions are available, which can be perfectly suited for consumer and professional applications.



PURATI IS A EUROPEAN-DESIGNED PREMIUM LIGHTING BRAND WITH OUR OWN PRODCUTION. PERFORMANCE, UNIQUENESS, RESPONSIBILITY, AESTHETICS, TECHNOLOGY, INNOVATION (PURATI). THOSE ARE OUR VALUE AND FOUNDATION OUR LIGHTS SAVE SPACE, SAVE RESOURCES, AND OFFER GREATER QUALITY. WE OFFER ARCHITECTURAL LIGHTING OF PREMIUM QUALITY AND PERFORMANCE WITH UNIQUE DESIDN.


PURATI SYDNEY AUSTRALIA DESIGN IS ONE OF THE MOST VALUED INTERNATIONAL DESIGN AGENCIES IN THE NETHERLANDS, WITH OVER 40 YEARS OF EXPERIENCE. THE COMPANY OFFERS A WIDE RANGE OF SERVICES INCLUDING STRATEGIC ADVICE, INDUSTRIAL DESIGN, SERVICE DESIGN, GRAPHIC DESING, AND PUBLIC DOMAIN PROJECTS, AS WELL AS SUPPLY MANAGEMENT.


NPK DESIGN

LEIDEN, THE NETHERLANDS









#### Pura Trim 270 / 350

The Pura Trim is a clean, durable design style that reveals architectonic and balanced character. With its various functions and multiple applications, making it the ideal choice for any indoor and semi-outdoor projects with high output requirements. Variable in rich colors, fine finishing and two sizes. Precisely designed two quick release buttons on each side that results in making the installation easy and quick removal of the entire installation base for

maintenance.






Pura series is a clean, durable design style that reveals an architectonic and balanced character. It makes the luminaire an aesthetic highlight for any room. This series can be surface mounted, wall mounted, suspended or on track.



#### Pura Trim 270

The Pura Trim is a clean, durable design style that reveals architectonic and balanced character. With its various functions and multiple applications, making it the ideal choice for any indoor and semi-outdoor projects with high output requirements. Variable in rich colors, fine finishing and two sizes. Precisely designed two quick release buttons on each side that results in making the installation easy and quick removal of the entire installation base for maintenance.



# Light & Life

Light, Life and Love are like three glow- worms at thy feet the whole universe of stars, the dewdrops on the grass whereon thou walkest!









PURATI is a European-designed premium lighting brand with our own production.
Performance, Uniqueness, Responsibility,
Aesthetics, Technology, Innovation (PURATI).

Those are our value and foundation.

Our lights save space, save resources, and offer greater quality.

We offer architectural lighting of premium quality and performance with unique design.


The Pura Trim is a clean and durable design style that reveals an architectonic and balanced character that renders it highly suitable for office environment.

Thanks to its easy-to-install design with both side cable entry, Pura Trim offers flexibility and ensures a seamless installation process, ultimately saving valuable time for any project.

The concept of Purati Lighting is focused on creating a good lighting environment that supports our well-being and enhances daily experiences.

Whether at home or at work, hope Purati Lighting can help to create a space that is both functional and beautiful. Light means life, Light quality means quality of life. It will be creating a sense of harmony and balance.






# THE PURA collection









#### PURA BUILD-ON 100 IP65 SURFACE MOUNTED DOWNLIGHT

With a simple and pure design without visible screws and high IP rating protection, the Pura Build-on 100 IP65 downlight is prefect for illuminating both indoor and outdoor space. Such as living areas (bathroom, kitchen, or the wet areas), entrances, balconies, porches. In addition, this downlight comes with easy to use turning lock installation and its surface mounted construction, making it ideal for the concrete ceilings or timber ceilings.





# THE CONTEMPORARY DESIGN WITH IP65 SURFACE MOUNTED DOWNLIGHT SUITABLE FOR LIGHTING RESIDENTIAL AND COMMERCIAL AREAS

Illuminating a personalised and luxurious bathroom environment, clean & durable. It also gives you a feel-good ambience when looking across a space.

The Pura Build-on 100 IP65 has three beam angle options:  $24^{\circ}$ ,  $36^{\circ}$  and  $60^{\circ}$ , that can be customised to best suit the projects.







#### Pura Build-on 100 / 150

This build-on downlight combines a sleek design with an opal diffuser for even light distribution that perfectly suited for any space, while its simple shape with refined details enriches each interior just by its presence. This luminaire comes in three different colors, two different water resistances and it can be installed in using two mounting options choose from surface mounted and suspended.



#### **PURA TRIM SERIES**



**Pura Trim 270** Surface mounted Matte White



Pura Trim 270 Surface mounted Matte Black



**Pura Trim 270** Surface mounted Matte Silver



Pura Trim 350 Surface mounted Matte White



Pura Trim 350 Surface mounted Matte Black



**Pura Trim 350** Surface mounted Matte Silver



**Pura Build-on 150** Surface mounted Matte White



Pura Build-on 150 Surface mounted Matte Black



**Pura Build-on 150** Surface mounted Matte Silver



Pura Build-on 100 Surface mounted Matte White



Pura Build-on 100 Surface mounted Matte Black

#### **Product Collection**



Pura Trim Suspended Ceiling Light



Pura Trim 270 Track Light

#### **TECHNICAL DATA**

#### Pura Trim 270

Mounting:	Surface mounted
Material:	Polycarbonate
Finishes:	White / Black / Silver
IP / IK Rating:	54/10
Lumens Flux:	2400lm 24W/1800lm 18W/1000lm10W
Voltage:	220-240V AC / 216(186-260)DC
Functions:	On/Off motion sensor, 90 mins @ 2W Emergency
сст:	3000 / 4000K
CRI:	>90
SDCM:	<5
Lifetime:	L80 / 50,000h
Warranty:	5 Years
Dimming options:	No Dim / DIM / DALI (DL6)
Power Switch CRI>	90 SDCM<5 IP54 IK10 5 YEARS

#### Pura Build-on 150

Mounting:	Surface mounted
Material:	Aluminium + Polycarbonate
Finishes:	White / Black / Silver
IP Rating:	IP44/20 (option)
IK Rating	IK 10
Lumens Flux:	1200lm 12W/850lm 8W/700lm 6W
Voltage:	220-240V AC / 216(186-260)DC
	2000 / 4000 /
CCT:	3000 / 4000K
CRI:	>90
	· ·
CRI:	>90
CRI:	>90 <5
CRI: SDCM: Lifetime: Warranty:	>90 <5 L80 / 50,000h

#### Pura Trim 350

Mounting:	Surface mounted
Material:	Aluminium + Polycarbonate
Finishes:	White / Black / Silver
IP / IK Rating:	54 / 10
Lumens Flux:	3200lm 32W / 2400lm 24W
Voltage:	220-240V AC / 216(186-260)DC
Functions:	On/Off motion sensor, 90 mins @ 2W Emergency
CCT:	3000 / 4000K
CRI:	>90
SDCM:	<3
Lifetime:	L80 / 50,000h
Warranty:	5 Years
Dimming options:	No Dim / DIM / DALI (DL6)
Power Switch CRI:	SDCM<3 IP54 IK10 SPARS S

#### Pura Build-on 150

m	em e	Lux AVG	Lux MAX			
1	308.26	60.74	222.80			
2	616.52	15.18	55.70			
3	924.79	6.749	24.76			
4	1233.05	3.796	13.93			
5	1541.31	2.430	8.912			
Angle	: 114.05°					
m	em e	Lux AVG	Lux MAX			
1	308.65	63.92	234.70			
2	617.29	15.98	58.67			
3	925.94	7.102	26.08			
4	1234.59					
5	1543.23	2.557	9.387			
Angle	: 114.11°					
m	Ф cm	Lux AVG	Lux MAX			
m 1						
	cm	AVG	MAX			
1	cm 310.57	AVG 70.73	MAX 259.4			
1 2	cm 310.57 621.14	70.73 17.68	MAX 259.4 64.85			
1 2 3	cm 310.57 621.14 931.71	70.73 17.68 7.859	MAX 259.4 64.85 28.82			
1 2 3 4 5	cm 310.57 621.14 931.71 1242.29	70.73 17.68 7.859 4.420	MAX 259.4 64.85 28.82 16.21			
1 2 3 4 5	cm 310.57 621.14 931.71 1242.29 1552.86 : 114.44°	70.73 17.68 7.859 4.420 2.829	MAX 259.4 64.85 28.82 16.21 10.38			
1 2 3 4 5	cm 310.57 621.14 931.71 1242.29 1552.86	70.73 17.68 7.859 4.420	MAX 259.4 64.85 28.82 16.21			
1 2 3 4 5 Angle	ст 310,57 621,14 931,71 1242,29 1552,86 : 114,44°	AVG 70.73 17.68 7.859 4.420 2.829	MAX 259.4 64.85 28.82 16.21 10.38			
1 2 3 4 5 Angle	cm 310.57 621.14 931.71 1242.29 1552.86 114.44°	AVG 70.73 17.68 7.859 4.420 2.829	MAX 259.4 64.85 28.82 16.21 10.38			
1 2 3 4 5 Angle m 1	ст 310.67 621.14 931.71 1242.29 1552.86 114.44°	AVG 70.73 17.68 7.859 4.420 2.829 Lux AVG 74.18	MAX 259.4 64.85 28.82 16.21 10.38 Lux MAX 272.2			
1 2 3 4 5 Angle m 1 2	ст 310.67 621.14 931.71 1242.29 1552.86 ст 310.42 620.85	AVG 70.73 17.68 7.859 4.420 2.829 Lux AVG 74.18	MAX 259.4 64.85 28.82 16.21 10.38 Lux MAX 272.2 68.05			
1 2 3 4 5 Angle m 1 2 3	Cm 310.57 621.14 931.71 1242.29 1552.86 cm 310.42 620.85 931.27	AVG 70.73 17.68 7.859 4.420 2.829  Lux AVG 74.18 18.55 8.242	MAX 259.4 64.85 28.82 16.21 10.38 Lux MAX 272.2 68.05 30.24			
1 2 3 4 5 Angle m 1 2 3 4 5 5	ст 310 67 621.14 931.71 1242.29 1552.86 : 114.44° ф ст 310.42 620.85 931.27	AVG 70.73 17.68 7.859 4.420 2.829  Lux AVG 74.18 18.55 8.242 4.636	MAX 259.4 64.85 28.82 16.21 10.38 Lux MAX 272.2 68.05 30.24			

5	1544.41	4.119	15.16
Angle:	113.21°		
m	Φ cm	Lux AVG	Lux MAX
1	310.01	107.8	396.0
2	620.02	26.96	99.00
3	930.03	11.98	44.00
4	1240.03	6.739	24.75
5	1550.04	4.313	15.84
Angle:	114.34°		

#### Pura Trim 270

m	Φ cm	Lux AVG	Lux MAX		m	Φ cm	Lux AVG	L.
1	308.79	86.97	320.2		1	308,91	91.31	33
2	617.59	21.74	80.05		2	617.82	22.83	83
3	926.38	9.663	35.58		3	926.73	10.15	37
4	1235.17	5.435	20.01		4	1235.64	5.707	20
5	1543.96	3.479	12.81		5	1544.55	3.652	13
Angle:	114.14°				Angle:	114.16°		
m	Φ cm	Lux AVG	Lux MAX		m	Φ cm	Lux AVG	Lu Ma
1	308,71	156.9	577.5		1	308,00	164.9	607
2	617.41	39.23	144.4		2	616.00	41.23	15
3	926.12	17.43	64.17		3	923.99	18.33	67.
4	1234.82	9.807	36.10		4	1231.99	10.31	37.
5	1543.53	6.276	23.10		5	1539.99	6.597	24.
Angle:	114.12°				Angle:	114.00°		
m	Φ cm	Lux AVG	Lux MAX		m	Φ cm	Lux AVG	Lu M
1	307.65	213.8	746.6		1	307.70	222.4	775
2	615.29	53.45	186.6		2	615.41	55.59	193
3	922.94	23.76	82.95		3	923.11	24.71	86.
4	1230.58	13.36	46.66		4	1230.82	13.90	48.
5	1538.23	8.553	29.86		5	1538.52	8.894	31.
Anglo	113.94°			1	Annie -	113.95°		•

#### Pura Trim 350

m	Φ cm	Lux AVG	Lux MAX	n	n	Φ cm	Lux AVG	L
1	312.76	209.8	767.6	1		312.91	220.3	80
2	6 <b>25</b> .52	52.45	191.9	2		625.81	55.07	20
3	938.27	23.31	85.29	3		938.72	24.48	88
4	1251.03	13.11	47.97	4		1251.62	13.77	51
5	1563.79	8.392	30.70	5		1564.53	8.811	32
Angle	: 114.80*			A	ngle	: 114.83°		
m	Ф cm	Lux AVG	Lux MAX	п	n	Ф cm	Lux AVG	L
1	310.25	275.5	1014	1		310.48	284.2	10
2	620.49	68.88	253.4	2		620.97	71.05	26
3	930.74	30.61	112.6	3		931.45	31.52	11
4	1240.98	17.22	63.35	4		1241.94	17.76	65
5	1551.23	11.02	40.54			1552.42	11.37	41

### INTERESTED?

Contact us for samples

#### **Head Office**

Unit 10, 80 O'Riordan Street, Alexandria NSW 2015

#### Phone

+61 2 8065 8181

#### Sales

sales@purati.com









Unique & performance

