

Thales Palm Scanner CS1000q



Identity & Biometrics Solutions

The Thales Palm Scanner CS1000q is a brand new Thales palm scanner with a superior image quality of 1000 ppi. The palm scanner has a very compact design and the USB 3.0 interface assures a fast acquisition speed.

The Thales Palm Scanner CS1000q is provided with an integrated heater that will keep the prism's surface at the right temperature and provide assurance in achieving the best fingerprint acquisition even in low temperature environments.

FBI APP. F Certified and APP.P Compliant

CS1000q Palm Scanner can address all the applications where FBI IAFIS IQS Appendix F certified palm, 10-print and rolled acquisitions are requested.

Having a resolution of 1000 dpi and an active scanning window of 5,4" x 5", the Thales Palm Scanner CS1000q allows an acquisition speed of up to 6 fps in full frame mode and up to 16 fps for rolled prints.

An easy-to-integrate and features rich SDK for all common platforms reduces integration time to a minimum, thus making the Thales Palm Scanner CS1000q the perfect choice for system integrators and solution providers.

MultiScan SDK Features

- **CORRECT POSITION AND SLAP COMPLETENESS CHECK:** checks for correct finger placing; checks for incomplete slaps or palms.
- **ELIMINATION OF LATENT PRINTS:** originating from recent scans.
- **HALO ELIMINATION:** elimination of halo due to moist fingerprints during acquisition.
- **ROLLED FINGERPRINT CAPTURING:** displays in real-time, self-adaptive to rolling speed and directions, automatic stop detection.
- **SEGMENTATION:** automatic segmentation of four-slap and two-thumbs fingerprint images in single flat images.
- **AUTOMATIC ACQUISITION START AND STOP:** sensing of finger placement and automatic acquisition of the image with the highest quality.
- **SLIDE DETECTION FOR FLAT PRINTS:** detects deformations of fingerprints due to sliding during acquisition.
- **REAL-TIME IMAGE QUALITY CHECKING:** real-time estimation of fingerprint image quality during scanning process according to NISTIR7151 (NFIQ and NFIQ2).
- **IMAGE COMPRESSION:** FBI certified jpeg2000.
- **ADAPTIVE ROLLED ACQUISITION:** rolled acquisition on all the front prism area.
- **DRY FINGER IMAGE ENHANCEMENT:** low contrasted images due to dry skin conditions are automatically improved.
- **LOWER VS. UPPER PALM IDENTITY CHECK:** based on inter digital area to check if both half-palm images are from the same hand.
- **SEGMENTATION AND SEQUENCE CHECK FOR UPPER PALM:** for cases when the upper palm is acquired instead of 4-finger slap.
- **ARTIFACTS CONTROL:** detects artifacts created during improper rolled print acquisition.

Supplemental prints

The CS1000q Palm Scanner can also acquire supplemental prints such as writer's palm, thenar, rolled thenar & hypo-thenar, full finger prints and fingertip prints.

User-friendly ergonomics

Well studied ergonomics and a full color LCD touchscreen help enhancing the workflow efficiency while reducing the need for skilled operators.

The Thales Palm Scanner CS1000q is designed with a small footprint, it can be used in a desktop setting or integrated into other systems like kiosks

Technical Data

ACTIVE SCANNING WINDOW

- 4-slaps and half-palms up to 5,4" x 5"
- Rolled thenar up to 4.5" x 3"
- Flat Fingertips up to 3,2" x 3,0"
- Rolled fingertips up to 1,6" x 1,6"
- Image Resolution: 1000 dpi - 256 gray

INTERFACE

USB 3.0

IMAGE QUALITY AND FORMATS

- FBI IAFIS IQS Appendix F certified and Appendix P compliant
- ANSI/NIST-ITL 1-2007/2011, ISO/IEC FCD 19794-4
- ANSI/NIST-ITL 1-2000, ANSI/NIST-ITL 1-2000 Interpol Implementation

TEMPERATURE

- Storage: from -20°C to +60°C
- Operating: from 0°C to +50°C

HUMIDITY

From 10 to 90% (R.H. non-condensing)

DIMENSIONS

265 x 374 x 201 mm

WEIGHT

8,9 kg

SUPPORTING OPERATING SYSTEMS

- Microsoft Windows® up to Win11 64-bit configuration
- Linux, Ubuntu 14.04 in 32-bit and 64-bit configuration
- Android

IP RATING

IP54

CERTIFICATIONS

CE, FCC, CB, REACH, RoHS

POWER SUPPLY

- Input 100-240 Vac, 50 - 60 Hz.
- Output 5Vdc, 30W max

OPTIONS

- Silicone Membrane
- Foot Pedal