DISC







PURATI IS A EUROPEAN-DESIGNED PREMIUM LIGHTING BRAND WITH OUR OWN PRODCUTION. PERFORMANCE, UNIQUENESS, RESPONSIBILITY, AESTHETICS, TECHNOLOGY, INNOVATION (PURATI). THOSE ARE OUR VALUE AND FOUNDATION OUR LIGHTS SAVE SPACE, SAVE RESOURCES, AND OFFER GREATER QUALITY. WE OFFER ARCHITECTURAL LIGHTING OF PREMIUM QUALITY AND PERFORMANCE WITH UNIQUE DESIDN.

PURATI SYDNEY AUSTRALIA

MANUFACTURED BY PURATI OWN FACTORY NINGBO, CHINA

NPK DESIGN IS ONE OF THE MOST VALUED INTERNATIONAL DESIGN AGENCIES IN THE NETHERLANDS, WITH OVER 40 YEARS OF EXPERIENCE. THE COMPANY OFFERS A WIDE RANGE OF SERVICES INCLUDING STRATEGIC ADVICE, INDUSTRIAL DESIGN, SERVICE DESIGN GRAPHIC DESING, AND PUBLIC DOMAIN PROJECTS, AS WELL AS SUPPLY MANAGEMENT

NPK DESIGN

LEIDEN. THE NETHERLANDS







a warm alcome









WE ARE TECHNICAL



"The light shines in the darkness, and the darkness has not overcome it. we do not see"

In 2010, we cooperated with a strong partner, NPK design agency in the Netherlands, and have since succeeded in adding new innovative design with new functionality to our product series every year. As a result, we produce premium quality and high-performance LED luminaires, which are distributed to more than 30 countries around the world.





Disc pendant features both an up and down light that will create an interesting effect on the ceiling. Variable in white and black color and comes in 220mm and 300mm diameter. This suspension can choose between power (24/18w/10w) and color temp (3000K/4000K) switchable by using the switch in the installation base.



Disc 300 Track light is the newest extension of the Disc Series. The design features both an up and down light on track that will create an interesting effect on the ceiling. It's the first direct and indirect track light from PURATI with a rotational adjustment of 350° and an angular adjustment of 90° that creates a flood beam to be turned in the required direction. This luminaire can choose between power (24W/18W/10W) and Color temp (3000K/4000K) switchable by using the switch in the installation base.

Disc Track Light is suitable for Eutrac and Global 240V 3-circuit track system.







Disc 300 Suspended Ceiling Light

Disc pendant features both an up and down light that will create an interesting effect on the ceiling. Variable in white and black color and comes in 220mm and 300mm diameter. This suspension can choose between power (24/18w/10w) and color temp (3000K/4000K) switchable by using the switch in the installation base.

Disc 300 Track Light

Disc 300 Track light is the newest extension of the Disc Series. The design features both an up and down light on track that will create an interesting effect on the ceiling. It's the first direct and indirect track light from PURATI with a rotational adjustment of 350° and an angular adjustment of 90° that creates a flood beam to be turned in the required direction. This luminaire can choose between power (24W/18W/10W) and Color temp (3000K/4000K) switchable by using the switch in the installation base. Disc Track Light is suitable for Eutrac and Global 240V 3-circuit track system.







Disc series

The Disc series is a pleasant general lighting with an ultra-thin and high-performance design possibilities for interior projects. The special internal reflector design features both an up and down light which creates 360° of uniform light distributed for additional emphasis of the ceiling. This series is available in a variety of applications: for suspended installation, ceiling and wall surface mounted or insert for 3-phase track system.

Disc 300 Track Light

Disc 300 Track light is the newest extension of the Disc Series. The design features both an up and down light on track that will create an interesting effect on the ceiling. It's the first direct and indirect track light from PURATI with a rotational adjustment of 350° and an angular adjustment of 90° that creates a flood beam to be turned in the required direction. This luminaire can choose between power (24W/18W/10W) and Color temp (3000K/4000K) switchable by using the switch in the installation base. Disc Track Light is suitable for Eutrac and Global 240V 3-circuit track system.





DISC SERIES



Disc 220Surface mounted
Matte White



Disc 220Surface mounted
Matte Black



Disc 300Surface mounted
Matte White



Disc 300Surface mounted
Matte Black

Product Collection



Disc Suspended Ceiling Light



Disc 220 & 300 Track Light

NEED MORE INFORMATION ON A SPECIFIC PRODUCT?

Download the specification sheet from the product pages on our website for technical further information such as: IES files, Installation instrictions, product images and line drawings.

TECHNICAL DATA

Disc 220

Mounting:	Surface mounted					
Material:	Aluminium + Polycarbonate					
Finishes:	White / Black					
IP / IK Rating:	20 / 8					
Lumens Flux:	1500lm 15W/1000lm 10W/800lm 8W					
Voltage:	220-240V AC / 216(186-260)DC					
Functions:	nctions: On/Off motion sensor					
CCT: 3000 / 4000K						
CRI:	>90					
SDCM:	<5					
Lifetime:	L80 / 50,000h					
Warranty:	5 Years					
Dimming options:	No Dim / DIM / DALI (DL6)					
Power Switch CRI>90	SDCM<5 IP20 IK08 5 YEARS					

Disc 220

m	cm	Lux AVG	Lux MAX	m	cm	Lux AVG	Lux MAX
1	297.65	75.17	257.0	1	297.82	77.12	263.5
2	595.31	18.79	64.26	2	595.64	19.28	65.89
3	892.96	8.352	28.56	3	893.46	8.569	29.28
4	1190.61	4.698	16.06	4	1191.29	4.820	16.47
5	1488.27	3.007	10.28	5	1489.11	3.085	10.54
Angle	: 112.20°			Angle:	112.23°		
m	Φ cm	Lux AVG	Lux MAX	m	Ф cm	Lux AVG	Lux MAX
1	301.22	87.42	298.6	1	301.90	89.8	306.7
2	602.44	21.86	74.64	2	603.81	22.45	76.67
3	903.65	9.714	33.17	3	905.71	9.977	34.07
4	1204.87	5.464	18.66	4	1207.62	5.612	19.17
5	1506.09	3.497	11.94	5	1509.52	3.592	12.27
Angle	: 112.83°			Angle:	112.95°		
m	Ф cm	Lux AVG	Lux MAX	m	Ф cm	Lux AVG	Lux MAX
1	301.16	125.90	430.1	1	302.02	130.10	444.1
2	602.32	31.48	107.5	2	604.04	32.52	111.0
3	903.48	13.99	47.79	3	906.06	14.45	49.35
4	1204.64	7.870	26.88	4	1208.07	8.129	27.76
5	1505.81	5.036	17.20	5	1510.09	5.203	17.77
Angle	: 112.82°			Angle:	112.97°		

Disc 300

Mounting:	Surface mounted					
Material:	Aluminium + Polycarbonate					
Finishes:	White / Black					
IP / IK Rating:	20 / 8					
Lumens Flux:	2400lm 24W/1800lm 18W/1000lm10W					
Voltage:	220-240V AC / 216(186-260)DC					
Functions:	On/Off motion sensor, 90 mins @ 2W Emergency					
сст:	3000 / 4000K					
CRI:	>90					
SDCM:	<5					
Lifetime:	L80 / 50,000h					
Warranty:	5 Years					
Dimming options:	No Dim / DIM / DALI (DL6)					
Power Switch CRI>9	0 SDCM<5 IP20 IK08 YEARS					

Disc 300

m	Ф	Lux AVG	Lux MAX	m	Φ cm	Lux AVG	L
1	302.65	95.65	335.8	1	303.86	101.0	35
2	605.30	23.91	83.96	2	607.72	25.25	88
3	907.95	10.63	37.31	3	911.58	11.22	39
4	1210.60	5.978	20.99	4	1215.43	6.312	22
5	1513.25	3.826	13.43	5	1519.29	4.040	14
Angle:	113.08°			Angle	: 113.29°		
m	Ф cm	Lux AVG	Lux MAX	m	Ф cm	Lux AVG	L
1	301.90	172.9	591.2	1	303.17	178.8	62
2	603.81	43.23	147.8	2	606.83	44.71	15
3	905.71	19.21	65.69	3	909.50	19.87	69
4	1207.62	10.81	36.95	4	1212.67	11.18	35
5	1509.52	6.917	23.65	5	1515.83	7.153	2
Angle:	112.95°			Angle	: 113.17°		
В	Φ cm	Lux AVG	Lux MAX	m	Φ cm	Lux AVG	L N
1	302.36	215.3	756.3	1	303.40	226.1	79
2	604.72	53.83	189.1	2	606.79	56.52	18
3	907.09	23.92	84.03	3	910.19	25.12	88
4	1209.45	13.46	47.27	4	1213.59	14.13	49
5	1511.81	8.612	30.25	5	1516.99	9.043	31
Anglo	113.03°			Angle	: 113.21°		

INTERESTED?

Contact us for samples

Head Office

Unit 10, 80 O'Riordan Street, Alexandria NSW 2015

Phone

+61 2 8065 8181

Sales

sales@purati.com









Unique & performance

