

SUPERLOCK 2.0 QUICK EXIT | NO ACCESS

Specification Sheet BQ-NA 2.0

FEATURES

- Quick-Exit: Push pad designed to facilitate rapid exit through gates, with a 14 digit keypad for secure entry.
- Easy to fit: Slim 70mm (2 3/4") wide lock case, along with an adjustable and removable latchbolt, ensures easy fitting to gates.
- Secure: The latchbolt moves 15mm (5/8"), ensuring the bolt enters deep into the gatepost.
- Durable: The latchbolt is supported on the edge of the gatepost to reduce friction and wear.
- Anti-corrosion: Designed for outdoor use for long-lasting performance.
- A security shroud is available to prevent access to the push pad from the outside



PRODUCT DETAILS

Product code	Description
BQ1030LNA	To fit 10-30mm (1/2" - 1 1/4") gate frames, left hand
BQ1030RNA	To fit 10-30mm (1/2" - 1 1/4") gate frames, right hand
BQ4060LNA	To fit 40-60mm (1 1/2" to 2 1/4") gate frames, left hand
BQ4060RNA	To fit 40-60mm (1 1/2" to 2 1/4") gate frames, right hand
Compatible with: Superlock Keeps (BSK, BSKS, BSKG) & Shroud (BQS)	

5 Year Warranty

INCLUDED IN THE BOX

- 2.5mm hex key + 3mm hex key
- Latchbolt
- M8 fixing bolts
- Strike plate (self-drilling fasteners)
- Face plate

INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 140mm (5 1/2") centres for fixing bolts provided.
2. Drill a 18mm (3/4") clearance hole for the latchbolt at 60mm (2 3/8") centres up from the bottom fixing hole.
3. Hold the lock against the back of the box section and screw on the latchbolt through the larger hole.
4. Lock the latchbolt with the hex key supplied by inserting the hex key into the end of the latchbolt.
5. Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt moves freely.
6. Fix strike plate by either welding or screw fixing onto the gate post.

Maintenance: Every 6 months, lubricate the latchbolt with light oil.

Annually, dismantle the lock and spray mechanism with light oil.

