

VINYL

Turin Oak

OLYMPIC 3 COLLECTION

1/8" x 6" x 48" (nominal) | 3.0mm x 152.4mm x 1219.2mm

Paris Oak

Whistler Oak

Turin Oak

Tokyo Oak*

Sydney Oak*

London Oak

Athens Oak

Rio Walnut*
(All Over Texture)

MDBV-515

MDBV-516

MDBV-517

MDBV-518

MDBV-519

MDBV-520

MDBV-521

MDBV-522

MARQUEE FLOORS
by **TORLYS**

*High Shade Variation torlys.com

OLYMPIC 3 COLLECTION

Beautiful Wood Looks, Incredible Durability.

Realistic wood patterns and textures with a contemporary colour palette. The enhanced UV finish for easy cleaning and maintenance, along with the 0.5mm wear layer for long lasting durability, makes it the perfect choice for commercial applications

- Kissed bevel edges to enhance visual
- 3mm thick with a 0.5mm wear layer
- Direct glue, dry back vinyl flooring for high traffic commercial applications
- Durable & waterproof, perfect for commercial settings
- EIR textures*
- Enhanced UV finish for easier cleaning and ongoing maintenance
- FloorScore® Certified
- Contains no recycled content, 100% virgin PVC

*Rio Walnut is not EIR

RECOMMENDED UNDERLAYMENT TORLYS VersaLay

DIMENSIONS

Plank

6" x 48" (nominal)
152.4mm x 1219.2mm

Thickness

1/8" | 3mm

Wear Layer Thickness

0.5mm | 20mil

35.95 sq.ft per carton

WARRANTY

Lifetime Limited Residential Warranty
15 Year Commercial Warranty

TECHNICAL DATA

Test Item	Test Method	Test Requirement As Per ASTM F1700-13A	Test Result
Squareness	ASTM F2055-10	≤0.25mm / 305mm	Pass
Residual Indentation	ASTM F1914-07(2011)	Average ≤8% Max ≤10%	Pass
Flexibility	ASTM F137-08(2013)	No crack or break when using 25.4mm mandrel	Pass
Dimensional Stability	ASTM F2199-09(2014)	≤0.51 mm / 305mm	Pass
Static Load	ASTM F970-07(2011)	250 lbs	Residual Indentation: 0.03mm
Thermal Resistance R	ASTM C518-15	n/a	0.035 (m ² ·K)/W