

SUPERLOCK 2.0 LATCH DEADLOCK



Watch installation video

Specification Sheet **BLD 2.0**

FEATURES

- Engineered for strength: The new one-piece casing design eliminates joints and welds, providing enhanced durability and a sleek, professional appearance.
- Built to withstand harsh environments: Improved materials and finishes deliver longer-lasting protection against rust and weathering.
- Constructed for high-impact outdoor use: Ensures unmatched strength, security, and reliability.



5 Year Warranty

PRODUCT DETAILS

Product code	Description
BLD1030	To fit flat bar and up to 30mm (1 ¼") box section
BLD4060	To fit 40 to 60mm box section (1 ½" to 2 ¼")
Compatible with: Superlock Keeps (BSK , BSKS , BSKG)	

Style of handle	Description
P	Plain lever handle set
T	Traditional lever handle set



Traditional lever handle set



Plain lever handle set

INCLUDED IN THE BOX

- 1x3mm hex key
- Latchbolt
- M8 fixing bolts
- Strike plate (self-drilling fasteners)
- Face plate
- A set of keys (3)

INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 140mm (5 ½") centres for fixing bolts provided.
2. Drill a 18mm (¾") clearance hole for the latchbolt at 60mm (2 3/8") centres up from the bottom fixing hole.
3. Hold the lock against the back of the box section and screw on the latchbolt through the larger hole.
4. Lock the latchbolt with the hex key supplied by inserting the hex key into the end of the latchbolt.
5. Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt moves freely.
6. Fix strike plate by either welding or screw fixing onto the gate post.

Maintenance: Every 6 months, lubricate the latchbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.

