


Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130

Email: info@fmlgy.com

Visit us at WWW.FMLGY.COM







Weight according EPTA-Procedure 01/2003: 8.2 lb.

Disc diameter: 4-17/32 in Max. cutting depth: 0.94 in

Trigger type: lockable on / off



## **AG 700-14D ANGLE GRINDER**

7" Angle grinder With dead man's Switch for rinding and cutting metal, concrete, or masonry.

Weight according EPTA-Procedure 01/2003: 11.5 lb.

Disc diameter: 7 in

Max. cutting depth: 1.65 in

Trigger type: Paddle with dead man's switch



#### Contact us for more options



A CROSBIE

MEMBER

COMPANY





# TE 800-AVR CONCRETE DEMOLITION HAMMER

Very powerful TE-S demolition hammer for heavy-duty chiseling in concrete, with Active Vibration Reduction (AVR

Weight according EPTA-Procedure 01/2003: 23.4 lb.

Single impact energy: 15.5 ft-lbs

Full hammering frequency: 1890 impacts/minute

Working direction: Wall, Floor

Triaxial vibration for chiseling into concrete:8.0 m/s<sup>2</sup> 1

Tool chuck type: TE-S



# TE 2000-AVR ELECTRIC JACKHAMMER

Compact SDS Max (TE-Y) rotary hammer for drilling and chiseling in concrete

Weight according EPTA-Procedure 01/2003: 13.4 lb.

Single impact energy: 4.4 ft-lbs

Hammer drilling diameter range: 5/32 - 1-3/32 in

Optimum Hammer drilling range: 1/4 - 5/8 in

Hammer drilling diameter range: 5/32 - 1-9/16 in

#### Contact us for more options



A CROSBIE

MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130





## TE 3-CL ROTARY HAMMER

Powerful pistol-grip, triple-mode SDS Plus (TE-C) rotary for hammer drilling, rotary-only drilling, chiseling, and chipping function.

Weight according EPTA-Procedure 01/2003: 6.6 lb

Working mode: Hammer drilling, Chiseling, Drilling

Hammer drilling diameter range: 5/32 - 1-3/32 in

Optimum Hammer drilling range: 1/4 - 5/8 in



## TE 50-AVR ROTARY HAMMER

Compact SDS Max (TE-Y) rotary hammer for drilling and chiseling in concrete

Weight according EPTA-Procedure 01/2003: 13.4 lb.

Single impact energy: 4.4 ft-lbs

Hammer drilling diameter range: 5/32 - 1-3/32 in

Optimum Hammer drilling range: 1/4 - 5/8 in

Hammer drilling diameter range: 5/32 - 1-9/16 in

Full hammering frequency: 3510 impacts/minute

Functionality: Active Vibration Reduction (AVR), Chiseling, Depth gauge

Triaxial vibration value for hammer drilling into concrete (ah,HD): 9 m/s<sup>2</sup> 1

#### Contact us for more options



A CROSBIE

MEMBER

COMPANY

Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130



### DD 160 CORE DRILL

Compact but powerful diamond coring machine for rig-based concrete coring from 25-202 mm (31/32 - 7-15/16") in diameter

Diameter range 31/32 - 7-15/16 in

**Base material: Concrete** 

Operation mode: Rig-based drilling system

Weight of complete system: 36 lb.

Number of gears: 3



## DD-WMS 100 WATER MANAGEMENT SYSTEM

A single unit for the supply of cooling water as well as the collection and filtration of wastewater from diamond drilling systems

Filling volume: 14 L

Flow rate: 2 L/min

Hose length: 5000 mm

Weight: 49.6 lb.

Max. water pressure: 7 bar

#### Contact us for more options



A CROSBIE MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130

Email: info@fmlgy.com

Visit us at WWW.FMLGY.COM



### TE 6-A22 CORDLESS ROTARY HAMMER

Powerful D-grip 22V cordless rotary hammer with superior concrete drilling and chipping performance

Weight according EPTA-Procedure 01/2003: 8.2 lb.

Optimum Hammer drilling range: 1/4 - 5/8 in Hammer drilling diameter range: 5/32 - 25/32 in

Single impact energy: 1.8 ft-lbs Hammer drilling RPM: 1050 rpm

Full hammering frequency: 5100 impacts/minute

Triaxial vibration value for hammer drilling into concrete (ah,HD)......9.5 m/s² (Recommended Combination:

5.2 Ah battery + DRS)



#### SBT 4-A22 CORDLESS DRILL DRIVER

Cordless drill driver for predrilling accurate holes and installing S-BT fasteners Compact and lightweight.

RPM: 2140 rpm

Max. Torque: 442.5 in-lbf Rated voltage: 21.6 V

Chuck type: Keyless, steel jaws, 1.5 to 13 mm



### SF BT 22-A CORDLESS DRILL

Compact and lightweight Cordless drill for predrilling accurate holes for X-BT fasteners.

RPM: 4,000

Max. Torque: 2 ft-lbs Rated voltage: 21.6 V

#### Contact us for more options



A CROSBIE MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urguhart Street | Georgetown | Tel: +592-226-8130



## HDE 500-A22 CORDLESS ADHESIVE DISPENSER

Battery-powered hybrid/epoxy adhesive anchor dispenser

Battery type: 22 V

Dispenser type: Battery



### SR 6-A22 RECIPROCATING SAW

Cordless 22V reciprocating saw engineered for heavy-duty demolition and cutting to length with minimal vibration and advanced ergonomics.

Base material: Metal, Wood

Stroke length: 1-1/4 in

Stroke: Rate2600 strokes / minute

Dust removal system: AvailableSR DRS



### **GDG 6-A22 CORDLESS DIE GRINDER**

Variable-speed cordless die grinder with high-performance brushless motor for metal fabrication and architectural metalwork

Rated voltage: 21,6 V

Weight according EPTA-Procedure 01/2003: 5.7 lb.

#### Contact us for more options



A CROSBIE

MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130







## BX 3-BT (02) CORDLESS FASTENING TOOL

22V cordless nailer for fastening X-BT threaded stud.

Tool body weight: 7.6 lb.

Fastener length range: 0.84 - 1.23 in

Rated voltage: 21.6 V



### RT 6-A22 CORDLESS RIVET TOOL

22V cordless rivet tool powered by Li-ion batteries for installation jobs and industrial production using rivets up to 3/16" in diameter (up to 13/64" for aluminium rivets)

Rivet diameter range: 3/32 - 3/16 in

Rivet material: Aluminium, Stainless steel, Steel

Nose piece sizes: 3/32 in, 1/8 in, 2/32 in, 5/32 or 3/16 in

Stroke length: 31/32 in Pull force: 2248.09 lbf



## SCM 22-A CORDLESS METAL SAW

Cordless metal circular saw for fast, precise cold cuts in sheet, panels, pipes and profiles

Max. cutting depth: 2.24 in

Blade diameter: 6.5 in

Base Material: Metal, Sandwich panel

No load RPM: gear 1: 3500 rpm Guiding rail compatibility: Yes

#### Contact us for more options



A CROSBIE

MEMBER

COMPANY

Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130



### DSH 600 A22 CUTOFF SAW

Battery powered cut off saw for concrete, metal and masonry (Nuron battery platform)

Base materials: All types of concrete and brick, All types of masonry (hollow brick, limestone,

etc), Asphalt, Steel, Masonry

Arbor Size: Option 1 : 1 in; Option 2: 20 mm
Work environment: Interior and Exterior
Protection class: IEC Battery operated



## TE 2000 AVR A22 CORDLESS JACKHAMMER

Powerful and light battery-powered jackhammer for breaking up concrete and other demolition work (Nuron battery platform)

Working direction: Floor Tool chuck type: TE-S Tool body weight: 38.4 lb.

Full hammering frequency: 1800 impacts/minute



## TE6 DRS A22 CORDLESS ROTARY HAMMER WITH DUST REMOVAL SYSTEM

Powerful D-grip 22V cordless rotary hammer with superior concrete drilling and chipping performance

Hammer drilling diameter range: 4 - 20 mm

Single impact energy: 2.5 J

Hammer drilling RPM: 1050 rpm

Full hammering frequency: 5100 impacts/minute

#### Contact us for more options



A CROSBIE MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130



## AG 6D A22 (125) 6" CORDLESS ANGLE GRINDGER

Powerful cordless angle grinder with brushless motor, SensTech control and advanced safety features for discs up to 6" (Nuron battery platform)

Disc diameter: 6 in

Max. cutting depth: 1.81 in

No load RPM: Gear 6: 8500 rpm



## **BX 3-22 CORDLESS CONCRETE NAILER**

Nuron battery-powered fastening tool for attaching drywall track and other light-duty fastening to concrete, steel and masonry (max. nail length 30 mm | 1-1/8")

Fastener Intake: 30 nails

Fastener length range: 0.55 - 1.18 in

Bluetooth: Yes



## SIW 8-22 1/2" CORDLESS IMPACT WRENCH

Ultimate-class, high-torque cordless impact wrench with 1/2" friction ring anvil for structural bolting and anchoring (Nuron battery platform)

Anvil type: 1/2" friction ring

Maximum torque: 443 ft-lbs (1); 738 ft-lbs (2) 1 Full hammering frequency: 2.950 impacts/minute No load RPM: gear 1: 1250 rpm; gear 2: 1500 rpm

#### Contact us for more options



A CROSBIE MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130





## NCT 45 S-22 ACSR AND GUY WIRE CORDLESS CABLE CUTTER

Guillotine-style cordless hydraulic cable cutter with larger cutting capacity for ACSR cable and guy wire (Nuron battery platform)

Cutting capacity: 1/2 guy wire (EHS)", 1590 kcmil (Falcon), 5/8 guy wire (HS)", ACSR: Max. outer diameter 45 mm, Guy Wire (EHS): Max. outer diameter 13 mm, Guy Wire (HS): Max. outer diameter 15.9 mm

Head rotation: 350 °



## Contact us for more options



A CROSBIE MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130

Email: info@fmlgy.com

Visit us at WWW.FMLGY.COM