

SLA

READY TO START

SLA (Sealed Lead Acid) batteries will make your gardening tasks easier. No more handling acid or waiting for batteries to charge—everything is now much simpler! SLA batteries are sealed, non-spillable, factory-activated and no maintenance. These ready-to-use batteries are extremely easy to install and carry, all at a very attractive price. Discover the widest range available on the market, designed to meet all your gardening power needs.

ORIGINAL EQUIPMENT
OEM
MANUFACTURER

**plug
and
play**



FACTORY ACTIVATED

AGM (Absorbent Glass Mat) technology.



READY TO USE

Just plug & play.



NO MAINTENANCE

VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN

Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING

Very safe.




HIGH STARTING POWER & EXTENDED CYCLE LIFE



MOUNTING ANGLES

**HIGH INCLINATION
NON-SPILLABLE**



COMPATIBLE CHARGERS

BS 10 Battery size up to 20Ah	BS 15 Battery size up to 30Ah
BS 30 Battery size up to 60Ah	BS 30 MAX Battery size up to 60Ah
BS 60 Battery size up to 120Ah	BK 20 Battery size up to 40Ah

DID YOU KNOW?

SLA range can replace 95% of Maintenance Free and DRY batteries.

SLA batteries are non-spillable, so they're safe to ship and e-commerce ready!

BS BATTERY TYPE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
U1-9 (12N24-4A)	300901	-	28	300	195	125	176		
U1R-9 (12N24-3A)	300902	-	28	300	195	125	176		
U1-12 (12N24-4A)	300877	-	32	400	195	125	176		
U1R-12 (12N24-3A)	300878	-	32	400	195	125	176		
SLA12-20	300879	20	21.1	180	182	77	168		
BTZ7S	300635-1	6	6.3	130	113	70	105		
BTX16	300763	14	14.7	230	150	87	161		
BTX14AH/BB14-A2/B2 (12N14-4A)	300758	14	14.7	210	135	90	164		
BTX14AHL/BB14L-A2/B2 (12N14-3A)	300759	14	14.7	210	135	90	164		
BTX24HL/B50-N18L-A/A2/A3 (12N18-3A)	300770	21	22.1	350	205	87	162		
53030 (B60-N30L-A)	300880	30	31.6	300	178	123	166		

SLA^{MAX}
FACTORY ACTIVATED


BS BATTERY TYPE	BS CODE	CAPACITY AH (10HR)	CAPACITY AH (20HR)	CCA A (-18°C)	DIMENSIONS (±2MM)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
U1-500	300899	30	31.6	500	195	125	176		



REINFORCED CASING WITH GRID FRAMEWORK
For a maximum vibration resistance.



8,8 MM TERMINALS
M6 adapter included for lawn and garden applications.



TALLER PLATES
For enhanced CCA & Capacity.

BATTERY RANGE OVERVIEW

COMPARATIVE CHART



	LITHIUM LiFePO4	SLA FACTORY ACTIVATED	DRY BATTERY	VRLA BATTERY
TECHNOLOGY	LiFePO4	AGM/VRLA	Flooded dry	AGM/VRLA
FACTORY ACTIVATED READY TO USE	✓	✓	—	✓
NO ACID HANDLING	✓	✓	—	✓
NO MAINTENANCE	✓	✓	—	✓
NON-SPILLABLE	✓	✓	—	✓
INCLINATION LEVEL				
SUITABLE FOR E-COMMERCE COMPLIANT WITH EU REGULATION 2019/1148 (FOR THE SALE OF ACID FOR BATTERIES)	✓	✓	—	✓
EASY TO SHIP	✓	✓	—	✓
TRANSPORT TYPE				

(1) Once activated

(2) According to ADR, IMDG & IATA regulations