

OLYMPIC 5 COLLECTION

 $3/16" \times 7" \times 48"$ (nominal) | 5.0mm × 177.8mm × 1219.2mm

Paris Oak	Whistler Oak	Turin Oak	Tokyo Oak*	Sydney Oak*	London Oak	Athens Oak	Rio Walnut* (All Over Texture)
MQLL-550	MQLL-551	MQLL-5 <i>5</i> 2	MQLL-553	MQLL-554	MQLL-555	MQLL-556	MQLL-557



OLYMPIC 5 COLLECTION

Comfortable, quiet, waterproof and durable 5mm loose lay.

One of the very few EIR Loose Lay collections on the market, that is 100% Virgin Phthalate Free PVC.

- 100% Waterproof Multilayered Engineered Loose Lay with incapsulated stable fiberglass
- Sound absorbent SafeGrip backer
- TORLYS Maxx Commercial Finish resists high traffic wear and staining and features built-in antimicrobial protection to keep floors cleaner between cleanings
- Kissed bevel edges
- EIR textures*
- · Warm, comfortable and quiet underfoot
- Floorscore® Certified
- 100% Virgin PVC
- Anti-telegraphing performance for imperfect subfloors

DIMENSIONS

Plank

7" x 48" (nominal) 177.8mm x 1219.2mm

Thickness

3/16" | 5mm

Wear Layer Thickness

0.5mm | 20mil

18.67 sq.ft per carton

RECOMMENDED UNDERLAYMENT

TORLYS VersaLay

WARRANTY

Lifetime Limited Residential Warranty
15 Year Limited Commercial Warranty

TECHNICAL DATA						
Test	Test Method	Result				
Flexibility	ASTM F137-08 (2013)	Pass				
Resistance to Chemicals	ASTM F925-13	Pass				
Resistance to Heat	ASTM F1514-03 (2013)	Pass				
Effect of Castor Chair	NALFA LF 01-2011 Section 3.9	Pass				
Dimensional Stability (after heat exposure)	ASTM F2199-09 (2014)	Pass				
Static Load Limit	ASTM F970 (250 lb)	Residual Indentation 0.011 mm				
Critical Radiant Flux	ASTM E648/NFPA classification	Class 1				
Coeffcient of Friction	ASTM D2047	Pass				
Thermal Conductivity	ASTM C518-17	0.128W/(m.K)				
Phthalate Content Test	CPSC-CH-C1001	Non detected				









^{*}Rio Walnut is not EIR