

# READY-TO-USE & NON-SPILLABLE




## TECHNOLOGY

The **SLA** range is engineered to deliver **maximum performance**, reliability, and safety. Ready-to-use straight from the box, the **Sealed Lead-Acid (SLA)** battery requires no acid handling, no initial preparation, and no maintenance.

Its non-spillable design, combined with strong starting power and long-lasting performance, makes it the ideal solution **for all ride-on mowers and lawn tractors**.

**NON-SPILLABLE**



## FEATURES

- » **Ready-to-use:** factory activated for immediate use
- » **100% maintenance-free:** no refilling required
- » **Non-spillable (VRLA):** safe to ship and handle
- » **Multi-positional fitment:** up to 90°
- » **Reinforced case:** extra durability for extreme conditions
- » **Extended service life:** designed for long-lasting reliability

## COMPATIBLE CHARGERS

- » **Fulload 1000:** battery capacity up to 20Ah
- » **Fulload F4:** battery capacity up to 80Ah
- » **Fulload F10:** battery capacity up to 200Ah
- » **Fulbank F2:** battery capacity up to 40Ah

| DESIGNATION           | P/N    | VOLTAGE (V) | CAPACITY Ah (20hr) | CAPACITY Ah (10hr) | CCA (A) | DIMENSIONS (+/- 2 mm) |     |     | POLARITY | TERMINAL |
|-----------------------|--------|-------------|--------------------|--------------------|---------|-----------------------|-----|-----|----------|----------|
|                       |        |             |                    |                    |         | L                     | W   | H   |          |          |
| U1-9 SLA (12N24-4A)   | 550901 | 12          | 28                 | -                  | 300     | 195                   | 125 | 176 | +        | +        |
| U1R-9 SLA (12N24-3A)  | 550902 | 12          | 28                 | -                  | 300     | 195                   | 125 | 176 | +        | +        |
| U1-12 SLA (12N24-4A)  | 550903 | 12          | 32                 | -                  | 400     | 195                   | 125 | 176 | +        | +        |
| U1R-12 SLA (12N24-3A) | 550904 | 12          | 32                 | -                  | 400     | 195                   | 125 | 176 | +        | +        |
| SLA12-18              | 550633 | 12          | 18.9               | 18                 | 150     | 182                   | 77  | 168 | +        | +        |
| SLA12-20              | 550879 | 12          | 21.1               | 20                 | 180     | 182                   | 77  | 168 | +        | +        |
| SLA12-22              | 550907 | 12          | 23.1               | 22                 | 210     | 182                   | 77  | 168 | +        | +        |
| FTX16                 | 550763 | 12          | 14.7               | 14                 | 230     | 150                   | 87  | 161 | +        | +        |
| FTZ75                 | 550635 | 12          | 6.3                | 6                  | 130     | 113                   | 70  | 105 | +        | +        |
| FB14L-A2 (12N14-3A)   | 550927 | 12          | 14.7               | 14                 | 175     | 135                   | 90  | 167 | +        | +        |
| FB14-A2 (12N14-4A)    | 550946 | 12          | 14.7               | 14                 | 175     | 135                   | 90  | 167 | +        | +        |
| F50-N18L-A (12N18-3A) | 550982 | 12          | 22.1               | 21                 | 350     | 205                   | 87  | 162 | +        | +        |
| 53030 (F60-N30L-A)    | 550945 | 12          | 31.6               | 30                 | 300     | 178                   | 123 | 166 | +        | +        |
| 53034 (F60-N30-A)     | 550843 | 12          | 31.6               | 30                 | 300     | 178                   | 123 | 166 | +        | +        |