

Hyosung 9I

**Elevate the branch experience
with the industry's most
efficient cash recycler.**

The Hyosung 9I island drive-up ATM revolutionizes digital branch transformation with state-of-the-art engineering and a wide range of self-service capabilities powered by our industry-leading BlueVerse™ software.

Feature Highlights

Advanced Cash Recycling

Reduce operating costs and increase availability

Innovative Modular Design

Maximize ATM availability and serviceability

Flexible Configurations

Choose modules that best meet your needs

Full Denomination Support

with split cassette option



Modular
Design



19"
Touchscreen



Recycle up to
6 denominations



100 notes
per transaction



Up to 3,440
note capacity per
cassette

Specifications

Dimensions

- Height: 1,488mm (58.6")
- Width: 1,089mm (42.9")
- Depth: 1,000mm (39.4")
- Weight: 1,071 kg (2,361.2 lbs)

Environmental Conditions

- Temperature: 0°C ~ 40°C (32°F ~ 104°F)
Exterior with heater/AC: -35°C ~ 50°C (-31°F ~ 122°F)
- Humidity: 25% ~ 85%

System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™

Customer Interface

- 19" Landscape LCD Sunlight Viewable Touchscreen
- Card Reader
- NFC Reader
- Audio Jack

Servicing

- Front Access
- State of health indicators for all modules

Media Handling

- Recycling/Deposit Module (Presenter Cash Tray)
 - Configurable with up to 4 large recycling cassettes or 2 large recycling cassettes and 4 small recycling cassettes, plus 1 deposit cassette
 - Large Cassette: 430mm capacity¹
 - Split Cassette: Top 100mm capacity¹
Bottom 185mm capacity¹
 - Deposit Cassette²: 430mm capacity¹
 - Retract Cassette: 50mm capacity¹
 - Bundle up to 100 notes per withdrawal/deposit transaction
- Check Acceptor
 - Up to 30 checks per transaction
 - Deposit cassette: 160mm capacity¹
 - Retract bin: 50 checks
 - OCR E13B/CMC7 capable

Security

- Safe – CEN-III ExGas
- Cencon Lock
- Alarm (Seismic & heat)
- Security Camera (IP or CCD optional)

Printer

- 3.1" graphical thermal receipt printer

Power Supply

- AC 100 ~ 127V ± 10% / 10.0A, 50 ~ 60Hz

Additional Features

- Lead-through indicator
- Speaker
- Communication – TCP/IP
- Fitness sorting
- Multi-channel communications
- ActiveTeller capable
- Battery backup built in
- Barcode reader
- Palm vein reader (optional)
- ID scanner (optional)
- Heater

Footnotes:

1: Subject to media quality and other variables

2: Deposit cassette configurations:

- 1 Slot: 430mm capacity¹
- 2 Slots: 65mm / 330mm capacity¹
- 3 Slots: 65mm / 65mm / 225mm capacity¹

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

