

SUPERLOCK 2.0 KEYLATCH

Specification Sheet BK 2.0

FEATURES

- The single-body design removes joints and welds, increasing durability and giving the lock a clean, professional finish.
- Engineered and tested for high-impact outdoor use, the Superlock 2.0 delivers unmatched strength, and reliability.
- Simple key operated latch, push the gate shut and open with the key.
- Easy to fit – Slim 70mm (2 3/4") wide lock case along with adjustable and removable latchbolt ensure easy fitting to gates.
- Latchbolt is adjustable in length for precise fitting on site. Easy to rotate for left and right handed gates, latch retracts 15mm (5/8").
- Perfect for both left hand and right hand gates.

PRODUCT DETAILS

Product code	Description
BK1030	To fit up to 30mm (1 1/4") box section
BK4060	To fit 40-60mm box section (1 1/2" to 2 1/4")
Compatible with: Superlock Keeps (BSK , BSKS , BSKG)	

INCLUDED IN THE BOX

- 2.5mm hex key + 3mm hex key
- M8 fixing bolts
- Face plate
- Latchbolt
- Strike plate (self-drilling fasteners)
- A set of keys (3)

INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 140mm (5 1/2") centres for fixing bolts provided.
 2. Drill a 18mm (3/4") clearance hole for the latchbolt at 60mm (2 3/8") centres up from the bottom fixing hole.
 3. Hold the lock against the back of the box section and screw on the latchbolt through the larger hole.
 4. Lock the latchbolt with the hex key supplied by inserting the hex key into the end of the latchbolt.
 5. Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt moves freely.
 6. Fix strike plate by either welding or screw fixing onto the gate post.
- Maintenance:** Every 6 months, lubricate the latchbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.



5 Year Warranty

