

# HYOSUNG

# MX2800T

## Hyosung is Revolutionizing the Self-Service Industry.

The **MX2800T** brings you through-the-wall convenience and the latest advancements in ATM technology. Plus, the appealing and weatherized exterior is suitable for even the most high-end locales. This heavy-duty machine gives you the dependability and ease of maintenance with the added bonus of high-capacity note storage. You get the same high quality and proven reliability you expect from industry leader Hyosung.

## Features

---

### Innovative Design

The **MX2800T** offers a wide range of transactions and features a user-friendly interface with a large 12.1" display screen and tactile touch with function keys.

### Capacity

A significant advantage of the **MX2800T** ATM is its high-capacity note storage able to accommodate up to three removable cassettes to make managing your cash easier.

### Reliability

Ease of maintenance and simplified service routines provide maximum availability and increased uptime with minimal operational intervention.

### Visibility

The built-in LED backlit sign makes this already attractive ATM even more visible. Add a video topper to stream advertising of your choice to attract more sales and customers.



# HYOSUNG

# MX2800T

## Specifications

### Dimensions

- Height: 1828mm (72")
- Width: 400mm (15.75")
- Depth: 670mm (26.38") for 3" wall
- Depth: 670mm (26.38") for 10" wall
- Weight: 150kg (330lbs)

### Environmental Conditions

- Storage Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 10% – 90%
- Operational Temperature: 41°F – 95°F (5°C ~ 35°C)
- Humidity 25% – 85%

### System Platform

- Microsoft Windows® CE 6.0

### Customer Interface

- 12.1" TFT LCD
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- PCI Compliant
- Card Reader – EMV compliant, anti-skimming, ISO 1,2,3, and IC card reader (optional)

### Media Handling

- 3 cassettes 2,000 notes each
- 40 notes/transaction
- Note by note reject (200 bills max)

### Security

- Safe – UL291 business hours
  - UL291 Level-1 (optional)
- Locking Device – electronic lock
  - KABA Mas Cencon (optional)
  - Dial lock (optional)

### Wall Kit

- 3" throat
- 10" throat (optional)

### Printer

- 3.1" graphical thermal receipt printer

### Servicing

- Rear access
- State of health indicators for all modules

### Power Supply

- Input Voltage / Currency: 100W Free Voltage (90-264VAC), 90 – 132 Vac / 5.0A; 180 – 264 Vac / 2.5A
- Frequency: 47 – 63 Hz

### Additional Features

- Communication – TCP/IP
- Weatherized
- Illuminated topper
- EPP illumination
- Supports six languages; English, Spanish, French, Japanese, Chinese, & Korean
- Heater (optional)

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.