

5100T

The 5100T is a through-the-wall ATM that delivers high availability and offers a wide variety of optional modules along with traditional service offerings. The 5100T offers best in class reliability, security, and high capacity. It can easily scale up after installation to suit growing demand.

Features

HIGH AVAILABILITY

The 5100T is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

FUNCTIONALITY

The 5100T is available as a walk-up, drive-up, through-the-wall and freestanding kiosk. It features a small footprint and compact design that offers flexible options at an affordable price.

An optional 10.4" sunlight viewable color display is designed to perform clearly inside or outside.

FLEXIBILITY

Designed with an open architecture platform allowing for easy future upgrades and module modifications.

The modular design helps our customers' save cost and provide maximum convenience.

SECURITY OPTIONS

Hyosung ATMs defend against physical and logical attacks with a combination of multi-level anti-skimming, locked-down operating system, white-listing, and encryption.



Standard Features

DIMENSIONS

- Height: 59.4"
- Width: 23.6"
- Depth: 32.6"
- Weight: 441.5 lbs

ENVIRONMENTAL

- Temperature: 32°F – 104°F
(0°C ~ 40°C)
- Humidity 25% – 85%

SOFTWARE

- Microsoft Windows® 7
- Windows10 ready

CUSTOMER INTERFACE

- 10.4" TFT LCD sunlight viewable
- Input Method – Touch screen
- Privacy Filter – 10.4" filter
- PIN Pad – PCI compliant
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant

MEDIA TECHNOLOGY

- Dispense
 - 2,000 notes per cassette
 - Up to 4 cassettes

SECURITY

- Safe: UL 291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic safe lock, KABA Mas Cencon (optional)
- Sensor – Safety Door Sensor
- Security – Terminal block for easy security connections
- Terminal Block (External I/F)
- Key Lock – Common Key

SERVICING

- Rear access
- State of health indicators across all modules
- 5.7" Supervisor display

PRINTER

- 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication – TCP/IP

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.

