

# IRD-SFP-25G-MUM

Transceptor Óptico SFP28 25Gbps Multimodo, 850 nm, LC Duplex, até 100 m (25GBASE-SR)

## CARACTERÍSTICAS

- Transceptor óptico SFP28 para Ethernet de 25 Gbps (25GBASE-SR)
- Compatível com taxas de 8,5 a 28,1 Gbps, inclusive 10 Gbps (10GBASE-SR)
- Utiliza fibra multimodo (MMF) com conectores LC duplex
- Comprimento de onda: 850 nm (laser VCSEL)
- Alcance máximo: 100 m (indicado para MMF, especialmente OM4)
- Suporte a Digital Diagnostics (DDM/DOM) para monitoramento em tempo real
- Hot-pluggable (inserção/removal sem desligamento)
- Faixa de temperatura operacional padrão: 0 °C a 70 °C (comercial)
- Consumo de energia reduzido ( $\approx \leq 0,3$  W)
- Projeto compacto com carcaça metálica resistente a interferência (EMI)
- Compatível com padrões SFP28 MSA, SFF-8431, SFF-8472, IEEE 802.3by
- Certificações: RoHS, CE, Class I laser safety



A imagem apresentada é apenas para fins ilustrativos

SFP28

850nm

Multimodo

100m



## INTRODUÇÃO

O IRD-SFP-25G-MUM é um módulo óptico SFP28 de alta performance, projetado para enlases de 25 Gigabit Ethernet em fibra multimodo. Sua construção compacta e compatibilidade com o padrão MSA asseguram operação confiável em diferentes fabricantes de switches e roteadores, oferecendo flexibilidade e baixo consumo de energia.

Além de sua performance comprovada, o transceiver permite migração simplificada de 10G para 25G, aproveitando a mesma infraestrutura de fibra multimodo já existente em data centers e redes corporativas. Com alcance de até 100 m em OM4, diagnóstico digital integrado e carcaça metálica para proteção contra EMI, o IRD-SFP-25G-MUM garante alto desempenho, monitoramento contínuo e excelente custo-benefício em ambientes de missão crítica.

## ESPECIFICAÇÕES TÉCNICAS

### Funcionalidades

- Suporte nativo a 25GBASE-SR Ethernet, com retrocompatibilidade para 10GBASE-SR
- Alcance:
  - até 100 m em OM4 (geralmente ~70 m em OM3 com orçamento óptico marginal)
- Suporta taxas entre 8,5–28,1 Gbps, ideal para diversos cenários de rede
- Monitoramento digital (DDM) para parâmetros como: temperatura, TX/RX power, tensão, corrente
- Interface óptica LC duplex e interface elétrica SFP28 MSA
- Hot-pluggable e pronta para operação imediata
- Carcaça em zinco/metálica para redução de EMI
- Compatível com os principais switches e roteadores do mercado
- Design robusto, blindagem metálica contra EMI

### Ópticas

- **Transmissor:**
  - Comprimento de onda: 840 – 860 nm (850 nm típico)
  - Largura espectral RMS:  $\leq 0,6$  nm
  - Potência óptica média: -6,7 a +2,4 dBm
  - Laser off power:  $\leq -30$  dBm
  - Relação de extinção:  $\geq 2$  dB
  - RIN:  $\leq -130$  dB/Hz
  - ORL tolerado: 12 dB
- **Receptor:**
  - Comprimento de onda: 840 – 860 nm
  - Potência de entrada: -10 a +2 dBm
  - Sensibilidade (OMA):  $\leq -10$  dBm
  - LOS Assert:  $\leq -26$  dBm
  - LOS De-Assert:  $\geq -13$  dBm
  - Histerese LOS: 0,5 – 5 dB
  - Potência de sobrecarga: +2 dBm

### Elétricas e Consumo

- Alimentação: +3,3 V (0 a 3,6V)
- Consumo:  $\leq 0,3$  W

### Ambiental

- Temperatura operacional: 0 °C a 70 °C (comercial)
- Temperatura de armazenamento: até -40 °C a +85 °C
- Umidade relativa: 5%–85% sem condensação

### Diagnóstico Digital (DDM / SFF-8472)

- Parâmetros monitorados: temperatura, potência TX/RX, tensão, corrente de bias
- Interface: via I<sup>2</sup>C conforme SFF-8472
- Temperatura: erro máx.  $\pm 3$  °C
- Potência TX: erro máx.  $\pm 3$  dB
- Potência RX: erro máx.  $\pm 3$  dB
- Tensão: erro máx.  $\pm 3\%$
- Corrente de bias: erro máx.  $\pm 10\%$

### Elétricas

- Transmissor
  - Impedância diferencial de entrada: 90 – 110 ohms
  - Swing de entrada diferencial: 200 – 900 mV
  - Disable TX: Vcc – 1,3 a Vcc
  - Enable TX: Vee a Vee + 0,8 V
- Receptor
  - Swing de saída diferencial: 400 – 900 mV
  - LOS Fault: Vcc – 0,5 a Vcc\_host
  - LOS Normal: Vee a Vee + 0,5 V

### Mecânicas e Compatibilidade

- Formato: padrão SFP28
- Conector óptico: LC duplex (fêmea)
- Interfaces compatíveis com Cisco, Huawei, Juniper, HPE, Dell, Mellanox e outros fabricantes via MSA
- Certificações: RoHS, CE, Class I Laser Safety, IEEE 802.3by, SFP28 MSA, SFF-8431, SFF-8472

### Temporização

- Assert TX Disable: até 100  $\mu$ s
- Negação TX Disable: até 2 ms
- Inicialização do módulo: até 300 ms
- Assert TX Fault: até 1 ms
- Reset TX Fault:  $\geq 10$   $\mu$ s
- Delay Assert Rx LOS: até 100  $\mu$ s
- Delay Negate Rx LOS: até 100  $\mu$ s

contato@IRD.Net.br

<https://www.IRD.Net.br>

0800-591-8455

**IRD.Net**<sup>®</sup>  
Inovação em Redes Digitais

Aviso Legal: As informações e especificações contidas neste documento estão sujeitas a alteração sem aviso prévio. A IRD.Net não se responsabiliza por eventuais erros de digitação ou omissões, nem por danos decorrentes do uso inadequado ou instalação incorreta do produto. O uso deste equipamento deve seguir as normas e regulamentações locais aplicáveis. Nenhuma parte deste material pode ser reproduzida, distribuída ou utilizada para fins comerciais sem autorização prévia e por escrito da IRD.Net.

Room 303, Building 1, No.316, Renzhou Road,  
Shatian Town, Dongguan City, Guangdong Province  
www.junantest.com



# CERTIFICATE OF CONFORMITY

No: JAT25040302947EC-1

Applicant : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
Manufacturer : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
EUT : Commercial and Industrial Grade SFP Modules (Optical Modules)  
Trade Mark : IRD.Net  
M/N : See model list

The submitted sample of the above equipment has been tested and found to comply with the following European Directive:

### Electromagnetic Compatibility Directive 2014/30/EU

The standard(s) used for showing compliance with the essential requirements:

Applicable Standard(s)	Test Report(s) Number
<b>EN 55032:2015+A11:2020</b> <b>EN 55035:2017+A11:2020</b> <b>EN IEC 61000-3-2:2019+A2:2024</b> <b>EN 61000-3-3:2013+A2:2021+AC:2022-01</b>	<b>JAT25040302947ER-1</b>

This certificate is part of the full test report(s) and should be read in conjunction with it. This certificate is based on an evaluation of one sample of above mentioned product. It does not imply assessment of the production of the product. Without the written approval of Dongguan Jun'an Testing & Certification Co., Ltd., this certificate is not permitted to be reproduced, except in full. It is not permitted to use the test lab's logo. The CE marking may only be used if all the relevant and effective European Directive are applicable.



(Manager)  
March 31, 2025



Model list:

The IRD-SFP-T2.5G, IRD-SFP-T1G, IRD-SFP-T10G, IRD-SFP-X-Y-ZW and IRD-SFP-X-Y-Z-IW model families follow a naming convention where each part of the code corresponds to a specific characteristic of the module. Below is a detailed explanation of each field:

1. **X (Speed)**

- Possible values: *100M*, *622M*, *1G*, *2.5G*, *10G*, *16G*, *25G*, *40G*, *50G*, or *100G*.
- Indicates the supported data rate, covering anything from Fast Ethernet (100 Mbps) up to 100 Gbps.

2. **Y (Fiber Type)**

- Possible values: *SM* (singlemode) or *MUM* (multimode).
- Specifies the type of fiber optic cable for which the transceiver is designed.

3. **Z (Maximum Distance)**

- Possible values: *0.1*, *0.3*, *0.5*, *2*, *10*, *20*, *40*, *60*, *80*, *100*, *120*, and *160*.
- Typically expressed in kilometers (km), it refers to the approximate reach of the module according to its optical specification.

4. **Temperature/Operating Grade**

- After the value **Z**, the presence of **I** indicates an *industrial-grade* product (extended operating temperature range), whereas the absence of **I** (NULL) means it is *commercial-grade*.
- Examples:
  - **IRD-SFP-X-Y-ZW** → “Commercial-grade” version
  - **IRD-SFP-X-Y-Z-IW** → “Industrial-grade” version

5. **W (Additional Type)**

- Possible values: *NULL*, *A*, *B*, *C*, *D*, *E*, *F*, *G*, or *H*.
- This suffix provides additional information about the product variant. It may indicate extra features, extended compatibility, special applications, and so on.

Room 303, Building 1, No.316, Renzhou Road,  
Shatian Town, Dongguan City, Guangdong Province  
www.junantest.com



# SDoC's Compliance Information Statement

No: JAT25040302947FC-1

Applicant : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
Manufacturer : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
EUT : Commercial and Industrial Grade SFP Modules (Optical Modules)  
Trade Mark : IRD.Net  
M/N : See model list

The submitted sample of the above equipment has been tested and found to comply with the following requirement of 47 CFR of PART 15.

The assessment of compliance of the product with the requirements relating to FCC rules was based on the following standards and procedure:

Applicable Standard(s)	Test Report(s) Number
<b>FCC Part 15, Subpart B:2017</b> <b>ANSI C63.4:2014</b>	<b>JAT25040302947FR-1</b>

This verification is part of the full test report(s) and should be read in conjunction with it. This verification is based on an evaluation of one sample of above mentioned product. It does not imply assessment of the production of the product. Without the written approval of Dongguan Jun'an Testing & Certification Co., Ltd., this verification is not permitted to be reproduced, except in full. It is not permitted to use the test lab's logo.



(Manager)

March 31, 2025



Model list:

The IRD-SFP-T2.5G, IRD-SFP-T1G, IRD-SFP-T10G, IRD-SFP-X-Y-ZW and IRD-SFP-X-Y-Z-IW model families follow a naming convention where each part of the code corresponds to a specific characteristic of the module. Below is a detailed explanation of each field:

1. **X (Speed)**

- Possible values: *100M*, *622M*, *1G*, *2.5G*, *10G*, *16G*, *25G*, *40G*, *50G*, or *100G*.
- Indicates the supported data rate, covering anything from Fast Ethernet (100 Mbps) up to 100 Gbps.

2. **Y (Fiber Type)**

- Possible values: *SM* (singlemode) or *MUM* (multimode).
- Specifies the type of fiber optic cable for which the transceiver is designed.

3. **Z (Maximum Distance)**

- Possible values: *0.1*, *0.3*, *0.5*, *2*, *10*, *20*, *40*, *60*, *80*, *100*, *120*, and *160*.
- Typically expressed in kilometers (km), it refers to the approximate reach of the module according to its optical specification.

4. **Temperature/Operating Grade**

- After the value **Z**, the presence of **I** indicates an *industrial-grade* product (extended operating temperature range), whereas the absence of **I** (NULL) means it is *commercial-grade*.
- Examples:
  - **IRD-SFP-X-Y-ZW** → “Commercial-grade” version
  - **IRD-SFP-X-Y-Z-IW** → “Industrial-grade” version

5. **W (Additional Type)**

- Possible values: *NULL*, *A*, *B*, *C*, *D*, *E*, *F*, *G*, or *H*.
- This suffix provides additional information about the product variant. It may indicate extra features, extended compatibility, special applications, and so on.

Room 303, Building 1, No.316, Renzhou Road,  
Shatian Town, Dongguan City, Guangdong Province  
www.junantest.com



# CERTIFICATE OF CONFORMITY

No: JAT25040302947RC-1

Applicant : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
Manufacturer : IRD Produtos de Informática Ltda  
Address : RUA MARIA LOPES BORBA, 474, NAVEGANTES-SC, 88370340,  
BRAZIL  
EUT : Commercial and Industrial Grade SFP Modules (Optical Modules)  
Trade Mark : IRD.Net  
M/N : See model list

The submitted sample of the above equipment has been tested and found to comply with the following European Directive:

**RoHS Directive 2011/65/EU & (EU) 2015/863 & (EU) 2017/2102**

The standard(s) used for showing compliance with the essential requirements:

Applicable Standard(s)	Test Report(s) Number
<b>IEC 62321-1:2013, IEC 62321-2:2013 IEC 62321-3-1:2013, IEC 62321-3-2:2020 IEC 62321-4:2013, IEC 62321-5:2013 IEC 62321-6:2015, IEC 62321-7-1: 2015 IEC 62321-7-2:2017, IEC 62321-8:2017</b>	<b>JAT25040302947RR-1</b>

This certificate is part of the full test report(s) and should be read in conjunction with it. This certificate is based on an evaluation of one sample of above mentioned product. It does not imply assessment of the production of the product. Without the written approval of Dongguan Jun'an Testing & Certification Co., Ltd., this certificate is not permitted to be reproduced, except in full. It is not permitted to use the test lab's logo.

# RoHS



(Manager)  
March 31, 2025



Model list:

The IRD-SFP-T2.5G, IRD-SFP-T1G, IRD-SFP-T10G, IRD-SFP-X-Y-ZW and IRD-SFP-X-Y-Z-IW model families follow a naming convention where each part of the code corresponds to a specific characteristic of the module. Below is a detailed explanation of each field:

1. **X (Speed)**

- Possible values: *100M*, *622M*, *1G*, *2.5G*, *10G*, *16G*, *25G*, *40G*, *50G*, or *100G*.
- Indicates the supported data rate, covering anything from Fast Ethernet (100 Mbps) up to 100 Gbps.

2. **Y (Fiber Type)**

- Possible values: *SM* (singlemode) or *MUM* (multimode).
- Specifies the type of fiber optic cable for which the transceiver is designed.

3. **Z (Maximum Distance)**

- Possible values: *0.1*, *0.3*, *0.5*, *2*, *10*, *20*, *40*, *60*, *80*, *100*, *120*, and *160*.
- Typically expressed in kilometers (km), it refers to the approximate reach of the module according to its optical specification.

4. **Temperature/Operating Grade**

- After the value **Z**, the presence of **I** indicates an *industrial-grade* product (extended operating temperature range), whereas the absence of **I** (NULL) means it is *commercial-grade*.
- Examples:
  - **IRD-SFP-X-Y-ZW** → “Commercial-grade” version
  - **IRD-SFP-X-Y-Z-IW** → “Industrial-grade” version

5. **W (Additional Type)**

- Possible values: *NULL*, *A*, *B*, *C*, *D*, *E*, *F*, *G*, or *H*.
- This suffix provides additional information about the product variant. It may indicate extra features, extended compatibility, special applications, and so on.