

SELECT PRO BOLT-ON KEYED QUICK EXIT

Specification Sheet SBQEKL

FEATURES

- Quick-Exit: Push pad designed to facilitate rapid exit through gates with key entry.
- Precise: Stainless steel adjustable latchbolt which springs 22mm into the gate post for precise fitting on site.
- Auto-latching: Includes a gate post strike plate for seamless latching.
- A security shroud is also available to prevent access to the push pad from the outside.
- Digital keypad/no outside access versions also available.

PRODUCT DETAILS

Product code	Description
SBQEKLL01	To fit 10-30mm (½" - 1 ¼") gate frames, left hand
SBQEKL R01	To fit 10-30mm (½" - 1 ¼") gate frames, right hand
SBQEKLL02	To fit 40-60mm (1 ½" - 2 ¼") gate frames, left hand
SBQEKL R02	To fit 40-60mm (1 ½" - 2 ¼") gate frames, right hand

INCLUDED IN THE BOX

- 1x3mm hex key
- M8 fixing bolts
- Face plate
- Latchbolt
- Strike plate (self-drilling fasteners)
- A set of keys (3)

INSTALLATION

1. Drill 2 x 9mm (3/8") holes at 92mm (3 2/3") centres for M8 fixing bolts provided.
2. Drill a 18mm (¾") clearance hole for the latchbolt at 22mm (7/8") centres up from the bottom fixing hole.
3. Fix lock in place using the stainless steel clamp plate, bolt support plate and 2 stainless steel countersunk fixing bolts supplied.
4. Drill clearance hole in keep or outer frame to receive the latchbolt. Slot this hole vertically to allow for gate sag. Fit strike plate by either welding or screw fixing to the gate post.
5. Ensure latchbolt moves freely without binding on gate or frame.
6. **Maintenance:** Every 2 months, lubricate the latchbolt with light oil. Annually, dismantle the lock and spray the mechanism inside with light oil.

