

GATE LOCKING BOLT

Specification Sheet **GLB**

FEATURES

- Features strong deadbolt which moves 53mm (2-1/8") with one turn of the key. Suitable for left and right handed gates.
- Keyed both sides and is manufactured from all stainless steel.
- Two sizes of eurocylinder, two colours to choose from silver or black.
- Includes keep plate, 3 keys, cylinder escutcheon and stainless steel screws. Weld-in lock plates available separately.

PRODUCT DETAILS

	Product code	Description
Silver	GLB	Euro cylinder extends 24mm (1")
	GLBKA	Euro cylinder extends 24mm (1"), keyed alike
	GLB02	Euro cylinder extends 60mm (2-3/8")
	GLB02KA	Euro cylinder extends 60mm (2-3/8"), keyed alike
Black	GLBB	Euro cylinder extends 24mm (1")
	GLBBKA	Euro cylinder extends 24mm (1"), keyed alike
	GLBB02	Euro cylinder extends 60mm (2-3/8")
	GLBB02KA	Euro cylinder extends 60mm (2-3/8"), keyed alike

Material: Stainless steel

Available options: Two eurocylinder sizes to choose from and two colour options. Keyed alike option available.

Suitable for left and right handed gates. Includes keep plate, 3 keys, cylinder escutcheon and stainless steel screws.

INSTALLATION

Watch the installation video



1. Mark the fixing holes for the lock on the inside of the gate, at a comfortable and accessible height.
2. Fix the lock in position with screws of your choice, ensuring that the lock is straight and level.
3. Line the keep plate up with the bolt in the locked position and screw the keep to the post or frame.

MAINTENANCE

Lubricate with oil periodically.

GLB



GLBB

