


Ca/Ca

READY-TO-USE



TECHNOLOGY

The **Ca/Ca** range is engineered to deliver high starting power and extended service life. Ready-to-use and easy to install, these batteries require **no acid handling** and are designed for **low water consumption**, ensuring completely **maintenance-free** operation throughout their lifespan.



FEATURES

- » **Ready-to-use:** factory activated for immediate use
- » **100% maintenance-free:** no refilling required
- » **Upright installation only:** no inclination
- » **Reinforced case:** extra durability for extreme conditions
- » **Extended service life:** designed for long-lasting reliability
- » **Integrated venting system:** safe release of gases and reduced pressure build-up
- » **Convenient handle:** easy transport and handling
- » **"Magic eye" charge indicator:** quickly shows battery status

COMPATIBLE CHARGERS

- » **Fulload 1000:** battery capacity up to 20Ah
- » **Fulload F4:** battery capacity up to 80Ah
- » **Fulload F10:** battery capacity up to 200Ah
- » **Fulbank F2:** battery capacity up to 40Ah

| DESIGNATION | P/N | VOLTAGE (V) | CAPACITY Ah (20hr) | CAPACITY Ah (10hr) | CCA (A) | DIMENSIONS (+/- 2 mm) | | | POLARITY | TERMINAL |
|-------------|--------|-------------|--------------------|--------------------|---------|-----------------------|-----|-----|----------|----------|
| | | | | | | L | W | H | | |
| U1-9 | 550875 | 12 | 28 | - | 300 | 195 | 130 | 180 | + | + |
| U1R-9 | 550876 | 12 | 28 | - | 300 | 195 | 130 | 180 | - | - |
| NS40(+D) | 550883 | 12 | 36 | - | 335 | 195 | 126 | 221 | + | + |
| NS40(+G) | 550884 | 12 | 36 | - | 335 | 195 | 126 | 221 | + | + |
| NS60(+D) | 550820 | 12 | 45 | - | 350 | 236 | 128 | 222 | + | + |
| NS60(+G) | 550821 | 12 | 45 | - | 350 | 236 | 128 | 222 | + | + |