

# BLACK EDITION

---

## CONTRACT WALLCOVERING



IN STOCK



RYRH-05



































ti-rc15005















































































































RYSR-6

# Specifications

---

Black Edition Type I & Type II patterns meets or exceeds all Type I & Type II requirements of CCC-W-408D and W-101

---

Specifications: Performance:  
Weight (Avg): 15 oz/ly (340 gr/m<sup>2</sup>)  
Width: 52" (132 cm)  
Backing: Scrim

Installation: Reverse hang / Random match  
Custom colors, weights, widths and microventing are available.

---

#### Fire Safety:

- Class A - ASTM E-84 (GRC)
  - NFPA 101 Life Safety Code
- 

#### Environmental and Health:

- Meets State of Washington Building Specification for Indoor Air Quality
    - Meets California Section 01350 Indoor Air Quality Standard
  - Aggressive manufacturing materials recovery and reuse program
    - Highly cleanable water-based inks
    - Antimicrobial additives
- 

#### USGBC LEED Support:

- MR – Materials and Resources – Construction waste management
  - EQ – Indoor Environmental Quality – Low emitting materials
- 

#### Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

---

#### Warranty:

Black Edition is guaranteed to be free of defects in workmanship and material for five years.