

2750 Multi Slide System



2750 Multi Slide System

Features and Benefits

■ Sizing

- Standard sizing in 9' x 8' and 12' x 8' in 3 panel configuration.
- Standard sizing in 12' x 8' and 16' x 8' in 4 panel configuration.
- Maximum panel size is 4' x 8'.
- Maximum frame width of 3 panel door system at 12'.
- Maximum width of 4 panel door system at 16'.
- Custom sizing available.

■ Frame

- KD or welded main frame.
- 7 $\frac{3}{4}$ " total width 6 $\frac{3}{4}$ " jamb depth all PVC multi-chambered profile frame system (on 3 panel).
- 10 $\frac{3}{16}$ " total width 9 $\frac{3}{16}$ " jamb depth all PVC multi-chambered profile frame system (on 4 panel).
- Integrated nail fin application with 1" or 1 $\frac{3}{8}$ " set back.
- Full length weather stripping on all 4 frame components.
- Integrated sill drainage with snap-in sill covers.

■ Sash

- Fully welded vinyl sash with internal aluminum reinforcement with $\frac{7}{8}$ " standard IG, or a 1 $\frac{1}{4}$ " triple insulated glass system.
- Many high energy-efficient glass options for the most extreme temperature sensitive regions.
- Standard glazing, Cardinal™ LoE 366® dual glazed tempered glass.
- All stiles are metal reinforced for extreme wind load resistance.
- Unique internal drainage system to minimize risk of seal failures interior glazed for better performance.

■ Hardware

- Truth Nexus 2 point lock with opposing lock points.
- Anti-lock feature preventing a "false" sense of lock up.
- Stainless steel roller housing and composite wheel with end adjustment, AAMA rated to carry a 500 pound panel for 10,000 cycles without change to adjustment.
- Hardware colors; white, beige, black powder coat, and brushed chrome.

■ Extruded Vinyl Colors



■ Optional Exterior Stocked Colors



■ Optional

- Black Exterior Specialty Laminate
Featuring **WINSHIELD**

