Storage Design Limited

S-Q

SDL ~ TRADER ~ 2025 'B'

C

Bespoke products; bringing your vision to reality.

Whilst we produce many different products, there is always a need for something bespoke, and we are equipped to help.

We have produced 100's of bespoke products over the years. Simply share your vision with us and we will create a full product spec, drawings, costings and physical prototype.

Bespoke products can be made as a 'one off' or batch production, just tell us how many you need and we will make it happen.

The VNA Forklift Cage Trolley

Promoting our Bespoke services into modern warehousing.

These Picking Cages are made especially designed and made to connect and anchor on to major brands of Forklift trucks. Once 'locked on' the cage can be lifted with personnel inside, allowing picking to take place at very high heights without picking and unloading the pallet.





Bespoke Services

Mobile Steps	6 - 29
Trucks & Trolleys	30 - 51
Plate & Sheet Handling & Storage	52 - 55
Drum Storage & Handling	56 - 63
Cylinder Storage & Handling	64 - 73
Trailers	74 - 79
Sack Trucks & Stairclimbers	80 - 96
Plastic Container Systems	97 - 107
Access Platform & Roller Platforms	108 - 109
Book Trolleys & Chair Handling	110 - 115
Racking Protection & Warehouse Barriers	116 - 121
Snow Ploughs	122 - 123
Recycling Bins	124 - 127
Cabinets / Drawer Systems & Shelving Units	128 - 145
Workbenches & Accessories	146 - 161



Steptek

Steptek steps are strong, sturdy and designed with stability and mobility in mind, an unbeatable combination.



Tread Surface Options



Ribbed Rubber Tread Great for general usage Cost effective solution Clamp option adds high visibility



Anti-slip Tread Reduced risk of slips, trips and falls Added safety Cost effective solution



Punched Steel Tread Reduced risk of slips, trips and falls Hard wearing and durable Maintenance free



Aluminium Tread Hard wearing and durable Reduced risk of slips, trips and falls Added safety

Expamet Tread

Mesh tread construction Easy to keep debris free

Great for use outside



GRP Tread - Available on Request Glass reinforced plastic Extreme grip to surface Added safety

Classic Castor System

Steps fitted with dome with dome covered spring loaded swivel castors which retract when weight is applied to the steps, giving firm contact with the floor. Dome covers have a double rolled bottom edge together with a protective cover strip and grey non marking tyres.



Standard and Optional Safety Features



Hinged Stabilisers For extra stability when working at height.



Safety Warning Bar Deters climbing when steps are in mobile mode.



Security Gate With padlock facility to prevent unauthorised use.



Handlock Anchorage When locked the feet rest firmly on the floor.

British Standard Safety Step Range.



BS EN 131-7:2013 Mobile Ladders with Platform - The standard explained

The following is the key criteria (plus more) to certifying a set of mobile steps to BS EN 131-7:2013. They detail what to look out for when comparing British Standard Safety Steps to others claiming to be 'certified'.

Scope

This European Standard defines the general design characteristics of mobile ladders with platform. It applies to mobile ladders with a working platform, maximum of 1m2, and a maximum platform height of 5000mm, to be used only by one person at a time. The maximum load is 150kg which includes a maximum combined load of the user and any tools, equipment and materials.

EN 131-7:2013 is the only standard that applies to mobile ladders with platform. Parts 1-6 of the EN131 standard, specifically state that they do not apply to mobile ladders.

Ascending Treads

The minimum tread depth is 80mm. The maximum gap between the treads is 50mm. The minimum 1st tread height is 150mm from the ground, the maximum is the tread spacing plus 40mm. The minimum tread spacing is 200mm (after the 1st tread, from surface to surface) and must be constant, the maximum is 250mm.

Ascending treads must also pass torsion and bending tests according to the standard.

Stability

The mobile step must pass a stability test. This test is a side pull where 750N test load is applied to the most unfavourable position on the platform. For indoor use a horizontal pulling force of 300N is applied gradually to the side of the platform in the most unfavourable position and direction. The test is passed if the mobile ladder does not overturn.

Spring Loaded Steps

For steps with spring loaded castors a test load of 200N is applied in turn to each ascending tread and platform. The test requirement is that both feet of the side of the step where the load is applied shall be in contact with the floor during the test.

Marking, User and Safety Instructions

Marking shall be displayed as specified in the standard. These must also pass a durability test and be specific to the individual mobile ladder showing important visual safety pictograms and also manufacturing information.

User instructions shall be provided as specified in the standard. These are supplied with the steps.

Prevention of Falls (Guardrails and Middle Rails)

The minimum handrail height is 950mm. The maximum handrail height is 1100mm. The guardrails and middle rails shall avoid a sphere of 470mm diameter to pass.



Handrails/Guardrails/Middle Rails

The ascending handrail should be positioned so the lowest grab point is a maximum of 1000mm from the ground. Handrails/Guardrails must also pass multiple strength and deflection tests according to the standard.

Working Area Dimensions (enclosed handrail area)

The minimum working area dimensions are 400mm wide x 400mm deep x 950mm high. The maximum working area dimensions are 1000mm wide x 1000mm deep x 1100mm high.

Platform and Toe Board Dimensions

The minimum platform dimensions are 400mm wide x 400mm deep with a 50mm toe board to 3 sides. The maximum platform dimensions are 1000mm wide x 1000mm deep. The platform must also pass multiple strength and deflection tests according to the standard.

Kitemark

These are the only steps of their type (at time of print) to be awarded with the British Standard Kitemark from the BSI. The award of the BSI Kitemark for this range of mobile safety steps demonstrates a new benchmark for quality and reliability in this sector.



KM 608967 BS EN 131-7

British Standard Classic Colour Range

The Classic Colour BS Step Range is ideal for warehouse or office use. They are available with 2, 3, 4 or 5 steps including platform, providing a maximum working height of up to 2.77mm. The steps are available in a range of eight colours.







Tread Clamps

Ribbed rubber treads models are supplied complete with tread clamps ensuring high visibility and preventing edges from peeling.



Platform W x D: 406 x 406mm | Tread width: 460mm

					Order Ref	
Treads (inc platform)	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	Ribbed Rubber treads	Anti-slip treads
2	508	2.00	1460 × 615 × 730	14	S360	S361
3	762	2.26	1715 x 800 x 915	16	S362	S363
4	1016	2.52	1965 × 1000 × 1075	19	S364	S365
5	1270	2.77	2220 x 1200 x 1240	22	S366	S367
Colour Options	GN R B	Y GY S O W				



Mobile Ladders with Platform

KITEMARK™

KM 608967 BS EN 131-7



8

Robust, hardworking narrow aisle units with spring loaded castors. All welded construction. Spring loaded castors allows the feet to lower to the ground under operator's weight. Treads are formed sheet steel with choice of ribbed rubber or anti-slip surface. All colour finishes are hard wearing powder coated.



Complete with hinged stabilisers



Tread Clamps

Ribbed rubber treads models are supplied complete with tread clamps ensuring high visibility and preventing edges from peeling.



Platform W x D: 406 x 406mm | Tread width: 400mm

Steptek

							Order Rei	
Treads (inc platform)	Platform height mm	Average Working Height m	Stabilisers	Width with stabilsers	Overall H x W x D mm (inc rails)	Weight kg	Ribbed Rubber treads	Anti-slip treads
2	500	2.00	No	N/A	1455 x 500 x 640	15	S400	S401
3	750	2.25	Yes	1085	1705 x 500* x 820	20	S402	S403
4	1000	2.50	Yes	1085	1950 x 500* x 1090	24	S404	S405
5	1250	2.75	Yes	1085	2200 x 500* x 1240	28	S406	S407
Colour Options GN R B	Y GY S	5 O W		*With stabilisers retra	acted.			





A SDL

British Standard Narrow Aisle Spring Loaded Steps

British Standard Premier Commercial Steps



As its name suggests, the Premier Commercial BS Steps are built with the most demanding environments in mind. Their robust all welded steel construction and choice of factory fitted tread surfaces offer a highly durable solution. This range also comes complete with hinged stabilisers for extra stability when working at height.



Complete with hinged stabilisers





Tread Clamps

Ribbed rubber treads models are supplied complete with tread clamps ensuring high visibility and preventing edges from peeling.

Order Re



Platform W x D: 560 x 400mm | Tread width: 560mm

Treads (inc platform)	Platform height mm	Average Working Height m	Stabilisers	Width with stabilisers	Overall H x W x D mm (inc rails)	Weight kg	Ribbed Rubber Treads			Aluminium Treads
3	685	2.21	No	N/A	1640 x 640 x 760	27	S410	S412	S411	S413
4	915	2.44	Yes	1250	1870 x 640* x 1055	31	S414	S416	S415	S417
5	1145	2.65	Yes	1250	2100 × 640* × 1155	35	S418	S420	S419	S421
6	1400	2.90	Yes	1250	2355 x 640* x 1315	39	S422	S424	S423	S425

*with stabilisers retracted.





10

British Standard Premier Commercial Steps

British Standard Steptek Quality Red Range

Handbuilt with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation.

Welded steel tube and bar construction with a 560mm tread width. Fitted with handlock anchorage; when locked the front feet rest firmly on the floor, feet fitted with protective plastic floor pads. The outboard axle mounted rear wheels gives extra stability.

Finish: All steelwork red epoxy finish

Wheels: Front 2 swivel castors with 100mm diameter rubber-tyred wheels with roller bearings. Rear 2 axle mounted 200mm diameter wheels with rubber tyres and roller bearings.

Caution Notice: A caution notice is fitted to each set to remind user of operation procedure. A health and safety at work information sheet is supplied.







See page 25 for optional extras.





KM 608967 BS EN 131-7



Handlock Anchorage When locked the feet rest firmly on the floor.

Platform W x D: 560 x 400mm | Tread width: 560mm

Number of treads inc platform	Platform height mm	Average working height m	Overall dimension (H x W x D) mm	Weight Kg	R/Rubber Treads Order Ref	Weight Kg	Punched Treads Order Ref	Weight Kg	Anti Slip Treads Order Ref	Weight Kg	Aluminium Treads Order Ref
3	750	2.25	1710 x 860 x 860	48	S310	46	S314	48	S318	49	S322
4	1000	2.50	1960 x 905 x 1040	50	S311	48	S315	50	S319	51	S323
5	1250	2.75	2210 x 950 x 1220	53	S130	51	S140	53	S150	54	S160
6	1500	3.00	2460 x 995 x 1400	58	S131	56	S141	58	S151	60	S161
7	1750	3.25	2710 x 1040 x 1580	63	S132	61	S142	63	S152	65	S162
8	2000	3.50	2960 x 1085 x 1760	70	S133	68	S143	70	S153	73	S163
9	2250	3.75	3210 × 1130 × 1940	76	S134	73	S144	76	S154	78	S164
10*	2500	4.00	3460 x 1175 x 2200	89	S135	85	S145	89	S155	92	S165
11*	2750	4.25	3710 x 1220 x 2380	98	S136	94	S146	98	S156	101	S166
12*	3000	4.50	3960 x 1265 x 2560	110	S137	106	S147	110	S157	113	S167
13*	3250	4.75	4210 × 1310 × 2740	117	S138	112	S148	117	S158	121	S168
14*	3500	5.00	4460 x 1355 x 2920	124	S139	120	S149	124	S159	127	S169
15*	3750	5.25	4710 x 1400 x 3100	160	S312	158	S316	160	S320	161	S324
16*	4000	5.50	4960 x 1450 x 3280	169	S313	167	S317	169	S321	170	S325
*10 tread and a			for transport purposes.								

Refer to page 25 for optional extras

Steptek







British Standard Steptek Quality Red Range

British Standard Steptek Quality Extra Heavy Duty Narrow Base Model

Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation. Over load tested to 200kg.

Construction: Welded heavy gauge steel box section and bar. Fitted with hand lock lever anchorage; when locked, the front feet rest firmly on the floor, feet fitted with protective grey nonmarking rubber feet. Safety warning bar fitted to protrude in front of steps, linked to hand lock lever mechanism, to deter users from climbing steps when still in 'mobile' mode.

Narrow base model: Outboard wheels mounted on straight base frame for optimum space saving requirements. Finish: Main structure blue epoxy finish; safety bar and hand lever mechanism in safety yellow.

Wheels: Front 2 swivel castors with 100mm diameter rubber tyred wheels, with roller bearings. 2 rear axle mounted 200mm diameter wheels with rubber tyres and roller bearings.

A caution notice is fitted to remind user of operation procedure. A health and Safety at Work information sheet is supplied.





See page 25 for optional extras.





Platform W x D: 540 x 500mm | Tread width: 490mm

Number of treads Including platform	Platform height mm	Average working height m	Overall dimension (H x W x D) mm	Weight Kg	R/Rubber Treads Order Ref	Weight Kg	Expamet Treads Order Ref
3	690	2.19	1690 x 700 x 930	51	S960	43	S980
4	920	2.42	1920 x 700 x 1140	59	S961	51	S981
5	1150	2.65	2150 x 700 x 1240	69	S962	57	S982
6	1380	2.88	2380 x 700 x 1410	88	S963	76	S983
7	1610	3.11	2610 x 700 x 1570	97	S964	84	S984
8	1840	3.34	2840 x 700 x 1740	107	S965	94	S985
9	2070	3.57	3070 x 700 x 1900	117	S966	104	S986
10*	2300	3.80	3300 x 900 x 2060	131	S967	119	S987
11*	2530	4.03	3530 x 900 x 2230	140	S968	127	S988
12*	2760	4.26	3760 x 900 x 2400	151	S969	138	S989
13*	2990	4.49	3990 x 1230 x 2560	163	S970	148	S990
14*	3220	4.72	4220 x 1230 x 2730	175	S971	160	S991
15*	3450	4.95	4450 x 1230 x 2890	187	S972	172	S992

*10 tread and above supplied in 2 halves for transport purposes. Refer to page 25 for optional extras





BS Steptek Quality Extra Heavy Duty Range

BS Steptek Quality Extra Heavy Duty Range

British Standard Steptek Quality Extra Heavy Duty Stability Base Model

Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation. Over load tested to 200kg.

Construction: Welded heavy gauge steel box section and bar. Fitted with hand lock lever anchorage; when locked, the front feet rest firmly on the floor, feet fitted with protective grey nonmarking rubber feet. Safety warning bar fitted to protrude in front of steps, linked to hand lock lever mechanism, to deter users from climbing steps when still in 'mobile' mode.

Stability base model: Outboard wheels mounted on splayed base frame gives superior stability. Finish: Main structure red epoxy finish; safety bar and hand lever mechanism in safety yellow.

Wheels: Front 2 swivel castors with 100mm diameter rubber tyred wheels, with roller bearings. 2 rear axle mounted 200mm diameter wheels with rubber tyres and roller bearings.

A caution notice is fitted to remind user of operation procedure. A health and Safety at Work information sheet is supplied.







See page 25 for optional extras.





Platform W x D: 540 x 500mm | Tread width: 490mm

Number of treads Including platform	Platform height mm	Average working height m	Overall dimension (H x W x D) mm	Weight Kg	R/Rubber Treads Order Ref	Weight Kg	Expamet Treads Order Ref
3	690	2.19	1690 x 780 x 955	56	S920	48	S940
4	920	2.42	1920 x 850 x 1120	64	S921	56	S941
5	1150	2.65	2150 x 910 x 1290	74	S922	62	S942
6	1380	2.88	2380 x 960 x 1425	93	S923	81	S943
7	1610	3.11	2610 x 1010 x 1610	102	S924	89	S944
8	1840	3.34	2840 x 1060 x 1790	112	S925	99	S945
9	2070	3.57	3070 x 1140 x 1955	122	S926	109	S946
10*	2300	3.80	3300 x 1220 x 2130	136	S927	124	S947
11*	2530	4.03	3530 x 1270 x 2290	145	S928	132	S948
12*	2760	4.26	3760 x 1270 x 2400	157	S929	143	S949
13*	2990	4.49	3990 x 1370 x 2560	168	S930	153	S950
14*	3220	4.72	4220 x 1540 x 2730	180	S931	165	S951
15*	3450	4.95	4450 x 1565 x 2890	192	S932	177	S952

*10 tread and above supplied in 2 halves for transport purposes. Refer to page 25 for optional extras





Steptek



British Standard Tilt and Go Steps

Welded steel tube and bar construction. Expamet treads and large working top platform makes them ideal for loading and unloading items outside. The steps have 2 handles at the front fitted with knuckle guard hand grips for safe lifting and moving.

Wheels: 2 rear 200mm steel centred wheels with rubber tyres and roller bearings.



Option Inward opening gate on platform end*. Ref: S700 (Extra).



Expamet

Platform W x D: 500 x 600mm | Tread width 500mm

No. of Treads	Platform height	Average working height	Overall (H x W x D)	Blue Expa	amet	*Galvanis	ed Expamet
(inc platform)	mm	m	mm	Wt. Kg	Order Ref	Wt. Kg	Order Ref
3	750	2.25	1760 x 650 x 1345	36	S701	36	S711
4	1000	2.50	2010 x 850 x 1535	41	S702	41	S712
5	1250	2.75	2260 x 1050 x 1725	46	S703	46	S713
6	1500	3.00	2510 x 1250 x 1915	51	S704	51	S714

*Galvanised steps are made to order non-returnable



*7 & 8 tread versions have bolt on handles for transport purposes.

**Galvanised steps are made to order non-returnable

Easy Rise Steps with Truck/Dock Platform

48 degree slope for extra safety and comfort, designed to allow user to descend the steps facing forward. Large platform with removable chain on end and both sides for 3-sided access. Welded steel tube and bar construction. Fitted with handlock anchorage.

Front feet fitted with protective plastic floor pads. Expamet treads and large working top platform makes them ideal for loading and unloading items outside.

Wheels: 2 front swivel castors with 100mm diameter rubber tyred wheels with roller bearings, 2 rear axle-mounted 200mm wheels with rubber tyres and roller bearings.

Finish: All steelwork red epoxy or galvanised finish**.

Platform W x D: 750 x 1200mm | Tread width 750mm

No. of Treads	Platform height	Average working	Overall (H x W x D)	Red Expar	net	**Galv Expar	ranised net
(inc platform)	mm	height m	mm	Wt. Kg	Order Ref	Wt. Kg	Order Ref
3	690	2.19	1680 x 960 x 1680	80	S680	80	S690
4	920	2.42	1910 × 960 × 1870	89	S681	89	S691
5	1150	2.65	2140 x 960 x 2060	98	S682	98	S692
6	1380	2.88	2370 x 960 x 2250	107	S683	107	S693
7*	1610	3.11	2600 x 960 x 2440	116	S684	N/A	N/A
8*	1840	3.34	2830 x 960 x 2630	125	S685	N/A	N/A



14

Step Ladders

- Foldable for easier storage
- Working load 150kg
- Distance between treads 230mm
- Fitted with a rubber comfort handle
- Non-slip treads
- Powder coated finish in silver / grey



Treads (inc platform)	Tread W x D mm	Platform height mm	Open size H x W x D mm	Folding size $H \times W \times D$ mm	Order Ref
2		490	775 x 485 x 510	890 x 135 x 485	BSL-2
3	380 x 260	710	1065 x 490 x 665	1220 × 140 × 490	BSL-3
4		930	1290 x 490 x 830	1475 x 145 x 490	BSL-4

Round Step

Steel Kicksteps

Simple round step for convenient access and hands-free movement.
Moulded from high density polypropylene for good durability with an
'Arched' design for extra strength. The heavy duty rubber bumper around
base provides ultimate grip when weight is applied and the anti-slip
moulded plastic to both treads. Easily manoeuvred, mounted on 3
spring-loaded castors which retract when weight is applied.

Height mm		Diameter mm	Order Ref
410		440	RSK-1
Colour Options	P F	BK GY	







Premium GS approved quality mobile step finished in a choice of colours.

Provides easy step up access preventing excess stretching, supplied in two sections that permanently lock together via a built in bolt-free mechanism.

Mounted on retractable spring mounted castors, can be easily moved into position without bending or lifting and when stepped on locks into position allowing safe access. Sturdy steel construction with anti slip rubber treads provide a solid platform from which to work.

Designed to conform to BS EN 14183

Steptek

Over height mm	Diameter (top)mm	Diameter (base)mm	Order Ref	
400	260	430	RSK-2	
Colour Options	R B BK			







Robust Coloured Portable Steps

Framework manufactured from ERW mild steel tube with formed sheet steel treads, fitted with ribbed rubber to surface. GNM rubber feet for extra grip and floor protection, epoxy coated finish in a choice of 4 colours.





Post / Handrail	Tread W x D mm	Platform height mm	OverallHxWxDmm	Weight kg	Order Ref
No handrail		250	250 x 415 x 280	4	S750
With post rail		250	1160 x 415 x 280	5	S751
No handrail	355 x 215	500	500 × 415 × 590	5	S752
With post rail			1160 x 415 x 590	6	S753
With handrail			1160 x 415 x 590	7	S754
	No handrail With post rail No handrail With post rail	No handrail With post rail No handrail With post rail With handrail	No handrail 250 With post rail 355 x 215 With post rail 500 With handrail 500	No handrail 250 x 415 x 280 With post rail 355 x 215 250 x 415 x 280 No handrail 355 x 215 500 x 415 x 590 With post rail 500 x 415 x 590 1160 x 415 x 590 With handrail 1160 x 415 x 590 1160 x 415 x 590	No handrail 250 x 415 x 280 4 With post rail 355 x 215 1160 x 415 x 280 5 With post rail 355 x 215 500 x 415 x 590 5 With post rail 355 x 215 1160 x 415 x 590 6 With post rail 1160 x 415 x 590 7



Wheelalong Two Step with Grab Handle

Stable to use and easy to move. Ideal moveable access steps for industry, offices, libraries and hospitals etc. Finished in a choice of four powder coated colours.

Treads (inc platform)	Tread W x D mm	Platform height mm	Overall H x W x D mm	Weight kg	R/Rubber treads Order Ref	Anti-slip treads Order Ref
2	355 x 215	385	1030 x 500 x 355	8	S230	S240
Colour Options R	B Y GY					

16

Portable Steps

Wheelalong Two, Three and Four Steps



Static steps which are fitted with 2 x 75mm diameter wheels to the rear frame. When steps are tilted, wheels allow easy movement to next location. Powder coated finish

Fitted with 75mm wheels with grey non marking rubber tyres.

Treads (inc platform)	Platform height mm	Overall H x W x D mm	Weight kg	R/Rubber treads Order Ref	Anti-slip treads Order Ref
2	510	1025 x 455 x 605	7	S028	S241
3	762	1310 x 455 x 785	10	S029	S242
4	1020	1700 x 590 x 1030	14	S243	S244

Colour Options R B Y GY

S243/B S029/R S028/Y

Single Sided Mobile 2 Step

Single sided units without handrail, single grab handle, or twin side handrails and cross bar. Crossbar accepts optional accessories - hook-on basket or tray.

Accessories

(Only suitable for S248/S251)

Hook-on wire basket Ref: S015 Load capacity 3 kg L x W x D: $350 \times 220 \times 220$ mm



Hook-on tray unit - **Ref: S250** (load capacity 3 kg) L x W x D: 415 x 260 x 40mm



The steps should not be moved with loaded basket in place.



Castor

System

Max Load

125ka

Made in

Britain

Platform W x D: 380 x 180mm | Tread width: 380mm

Steptek

Treads (inc platform)	Handrail	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	R/Rubber treads Order Ref	Anti-slip treads Order Ref
2	Without handrail	508	2	610 x 530 x 540	8	S001	S002
2	With 1 handrail	508	2	1185 x 530 x 540	10	S003	S004
2	With 2 handrails	508	2	1185 x 530 x 540	12	S248	S251
Colour Options	GN R	B Y GY	S O W				



Wheelalong Steps



Stainless steel mobile step units with close fitting handrail round three sides of platform.

High quality range of mobile step units, manufactured from formed tube and sheet stainless steel of quality particularly suitable for food drink and chemical industries. Fully welded throughout for maximum rigidity. All step units fitted with 4 x 80mm diameter spring loaded castors with grey non marking rubber tyres fitted in heavy zinc plated housing which retract when weight is applied to the steps, giving firm contact with the floor.



Anti-slip tread surfaces.

Each unit is fitted with four grey non marking rubber feet. Stainless steel treads covered with anti-slip surface which is both hard wearing and resistant to water, oil and most chemicals.

Please note:

Steps are not a polished finished.

Steps are not designed for clean rooms as they have an anti-slip tread surface - punched tread option available upon request.

Steptek

凮

Platform W x D: 380 x 280mm | Tread width: 380mm

Treads (inc platform)	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	Order Ref
3	765	2.26	1425 x 790 x 710	14	S215
4	1016	2.52	1683 x 790 x 885	17	S216
5	1270	2.77	1940 x 790 x 1140	20	S217

18

Classic Colour Range

Classic Colour Range

The markets leading step range.

Castor Max Load System 125kg



Close fitting continuous single rail guard around top platform, extending down each side of stairway as a short handrail. All Classic models are fully welded throughout and available with ribbed rubber or anti-slip treads. All colour finishes are hard-wearing powder coated.



Accessories



Hook-on wire basket **Ref: S015** Load capacity 3 kg L x W x D: 350 x 220 x 220mm



Hook-on tray unit Ref: S250 Load capacity 3 kg L x W x D: 415 x 260 x 40mm

(Steps should not be moved with loaded basket in place.)

Steptek

Platform W x D: 380 x 280mm | Tread width: 380mm

					Order Ret	
Treads (inc platform)	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	Ribbed Rubber treads	Anit-slip treads
2	508	2.00	1185 x 580 x 615	12	S005	S006
3	762	2.26	1425 × 580 × 795	14	S009	S010
4	1016	2.52	1683 x 580 x 955	17	S011	S012
5	1270	2.77	1940 x 580 x 1120	20	S013	S014
Colour Options	GN R B	Y GY S O W				



Classic Colour Range

Classic Colour Range

Classic Plus Colour Range

All models have larger top platform W x D:400 x 380mm. The double rail platform guarding 4 and 5 steps have long handrails on both sides of stairway.





SZEGY SZEGY

Tread Clamps

Ribbed rubber treads models are supplied complete with tread clamps ensuring high visibility and preventing edges from peeling.

Accessories



Hook-on wire basket **Ref: S015** Load capacity 3 kg L x W x D: 350 x 220 x 220mm



P

Hook-on tray unit **Ref: S250** Load capacity 3 kg L x W x D: 415 x 260 x 40mm

Order Ref



Platform W x D: 406 x 380mm | Tread width: 406mm

	Olderhei												
Treads (inc platform)	Platform height mr	n	Averaç height		king	Handr	ails	Overa H x W	all ' x D mm (inc rails)	Weight kg	Ribbed Rubber treads		Anti-slip treads
2	508		2.00			none		570 x	565 x 650	7	S218	S349	S219
2	508		2.00			single		1175 x	565 x 650	9	S220	S350	S225
2	508		2.00			full		1175 x	565 x 650	11	S221	S351	S226
3	762		2.26			full		1430 :	x 565 x 790	14	S222	S352	S227
4	1016		2.52			full		1680	x 565 x 1005	17	S223	S353	S228
5	1270		2.77			full		1935 :	x 565 x 1225	20	S224	S354	S229
Colour Options		GN	R	В	Y		S	0	W				



Classic Colour Range SDL TEL:0144677

Narrow Aisle Spring Loaded Steps

Robust, hardworking narrow aisle units with spring loaded castors. All welded construction. Spring loaded castors allows the feet to lower to the ground under operator's weight. Treads are formed sheet steel with choice of ribbed rubber or anti-slip surface. All colour finishes are hard wearing powder coated.



Narrow Aisle Spring Loaded Steps



Platform W x D: 395 x 395mm | Tread width: 395mm

GN R

Steptek

					Order Ref	
Treads (inc platform)	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	Ribbed Rubber treads	Anti-slip treads
2	500	2.00	1300 x 500 x 600	13	S301	S302
3	750	2.25	1550 x 500 x 780	18	S303	S304
4	1000	2.50	1800 x 500 x 1050	22	S305	S306
5	1250	2.75	2050 x 500 x 1200	26	S307	S308

B Y GY S O W

Colour Option:



Narrow Aisle Spring Loaded Steps

. . . .

Premier Commercial Steps

Robust, hardworking narrow aisle units with spring loaded castors. All welded construction. Spring loaded castors allows the feet to lower to the ground under operator's weight. Treads are formed sheet steel with choice of ribbed rubber or anti-slip surface. All colour finishes are hard wearing powder coated.





Platform W x D: 560 x 340mm | Tread width: 560mm

Treads (inc platform)	Platform height mm	Average working height m	Overall H x W x D mm (inc rails)	Weight kg	R/Rubber treads	
3	685	2.21	1530 x 640 x 695	24	S040	S041
4	915	2.44	1760 x 640 x 850	28	S044	S045
5	1145	2.65	1985 x 640 x 1000	32	S048	S049
6	1400	2.90	2230 x 640 x 1170	36	S260	S261







22 Premier Commercial Steps

SDL

Steptek Economy Step Range

Steptek Economy Step Range

Welded tubular construction, fitted with anti-ascent pull through bar which locks in mobile position onto tread via hook mechanism. Moves fully through tread when in static postion allowing castors to retract. Grey non-marking feet to front legs. Mounted on 2 \times 200mm fixed solid rubber tyred wheels and $2\,\times\,75\text{mm}$ grey non-marking swivel castors (castors retract with lever) choice of anti-slip or punched treads.

Finish: light grey epoxy/yellow anti-ascent bar.

Anti-ascent pull through bar



Tread options:







Punched

Platform size: 560 x 400mm | Tread width: 560mm

Number of treads inc platform	Platform height mm	Average working height m	Overall dimension (H x W x D) mm	Weight kg	Anti Slip Treads Order Ref	Punched Treads Order Ref
4	1000	2.50	2000 x 905 x 965	41	S804	S814
5	1250	2.75	2250 x 950 x 1120	46	S805	S815
6	1500	3.00	2500 x 995 x 1275	51	S806	S816
7	1750	3.25	2750 x 1040 x 1430	56	S807	S817
8	2000	3.50	3000 x 1085 x 1585	61	S808	S818
9	2250	3.75	3250 x 1130 x 1740	66	S809	S819
10	2500	4.00	3500 x 1175 x 1895	71	S810	S820
11	2750	4.25	2750 x 1220 x 2050	76	S811	S821
12	3000	4.50	4000 x 1265 x 2205	81	S812	S822
13	3250	4.75	4250 x 1310 x 2360	86	S813	S823





Made in

Britain



for optional extras.

A SDL

Steptek

Steptek Economy Step Range

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Mobile Steps with Handlock Anchorage

Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation.

All steelwork blue epoxy finish. Wheels: Front swivel and rear fixed castors with 100mm diameter white nylon wheels and roller bearings. All models fitted with hand lock anchorage. When locked the front feet rest firmly on the floor; fitted with protective plastic floor pads.





Anti-slip



Expamet



Punched Steel





Designed to conform to BS EN 131-7

See page 25 for optional extras.





Retracting Castors fitted as standard.

Platform W x D 610 x 400mm | Tread width 610mm

Number of treads inc platform	Platform height mm	Average working height m	Overall dimension (H x W x D) mm	Wt. Kg	Ribbed Rubber Treads Order Ref	Wt. Kg	Expamet Treads Order Ref	Wt. Kg	Anti Slip Treads Order Ref	Wt. Kg	Punched Treads Order Ref
4	915	2.40	1875 x 710 x 1035	45	S052	45	S061	45	S070	43	S079
5	1145	2.70	2105 x 710 x 1210	50	S053	50	S062	50	S071	48	S080
6	1370	2.90	2330 x 710 x 1385	56	S054	56	S063	56	S072	53	S081
7	1600	3.10	2560 x 710 x 1650	65	S055	65	S064	65	S073	62	S082
8	1830	3.40	2790 x 710 x 1865	70	S056	70	S065	70	S074	67	S083
9	2060	3.60	3020 x 710 x 1995	76	S057	76	S066	76	S075	73	S084
10*	2285	3.80	3245 x 710 x 2175	88	S058	88	S067	88	S076	84	S085
11*	2515	4.00	3475 x 710 x 2350	96	S059	96	S068	96	S077	91	S086
12*	2745	4.30	3705 x 710 x 2530	104	S060	104	S069	104	S078	99	S087

*10 tread and above supplied in 2 halves for transport purposes. Refer to page 25 for optional extras



Handlock Anchorage

24 Handlock Anchorage

SDL

Optional Extras for Warehouse Steps

Platform Gate to End



Platform Gate to Side



Double Hinged Bar to End



Doubled Hinged Bar to Side



Double Hinged Bar to Front





Inward opening spring loaded gate secured with spring loaded plunge bolt. Fitted to the end of the platform. Platform depth increases to 760mm.

Ref: **S175E**



Gate to left hand side of platform. Ref: S175L

Gate to right hand side of platform. Ref: S175R

Double hinged bar fitted to end of platform.

Double hinged bar fitted to the

increases to 760mm.

Ref: S176L

Ref: S176R

side of the platform. Platform depth

Gate to left hand side of platform.

Gate to right hand side of platform.

Ref: S176E

Platform Chain to Front



Double chain fitted to front of platform, secured by locking spring clip. Secures user onto platform. Platform depth increases to 760mm.

Ref: **S179**

Platform Chain to Side



Double chain fitted to the side of the platform, secured by locking spring clip. Increases platform depth to 760mm.

Chain to left hand side of platform.

Ref: S178L

Chain to right hand side of platform. Ref: S178R

Platform Chain to End



Double chain fitted to end of platform, secured by locking spring clip.

Ref: **S178E**

Security Gate



Hinged security gate fitted to bottom of steps with padlock facility. Stops unauthorised users using the steps. Folds through 270 degrees.

Ref: S170

Hook on Tool Tray



Dimensions: (L x W x D) 600mm x 250mm x 220mm Load capacity: 5kg

Ref: **S089**

Hook on Wire Basket



Dimensions: (L x W x D) 600mm x 220mm x 220mm Load capacity: 5kg Ref: 5088

Note: Optional extras are factory fitted and are non-returnable.



SDL

Optional Extras for Warehouse Steps

25

Step Tray Trolleys

Step Tray Trolleys - 3 Step

Ideal for stock picking and putting away in stores, warehouse, office, library etc.

Spring loaded step unit, with ribbed rubber treads, locates firmly on floor when foot placed on first step, immobilising trolley. Top tread height 686mm. Fully welded construction, from RSA angle and ERW tube. Rubber feet fitted to step unit. Blue epoxy finish.

Tray options (For medium or heavy duty trolleys):

Fixed sheet steel trays - with 20mm lip all round, blue epoxy finish.
Fixed plywood shelves - recessed with 10mm lip all round.
Removable steel trays - reversible to give either a flush finish, or 25mm lip all round, white powder coated finish.
Removable wire baskets - 160mm high sides,

white powder coated finish.

Medium Duty - 125kg total load capacity 2 and 3 tray

Heavy Duty - 175kg total load capacity 2 and 3 tray

Heavy Duty Castors: 2 swivel and 2 fixed castors with 125mm diameter rubber tyred wheels with roller bearings.



Made in Britain





Medium Duty Castors: 4 stem fitting swivel castors with 125mm diameter wheels with grey non marking tyres and thread guards.



Tray Type	Duty	Cap.	No. of	Tray He	ights mm		Usable	Overall	Wt.	Ref	Reversible
		Kg	Tiers	Тор	Middle	Bottom	WxLmm	H x W x L mm	Kg		steel trays
Fixed blue	Medium	125	2	920	-	310	465 x 780	1150 x 495 x 1325	33	S180	
trays		125	3	920	615	310	465 x 780	1150 x 495 x 1325	40	S181	
	Heavy	175	2	955	-	180	465 x 780	1070 x 475 x 1325	36	S188	
		175	3	955	570	180	465 x 780	1070 x 475 x 1325	43	S189	
Fixed ply-	Medium	125	2	920	-	310	465 x 780	1150 x 495 x 1325	30	S182	
wood shelf		125	3	920	615	310	465 x 780	1150 x 495 x 1325	35	S183	
	Heavy	175	2	955	-	180	465 x 780	1070 x 475 x 1325	33	S191	
		175	3	955	570	180	465 x 780	1070 x 475 x 1325	38	S192	Removable
Reversible	Medium	125	2	920	-	310	455 x 770	1150 x 495 x 1325	34	S184	wire baskets
white trays		125	3	920	615	310	455 x 770	1150 x 495 x 1325	42	S185	
	Heavy	175	2	955	-	180	455 x 770	1070 x 475 x 1325	38	S194	
		175	3	955	570	180	455 x 770	1070 x 475 x 1325	46	S195	
Removable	Medium	125	2	1060	-	450	450 x 755	1150 x 495 x 1325	31	S186	
baskets		125	3	1060	755	450	450 x 755	1150 x 495 x 1325	37	S187	
	Heavy	175	2	1095*	-	320*	450 x 755	1095 x 475 x 1325	33	S197	STATISTICS OF STATISTICS
		175	3	1095*	710*	320*	450 x 755	1095 x 475 x 1325	39	S198	and the second second

* Dimension to top of basket. Recommended working height with Steptek models is 1.5m from top tread



Step Tray Trolleys

Heavy Duty Step Tray Trolleys - 5 Steps

3 tray tiers - 5 steps. Top tread height 1145mm. Fitted with 2 retractable castors in front and 2 fixed castors to rear, each with 125mm rubber tyred wheels and roller bearings. Operation: Front castors retract with hand operated lever to immobilise trolley.

Steps

Fixed steps, handrail fitted to each side and across top. Construction: Fully welded from RSA angle and ERW tube. Finish: Blue epoxy

Tray options:

Fixed sheet steel trays - with 20mm lip all round, blue epoxy finish.

Fixed plywood shelves - recessed with 10 mm lip all round. **Removable steel trays** - reversible to give either a flush finish, or 25mm lip all round, white powder coated finish.

Removable wire baskets - 160mm high sides,

white powder coated finish.





Tray heights mm

650

650

650

785*

Middle Bottom

185

185

185

320*

Тор

1115

1115

1115

1245*



Reversible steel trays

Removable wire baskets



*Dimension to top of basket. Maximum recommended step load is 125kg (operator and goods carried) Trolley capacities as stated.

Usable

WxLmm

525 x 935

525 x 935

510 x 920

Overall

500 x 905 2075 x 620 x 1730

 $\mathsf{H} \, {\mathsf x} \, \mathsf{W} \, {\mathsf x} \, \mathsf{L} \, \mathsf{mm}$

2075 x 620 x 1730

2075 x 620 x 1730

2075 x 620 x 1730



Tray type

Fixed blue trays

Fixed ply shelves

Reversible white trays

Removable baskets

Steptek

Step Tray Trolleys

27

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Wt.

Kg

67

61

71



A RANGE OF PRODUCTS WELL BUILT IN BRITAIN FOR MATERIAL HANDLING

RAJA



Loadtek

Loadtek products are built to vigorous standards for many years of relentless use.

The product ranges come with a choice of materials, styles, sizes and colours. Additional specification is available to modify your choice of product including handle, wheel, bumper and brake options for the majority of the ranges.

Covering an extensive range of lifting and moving tasks, Loadtek products are built to solve all your handling problems.



Choosing the right product



Weight to be transported

It is important to understand the weight being transported when choosing the correct product.



Size to be transported

The Loadtek product range has been built through years of innovation and metal manufacturing expertise.



Wheel type

Understanding the environment your product is going to be commonly used will help you choose the right wheel.

Usage guide

0-150kg - Light Duty 150-300kg - Medium Duty 300kg+ - Heavy Duty

Developed with the needs of industry at the forefront of our thinking, we have developed a comprehensive range of products to handle all shapes and size of items.

Wheel Options

Pneumatic - Ideal for rough or uneven terrain Solid - Long lasting and smooth running Foam Filled - Puncture proof and long lasting

Utility Tray Trolleys



A unique range of robust tray trolleys designed for most environments, including warehouses, garages, catering, serving and general everyday use. The specially formed aluminium uprights and ribbed plastic shelves provide strength, durability and stability. Fitted with 100mm diameter thermoplastic swivel rubber castors (2 braked).



30

Description	Overall H x W x D mm	Platform Size W x D mm	Wheel dia mm	Capacity kg	Order Ref
Standard - 2 Shelves	940 x 460 x 750	424 × 630		100	TT40
Large - 2 Shelves	ves 970 x 513 x 990 500 x 86		100	120	TT41
Standard - 3 Shelves	980 x 460 x 750	424 × 630	100	150	TT42
Large - 3 Shelves	1010 x 513 x 990 500 x 866			200	TT43

Folding Flatbed Trolleys

A sturdy range of highly manoeuvrable steel trolleys suitable for transporting various goods. Ideal for indoor and outdoor use.

- Folds flat for compact storage
- Non-slip rubber platforms and scuff resistant corners
- Non-marking wheels (2 fixed and 2 swivel)
- Powder coated steel handles





Description	$Overall\ H\ x\ W\ x\ D\ mm$	Folded Height mm	Wheel dia mm	Capacity kg	Order Ref
Standard Folding Flatbed	810 x 470 x 730	230	100	150	TT44
Large Folding Flatbed	870 x 608 x 907	285	125	300	TT45

30 Tray Trolleys

Low Cost Tray Trolleys

KG	
Max Load	Made in
150kg	Britain

2 or 3 fixed steel trays. Fully welded construction. Fixed steel trays with smooth folded lips. Trays are welded in position at specified heights.

Wheels: 4 swivel castors with 125mm diameter. grey non-marking tyres with thread guards. Powder coated finish.





Description (Overall H x W x D mm	Platform Size W ${\rm xD}$ mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
2 Shelves 8	840 x 465 x 890	457 x 762	190, 840	105	19	ТТ70
3 Shelves 8	840 x 465 x 890	457 x 762	190, 515, 840	125	23	TT71





TT350 Series

Special heavyweight tray trolleys custom built to your specification if required.

Strong construction from square and round section steel tubes and steel shelves with lip.

Wheels: 2 fixed and 2 swivel castors with 200mm diameter red centred wheels fitted with solid rubber tyres and roller bearings.

Finish: Blue epoxy



Description	Overall H x W x D mm	Platform Size W x D mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
3 Shelves	900 x 500 x 1090	F00000	280, 590, 900	200	58	TT34
	1200 × 500 × 1090	500 × 900	280, 740, 1200	200	56	TT35

Optional extra

Total stop brakes - Ref: B013 (pair)





Tray Trolleys

Choice of elegant and smart removable and reversible white or blue trays in blue frame, or fixed ply shelves. Tough durable epoxy finish throughout.

Choice of 2 or 3 removable steel trays or fixed ply shelves. Removable and reversible steel trays for flush or recessed fitting. Welded tube and angle construction.

Wheels: 125mm diameter stem fitting castors. Grey non marking tyres with thread guards.





TT62





TT63

TT77





TT65



TT61

Description	Overall Height mm	Platform Size L x W mm	Shelf Heights mm	Wheel dia mm	Wt kg	TTW Series White epoxy trays Order Ref	Wt kg	TTB Series Blue epoxy trays Order Ref	Wt Kg	TT60 Series Fixed Ply trays Order Ref
2 Shelves	1065	760 x 457	245, 945		25	TT62	25	TT72	20	ТТ60
2 Shelves	1065	1065 x 610	245, 945	125	38	ТТ66	38	TT76	31	TT64
3 Shelves	1065	760 x 457	245, 595, 945	125	34	ТТ63	34	ТТ73	27	TT61
3 Shelves	1065	1065 x 610	245, 595, 945		52	ТТ77	52	ТТ65	41	TT67

Optional extras

Revolving Protector Buffers to protect walls and trolley. Factory fitted Ref: B171 (set)



Total Stop Brakes always recommended Ref: B047 (pair)



Pneumatic Tyres complete set of 4 Ref: **B009**



<u>j</u>D

Loadtek



32

32

Tray Trolleys SDL

TT37B

Industrial Tray Trolleys

2 or 3 tray in varnished ply timber panel or sheet steel trays. Tough, high capacity industrial design with heavy duty, fully welded angle and tube construction.

Highly suited to industrial use in stores, workshops and factories. Finish: Blue or red epoxy.

Wheels: Plate fixing castors with 160mm diameter rubber tyred wheels.Roller bearings, 2 swivel and 2 fixed.

TT36R



TT37R















TT39R

Timber Shelves: 10mm raised edge Steel Shelves: 20mm raised edge

2 Timber Shelves 3 Timber Shelves 260,950 40 TT36 3 Timber Shelves 260,605,950 45 TT37 2 Steel Shelves 260,605,950 50 TT38 3 Steel Shelves 260,605,950 57 TT39	Description	Overall H x W x D mm	Platform Size W x D mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
2 Steel Shelves 1045 x 615 x 1070 600 x 1000 160 50 TT38	2 Timber Shelves			260, 950		40	ТТЗ6
2 Steel Shelves 260, 950 50 TT38	3 Timber Shelves	10.45 015 1070	C00 ·· 1000	260, 605, 950	100	45	ТТ37
3 Steel Shelves 260, 605, 950 57 TT39	2 Steel Shelves	1045 x 615 x 1070	600 X 1000	260, 950	100	50	ТТ38
	3 Steel Shelves			260, 605, 950		57	TT39

Loadtek



Optional extras







Ideal truck series for tough work in stores, warehouses, factories and workshops.

Welded steel construction throughout with a choice of timber or steel decks. Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors 200mm diameter rubber tyred wheels.

Recessed Deck Option

Recessed top and bottom decks optional at no extra cost. Add suffix RD to chosen Ref.





Description	Overall	Platform Size	Shelf Heights	Wheel	Timber Deck		Steel Deck		Stainless Steel Deck	
	H x W x D mm	W x D mm	mm	dia mm	Wt kg	Order Ref	Wt kg	Order Ref	Wt kg	Order Ref
Top Shelf Only	895 x 620 x 1135	600 x 1000	895		42	TT205T	40	TT205S	-	-
Top & Bottom Shelf	895 x 620 x 1135	600 x 1000	275, 895		52	TT200T	48	TT200S	50	SP606S
Top Shelf Only	895 x 720 x 1135	700 x 1000	895	200	46	TT230T	44	TT230S	-	-
Top & Bottom Shelf	895 x 720 x 1135	700 x 1000	275, 895	200	56	TT210T	52	TT210S	-	-
Top Shelf Only	895 x 820 x 1135	800 x 1000	895		53	TT240T	50	TT240S	-	-
Top & Bottom Shelf	895 x 820 x 1135	800 x 1000	275, 895		66	TT220T	64	TT240S	-	-

Optional extras

Protective bumper strips (factory fitted): Deck size 1000 x 600mm - **Ref: BS1** Deck size 1000 x 700mm - **Ref: BS2** Deck size 1200 x 800mm - **Ref: BS3**



Total stop brakes Ref: B013 (pair)



Total stop brakes -**Ref: B229 (pair)** for SP606S only

<u>j</u>



_oadtek

34

Table Trucks SDL TEL:014467

Workshop Trolleys

 \mathbf{N}

Made in

Britain

кg

Max Load **150kg**

TT168



Welded tubular and flat steel chassis frame. All plywood shelves are fixed, polyurethane coated with hardwood edge and have 20mm upstand. Steel shelves have 25mm upstand. All steelwork is finished in blue epoxy.

Cupboards and drawers supplied with lock and 2 keys.

Wheels: Standard design 2 swivel and 2 fixed 160mm diameter rubber tyres.





Drawer Size H x W x D mm: 95 x 500 x 460 Cupboard Size H x W x Dmm: 485 x 500 x 600

Description	OverallHxWxDmm	Platform Size W \times D mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
2 Steel Shelves			285, 805		37	TT168
2 Plywood Shelves			285,805	160	30	TT160
3 Plywood Shelves	1045 620 1160	600 × 1000	285, 545, 805		37	TT161
1 Shelf 2 x Half Shelves 1 x Cupboard	1045 x 620 x 1160		285, 545, 805		52	TT162
2 Shelves 2 x Drawers			285,805		51	TT165
2 Shelves 1 x Drawer 1 x Cupboard			285, 805		51	TT166

Optional extras (factory fitted)

Pneumatic tyres set of 4 200 x 50mm Ref: **B008**



All swivel castors 125 dia. RT castors: Ref: **B031**



Total stop brakes (pair): Ref: 8032



TT166



Loadtek

Workshop Trolleys TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk



Max Load 500kg



Parcel Trucks

With 3 fixed tubular sides. Push handle one end. Polyurethane coated plywood platform flush fitted into angle frame chassis. Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors with 200mm diameter rubber tyred wheels and roller bearings.

Effective Height: 1300mm

Description	Overall H x W x D mm	Platform Size L x W mm	Shelf Height mm	Wheel dia mm	Weight Kg	Order Ref
Small Platform	1575 x 730 x 1190	1000 x 700	275	200	60	WT20
Large Platform	1575 x 830 x 1390	1200 x 800	275	200		WT21

WT20

Optional extras Total stop brakes



Protective bumper strips (factory fitted): Deck size 1000 x 700mm. Ref: BS2 Deck size 1200 x 800mm. Ref: BS3





Stanchion Trucks

Ideal for long bulky loads. 625mm removable corner stanchions for easier loading and unloading. 2 deck sizes and 2 models: 500kg and 1000kg heavy duty fully welded construction. Steel angle with tubular post pockets. Finish: Blue epoxy.

Wheels: 2 swivel 2 fixed castors with 200 or 250mm diameter rubber tyred wheels. Bright zinc plated steel centres and roller bearings.

Description	Overall H x W x D mm	Platform Size L x W mm	Shelf Height mm	Wheel dia mm	Capacityt Kg	Weight Kg	Order Ref
Medium Duty	980 x 770 x 1310	1300 x 700	275	200	500	40	WT23
Heavy Duty	980 x 770 x 1310	1300 x 700	355	250	1000	50	WT24
Medium Duty	980 x 870 x 1610	1600 x 800	275	200	500	50	WT25
Heavy Duty	980 x 870 x 1610	1600 x 800	355	250	1000	57	WT26

<u>j</u>D Loadtek TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Parcel / Stanchion Trucks

SDL

36
Platform and Frame Dollies

A range of dollies to suit most industrial needs. Steel frame construction with a choice of deck types in a compact 600 x 600mm deck size. Finish: Blue epoxy.

Wheels: 4 swivel castors with 125mm diameter rubber tyred roller bearing wheels with bright zinc plated centres.

Timber Deck 19 TD600 Steel Deck 600 x 600 198 125 21 TD601	Description	Platform Size L x W mm	Shelf Height mm	Wheel dia mm	Weight Kg	Order Ref
Steel Deck 600 x 600 198 125 21 TD601	Timber Deck				19	TD600
	Steel Deck	600 × 600	198	125	21	TD601
Open Frame Deck 15 TD602	Open Frame Deck				15	TD602

TD600

Tool Panel Trolleys

'A' frame double sided tool panel trolleys with integral sheet steel deck storage area. Fully welded steel frame construction with bolt-on tool panels. Tubular push/pull handle. Finish: Grey epoxy trolley (BS00A05) with Blue panels (RAL5017).

Wheels: 2 swivel braked and 2 fixed castors fitted with 125mm blue resilex wheels and roller bearings.



For tool hooks - see page 161





2 Panels 1220 1025 × 600 280 125 125 125 125 125 125 125 125 125 125	Description	Overall H mm	Base L x W mm	Deck H mm	Wheel dia mm	Order Ref
	2 Panels	1220	1025 000	200	105	LPT-02
	3 Panels	1600	1025 X 600	280	125	LPT-03



Loadtek

N

Made in

Britain

TD601

КG Max Load

300kg

TD602



Shelf Truck



Loadtek

Ĵ⊡

Welded angle chassis with tubular end frames. Fixed ply platform plus 3 drop-in ply shelves. 2 standard models. Both available as drawbar version. Spring loaded catch holds drawbar in vertical position. Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors with 200mm diameter rubber tyred wheels and roller bearings.

Capacity UDL Kg: Truck max 500; per shelf max 50; base 350 when shelves fully loaded





Deck Height: 275mm

Description	Overall H x L mm	Platform Size L x W mm	Shelf Heights mm at 300mm Centres	Wheel dia mm	Weight Kg	Order Ref	
Chanadand	1780 x 1200	1000 x 700	635, 1005, 1375			65	TS30
Standard	1780 × 1400	1200 x 800		200	80	TS31	
	1780 x 1200	1000 × 700		200	69	TS30T	
With drawbar handle	1780 × 1400	1200 x 800			84	TS31T	

Optional extra Total stop brakes: Ref: B013 (pair)



38

SDL

38

Shelf Truck with Mesh Superstructure



TS36

With mesh superstructure - 3 sides and top. Welded mesh infill 50×50 mm panels 5 drop-in shelves. Welded angle chassis and superstructure. Fixed ply platform and 5 removable ply shelves. Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors with 200mm diameter rubber tyred wheels and roller bearings.

Capacity UDL Kg: Truck max 500; per shelf max 50; base 250 when shelves fully loaded **TS37**

Deck Height: 275mm

Clearence: 230mm

Description	Overall H x L mm	Platform Size L x W mm	Shelf Heights mm at 250mm Centres	Wheel dia mm	Weight Kg	Open Fronted Order Ref	Weight Kg	Hinged Doors Order Ref
Ctoppland	1780 x 1200	1000 x 700	275, 525, 775, 1025, 1275, 1525		110	TS36	127	TS37
Standard	1780 x 1400	1200 x 800		200	120	TS38	138	ТS39
With drawbar bandla	1780 x 1200	1000 x 700		200	112	ТS36Т	129	TS37T
With drawbar handle	1780 x 1400	1200 x 800		122	122	TS38T	140	ТЅЗЭТ

Optional extra

Total stop brakes: Ref: B013 (pair)



Shelf Truck with Rod Superstructure

KG	
Max Load	Made in
500kg	Britain

TS32

TS33

Welded angle chassis and tubular superstructure with vertical retaining rods. Fixed ply platform and 4 removable ply shelves. Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors with 200mm diameter rubber tyred wheels and roller bearings.

Capacity UDL Kg: Truck max 500; per shelf max 50; base 250 when shelves fully loaded





Deck Height: 275mm Clearence: 280mm

Description	Overall H x L mm	Platform Size L x W mm	Shelf Heights mm at 300mm Centres	Wheel dia mm	Weight Kg	Open Fronted Order Ref	Weight Kg	Hook on Front Order Ref	
Chandrad	1780 x 1200	1000 x 700			88	TS32	98	TS33	
Standard	1780 x 1400 120	1200 x 800	570, 870, 1170, 1470	F70 070 4470 4470 000	200	106	TS34	117	TS35
	1780 x 1200	1000 x 700		200	90	TS32T	100	ТЅЗЗТ	
With drawbar handle	1780 x 1400	1200 x 800			108	TS34T	119	TS35T	

Optional extra Total stop brakes:

Ref: B013 (pair)

<u>j</u>D

SDL



Loadtek

Zinc Trolley - Build Your Own

All-round picking trolley. Highly customisable with a range of added extras. Chassis made of square tubing with welded bottom tray. Side panels made from square tubing frame with wire lattice, inserted into chassis and screwed into place.

Trolley Size: H:1830 x W:467 x D:1297mm

Hook in adjustable shelves are adjustable on 50mm increments, mesh size 50 x 25mm.

Chrome plated and powder coated finish.

Wheels: 4 swivel castors 125mm with GNM rubber tread. Including deflector rings made of rubber. Optional swivel castor set with 2 brakes or 2 fixed castors.

Adding bungie cords creates compartments in the trolley. 30 cords (4 rows of 6) creates 24 compartments.





Max Load

300kg

Made in

Britain

	Description	Order Ref
А	Mesh trolley 1830 x 467 x 1297mm	KT3-134618
в	Top shelf to suit 467 x 1297mm mesh trolley	KT3-TS1346
С	Adjustable shelf to suit 467 x 1297mm mesh trolley	KT3-SH1346
D	Rear panel to suit 1830 x 1297mm mesh trolley	KT3-RP1318
Е	Pair of handles for KT3 trolley	KT3-HAND
F	Centre wheel for mesh trolley	KT3-CW
G	Bungie Cords (Set of 5 = 1 column)	KT3-BUNGIE
н	Folding clipboard for KT3 trolley	KT3-A4
1	Hook on basket for KT3 trolley	KT3-BASKET
J	Folding step to suit 467mm wide mesh trolley	KT3-ST46





Zinc Trolley

Zinc Trolley - Ready to Go

One reference for complete Zinc Trolley and accessory combinations.





KT3-BASIC

	Description	Order Ref
А	Mesh trolley 1830 x 467 x 1297mm	KT3-134618
в	Top shelf to suit 467 x 1297mm mesh trolley	KT3-TS1346
с		KT3-SH1346
с	Adjustable shelf to suit 467 x 1297mm mesh trolley	KT3-SH1346
с		KT3-SH1346
Е	Pair of handles for KT3 trolley	KT3-HAND
G		KT3-BUNGIE
G	20 Bungies	KT3-BUNGIE
G	16 Compartments	KT3-BUNGIE
G		KT3-BUNGIE

KT3-BETTER

	Description	Order Ref
А	Mesh trolley 1830 x 467 x 1297mm	KT3-134618
В	Top shelf to suit 467 x 1297mm mesh trolley	KT3-TS1346
С		KT3-SH1346
С	Adjustable shelf to suit 467 x 1297mm mesh trolley	KT3-SH1346
С		KT3-SH1346
D	Rear panel to suit 1830 x 1297mm mesh trolley	KT3-RP1318
Е	Dair of handlos for I/T2 tralloy	KT3-HAND
Е	Pair of handles for KT3 trolley	KT3-HAND
F	Centre wheel for mesh trolley	KT3-CW
G		KT3-BUNGIE
G		KT3-BUNGIE
G	30 Bungies	KT3-BUNGIE
G	24 Compartments	KT3-BUNGIE
G		KT3-BUNGIE
G		KT3-BUNGIE

KT3-BEST

	Description	Order Ref
А	Mesh trolley 1830 x 467 x 1297mm	KT3-134618
в	Top shelf to suit 467 x 1297mm mesh trolley	KT3-TS1346
С		KT3-SH1346
С	Adjustable shelf to suit 467 x 1297mm mesh trolley	KT3-SH1346
С		KT3-SH1346
D	Rear panel to suit 1830 x 1297mm mesh trolley	KT3-RP1318
Е	Pair of handles for KT3 trolley	KT3-HAND
Е	Pair of handles for KTS trolley	KT3-HAND
F	Centre wheel for mesh trolley	KT3-CW
G		KT3-BUNGIE
G		KT3-BUNGIE
G	30 Bungies	KT3-BUNGIE
G	24 Compartments	KT3-BUNGIE
G		KT3-BUNGIE
G		KT3-BUNGIE
н	Folding clipboard for KT3 trolley	КТЗ-А4
Т	Hook on basket for KT3 trolley	KT3-BASKET

Boxtek Trolleys

The Boxtek Trolley is designed and manufactured by Redhill in the UK to the highest standards of quality and safety, facilitating the easy transportation and storage of equipment and goods in the warehouse, workshop or on the factory floor.

- Choice of models, with or without doors
- Two adjustable shelves in choice of plywood or steel
- Maximum load capacity per shelf: 100kg UDL
- Maximum load capacity per trolley: 500kg UDL
- Finished in a range of 5 standard colours
- Fitted with 2 swivel braked & 2 fixed heavy duty blue resilex castors with low rolling resistance and non marking tread
- Robust frame with steel base and open mesh lid





BW1P/GN













Without Doors				
Description	Overall H x W x D mm	Ref		
Plywood Shelves	1355 x 900 x 600	BW1P		
Steel Shelves	1222 X 900 X 600	BW1S		
Plywood Shelves	1355 x 1200 x 600	BW2P		
Steel Shelves	1355 X 1200 X 600	BW2S		
Plywood Shelves	1655 x 900 x 600	BW3P		
Steel Shelves		BW3S		
Plywood Shelves	4055 4000 000	BW4P		
Steel Shelves	1655 x 1200 x 600	BW4S		
Plywood Shelves	1955 x 900 x 600	BW5P		
Steel Shelves	1955 X 900 X 600	BW5S		
Plywood Shelves	1955 x 1200 x 600	BW6P		
Steel Shelves	1955 X 1200 X 600	BW6S		

B GN R

GY

Description	Overall H x W x D mm	Ref
Plywood Shelves	1355 x 900 x 600	BW1PG
Steel Shelves	1355 X 900 X 600	BW1SG
Plywood Shelves	1355 x 1200 x 600	BW2PG
Steel Shelves	1555 X 1200 X 600	BW2SG
Plywood Shelves	1655 x 900 x 600	BW3PG
Steel Shelves	1655 X 900 X 600	BW3SG
Plywood Shelves	1655 x 1200 x 600	BW4PG
Steel Shelves	1655 X 1200 X 600	BW4SG
Plywood Shelves	1955 x 900 x 600	BW5PG
Steel Shelves	1933 X 900 X 000	BW5SG
Plywood Shelves	1955 x 1200 x 600	BW6PG
Steel Shelves	1999 X 1200 X 600	BW6SG

BW5SG/GY



Hazardous Boxtek Trolleys

Tough, sturdy Hazardous Boxtek Trolley designed and manufactured in the UK by Redhill to the highest quality standards for the safe and secure storage and transportation between work areas of dangerous or hazardous materials.

- · Choice of models: with or without fitted doors
- Two adjustable shelves with choice of steel or plywood
- Maximum load capacity per shelf: 100kg UDL
- Maximum load capacity per trolley: 500kg UDL
- Finished in yellow, with hazardous warning stickers
- Fitted with 2 swivel braked & 2 fixed heavy duty blue resilex castors with low rolling resistance and non marking tread
- Robust frame with solid steel base and lid









TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Without Doors		
Description	Overall H x W x D mm	
Plywood Shelves	1355 x 900 x 600	HBW1P
Steel Shelves	1355 X 900 X 600	HBW1S
Plywood Shelves	1355 x 1200 x 600	HBW2P
Steel Shelves	1555 X 1200 X 600	HBW2S
Plywood Shelves	1655 x 900 x 600	HBW3P
Steel Shelves	1055 X 900 X 000	HBW3S
Plywood Shelves	1655 x 1200 x 600	HBW4P
Steel Shelves	1055 X 1200 X 000	HBW4S
Plywood Shelves	1955 x 900 x 600	HBW5P
Steel Shelves	1955 X 900 X 600	HBW5S
Plywood Shelves	1955 x 1200 x 600	HBW6P
Steel Shelves	1955 X 1200 X 600	HBW6S







Without Doors							
Description	Overall H x W x D mm	Ref					
Plywood Shelves	1355 x 900 x 600	HBW1PG					
Steel Shelves	1355 X 900 X 600	HBW1SG					
Plywood Shelves	1355 x 1200 x 600	HBW2PG					
Steel Shelves	1355 X 1200 X 600	HBW2SG					
Plywood Shelves	1655 x 900 x 600	HBW3PG					
Steel Shelves	1022 X 200 X 000	HBW3SG					
Plywood Shelves	1655 x 1200 x 600	HBW4PG					
Steel Shelves	1655 X 1200 X 600	HBW4SG					
Plywood Shelves	1955 x 900 x 600	HBW5PG					
Steel Shelves	1955 X 900 X 600	HBW5SG					
Plywood Shelves	1955 x 1200 x 600	HBW6PG					
Steel Shelves	1955 X 1200 X 600	HBW6SG					



Loadtek

КG

500kg

HBW4P

Made in

Britain

43

TC900 Series

Small deck size of 850 x 500mm. Choice of meshor plywood panels. Substantial timber deck. Blue epoxy finished frame with removable zinc plated mesh side panels or clear varnished plywood end and side panels. Handle ends are fully welded to all steel welded base.

Wheels: 2 swivel and 2 fixed castors with 160mm diameter rubber tyred roller bearing wheels.



Load Restraint Height: 520mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref	
Single Plywood End	005 505 025				30	TC901P	
Single Mesh End	985 x 505 x 935				30	TC901M	
Double Plywood End		500 x 850	235			37	TC902P
Double Mesh End				100	37	TC902M	
3 Plywood Sides	005 505 005			160	52	TC903P	
3 Mesh Sides	985 x 505 x 995				52	TC903M	
4 Plywood Sideds					51	TC904P	
4 Mesh Sides					51	TC904M	

Optional extras

Total stop brakes. Ref: B024 (pair)







N.B: B008 reduces the capacity to 250kgs, B010 increases the deck height by 100mm. Bumper strip (Factory fitted) 850 x 500mm. **Ref: BS1** i v

 \mathbf{N}

Made in

Britain

Max Load

500kg

TC901P



44

44 TC900 Series SDL TEL:(

500 Series

 \mathbf{N}

Made in Britain

кg

500 Series

Large Standard Euro Platform. Substantial timber deck, all steel welded frame.

Wheels: 2 swivel and 2 fixed castors with 160mm red centre wheels with rubber tyres and roller bearing wheels.





Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	235 x 605 x 1025	600 × 1000			25	TC600
Platform Only	235 x 705 x 1025	700 × 1000			26	TC700
	235 x 805 x 1210	800 x 1200			33	TC800
	985 x 605 x 1085	600 x 1000			29	TC601TB
Single End	985 x 705 x 1085	700 × 1000	235	160	30	TC701TB
	985 x 805 x 1285	800 x 1200			38	TC801TB
	985 x 605 x 1085	600 × 1000			33	TC602TB
Double End	985 x 705 x 1085	700 × 1000			34	TC702TB
	985 x 805 x 1285	800 x 1200			42	TC802TB

Optional extras Total stop brakes. Ref: B024 (pair) Bumper strip (Factory fitted) 1000 x 600mm. **Ref: BS1** 1000 x 700mm. **Ref: BS2** 1200 x 800mm. **Ref: BS3**





Loadtek

500 Series with Mesh Panels

Mesh panelled platform trucks. Choice of 3 deck sizes, Substantial timber deck. Blue epoxy finished frame with removable zinc plated mesh side panels or clear varnished plywood end and side panels. Handle ends are fully welded to all steel welded base.

Wheels: 2 swivel 2 fixed castors, with 160mm diameter rubber tyred roller bearing wheels.









Load Restraint Height: 520mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	985 x 605 x 1085	600 × 1000			30	TC601M
Single Mesh End	985 x 705 x 1085	700 × 1000			32	TC701M
	985 x 805 x 1285	800 × 1200			37	TC801M
	985 x 605 x 1145	600 × 1000			36	ТС602М
Double Mesh End	985 x 705 x 1145	700 × 1000			38	ТС702М
	985 x 805 x 1345	800 × 1200	235	160	44	ТС802М
	985 x 605 x 1145	600 × 1000	235	100	39	ТС603М
3 Mesh Sides	985 x 705 x 1145	700 × 1000			41	ТС703М
	985 x 805 x 1345	800 × 1200			48	тс803М
	985 x 605 x 1145	600 × 1000			42	TC604M
4 Mesh Sides	985 x 705 x 1145	700 × 1000			44	TC704M
	985 x 805 x 1345	800 x 1200			52	TC804M

Optional extras Total stop brakes. Ref: B024 (pair)

46







N.B: B008 reduces the capacity to 250kgs, and increases deck height by 40mm. B010 increases the deck height by 100mm. 1000 x 600mm. **Ref: BS1** 1000 x 700mm. **Ref: BS2** 1200 x 800mm. **Ref: BS3**

Bumper strip (Factory fitted)



500 Series with Mesh Panels

500 Series with Timber Panels

500 Series with Timber Panels

Timber panelled platform trucks. Choice of 3 deck sizes. Substantial timber deck. Blue epoxy finished frame with removable zinc plated mesh side panels or clear varnished plywood end and side panels. Handle ends are fully welded to all steel welded base.

Wheels: 2 swivel 2 fixed castors, with 160mm diameter rubber tyred roller bearing wheels.





N









TC704P

Load Restraint Height: 520mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	985 x 605 x 1085	600 × 1000			31	TC601P
Single Timber End	985 x 705 x 1085	700 × 1000			33	TC701P
	985 x 805 x 1285	800 × 1200			38	TC801P
	985 x 605 x 1145	600 × 1000			37	TC602P
Double Timber End	985 x 705 x 1145	700 × 1000	225		38	ТС702Р
	985 x 805 x 1345	800 × 1200		160	45	ТС802Р
	985 x 605 x 1145	600 × 1000	235	100	42	ТС603Р
3 Timber Sides	985 x 705 x 1145	700 × 1000			44	ТС703Р
	985 x 805 x 1345	800 × 1200			51	ТС803Р
	985 x 605 x 1145	600 x 1000			47	TC604P
4 Timber Sides	985 x 705 x 1145	700 × 1000			49	TC704P
	985 x 805 x 1345	800 x 1200			57	TC804P

Optional extras Total stop brakes. Ref: B024 (pair)







N.B: B008 reduces the capacity to 250kgs, and increases deck height by 40mm. B010 increases the deck height by 100mm. Bumper strip (Factory fitted) 1000 x 600mm. **Ref: BS1** 1000 x 700mm. **Ref: BS2** 1200 x 800mm. **Ref: BS3**



Long Goods Platform Trucks

Strong and robust, it features a substantial timber deck with an all steel welded frame, finished in a hard wearing blue epoxy coating. Making it ideal for carrying various loads in a factory, warehouse, store, shop or school environment.

Choice of Tubular or Timber sides.

Wheels: 2 swivel and 2 fixed castors 160mm diameter rubber tyred wheels and roller bearings.









TC705P

Retaining Sides for Tube Ends: 800mm Retaining Sides for Timber Ends: 520mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	1035 x 605 x 1025	600 × 1000			40	ТС605ТВ
Tube Ends	1035 x 705 x 1025	700 × 1000			41	TC705TB
	1035 x 805 x 1025	800 × 1200	235	160	47	ТС805ТВ
	1035 x 605 x 1025	600 × 1000	235	100	41	TC605P
Timber Ends	1035 x 705 x 1025	700 × 1000			43	ТС705Р
	1035 x 805 x 1025	800 x 1200			49	TC805P

Optional extra Total stop brakes Ref: B024 (pair)



Long Goods Platform Trucks

Stainless Steel Range

Stainless Steel Range

304 Grade Stainless Steel platform trucks. High specification range of platform trucks suitable for the food and drink industry. Completely formed from 304 grade stainless steel sheet, tube and wire mesh. Fixed mesh ends and removable mesh sides.

Wheels: 2 swivel and 2 fixed stainless steel castors fitted with 200mm diameter rubber tyred wheels with red centres and stainless steel roller bearings.









Mesh Panel Height: 480mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	295 x 600 x 1000	600 × 1000			33	SP600
Platform Only	295 x 700 x 1000	700 × 1000			35	SP700
	295 x 800 x 1200	800 x 1200			40	SP800
	985 x 600 x 1000 600 x 1000	37	SP601M			
Single Mesh End	985 x 700 x 1000	700 × 1000			39	SP701M
	985 x 800 x 1200	800 x 1200			45	SP801M
	985 x 600 x 1000	600 × 1000	295		41	SP602M
Double Mesh End	985 x 700 x 1000	700 × 1000		200	44	SP702M
	985 x 800 x 1200	800 x 1200			50	SP802M
	985 x 600 x 1000	600 × 1000			44	SP603M
3 Mesh Sides	985 × 700 × 1000	700 × 1000			47	SP703M
	985 x 800 x 1200	800 x 1200			54	SP803M
	985 x 600 x 1000	600 × 1000			47	SP604M
4 Mesh Sides	985 x 700 x 1000	700 × 1000			50	SP704M
	985 x 800 x 1200	800 x 1200			58	SP804M

Optional extra Total stop brakes: Ref. B229 (pair)

Bumper strip (Factory fitted) 1000 x 600mm: Ref. BS1 1000 x 700mm: Ref. BS2 1200 x 800mm: Ref. BS3



Colour Range

Coloured platform trucks. High quality powder coated decks in a range of attractive colours, with bright zinc plated fixed mesh ends and removable sides. End panels fixed, side panels removable.

Wheels: 2 swivel and 2 fixed castors with 200mm diameter, rubber tyred wheels with bright zinc plated centres and roller bearings.



50







Mesh Panel Height: 480mm

Description	Overall H x W x D mm	Platform Size W x D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	985 x 600 x 1000	600 × 1000			37	EP601M
Single Mesh End	985 x 700 x 1000	700 × 1000			39	EP701M
	985 x 800 x 1200	800 × 1200			45	EP801M
	985 x 600 x 1000	600 × 1000			41	EP602M
Double Mesh End	985 x 700 x 1000	700 × 1000	295		44	EP702M
	985 x 800 x 1200	800 × 1200		200	50	EP802M
	985 x 600 x 1000	600 × 1000	295	200	44	EP603M
3 Mesh Sides	985 x 700 x 1000	700 × 1000			47	EP703M
	985 x 800 x 1200	800 × 1200			54	EP803M
	985 x 600 x 1000	600 × 1000			47	EP604M
4 Mesh Sides	985 x 700 x 1000	700 × 1000			50	EP704M
	985 x 800 x 1200	800 x 1200			58	EP804M



Optional extras Total stop brakes: Ref. B073 (pair)





Pneumatic Tyres 260mm. **Ref: B010**

N.B: B008 reduces the capacity to 250kgs, B010 increases the deck height by 60mm. Bumper strip (Factory fitted) 1000 x 600mm. **Ref: BS1** 1000 x 700mm. **Ref: BS2** 1200 x 800mm. **Ref: BS3**





50

Series 700 Bright Zinc Plated

Comprehensive range of bright zinc plated platform trucks from basic platform to 4 mesh sides. Choice of 3 deck sizes. Steel chassis with steel deck. Fixed ends and removable long sides, bright zinc plated mesh infill. Smart durable bright zinc plated finish.

Wheels: 2 swivel and 2 fixed castors with 200mm diameter rubber tyred roller bearing wheels with bright steel centres.





Mesh Panel Height: 480mm

Description	Overall H x W x D mm	Platform Size W \times D mm	Deck Height mm	Wheel dia mm	Weight kg	Order Ref
	295 x 600 x 1000	600 x 1000			35	ZP600
Platform Only	295 x 700 x 1000	700 × 1000			38	ZP700
	295 x 800 x 1200	800 x 1200			45	ZP800
	985 x 600 x 1000	600 x 1000			38	ZP601T
Single Fixed Tube End	985 x 700 x 1000	700 x 1000			41	ZP701T
	985 x 800 x 1200	800 x 1200			49	ZP801T
	985 x 600 x 1000	600 × 1000			39	ZP601M
Single Fixed Mesh End	985 x 700 x 1000	700 × 1000			42	ZP701M
	985 x 800 x 1200	800 x 1200	295	200	49	ZP801M
	985 x 600 x 1000	600 x 1000	295	200	43	ZP602M
Double Fixed Mesh End	985 x 700 x 1000	700 × 1000			46	ZP702M
	985 x 800 x 1200	800 x 1200			54	ZP802M
	985 x 600 x 1000	600 x 1000			46	ZP603M
3 Mesh Sides (1 removable)	985 x 700 x 1000	700 × 1000			59	ZP703M
	985 x 800 x 1200	800 x 1200			58	ZP803M
	985 x 600 x 1000	600 × 1000			49	ZP604M
4 Mesh Sides (2 removable)	985 x 700 x 1000	700 × 1000			52	ZP704M
	985 x 800 x 1200	800 x 1200			62	ZP804M

Optional extras Total stop brakes: Ref. B073 (pair)





N.B: B010 increase the deck height by 60mm



Bumper strip (Factory fitted) 1000 x 600mm. Ref: BS1 1000 x 700mm. Ref: BS2 1200 x 800mm. Ref: BS3





Loadtek

Series 700 Bright Zinc Plated



Beam Trolley

Easy transportation of long loads in factories, showrooms and warehouses, for carpets, floor coverings, poles and timber products. Finish: Blue epoxy.

Tubular construction throughout with centre axle mounted with large 400mm diameter pneumatic tyred wheels for maximum mobility and soft ride, or 400mm diameter solid rubber tyred wheels.

We can manufacture to your special sizes on request.

Description	Overall H x D x L mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels		100	26	TP46
Pneumatic Wheels	420 x 660 x 1010	400	13	TP46P



Carpet Trolley

Strong tubular steel frame designed for moving heavy, cylindrical goods, especially carpets, with full welded construction. Finish: Red epoxy.

Mounted with large 400mm diameter pneumatic tyred wheels for maximum mobility and soft ride, or 400mm diameter solid rubber tyred wheels.

Description	Overall H x D x L mm	Central Frame Height mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels		400	100	27	TP42
Pneumatic Wheels	505 x 550 x 1540	420	400	14	TP42P



Sheet Buggies

For in-plant or on-site use; timber and metal sheets, frames and doors, chipboard and hardboard. Tubular steel construction, with plastic hand grips and finished in blue epoxy.

Wheels: 2 axle mounted 200mm diameter solid tyred wheels, or 260mm diameter pneumatic tyred wheels (all wheels roller bearings).

Description	Overall H x D x L mm	Platform Size L x W mm	Handle Length mm	Wheel dia mm	Weight kg	Order Ref
Plywood Platform with Solid Wheels	1220 x 550	800 x 250	2000	200	19	TP41
Plywood Platform with Pneumatic Wheels	1220 X 550		2000	260		TP41P
Ribbed Rubber Platform with Solid Wheels	1220 x 590	500 x 200	1180	200	21	TP40
Ribbed Rubber Platform with Pneumatic Wheels	1220 x 590	500 x 200		260		TP40P



Beam / Carpet Trolley

SDL

52

Hi-Frame Plate Trucks



The Big Plate Trucks. Heavy duty angle chassis with high tubular support frame for sheet material transport and storage. Fully welded throughout. Open frame or ply deck. Finish: Blue epoxy.

Wheels: 2 swivel 2 fixed castors with rubber tyred wheels, bright steel centres and roller bearings.

ТРЗІР



Frame Height: 1175mm Max Load Depth: 450mm

Description	Overall H x W x L mm	Deck Height mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
Open Frame	1500 x 700 x 2250	285	200	500	84	TP31
Open Frame	en Frame 11570 x 700 x 2250	355	250	750	92	TP32
Div Doold	1500 x 700 x 2250	300	200	500	94	TP31P
Ply Deck	11570 x 700 x 2250	370	250	750	104	TP32P

Standard Plate Trucks

Welded angle chassis with removable bars, 2 supplied (extras available). Finish: Blue epoxy.

Wheels: 2 swivel and 2 fixed castors with 200mm diameter rubber tyred wheels and roller bearings.





Support Bar Height: 725mm

Description Platform	Deck	Bars (2 supp	lied)	Wheel	Weight	Order	
	WxLmm	Height mm	Positions	Centres mm	dia mm	kg	Ref
Ply Deck	700 × 1000	225	5	168	200	46	TP35
	700 × 1200	325	6	155		54	TP36

Optional Extras	Order Ref
1000mm length additional Support Bars	TP7
1200mm length additional Support Bars	TP8

Loadtek

]□

SDL

Optional extras:
Total stop brakes extra (pair)
Ref: B013



53

Plate Handling 53



Multi-height Sheet Rack

Ideal for off-cuts and other variable sizes of sheet and plate. Fitted with sheet steel base and pre-drilled for floor fixing. Finished in blue epoxy.

Overall H x D x L mm	Distance Between Bars mm	Support Bar Heights mm	Weight kg	Order Ref
1000 × 1400 × 800	160	400, 550, 700, 850, 1000	75	MPR



Full-height Sheet Rack

Aultipurpose rack with formed sheet steel base. Pre-drilled for floor fixing (bolts not supplied). Finished in blue epoxy.

M	Multip Pre-dr
V	

Overall H x W x D mm	Distance Between Uprights mm	Central Support Beam Height mm	Weight kg	Order Ref
1220 x 1080 x 1015	305	575	53	FHSR





Vertical Bar Rack

Fully welded steel construction with steel base 600 x 250mm storage bays. Pre-drilled for bolting to floor (fixings not supplied). Finished in blue epoxy.

]□

Loadtek

Description	Overall H x D x L mm	Bay Size mm	Weight kg	Order Ref
4 Bays	1500 × 600 × 1200		84	VBR4
6 Bays	1500 x 600 x 1800	600 x 250	108	VBR6
8 Bays	1500 x 600 x 2400		135	VBR8



TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Horizontal Bar Rack

N

Made in Britain

Made in

Britain

Single or double sided freestanding units with a maximum load of 500kg per level single sided, 1000kg per level double sided. Six storage levels on single sided units, seven levels on double sided units. Finish: Blue epoxy.

HBR2





Starter bay - 2 uprights + cross bracing Extension bay - 1 upright + cross bracing

Description	Overall H x D x L mm	Centre line of uprights mm	Weight kg	Order Ref
Single sided starter bay	1880 x 860 x 2445		100	HBR1
Single sided extension bay	1880 x 860 x 2010		53	HBR1E
Double sided starter bay	1985 x 920 x 2445	1575	128	HBR2
Double sided extension bay	1985 x 920 x 2010		68	HBR2E

Stacking Bar Cradles

Flexible stacking cradles for storage of varying lengths of bar, tube, flats, and angles. Stacked at a maximum of 5 high with a load capacity of 1000kg per cradle.

Fitted with 127mm square pallet feet. Finished in blue epoxy.

Units MUST be sited on solid level ground.

Loadtek







Bar and Sheet Storage

Drum Lifters

Suitable for 210 litre steel drums.

Standard 2-wheel design with rear bar support. 4-wheel design with rear swivel castors, which helps operator move and manoeuvre loaded truck.

Tubular and hollow section construction with centre beam adjustable drum retaining hook.

Choice of solid or pneumatic tyres. Finished in blue epoxy with red plastic standard hand grips.











Loadtek

<u>j</u>

Description	Wheel dia mm	Rear Castors No. x Diameter mm	Weight kg	Order Ref
2 Solid Whools (rear bar support)	250		20	DT20
2 Solid Wheels (rear bar support)	400		34	DT21
2 Pneumatic Wheels (rear bar support)	400		21	DT23
	250	2 x 125	21	DT24
4 Solid Wheels (rear bar support)	400	2 x 125	36	DT25

Optional extra Protective Hand Grips Ref: E010 (pair)



56

Drum Handling SDL TEL:03

Made in Britain

Pallet Loading Drum Truck

Designed to assist loading and unloading 210 litre drums onto pallets or platforms etc. with sliding drum retention clamp. 190mm maximum pallet height for safe use.

Wheels: 2 x 250mm diameter. and 2 x 200mm diameter with roller bearings and solid rubber tyres.







Description	Overall H x W x L mm	Maximum Pallet Height mm	Wheel dia mm	Weight kg	Order Ref
Twin Loop Handles with Blue Epoxy Finish	1100 x x 610 x 1660	190	2 x 250 / 2 x 200	29	DT60
Twin Loop Handles with Zinc Plated Finish					DT60/ZP

Optional Clamps Clamp for Plastic Drums (can be retro fitted). Weight: 6kg. Order Ref: DT61



Zinc Plated Clamp for Plastic Drums (can be retro fitted). Weight: 6kg. Order Ref: DT61/ZP







Loadtek



Max Load Made in 250kg Britain

Universal Drum Truck

Suitable for steel, plastic or fibre drums. Welded construction flat and tube steel. Finish: Blue epoxy.

Fitted with adjustable quick release strap.

Rubber Tyred Wheels with roller bearings.

Overall H x W mm	Wheel dia mm	Weight kg	
1330 × 660	200	15	DT250



Drum Trolley and Pouring Stand

Suitable for 210 litre steel drums. Choose from pneumatic or solid tyred wheels: 2 x 400mm diameter. 4 Nylon drum rollers and strap supplied. Finish: Blue epoxy.

As manufacturers we are pleased to quote for drum movers for any specific diameter of kegs, drums, containers or rolls.



Description	Overall H x W x L mm	Height of Bung* mm	Weight kg	Order Ref
Pneumatic Wheels	F10 ··· 000 ··· 1000	200	22	DT30P
Solid Wheels	510 x 800 x 1220	360	35	DT30

58

Drum Handling

SDL

landling LOAdtek

Drum Stands

Manufactured from a robust and strong welded steel frame and finished with a tough, hard wearing red epoxy coating.

The tubular chassis is angled to hold the drum safely and securely, with two support bars to ensure rigidity.



59

Description	Overall H x W x L mm	Capacity kg	Weight kg	Order Ref
Static Stand	490 x 585 x 880	250	9	DS17
Optional extras Tilt Lever (factory fitted). Length 1070mm with hand grip Ref: DS29	Hook on Drip Tray L x W x H 387 x 28 Available for all dru Ref: DS30			
Complete Mobile Drur	m Stand	Max Load Made in		
Suitable for holding 210 litre stee steel welded construction and fin drum rotation rollers make it easy on the stand, and the tilt lever en to vertical position.	ished in a tough red epoxy coati v to change the position of the dr	ng. The um while		
Two fixed outrigger wheels, 150 > and two swivel castor nylon whee				5

Description	Overall H x W x L mm	Capacity kg	Weight kg	Order Ref
Mobile Stand	580 x 725 x 880	250	17	DS19

Hook on Drip Tray L x W x H 387 x 280 x 50mm Available for all drum stands. **Ref: DS30**

<u>j</u>

SDL



Loadtek

Drum Handling

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

N

Made in Britain

Drum Dollies

Circular Drum Dolly

Flat steel braces with 4 nylon wheels. 80mm diameter in swivel castor housings. Flat steel circular retention ring. Finish: Red epoxy.

Stainless Steel Circular Drum Dolly

Fully welded flat stainless steel bracers.

Flat stainless steel circular retention ring. Retention ring height: 40mm. Overall height: 153mm. Wheels: 4 x swivel stainless steel castors fitted with 80mm nylon wheels and roller bearings. Finish: Stainless steel grade 304.

4 Wheeled Drum Dolly

Immensely strong fabricated construction 4 nylon wheels in swivel castors. 80mm wheel diameter. Finish: Red epoxy.

3 Wheeled Drum Dolly

Suitable for 130 or 210 litre drums. Overall Height x Diameter: 120 x 800mm.Load height 55mm, 3 x 80mm diameter nylon swivel castors. Finish: Red epoxy.

Description	Internal dia mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
Circular Drum Dolley			300	9	DT10
Stainless Steel Circular Drum Dolly	610	00		10	DT10SS
4 Wheeled Drum Dolly		80	500	11	DT11
3 Wheeled Drum Dolly	800		300	8	DT12



Economy Drum Dollies

Economy Circular Drum Dolly

Manufactured from 3mm mild steel. Minimum drum diameter: 520mm. Overall height: 135mm. Retention lip height: 24mm.

Wheels: 4 x swivel castors fitted with 80mm nylon wheels and roller bearings. Finish: Light grey epoxy.

Economy Drum Dolly

Manufactured from 4mm mild steel. Minimum drum diameter: 450mm. Overall height: 135mm. Retention lip height: 20mm.

Wheels: 4 x swivel castors fitted with 80mm nylon wheels and roller bearings.Finish: Light grey epoxy.

<u>]</u>

Loadtek

Description	Internal dia mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
Economy Circular Drum Dolly	590	80	300	7	DT15
Economy Drum Dolly	600	80	500	6	DT16

60

NORIE O LUB

SCLA MORE

Drum Racking Units

N

Made in

Britain

CLA MORE

3

S GLAVAIORE

CLA MOR

0 LUB

CLA MORE

ORP

Stacking Drum Pallet Racking System

Flexible, expandable storage system for 200/220 litre steel drums. Pallet Unit: Holds 2 drums. Strong welded steel construction stackable pallet. Pallet feet 127mm square. Maximum stacking 3 units high. Also with Drum Rotation option. Finish: Red epoxy.

Sump Unit: Capacity 250 litres. Formed from 3mm sheet steel, fully welded seams. Ground clearance 100mm. Finish: Grey epoxy.

DS100 & DS2

CLA NORE

SEADIFCH

Fork Pocket W x H: 240 x 70mm Max Width Over Forks: 920mm Distance Between Pockets: 430mm

Description	Overall H x W x L mm	Weight kg	Order Ref
Pallet Unit	890 x 1460 x 615	50	DS100
Sump Unit	300 x 1250 x 1000	70	DS2

Optional extras

Drum retaining bars for added stability. Overall H x W x D: 1420 x 170 x 40mm. Weight: 6kg. Finish: Red epoxy.

Ref: DS103

Drum rotating sets: fitted with 4 x 65mm dia nylon rollers. Drops onto pallet unit 1 set per drum position. Weight: 4kg. Finish: Zinc plated.

Ref: DS101



Dispenser stand hooks onto pallet. Overall H x W x D: 330 x 340 x 290mm Weight: 6kg. Finish: Grey epoxy.

Ref: DS102





Loadtek

Drum Racking Units TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Drum Sump Storage System

Designed to store drums either vertically or horizontally for ease of use and access. In case of leakage, sumps are designed to hold more than the contents of the drum.

Products designed to assist conformance with Environmental Duties of Care and Oil Storage Regulations (England) 2001. Sump capacity >125% of drum contents.

Fully welded sump covered with removable galvanised steel grid and retaining chain (vertical stores only). Stores without roofs fitted with 125mm pallet feet for ease of stacking. Maximum stack 3 high. All sumps fully welded liquid tight, fitted with drain plug and fork locators.

Drum stand to take 2 horizontal drums fits over DS402.

Drum rotation frame for 1 horizontal drum, fits over DS411. Nylon wheels allow full rotation of drum.





Description	Overall H x W x L mm	Capacity Itrs	Order Ref
Drum Sump for 2 Vertical Drums	345 x 735 x 1365	250	DS401
Drum Sump for 4 Vertical Drums	345 x 1365 x 1365	470	DS402
Drum Stand for 2 Horizontal Drums	495 x 745 x 480	N/A	DS411
Drum Rotation Frame for 1 Drum	940 x 540 x 1375	IN/A	DS412

Optional extras Drain tap for drum sumps

Ref: MS117





62

62 Drum Sump Storage System

Mobile Drum Sump Trolley / Dispenser

Mobile Drum Sump

Drum trolley with integral sump. Sump trolley for 2 vertical or 1 horizontal drum when used with drum rotation frame. Sump capacity 250 ltrs. Removable galvanised steel support grid and drain plug. Fitted with tubular push handle and fork locators. 2 fixed, 2 swivel castors with 125mm nylon wheels and roller bearings. Braked castors available as an option.

Drum Rotation Frame

Drum rotation frame to fit drum sump trolley. Ideal for transport and dispensing purposes. 4 nylon wheels allow full rotation of drum in horizontal position.

DS403 & DS410



63



Description	Overall H x W x L mm	Wheel dia mm	Order Ref
Mobile Drum Sump	970 x 735 x 1405	125	DS403
Drum Rotation Frame	155 x 505 x 480	N/A	DS410

Optional extras

Brake option for DS403

Ref: B175

<u>]</u>

SDL



Loadtek



TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

N

Made in Britain



Economy Cylinder Wall Racks

Wall storage for 1, 2 or 3 cylinders. To suit cylinders size ranges of either 100 - 180mm diameter or 140 - 270mm diameter. Manufactured from 3mm sheet steel and supplied complete with zinc plated steel link retention chains. Finish: Light Grey epoxy to BS00A05 or Stainless Steel 304 grade.

Pre-drilled wall fixings holes (fixings not supplied). Wall racks must be fixed to the wall at height of at least two-thirds of cylinder height.



SC205



Description	Overall W x D mm	Cylinder dia mm	Weight Kg	Light Grey Epoxy Order Ref	Stainless Steel Order Ref
1 Cylinder Wall Rack	245 x 140		1	SC204	SC204SS
2 Cylinder Wall Rack	460 x 140	100 - 180	2	SC205	SC205SS
3 Cylinder Wall Rack	675 x 140		3	SC206	SC206SS
1 Cylinder Wall Rack	340 x 210		2	SC207	SC207SS
2 Cylinder Wall Rack	660 x 210	140 - 270	3	SC208	SC208SS
3 Cylinder Wall Rack	980 x 210		4	SC209	SC209SS



Economy Static Cylinder Floor Stands

Static floor storage stands for 1,2 or 3 cylinders. To suit cylinders size ranges of either 100-180mm diameter or 140-270mm diameter. Manufactured from 3mm sheet steel and supplied complete with zinc plated steel link retention chains. Finish: Light Grey epoxy to BS00A0S or Stainless Steel 304 grade.

Pre-drilled fixings holes for wall or floor (fixings not supplied). Units must either be bolted to the floor or a wall. Units can be bolted back to back to create double sided storage areas.

SC210	SC210SS	SC211 SC211SS	SC213 SC231SS
	Weight Kg	Light Grey Epoxy Order Ref	Stainless Steel Order Ref
	7	SC210	5021055

Description	Overall H x W x D mm	Cylinder dia mm	Weight Kg	Light Grey Epoxy Order Ref	Stainless Steel Order Ref
1 Cylinder Floor Stand	1005 x 255 x 255	100 100	7	SC210	SC210SS
2 Cylinder Floor Stand	1005 x 500 x 255	100 - 180	10	SC211	SC211SS
1 Cylinder Floor Stand	1005 x 340 x 345	140 270	9	SC212	SC212SS
2 Cylinder Floor Stand	1005 x 660 x 345	140 - 270	14	SC213	SC213SS



Cylinder Storage



64

SDL

64

 \mathbf{N}

Made in Britain

 \mathbf{N}

Made in Britain

Heavy Duty Cylinder Wall Racks

Wall storage units 2 or 3 cylinders. These racks must be fixed to the wall at a height of at least two-thirds of cylinder height. Finish: Blue epoxy or Galvanised.

Supplied with pre-drilled fixing holes (fixings not supplied). All racks fitted with steel link retention chains.





Description	Overall W x D mm	Cylinder dia mm	Weight Kg	Light Grey Epoxy Order Ref	Galvanised Order Ref
1 Cylinder Wall Rack	538 x 155	400,400	2	SC200	SC200G
2 Cylinder Wall Rack	765 x 155	100 - 180	3	SC201	SC201G
1 Cylinder Wall Rack	765 x 195	140 070	3	SC202	SC202G
2 Cylinder Wall Rack	1045 x 195	140 - 270	4	SC203	SC203G

Heavy Duty Floor Fixing Cylinder Racks

Single and double sided cylinder racks. Single sided units have rear frames pre-drilled. We strongly recommend that single sided units are fixed to the wall. Fully welded construction throughout. Steel link retention chains fitted. Finish: Blue epoxy.



Description	Overall H x W x D mm	Cylinder dia mm	Wt Kg	Order Ref
2 Cylinder Floor Stand	1000 x 540 x 370	100 - 180	12	SC300
3 Cylinder Floor Stand	1000 x 770 x 370	100 - 180	13	SC301
2 Cylinder Floor Stand	1000 x 725 x 400	140 - 270	13	SC302
3 Cylinder Floor Stand	1000 × 1040 × 400	140 - 270	14	SC303

Bases supplied pre-drilled for floor fixing (fixings not supplied)

Loadtek

]□

SDL

D		V	
			SC300
	X	J	

Double Sided				
Description	Overall H x W x D mm	Cylinder dia mm	Wt Kg	Order Ref
4 Cylinder Floor Stand	1000 x 540 x 685	100 - 180	14	SC304
6 Cylinder Floor Stand	1000 x 770 x 685	100 - 180	15	SC305
4 Cylinder Floor Stand	1000 x 725 x 685	140 270	15	SC306
6 Cylinder Floor Stand	1000 x 1040 x 685	140 - 270	16	SC307

Bases supplied pre-drilled for floor fixing (fixings not supplied)

65

Cylinder Storage

Hinged Latch Stands / Cylindrical Stands

Made in Britain

Hinged Latch Cylinder Stand: 3 sizes. 2 hinged access latches secured by wing nuts. RSA and mild steel flat section, fully welded throughout. Heavy duty base plate and support. Base plate pre-drilled for floor fixing (fixings not supplied). Finish: Blue epoxy.

Cylindrical Stand: 3 sizes. Rolled and formed mild steel flat section, fully welded throughout. Finish: Blue epoxy.



Description	Cylinder dia mm	Overall Height mm	Overall diameter/base mm	Weight Kg	Order Ref
Cylindrical Stand	100	330	310	9	SC11
	140	380	345	10	SC12
	180	610	420	11	SC13
Hinged Latch Stand	180	605	322 x 322	14	SC17
	230	605	380 x 380	15	SC18
	285	605	420 × 420	16	SC19



SC12



Cylinder Trolleys

Tandem Cylinder Trolley. Steel link retaining chain fitted. Finish: Blue epoxy.

<u>j</u>

Loadtek

Wheels: 2×250 mm diameter solid rubber tyres, 2×100 mm diameter rubber swivel castors.

	Description	Overall H x W x D mm	Cylinder Sizes mm	Wheel dia mm	Weight Kg	Order Ref
landem 10/0 x 4/5 x 1005 230 & 265 250 34 SCI	Tandem	1070 x 475 x 1005	230 & 265	250	34	SC115

66

5 Cylinder Storage and Handling

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

SDL ~ TRADER ~ 2025 'B'

'T' Bar Calor Truck

Designed for cylinders diameter x H: 325 x 535mm T-bar handle. Steel cross member cylinder support and vertical sides with cylinder retention chain. Finish: Blue epoxy.

Wheels: 200 mm diameter solid rubber tyres.

G		
Load Okg	Made in Britain	
		By
		Propi HIGHLY FL
		HIGHLY PL
		A CONTRACT OF THE OWNER

N

Max 100

Description	Overall Height mm	Cylinder dia mm	Wheel dia mm	Weight Kg	Order Ref
T Bar Handle	535	325	200	10	SC15

Single Cylinder Trolley

Cylinder sizes: 230 & 275mm diameter. Finish: Blue epoxy.

Wheels: 200mm diameter solid rubber tyred roller bearing wheels.



Description	Overall H x W x D mm	Cylinder dia mm	Wheel dia mm	Weight Kg	Order Ref
Bar Handle	1170 x 430 x 450	230	200	9	SC140
	1170 x 475 x 450	275	200	10	SC141

Tall Cylinder Support Trucks

Loadtek

Designed to carry cylinder loads on 3-wheel base, thus minimising operator fatigue and risk. Easy to load with flat foot plate (AR). Finish: Blue epoxy.

AR Series: Adjustable rake back. Max overall front-rear 1350mm

Wheels: All models with 200mm diameter wheels with roller bearings. Plate fixing rear swivel castor 125mm diameter rubber tyres.



Description	Overall H x W mm	Cylinder dia mm	Wheel dia mm	Weight Kg	Order Ref
AR Series	1140 x 430 x	230	200	25	SC146
	1140 x 475x	275	200	25	SC147



Welders Trolley



Trolleys to transport 1 Oxygen cylinder and 1 Acetylene cylinder with rods and cable holders. Steel link retaining chains fitted. Finish: Blue epoxy.

Wheels: 400mm diameter pneumatic or solid rubber tyred wheels with roller bearings - rear support models have 125mm swivel castors with solid rubber tyres and roller bearings.

SC118







SC119

Description	Cylinder Sizes mm	Overall $H \times W \times D$ mm (Upright)	Overall diameter/base mm	Wheel dia mm	Wt Kg	Order Ref
2 Solid Wheels	230 & 265	1085 x 915 x 540	N/A	400	32	SC114
2 Pneumatic Wheels		1085 X 915 X 540	N/A		25	SC114P
2 Solid Wheels with 1 rear support castor		1085 x 915 x 820	940 x 915 x 1050		35	SC118
2 Pneumatic Wheels with 1 rear support castor					21	SC118P
2 Solid Wheels with 2 rear support castor					37	SC119
2 Pneumatic Wheels with 2 rear support castor					23	SC119P



Keg Trolley

Designed to easily move 11 gallon casks or kegs. Manufactured with centre spine with formed hook from flat to locate into hand hold of keg. Formed tubular handle welded central. Finish: Black epoxy.

Mounted on 160mm diameter rubber tyred wheels.



Description	Overall H x W mm	Wheel dia mm	Weight Kg	Order Ref
Keg Trolley	1190 x 400	160	7	SC04



68

Propane and Calor Cylinder Trucks



Cylinder Storage and Handling

Designed for cylinders diameter x height: 380 x 1250mm. Twin rear handles fitted with protective hand grips. Solid foot plate and vertical side tubes with cylinder retention chain. Finish: Blue epoxy

Wheels: 260mm diameter pneumatic or 200mm diameter solid rubber tryed wheels with roller bearings - rear support models have 125mm swivel castors with solid rubber tyres and roller bearings.







Description	Cylinder Sizes mm	Overall H x W x D mm (Upright)	Overall diameter/base mm	Wheel dia mm	Wt Kg	Order Ref
2 Solid Wheels	230 & 265	1400 × 700 × 540	N/A	200	32	SC16
2 Pneumatic Wheels				260	25	SC16P
2 Solid Wheels with 1 rear support castor		1400 × 700 × 800	1010 x 700 x 1320	200	35	SC216
2 Pneumatic Wheels with 1 rear support castor				260	21	SC216P
2 Solid Wheels with 2 rear support castor				200	37	SC217
2 Pneumatic Wheels with 2 rear support castor				260	23	SC217P

Cylinder Lifting Trolleys

Combined cylinder trolley / lifting cradle. One product allowing cylinders to be moved with either overhead lifting gear, or wheeled into position. Finish: Red epoxy.

All cradles tested to 100% overload - test certificate supplied.

Single cylinder lifting trolley: 2 x 200mm diameter solid rubber wheels and 50mm diameter lifting eye. Top and bottom cylinder retention chains.

Two cylinder lifting trolley: 2 Fitted with rear castor for added safety and manoeuvrability. 2 x 400mm diameter rubber tyred wheels and a single 160mm diameter swivel castor on rear support frame for added safety and manoeuvrability. Top and bottom cylinder retention chains.



Description	Overall H x W mm	Cylinder dia mm	Wheel dia mm	Capacity Kg	Weight Kg	Order Ref
1 Oulindor	1870 x 740 x 410	180-230	200	150	23	SC25
1 Cylinder	1870 x 780 x 490	230-305	200		24	SC26
2 Culindar	1870 x 685 x 790		250	56	SC27	
2 Cylinder	1870 x 760 x 940	230-305	400	250	60	SC28



Loadtek

Cylinder Storage and Handling

N

Made in Britain

Cylinder Storage and Handling

Max Load lookg

Cylinder Storage / Transport Pallet

Heavy duty design to carry combinations of cylinder sizes. Manufactured from strong box section supports, thick sheet steel fork pockets and checker plate base. Cylinders secured with rachet straps mounted to internal framework. Finish: Blue epoxy.



Fork pocket H x W: 70 x 195mm

Description	Overall H x W x D mm	Deck Size Front W x D mm (Internal)	Deck Size Rear W x D mm (Internal)	Min Cylinder Height mm	Weight kg	Order Ref
Transport Pallet	1000 × 1020 × 1000	940 x 670mm	940 x 270mm	1000	98	SC6100



Small Cylinder Trolley

Cylinder trolley designed to carry either 12 x Size D or E oxygen cylinders. Located in 108mm hole supports complete with rubber cushioning to deck Finish: Light grey epoxy coated.

Wheels: 4 \times 100mm swivel castors (2 braked) fitted with grey non-marking tyres and roller bearings.



		Weight Kg	Order Ref
Small Trolley 930 x 490 x 720	100	15	SC117



Cylinder Storage and Handling

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Oxygen Cylinder Trolleys

Ideal for all medical services: Ideal for all hospitals, medial centres, pharmaceutical companies and laboratories. Also industrial and factory medical services. Easy to use: Quiet, Tough and Smart in Grey epoxy.

Protective rotating buffers fitted to front corners. One piece safety loop handle. Secure butterfly screw crossbar fitting for both cradles. Top and bottom cradles both rubber lined for grip and noise reduction.

Anti static wheels 160/200mm diameter.



Description	Overall H x W x D mm	Cylinder dia mm	Wheel dia mm	Weight Kg	Order Ref
Loop Handle Trolley	1100 x 430 x 585	140	160	11	SC08G
	1100 x 520 x 610	230	200	13	SC010G

Max Load

120kg

Made in

Britain

Oxygen Cylinder Trolleys

Splayed tubular framework with formed sheet steel toe plate. Suitable for cylinders with max diameter of 230mm. Drop over chains secure the cylinder. Easy to use yet robust by designer retention chains.

Mounted on 2 \times 160mm anti static wheels and 2 \times 100mm GNM rear swivel castors.





Description	Overall H x W x D mm	Cylinder dia mm	Wheel dia mm	Weight Kg	Order Ref
Drop Chain Trolley	910 x 480 x 1030	230	160	15	SC20G

Loadtek

Cv	linder	Storage	and	Handling
	maci	JUTUGE	unu	Turuning



Wall Mounted Cylinder Storage Racks

Suitable for storage of cylinders up to a maximum diameter of 100mm. Robust rubber ring to protect cylinders from damage. Ribbed rubber lining in the base for extra protection. Precut for securing to a wall and supplied without fixings. Finish: Light Grey







Description	H x W x D mm	Cylinder dia mm	Order Ref
1 x 1 Cylinder	250 x 165 x 165		SC220
1 x 2 Cylinder	250 x 300 x 165	100	SC221
1 x 3 Cylinder	250 x 435 x 165		SC222

72





Cylinder Storage
Cylinder Storage Cages

Strong and sturdy design cylinder storage security cage with hinged doors fitted with padlock facility (padlock not supplied). Doors open through 180 degrees. Manufactured from heavy duty box and angle section. Supplied complete with gas storage warning identification label. Finish: Blue epoxy.

Mobile Model

Mounted on 2 swivel and 2 fixed castors fitted with 200mm blue resilex wheels and roller bearings complete with push handle at one end.

Static Model

Mounted on 4 pallet feet. Available with or without centrally fixed shelf: Fixed shelf model to carry a maximum of 16 x calor gas type cylinders (max 380mm diameter x 650mm tall). Open shelf model to carry a maximum of 8 x propane type cylinders (max 380mm diameter x mm x 1690mm tall).



SC500





Internal clearance:

Open shelf model (H x W x D): 1690 x 1695 x 980mm. Fixed shelf model (H x W x D);

Base shelf: 850 \times 1695 \times 980mm, Shelf: 785 \times 1695 \times 980mm.

Description	OverallHxWxDmm	No. of Shelves	Shelf Height mm	Wheel dia mm	Weight Kg	Order Ref
Mobile Cage for 8 x Propane	2030 x 1960 x 1040	0	280	200	204	SC500
Mobile Cage for 16 x Calor	2030 X 1960 X 1040	1	1185	200	230	SC501
Static Cage for 8 x Propane	2020 - 1020 - 1040	0	280		194	SC502
Static Cage for 16 x Calor	2030 x 1830 x 1040	1	1185	-	220	SC503

Optional extra

Total stop braked castors (pair) Ref: B200

Loadtek



Cylinder Storage Cages

73

Max Load

Made in

Trader Truck Hand Turntable Trailer-

Fully welded construction from rectangular and round section steel tube. Metalwork finished in red epoxy. Optional sides finished in light grey epoxy.

- 3 deck sizes
- MDF or steel deck
- Solid rubber or pneumatic tyres
- Removable steel ends and sides option
- Loop handle

End / side panel kit. 200mm high panels. Corner posts fit into steel tubes and lock with simple bolt tightening. Formed steel side and end panels slot onto steel channels, reduces usable length and width by 50mm.

Post socket - remove cap and insert post, then lock by tightening bolt. Sides then simply slot in.



Handle dimensions:

Overall height above deck: 560mm Overall length: Deck length + 240mm

						End / Side P	anel Kit	
Description	DecK Size H x W x D mm	Wheel dia mm	Capacity kg	Weight kg		Weight kg		
MDF Deck with Solid Wheels	425 x 600 x 1200	200	350	37	TR120			
Steel Deck with Solid Wheels	425 X 600 X 1200	200	350	42	TR220			
MDF Deck with Pneumatic Wheels		260		39	TR121P	14	TR126SS	
Steel Deck with Pneumatic Wheels	450 x 600 x 1200	250 44 250 44	500	44	TR221P	14	1812022	
MDF Deck with Solid Wheels	450 x 600 x 1200		500	41	TR121S			
Steel Deck with Solid Wheels			46	TR221S				
MDF Deck with Solid Wheels				78	TR126			
Steel Deck with Solid Wheels			750	94	TR226			
MDF Deck with Pneumatic Wheels			750	55	TR126P			
Steel Deck with Pneumatic Wheels	500 x 750 x 1500			71	TR226P	17		
MDF Deck with Solid Wheels	500 x 750 x 1500			88	TR127	17	TR157SS	
Steel Deck with Solid Wheels		400		104	TR227			
MDF Deck with Pneumatic Wheels		400		65	TR127P			
Steel Deck with Pneumatic Wheels			1000	81	TR227P			
MDF Deck with Solid Wheels			1000	120	TR130			
Steel Deck with Solid Wheels	500 x 1000 x 2000			149	TR230	22	TR201SS	
MDF Deck with Pneumatic Wheels	500 x 1000 x 2000				98	TR130P	22	1820155
Steel Deck with Pneumatic Wheels				127	TR230P			

TR126

Optional extras:

Tee bar handle

Factory fitted at time of manufacture as alternative to loop handle, at no extra cost. Add suffix "T" to reference.



Parking brake

Factory fitted at time of manufacture. Brake is applied when handle is raised to vertical position. Order Ref: PB1 (extra)



<u>j</u>D

Loadtek

Made in

Britain

TR230P &

TR210SS

TR230P

TR230

74

74

Turntable Trailer with Drop Down Side Panels

General purpose hand pulling trailers with steel load retaining panels. Ends are removable and slide out sides are either fully removable or simply fold down. Ends & Sides height: 200mm.

Finish: Blue epoxy chassis, yellow epoxy sides.

- 3 deck sizes
- MDF or steel deck
- Solid rubber or pneumatic tyres
- Loop handle
- Parking brake option



TR126DDS

Handle dimensions:

Overall height above deck: 560mm Overall length: Deck length + 240mm

Description	DecK Size H x W x D mm	End / Side Height mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
MDF Deck with Solid Wheels	425 600 4200		200	250	51	TR120DDS
Steel Deck with Solid Wheels	425 x 600 x 1200		200	350	56	TR220DDS
MDF Deck with Pneumatic Wheels			260		53	TR121PDDS
Steel Deck with Pneumatic Wheels	450 000 4000		260	500	58	TR221PDDS
MDF Deck with Solid Wheels	450 x 600 x 1200		250	500	55	TR121SDDS
Steel Deck with Solid Wheels			250		60	TR221SDDS
MDF Deck with Solid Wheels					95	TR126DDS
Steel Deck with Solid Wheels		200		750	111	TR226DDS
MDF Deck with Pneumatic Wheels					72	TR126PDDS
Steel Deck with Pneumatic Wheels	500 x 750 x 1500	200			88	TR226PDDS
MDF Deck with Solid Wheels	500 x 750 x 1500				105	TR127DDS
Steel Deck with Solid Wheels			400		121	TR227DDS
MDF Deck with Pneumatic Wheels			400		82	TR127PDDS
Steel Deck with Pneumatic Wheels				10.00	121	TR227DDS
MDF Deck with Solid Wheels				1000	142	TR130DDS
Steel Deck with Solid Wheels	500 x 1000 x 2000				171	TR230DDS
MDF Deck with Pneumatic Wheels	500 x 1000 x 2000				120	TR130PDDS
Steel Deck with Pneumatic Wheels					149	TR230PDDS

Optional extras

Tee bar handle

Factory fitted at time of manufacture as alternative to loop handle, at no extra cost. Add suffix "T" to reference.



Parking brake Factory fitted at time of manufacture. Brake is applied when handle is raised to vertical position. Order Ref: PB1 (extra)



Turntable Trailers

TR126TU

Turntable Trailer with Tubular Supports

General purpose hand pulling trailers with tubular load retaining panels. Ends are fixed - sides lift off and are fully removable. Ends & Sides height: 610mm.

Finish: Blue epoxy chassis and ends, Yellow epoxy sides.

- 3 deck sizes
- MDF or steel deck
- Solid rubber or pneumatic tyres
- Loop handle
- Parking brake option





Handle dimensions:

Overall height above deck: 560mm Overall length: Deck length + 240mm

Description	DecK Size H x W x D mm	End / Side Height mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
MDF Deck with Solid Wheels	425 x 600 x 1200		200	350	56	TR120TU
Steel Deck with Solid Wheels	425 X 600 X 1200		200	350	61	TR220TU
MDF Deck with Pneumatic Wheels			260		58	TR121PTU
Steel Deck with Pneumatic Wheels	450 x 600 x 1200		260	500	63	TR221PTU
MDF Deck with Solid Wheels	450 x 600 x 1200		250	500	60	TR121STU
Steel Deck with Solid Wheels			250		65	TR221STU
MDF Deck with Solid Wheels					100	TR126TU
Steel Deck with Solid Wheels		610		750	116	TR226TU
MDF Deck with Pneumatic Wheels					77	TR126PTU
Steel Deck with Pneumatic Wheels	500 x 750 x 1500	010			93	TR226PTU
MDF Deck with Solid Wheels	500 x 750 x 1500				110	TR127TU
Steel Deck with Solid Wheels			400		126	TR227TU
MDF Deck with Pneumatic Wheels			400		87	TR127PTU
Steel Deck with Pneumatic Wheels				1000	103	TR227PTU
MDF Deck with Solid Wheels				1000	147	TR130TU
Steel Deck with Solid Wheels	500 x 1000 x 2000				176	TR230TU
MDF Deck with Pneumatic Wheels	500 x 1000 x 2000				125	TR130PTU
Steel Deck with Pneumatic Wheels					154	TR230PTU

Optional extras

Tee bar handle

Factory fitted at time of manufacture as alternative to loop handle, at no extra cost. Add suffix "T" to reference.



Parking brake Factory fitted at time of manufacture. Brake is applied when handle is raised to vertical position. Order Ref: PB1 (extra)



<u>j</u>

Loadtek



Turntable Trailers

76

SDL

Turntable Trailers with Mesh Cage Supports

Detachable mesh sides. General purpose hand pulling trailers with steel 50×50 mm mesh load retaining panels. Ends are fixed - sides are lift off and fully removable. Ends & Sides height: 760mm high

Finish: Blue epoxy chassis and ends, yellow epoxy sides.

- Fixed mesh ends detachable mesh sides
- 3 deck sizes
- MDF or steel decks
- Front turntable steering with loop handle
- Solid or pneumatic tyres
- Flush MDF deck polyurethane coated
- Parking brake option



Handle dimensions:

Overall height above deck: 560mm Overall length: Deck length + 240mm

Description	DecK Size H x W x D mm	End / Side Height mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
MDF Deck with Solid Wheels	425 x 600 x 1200		200	350	59	TR120MS
Steel Deck with Solid Wheels	425 x 600 x 1200		200	350	64	TR220MS
MDF Deck with Pneumatic Wheels			260		61	TR121PMS
Steel Deck with Pneumatic Wheels	450 000 4000		260	500	46	TR221PMS
MDF Deck with Solid Wheels	450 x 600 x 1200		250	500	63	TR121SMS
Steel Deck with Solid Wheels			250		120	TR226MS
MDF Deck with Solid Wheels					104	TR126MS
Steel Deck with Solid Wheels		760		750	120	TR226MS
MDF Deck with Pneumatic Wheels					81	TR126PMS
Steel Deck with Pneumatic Wheels	500 x 750 x 1500	760			97	TR226PMS
MDF Deck with Solid Wheels	500 x 750 x 1500				114	TR127MS
Steel Deck with Solid Wheels			400		130	TR227MS
MDF Deck with Pneumatic Wheels			400		91	TR127PMS
Steel Deck with Pneumatic Wheels				1000	107	TR227PMS
MDF Deck with Solid Wheels				1000	152	TR130MS
Steel Deck with Solid Wheels	500 x 1000 x 2000				181	TR230MS
MDF Deck with Pneumatic Wheels	500 x 1000 x 2000				130	TR130PMS
Steel Deck with Pneumatic Wheels					159	TR230PMS

Optional extras

Tee bar handle

јП

SDL

Factory fitted at time of manufacture as alternative to loop handle, at no extra cost. Add suffix "T" to reference.

Loadtek



Parking brake Factory fitted at time of manufacture. Brake is applied when handle is raised to vertical position.

Order Ref: PB1 (extra)



N

Made in

Britain

Turntable Trailers



Single Ackerman Trailer with Folding Sides

Heavy duty design with Single Ackerman steering. Sides and tailgate all fold down. Sides are easily removable. Ideal for both garden and industrial use.

Fitted with large 330mm wheels with optional removable canvas lining. Supplied flat pack for easy on site assembly.

Description	Overall W x L mm	Height of Walls mm	Wheel dia mm	Weight kg	Order Ref
4 Mesh Sides	620 x 1470	280	330	30	TR535



Heavy Duty Towing Trailers

Turntable Steering

Good solo manoeuvring in confined spaces. For in-plant operation - maximum towing speed 8 kph (5 mph). Finish: Blue epoxy.

- Fully welded steel chassis.
- Anti-drop tow bar.
- 35mm tow eye rear hitch and pin.
- Flush ply decks sanded and coated.



Rear hitch and pin



Description	DecK Size H x W x D mm	Wheel dia x Tread mm	Capacity kg	Weight kg	Order Ref
Solid Wheels	500 × 1000 × 2000	400 x 100		200	TR601
Solid Wrieels	500 x 1200 x 2400	400 x 100	1000	230	TR611
Pneumatic Wheels	500 x 1000 x 2000	400 x 110	1000	185	TR601P
Pheumatic wheels	500 x 1200 x 2400	400 x 110		215	TR611P
Solid Wheels	515 x 1000 x 2000	400 × 100		220	TR602
Solid Wrieels	515 x 1200 x 2400	400 x 100	2000	250	TR612
Pneumatic Wheels	550 × 1000 × 2000		2000	205	TR602P
Pheumatic wheels	550 x 1200 x 2400	500 x 120		235	TR612P
Solid Wheels	575 x 1000 x 2000	455 x 120		250	TR603
Solid Wrieels	575 x 1200 x 2400	455 X 120	3000	285	TR613
Pneumatic Wheels	720 × 1000 × 2000	610 x 150	3000	235	TR603P
Flieumatic wheels	720 x 1200 x 2400	010 x 150		270	TR613P



Turntable Trailers

78

Trailers



Standard deck height 510mm. Braced and reinforced all steel welded chassis with high quality polyurethane coated ply decks inset and finished flush. Protected all round by steel side frame. Fixed optional headboard complete with drop down sides and tailgate. All with polyurethane coated ply panels.

Wheels: Large 400mm diameter roller bearing wheels with either solid or pneumatic tyres. Finish: Blue epoxy.

Handles

Loop handles are supplied as standard. T bar handles can be supplied at no extra cost. Please specify T bar handle when ordering.

2 Options

- Flat Bed
- Headboard Sides and Tailgate

Turntable Steering

Front axle mounted ball race turntable. Highly manoeuvrable with tight turning circle.







Description	DecK Size H x W x D mm	Wheel dia x Tread mm	Weight kg	Order Ref
Flat Bed with Solid Wheels		400 x 100	112	TR100
End & Side Panels with Solid Wheels	510 x 800 x 1500	400 x 100	142	TR102
Flat Bed with Pneumatic Wheels	510 X 800 X 1500	400 440	85	TR100P
End & Side Panels with Pneumatic Wheels		400 × 110	115	TR102P
Flat Bed with Solid Wheels		400 400	137	TR110
End & Side Panels with Solid Wheels	540 4000 2000	400 × 100	175	TR112
Flat Bed with Pneumatic Wheels	510 x 1000 x 2000	400110	110	TR110P
End & Side Panels with Pneumatic Wheels		400 × 110	148	TR112P





Introducing the GoodsMan Sack Truck Range – Powered by Redhill



The GoodsMan Powered Sack Truck range, designed with precision, handles tough tasks with ease. With over 11 years of proven performance, this robust British-designed solution reduces fatigue, boosts efficiency, and offers a high ROI. It navigates grass, gravel, long distances, and steep slopes, making work easier, faster, and safer.

Key Features & Benefits:

- Effortless Mobility: Ideal for use on Grass, Gravel, Distances and Slopes, easy transport of goods even over deep gravel.
- Safe & Stable: Designed for inclines, maintaining safety even when loaded, mitigating risks.
- Forward and reverse variable drive.
- Proven ROI: Demonstrated high return on investment
- Built to Last: Trusted for over 11 years, delivering long-lasting performance and reliability.
- British Design & Manufacture: Proudly made in the UK, ensuring top quality.
- UK Patent: Protected by a proven UK patent, highlighting its unique design.
- Grab 'n Go Ready: Quick, easy deployment, making it perfect for busy environments.
- Reduces User Fatigue: The powered drive cuts physical effort, boosting workforce efficiency.
- 2-Year Warranty.*
- Battery run time: 1hour continuous use (typically 2-3 miles). Optional upgrade to double run time.

Take your operations to the next level with the GoodsMan Sack Truck range - Powered by Redhill, designed to handle the toughest tasks while keeping your team safe and productive.

Our Most Compact Powered Sack Truck

GoodsMan 400

On just 2 wheels, a massive 400kg transport capacity, this powerful sack truck is built for the most demanding applications in urban environments. Whether moving products from van to door or around your premises, the GoodsMan 400 is safe, versatile and affordable, the ultimate goods delivery solution.

- Lean Angle: Upright
- Supplied without Strap

Model: GoodsMan 400



Britain

82



Optional Extra Ref: MGB-Strap



Battery Power Meter

Throttle handle







Our Most Compact Powered Sack Truck

Powered Sack Truck with Demountable Back Wheel

The GoodsMan L is a significant leap forward for shifting anything from a van to your door, around your premises. Sharing the same attributes as the GoodsMan 400 but benefitting from a capacity of up to 500kg and 12" tyres for better transit over the roughest of terrain. Ideal for Water Cylinders and Tanks. The demountable castor wheel arrangement increases its versatility further.

- Lean Angle: Upright and 65 degrees on support wheel
- Supplied with Strap

Model: GoodsMan L



83







,

Battery Power Meter



Support height adjustment: 60 Overall height on support wheel: 850 to 910 | Overall depth on support wheel: 1400

Description	OverallHxWxDmm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Order Ref
Powered Sack Truck with Demountable Back Wheel	1370 x 610 x 1010	500 x 170	305	500	MGB-L



Powered Sack Truck with Demountable Back Wheel

Mason 3 Wheel Powered Sack Truck



Designed for moving monumental headstones, this machines solves the issue of safely moving masonry. With a capacity of up to 500kg this electric sack truck makes light work of moving your work. It's safe, great over rough terrain, easy to use, versatile and robust. Loading with ramps makes the process fast and efficient. 130 deep notched toe plate with layback angle for stone security, Rubber toe protection, 1000mm high rubber tube protection.

- Lean Angle: 10 degrees Upright and 65 degrees on support wheel.
- Supplied with Strap

Model: GoodsMan M



84







Battery Power Meter

Throttle handle

Support height adjustment: 60

Overall height on support wheel: 850 to 910 | Overall depth on support wheel: 1330

Description	Overall H x W x D mm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Order Ref
Mason 3 Wheel Powered Sack Truck	1370 x 610 x 950	500 x 130 with notch	305	500	MGB-M



Mason 3 Wheel Powered Sack Truck

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Inflatables Powered Sack Truck

Designed for moving any large heavy items such as bouncy castles. Large toe plate and wheel guards with a capacity of up to 500kg, this electric sack truck makes light work of moving your work. It's safe, great over rough terrain, easy to use, versatile and robust.

- Lean Angle: Upright and 65 degrees on support wheel
- Supplied with Strap

Model: GoodsMan B











Battery Power Meter

Throttle handle

Support height adjustment: 60

Overall height on support wheel: 850 to 910 | Overall depth on support wheel: 1400

Description	Overall H x W x D mm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Order Ref
Inflatables Powered Sack Truck	1370 x 610 x 1010	500 x 210	305	500	MGB-B



Inflatables Powered Sack Truck

Tine 2 Wheel Powered Sack Truck

Handle mini pallets not just from the ground but also off another pallet. Sharing the same attributes as the GoodsMan 400 but benefiting mini fork-lift tines that are both height and width adjustable but also can be swapped for a drop on toe-plate. Ideal for small pallets, cable drums and stoves. Supplied with a pair of removable/ adjustable tines and a removable toe plate, which makes this product unique to market.

• Lean Angle: Upright









Battery Power Meter

86

Strap point



Throttle handle

Length of tines: 500mm | N.B - Toe plate capacity: 175kgs

Description	Overall H x W x D mm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Order Ref
Tine 2 Wheel Powered Sack Truck	1370 x 580 x 350	500 x 230 (lift off)	260	300	MGB-T

86

GOODSMAN

Tine 2 Wheel Powered Sack Truck SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Wheelie Bin 3 Powered Sack Truck

Moving heavy 2 wheeled bins is now possible with a fast and versatile GoodsMan W. Food waste applications need a 3rd wheel. Patented 'grab-n-go' bin collection. Parks bin hinge against the wall which negates handling of heavy bins. Made for 240ltr and 360ltr wheeled bins. Drop down spring-loaded foot bar to aid tilting onto 3rd wheel when loaded. Can be adapted for 80ltr & 120ltr.

- Lean Angle: Upright and 55 degrees on support wheel
- Supplied without Strap

Model: GoodsMan W



87







Battery Power Meter

Throttle handle

Overall height on support wheel: 1120 | Overall depth on support wheel: 1020

Description	Overall H x W x D mm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Order Ref
Wheelie Bin 3 Powered Sack Truck	1370 x 580 x 540	No toe plate - Optional POA	260	500	MGB-W



Wheelie Bin 3 Powered Sack Truck

Trader Truck

This modern sack truck is available in blue epoxy finish with a choice





N

Made in Britain

Max Load 200kg





Description	Overall H x W x D mm	Toeplate W x D mm	Frame Width mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels	1100 x 580 x 440	410 × 230 4	100	200	12	ST12
Pneumatic Wheels	1100 x 580 x 500	410 X 230	400	260	13	ST12P

ST12



Stainless Steel Sack Trucks

The Trader Range of Stainless Steel Sack Trucks.

High guality range of sack trucks manufactured from sheet and tube stainless steel. Suitable for use in the food and drink industry. Red centred wheels and solid rubber tyres. Safety hand protectors fitted as standard.



Description	Overall H x W mm	Toeplate W x D mm	Back Frame H x W mm	Wheel dia mm	Weight kg	Order Ref
150kg Capacity	1075 x 485	375 x 150	805 x 370	160	9	ST20SS
200kg Capacity	1175 x 535	420 × 200	965 × 420	200	12	ST21SS



Sack Trucks with Plate Toe



Meticulous build quality in red epoxy finish with a choice of solid or pneumatic tyres. Exceptional value.



]□

SDL





ST22FP

250kg



Description	Overall H x W mm	Toeplate W x D mm	Frame H x W mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
Solid Wheels	1070 x 495	300 x 320	850 x 370	160	150	9	ST20F
Solid Wheels	1185 x 540	300 x 330	960 x 415	200	200	12	ST21F
Solid Wheels	1300 x 610	420 420		200	250	16	ST22F
Pneumatic Wheels	1300 x 680	420 × 420	1070 x 500	260			ST22FP

Loadtek TEL:01446772614

Model ST55 3-Position Truck

Strong and very versatile, these trucks have a multitude of uses. Tubular welded construction. Finish: Blue epoxy.

Wheels: 200mm diameter rubber tyred wheels. Rear Castors: 100mm diameter swivel castors with rubber tyres.







Positive retention in each truck position.

Platform Truck: Effective platform L x H x W mm: 905 x 260 x 420

Description	Platform Truck	4 Wheel Transporter	Sack Truck	Toeplate	Wheel dia	Weight	Order
	Overall H x W x D	Overall H x W x D	Overall H x W x D	W x D mm	mm	kg	Ref
Solid Wheels	750 x 550 x 950	880 x 550 1110	1185 x 550 x 460	420 x 200	200, 100	7	ST55



Super heavy duty. Rectangular section and round tube welded construction. Finish: Blue epoxy

Wheels: 200mm diameter solid, or 260mm diameter pneumatic, rubber tyred wheels. Rear Castors: 125mm diameter swivel castors with rubber tyres and roller bearings.



4 Wheel Transporter





Positive retention in each truck position.

Platform Truck: Effective platform L x H x W mm: ST56: 1085 x 250 x 475 | ST56P: 1085 x 320 x 475

Description	Platform Truck Overall H x W x D	4 Wheel Transporter Overall H x W x D	Sack Truck Overall H x W x D	Toeplate W x D mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels	830 x 480 x 1250	020 400 1170	1250 400 505	200 x 475 200 x 125 23 23	22	ST56	
Pneumatic Wheels		930 x 480 x 1170	1250 x 480 x 585		260, 125	23	ST56P







Max Load 250kg

Made in Britain



3-Position Sack Trucks

Made in

Britain

Max Load 400kg

4 Wheel Transporter

Sack Truck

ST101S

Rough Terrain Truck 6 Model Range



Made for rough ground and tough work. Choose from Solid or pneumatic tyres and 3 toe iron sizes. The large diameter wheels cope with rough and uneven ground with ease. Solid tyred wheels should be chosen if the truck is likely to frequently come in contact with sharp objects. The trucks are heavily built and very strong, coping easily with the maximum load rating of 350kg. Protective handgrips are fitted as standard and this also helps handling over rough terrain. Finish: Blue epoxy.





Loadtek

]□

SDL



Description	Overall H x W x Dmm	Toeplate W x D mm	Frame Width mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels	1140 x 605 x 610	395 x 230	430		29	ST10S
Pneumatic Wheels	1140 x 605 x 610	595 X 250			23	ST10P
Solid Wheels	1140 x 605 x 685	395 x 305 4		355	30	ST101S
Pneumatic Wheels	1140 x 605 x 685			222	24	ST101P
Solid Wheels	1140 COF 020	x 605 x 830 395 x 450			32	ST102S
Pneumatic Wheels	1140 x 605 x 830				26	ST102P

ST102P

91

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Sack Trucks

Max Load

200kg

ST26

Made in

Britain

An original design still meeting today's demands. Originally designed for use in markets, but suitable for many other applications. All models are manufactured from tough welded angle and tube with a one piece toe iron and centre strap for increased load support. Curved back design. Finish: Blue epoxy.

200mm diameter solid rubber or 260mm pneumatic tyred wheels with roller bearing centres. Protective hand grips as standard.



Description	Overall H x W x D mm	Toeplate W x D mm	Frame Width mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels	1170 x 635 x 520	355 x 305	510	200	18	ST26
Pneumatic Wheels	1170 x 635 x 588	355 x 305		260		ST26P
Solid Wheels	1170 x 635 x 672	355 x 450		200	20	ST27
Pneumatic Wheels	1170 x 635 x 740	355 x 450		260	20	ST27P



Euro Loop Handle Trucks

Continuous loop handles give convenient handling at all angles. Wide backs and choice of large fold-up toe or fixed toe plate, make these trucks very versatile. Finish: Blue epoxy.

]□

Loadtek

Mounted on 200mm diameter solid rubber tyred wheels.

Frame Width: 400mm

Description	Overall H x W x D mm	Toeplate W x D mm	Wheel dia mm	Weight kg	Order Ref
Solid Wheels	1150 x 595 x 480	440 255	200	16	ST15
Pneumatic Wheels	1150 x 620 x 510	410 x 255	200	15	ST15P

ST15P

92

92 Sack Trucks

Stairclimber Sack Trucks

Fitted with star wheel system to provide the greatest ease in transporting loads up and down steps and stairways. Large toe folds and locks to frame for compact storage. Model SM22 folds for handy storage and transportation. The star wheel system also helps transportation over rougher terrain making these trucks ideal for locations with variable terrain. Finish: Blue epoxy.

160mm diameter steel centred wheels with roller bearings and rubber tyres.







Description	Overall H x W mm	Toeplate W x D mm	Wheel dia mm	Capacity kg	Weight kg	Order Ref
Flat Back	1090 x 470 x 370	245 x 350	160	110	14	SM12
Folding Back	1090/600 x 470 x 370/720			80		SM22

Made in

Wheel dia mm

160

160

200

SM22

Optional extra

Load Strap: Order Ref: STP1



Loop Handle Stairclimber Sack Trucks

Fitted with star wheel system to provide the greatest ease in transporting loads up and down steps and stairways. The star wheel system also helps transportation over rougher terrain making these trucks ideal for locations with variable terrain. Finish: Blue epoxy.



Overall H x W x D mm

1150 x 595 x 405/810

1150 x 595 x 665

1150 x 595 x 705

Frame Width: 510mm

Description

јП

SDL

Britain	SM16
× ×	

Capacity kg

200

250

125

93





_oadtek

Stairclimber Sack Trucks

Weight kg

19

21

21

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Toeplate W x D mm

330 x 405

420 x 300

420 × 300



A lightweight aluminium sack truck with a large toe plate, ideal for travel, office and shop use.

- Unique design, quick and easy to extend and fold
- Lightweight and simple to operate
- Telescopic handle and folding footplate
- 965mm long elasticated retaining strap supplied
- Durable aluminium frame
- · Occupies very little space when folded / collapsed
- Fitted with rubber cushion wheels

Description	Open H x W x D mm	Folded H x W x D mm	Toeplate W x D mm	Wheel dia mm	Order Ref
60kg Capacity Sack Truck	1010 × 400 × 390	645 x 385 x 65	387 x 279	125	ST92



90kg - Telescopic Folding Sack Truck

A truck designed to transport small goods / parcels in almost any environment.

- Lightweight aluminium
- Collapses in overall size for compact storage
- Telescopic handle
- Folding footplate
- Fitted with rubber cushion wheels

Description	Open H x W x D mm	Folded $H \times W \times D$ mm	Toeplate W x D mm	Wheel dia mm	Order Ref
90kg Capacity Sack Truck	1105 × 400 × 410	740 × 400 × 180	355 x 240	150	ST91

100kg - Telescopic Folding Sack Truck

A lightweight aluminium sack truck with a large toe plate (485 x 385mm) and carrying capacity of 100kg.

- Telescopic handle and folding footplate
- 1500mm long elasticated retaining strap supplied
- Durable aluminium frame
- Occupies very little space when folded / collapsed
- Fitted with rubber cushion wheels



Description	Open H x W x D mm	Folded $H \times W \times D$ mm	Toeplate W x D mm	Wheel dia mm	Order Ref
100kg Capacity Sack Truck	1080 x 500 x 520	800 x 500 x 60	485 x 385	175	ST93

125kg - Telescopic Folding Sack Truck

A lightweight aluminium sack truck with a large toe plate (485 \times 350mm) and carrying capacity of 125kg.

- Telescopic handle and folding footplate
- 1500mm long elasticated retaining strap supplied
- Durable aluminium frame
- Occupies very little space when folded / collapsed
- Fitted with rubber cushion wheels





Description	Open H x W x D mm	Folded H x W x D mm	Toeplate W x D mm	Wheel dia mm	Order Ref
125kg Capacity Sack Truck	1110 x 520 x 510	770 x 500 x 65	485 x 350	175	ST94

200kg - Telescopic Folding Sack Truck

Ideal for heavier applications such as shops, stores, smaller warehouses and delivery vehicles with a large toe plate and carrying capacity of 200kg.

- Additional fold out handles for increased operating functionality
- 1500mm long elasticated retaining strap supplied
- Durable aluminium frame
- Occupies very little space when folded / collapsed
- Fitted with rubber cushion wheels



Description	Open H x W x D mm	Folded $H \times W \times D$ mm	Toeplate W x D mm	Wheel dia mm	Order Ref
200kg Capacity Sack Truck	1125 x 600 x 600	900 x 595 x 97	590 x 390	200	ST95

Folding Sack Trucks

95

Folding Sack Trucks 95

Tilting Skip Bin

Choice of two capacities – 200kg (200 litres) or 400kg (260 litres). Fabricated sheet steel body mounted on square frame chassis. Reinforced body rim. No sharp edges. Handle for pushing and load dumping. Load will not tip until retaining latch is released by the operator. Welded fork guides are available as an option. Finish: Blue epoxy.

Wheels: 200mm diameter axle mounted front wheels with single 200mm diameter rear swivel castor, fitted with solid rubber tyres and roller bearings.









Loose fitting perforated base and drain tap.

Description	Overall H x W x D mm	Body size H x W x D mm	Wheel dia mm	Weight kg	Order Ref
200kg (200 litres) Capacity	790 x 850 x 1175	525 x 580 x 1050	200	68	SB08
400kg (260 litres) Capacity	970 x 900 x 1320	700 x 630 x 1200	200	78	SB10

Including perf. base & drain tap				
Description	Order Ref			
200kg (200 litres) Capacity	SB08DT			
400kg (260 litres) Capacity	SB10DT			

Fork lift pockets (factory fitted extra) 125 x 40mm				
Description	Order Ref			
200kg (200 litres) Capacity	SB/FP			
400kg (260 litres) Capacity	SB/FP			

Optional extra

Total stop brake on single swivel castor. **Ref: B013/1**





Mobile Tray Racks

Rack construction: Welded square section steel tube construction with formed tray supports and steel top cover. Metal strap prevents trays being pushed through when loading. Finish: Blue epoxy coated.

Complete with specified Euro Container Box Trays external dimensions L x W 600 x 400mm.

Wheels: 4 swivel castors with 100mm diameter nylon wheels.



 \mathbf{N}

Description	Overall H x W x D mm	Tray H x W x D mm	Wheel dia mm	Weight kg	Order Ref
6 x PC005 Trays	1100 x 525 x 700	120 × 400 × 600	100	38	CT206
8 x PC005 Trays	1405 x 525 x 700			46	CT208
10 x PC005 Trays	1710 x 525 x 700			53	CT210

Optional extra Total stop brakes Ref: B103



For additional trays, please see page 102

Mobile Tray Racks



200kg



Rack construction: Welded square section steel tube construction with formed tray supports and steel top cover. Metal strap prevents trays being pushed through when loading. Finish: Blue epoxy coated.

Complete with specified Euro container box trays external L x W 600 x 400mm.

Wheels: 4 swivel castors with 100mm diameter nylon wheels.





Description	Overall H x W x D mm	Tray H x W x D mm	Wheel dia mm	Weight kg	Order Ref
6 x PC020 Trays	1420 x 525 x 700	170 x 400 x 600	100	42	СТ506
8 x PC020 Trays	1830 x 525 x 700			51	СТ508
4 x PC053 Trays	1250 x 525 x 700	200 x 400 x 600		37	СТ604
6 x PC053 Trays	1780 x 525 x 700			49	СТ606

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Optional extra Total stop brakes Ref: B103 For additional trays, please see page 102



Loadtek



Mobile Tray Racks

A versatile range of mobile steel racks. Welded square section steel tube construction with formed tray supports. Supplied complete with grey. Finish: Red epoxy.

European 600 x 400mm plastic containers. Trays: 21 litre solid grey containers.

Wheels: All swivel castors with 100mm diameter nylon wheels.

Description	Overall H x W x D mm	Tray H x W x D mm	Wheel dia mm	Weight kg	Order Ref
2 x 5 Trays	945 x 650 x 955	120 x 400 x 600	100	50	CT405
6 Trays	1100 x 650 x 525			33	CT406
8 Trays	1405 x 650 x 525			41	CT408
10 Trays	1710 x 650 x 525			48	CT410

Optional extra Total stop brakes Ref: B103





Mobile Tray Racks

Supplied with white non-toxic polyethylene food grade trays. All welded angle construction. Plastic trays slide onto fixed metal tray supports. Metal strap prevents trays being pushed through when loading. Optional steel top cover. Finish: Red epoxy.

Wheels: 4 swivel castors, white nylon 100mm diameter wheels

Tray specification: All round grip. Solid base and sides. Thermal resistance: -30°C to +60°C, washable up to 110°C. External H x W x L: 80 x 450 x 754mm Internal H x W x L: 68 x 412 x 717mm

Alternative sizes or models to suit customers own containers available on request.

Description	Overall Height mm	Overall Floor Area mm	Wheel dia mm	Weight kg	Order Ref
6 Trays	895	780 x 530	100	36	CT306
8 Trays	1120	780 x 530		45	CT308
10 Trays	1330	780 × 530		53	CT310
12 Trays	1555	780 × 530		62	CT312
16 Trays	2005	780 x 530		74	CT316

Optional extra Total stop brakes Ref: B103

SDL

Additional Trays **Ref: PC004 (single tray)**



Top Cover sheet steel (factory fitted) Weight: 5kg **Ref: CT3**



98

Plastic Container Systems

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Small Parts Storage Tray Racks

Rack construction: Welded square section steel tube construction with formed tray supports. Metal

strap prevents trays from being pushed through when loading.Finish: Blue epoxy. Complete with

Wheels: 4 swivel castors with 100mm diameter

specified Euro Container Box Trays.

nylon wheels and roller bearings.



CT226

CT16



Description Overall H x W x D mm Tray H x W x D mm Wheel dia mm Weight kg 12 Trays 945 x 650 x 955 29 120 × 300 × 400 100

Optional extra Total stop brakes Ref: B103

24 Trays



1100 x 650 x 525

Ref: PC023 (single tray)



Small Parts Storage Tray Racks

Rack construction: Welded square section steel tube construction with formed tray supports. Metal strap prevents trays from being pushed through when loading.Finish: Blue epoxy. Complete with specified Euro Container Box Trays.

Wheels: 4 swivel castors with 100mm diameter nylon wheels androller bearings.





49

Description	Overall H x W x D mm	Tray H x W x D mm	Wheel dia mm	Weight kg	Order Ref
Empty		None		25	CT270
10 Trays		10 Trays:120 x 400 x 600		N/A	CT271
8 Trays	1725 x 500 x 650	3 Trays: 120 x 400 x 600 4 Trays: 175 x 400 x 600 1 Tray: 75 x 400 x 600	100	N/A	CT272

Optional extra Total stop brakes Ref: B103

For additional trays, please see page 102



Loadtek

Plastic Container Systems

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

N

Made in Britain

KG

Max Load 200kg

CT91-2



Rack construction: Welded square section steel tube construction with welded cross braces adding durability. Trays angled to help access products stored. Finish: Blue epoxy coated. Supplied with or without Euro Containers L x W 600 x 400mm in single or double bays

Wheels: 2 swivel and 2 swivel braked 100mm diameter wheels



Description	Overall W x D mm	Tray H x W x D mm	Wheel dia mm	Order Ref
8 x PC005 Trays	000000	120 × 400 × 600		CT90-1
8 x PC020 Trays	820 x 660	170 × 400 × 600	100	CT90-2
16 x PC005 Trays	220 1220	120 x 400 x 600	100	CT91-1
16 x PC020 Trays	820 x 1320	170 × 400 × 600		CT91-2



Mobile Tray Racks

Welded tubular and angle frame construction. Swivel tiers can be tilted 15° or 30° in either direction Finish: Blue epoxy

Wheels: 2 fixed and 2 swivel castors with 125mm diameter rubber tyred wheels, roller bearings.

CT06



Frame levels: 200; 700; 1200mm

Description	Overall H x W x D mm	Construction	Wheel dia mm	Weight kg	Order Ref
3 x drop-in ply shelves		3 fixed tiers	125	24	СТ04
3 x drop-in grey trays (PC005)	1200 x 470 x 915	3 fixed tiers		28	СТ05
3 x drop-in grey trays (PC005)		1 fixed, 2 swivel tiers		30	СТ06

Optional extras: Brakes: Total stop Ref: B032

Additional Grey Trays Ref: PC005





Plastic Container Systems

SDL

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Euro Dolly



Euro Dolly with optional tug handle. Finish: Blue epoxy. Designed to carry European 600 x 400mm containers in any combination of heights. Containers are NOT included. For containers, please see page 102.

Wheels: 4 swivel castors with 125mm diameter wheels, solid rubber tyres and roller bearings.





Description	Overall H x W x D mm	Tray W x D mm	Wheel dia mm	Weight kg	Order Ref
Euro Dolley	195 x 415 x 640	400 × 600	125	12	CT408

Optional extra Euro Dolly Handle Ref: TD804



Total stop brakes (extra) Ref: B032



Euro Trolley

Finish: Blue epoxy.

Wheels: 2 fixed and 2 swivel castors with 160mm diameter wheels, solid rubber tyres and roller bearings.





Description	Overall H x W x D mm	Wheel dia mm	Weight kg	Order Ref
Euro Trolley	985 x 615 x 950	160	24	CT81

Optional extra

]□

SDL

Total stop brakes (extra) Ref: B024

Loadtek





Max Load 350kg Made in Britain

Euro Containers



Robust grey plastic containers that can interstack modularly with various sizes. Ideal for protective storage during transportation of goods.

Lids and dollies can be supplied separately. All containers and accessories are manufactured from high-density food grade polypropylene which has a temperature resistance from -5°C to +70°C.

Size ltr	External D	Dimensions	mm	Internal Dimensions mm		Individual	Pallet Quantity		
Size iti	Length	Width	Height	Length	Width	Height	Order Ref	No. on Pallet	Pallet Order Ref
5	300	200	120	260	160	110	PC050	288	PC050/288
10	400	300	120	356	256	110	PC023	144	PC023/144
20	400	300	220	356	256	211	PC051	104	PC051/104
22	600	400	120	555	358	105	PC005	72	PC005/72
27	600	400	150	560	255	138	PC052	56	PC052/56
30	600	400	170	560	360	157	PC020	52	PC020/52
40	600	400	200	552	353	185	PC053	44	PC053/44
52	600	400	270	560	358	257	PC021	32	PC021/32
60	600	400	320	552	353	304	PC022	36	PC022/36

Attached Lid Containers

These high quality Attached Lidded Euro Containers can be stacked when the lid is closed or nested to save space when not in use and lid is open. They allow for 'locking' by way of cable ties or similar when high value goods are stored and include a label \ card holder for ease of identification. They are manufactured from high-density food grade polypropylene which has a temperature resistance from -5°C to +70°C.



Size Itr	External Dimensions mm		Internal Dimensions mm				Pallet Quantity		
	Length	Width	Height	Length	Width	Height	Order Ref	No. on Pallet	Pallet Order Ref
56	600	400	310	547	365	280	PC019	85	PC019/85
65	600	400	365	547	365	345	PC016	85	PC016/85
77	600	400	400	547	365	380	PC017	85	PC017/85



102

B R Y GN

Plastic Containers

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Semi-open Fronted Containers

A simple and effective small parts storage system for a wide range of materials. Manufactured from polypropylene, can be stacked or used with louvre panels, cabinets and shelving systems. Containers can be manufactured in specific brand colours for high volume users.

- Strong, heavy duty with reinforced base, sides and stacking rim
- · Durable and resistant to most industrial solvents
- Capable of withstanding a temperature range of -15°C to +50°C
- Smooth inside faces guard against build of grease
- Index card slot for identification labels (not supplied)
- Available in 6 sizes and 4 colours as standard



Description	Length Width		Height	Pack Quantities		Pallet Quantities	
	mm	mm	mm	No. Per Pack	Order Ref	No. Per Pallet	Order Ref
No.2	165	100	75	20	PC101	90	PC101/90
No.3	240	150	132	10	PC102	54	PC102/54
No.4	350	205	132	10	PC103	25	PC103/25
No.5	350	205	182	10	PC104	20	PC104/20
No.6	375	420	182	5	PC105	20	PC105/20
No.7	520	310	200	5	PC106	16	PC106/16

Wall Mounted Louvre Panels

Featuring the unique double indented louvre for extra strength, this system offers the ideal solution for wall mounting and many other applications for TC containers and accessories. 2 imperial sizes available. Precision formed and finished in a grey epoxy powder coating.



Description	Overall H x W	Order Ref
Louvre Panel	438 x 457	WP50
Louvre Panel	946 x 457	WP52

Colour Options GN R B Y



Floor Standing Louvre Panels

Single or double sided freestanding storage units available in 3 heights for increased storage capacity when using TC containers and accessories. Units are finished in blue epoxy powder coating (other colours are available) with silver / grey feet.

For large application order one starter bay and the appropriate number of add on bays to make this a complete solution to suit individual requirements. Heavy duty adjusters permit levelling on uneven surfaces.

Description	Overall H x W x D mm	Starter Bay Ref	Add on Bay Ref
	1100 × 1000 × 500	LPT20	LPT30
Single sided	1600 × 1000 × 500	LPT21	LPT31
	2100 × 1000 × 500	LPT22	LPT32
	1100 x 1000 x 750	LPT23	LPT33
Double sided	1600 × 1000 × 750	LPT24	LPT34
	2100 x 1000 x 750	LPT25	LPT35



Louvre Panel Trolleys

'A' frame double sided louvre panel trolleys with integral sheet steel deck storage area. Fully welded steel frame construction with bolt-on louvre panels. Tubular push/pull handle. Available in 2 heights (2 or 3 panels). Finish: Grey epoxy frame (BS00A05) with blue panels (RAL5017).

Wheels: 2 swivel braked and 2 fixed castors fitted with 125mm blue resilex wheels and roller bearings.



Loadtek

<u>j</u>D

Description	Overall H x W x D mm	Deck Height mm	Bins Included	Wheel dia mm	Order Ref
2 Denell link	1200 000 1000		None		LPT-12
2 Panel High	1200 x 600 x 1000	205	72 x XL2 & 36 x XL3	125	LPT-12C
2 Depail Link	1600 × 600 × 1000		None		LPT-13
3 Panel High			108 x XL3		LPT-13C

For additional containers see page 103









SDL

N

Max Load 50kg

Multi-Trip Container Trolley

To carry 2 x 54ltr multi-trip containers (containers extra).

Welded tubular steel construction.Finish: Blue Epoxy.

Wheels: 4 x 125mm diameter swivel castors fitted with grey non-marking tyres.



Description	Overall H x W x D mm	Wheel dia mm	Weight kg	Order Ref
Trolley Without Containers	1010 x 420 x 952	125	12	CT03

Attached Lid Containers



Container Carrier Trolley

To carry 2 x 50ltr containers without lids (containers extra).

Welded tubular steel construction. Finish: Blue epoxy.

Wheels: 4×125 mm diameter swivel castors fitted with grey non-marking tyres.

Description	Overall H x W x D mm	Wheel dia mm	Weight kg	Order Ref
Trolley Without Containers	940 x 440 x 1180	125	14	CT07

Containers

Capacity	Internal	External	Weight	Order
Itr	L x W x H mm	L x W x H mm	kg	Ref
50	270 x 460 x 340	300 × 600 × 400	2.3kg	PC070



Steel clipboard (factory fitted) Blue epoxy finish **Ref: T07**

Loadtek





Max Load

50kg



105



Plastic Container Trucks

Capacity 360 litres. Welded steel angle construction with steel tube side bars to hold containers. Finish: Blue or red epoxy (to match container colour).

Wheels:

Standard wheels: 2 fixed and 2 swivel castors with 160mm diameter rubber tyred wheels with roller bearings.

Balance Configuration: (highly manoeuvrable): 2 fixed and 2 swivel castors with 160mm diameter rubber tyred wheels with roller bearings.

Container Bins:

Red or blue, polyethylene, non-food quality with smooth snag-free interiors; suitable for general products including clothing and textiles. Containers are removable and stackable when empty (containers are also available separately).

Temperature range -10° to +60°c.

Internal dimensions L x W x H: 930 x 640 x 610mm. External dimensions L x W x H: 1040 x 730 x 615mm.



CT82

N

Made in

Britain





Description	Overall H x W x D mm	Colour	Wheel dia mm	Weight kg	Order Ref
Standard wheels	1040 x 730 x 810	Blue	160	22	CT82
		Red			CT88
Balance wheels		Blue	160	32	CT87
		Red			СТ89

Bins





Total stop brakes (extra) Not available for Balance Wheels Ref: B024



SDL



Loadtek

106

CT48

CT47

PC022

PC053

M

PC020

PC005

107

Container Shelf Trolleys

A versatile range designed for 600 x 400mm Euro containers and / or open fronted yellow stock boxes. Use your own containers or choose from the selection below. Trolley: welded steel tube & angle construction

CT47 - Capacity: 400kg UDL.

4 standard 600 x 400mm Euro containers per shelf (containers not included). Finish: Blue epoxy.

Please note: Open style shelves not shelf, and is designed to hold Euro Containers only.

Wheels: 2 fixed and 2 swivel, 160mm diameter rubber tyred wheels with roller bearings.

CT48 - Capacity: 350kg UDL.

3 standard 600 x 400mm Euro containers per shelf (containers not included). Finish: Red epoxy with varnished plywood shelves.

Wheels: 2 fixed and 2 swivel, 160mm diameter rubber tyred grey non marking wheels with roller bearings.

CT49 - Capacity: 400kg UDL.

Accepts 2 standard 600 x 400mm Euro containers, or 6 yellow stock boxes per shelf (containers not included. Finish: Red epoxy with varnished plywood shelves.

1 400 مانه ما ما ب Wheels: 2 fixe marking whe

Description	Overall H x W x D mm	Shelf W x D mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
400kg Capacity	11315 x 615 x 1730	N/A	235, 595, 955, 1315		75	CT47
350kg Capacity	1410 x 650 x 1245	600 x 1215	235, 595, 955, 1515	160	63	CT48
400kg Capacity	1410 x 450 x 1245	405 x 1215	245, 520, 805, 1090		51	CT49

Containers

Plastic containers, available in packs, suitable for trolleys above.

Suit models: CT46; CT47; CT48 & CT49

Description	Overall W x D mm	Internal Height mm	External Height mm	Capacity Itrs	Weight kg	Order Ref
Dark Grey Euro Container		105	118	21	1.5	PC005
Dark Grey Euro Container		164	175	33	1.87	PC020
Dark Grey Euro Container	400 × 600	185	200	45	2.25	PC053
Dark Grey Euro Container		300	319	60	2.73	PC022
Euro Red Boxes		300	320	60	2.73	PC006

CT47

_oadtek

јП

SDL

Plastic Container Systems

	swivel, 160mm diameter Iler bearings.	rubber tyred grey non		•		
	Overall H x W x D mm	Shelf W x D mm	Shelf Heights mm	Wheel dia mm	Weight kg	Order Ref
icity	11315 x 615 x 1730	N/A	225 EOE OEE 1215		75	СТ47
city	1410 × 650 × 1245	600 x 1215	235, 595, 955, 1315	160	63	CT48
city	1410 × 4E0 × 124E	10E × 121E	24E E20 80E 1000		51	СТИЯ





Access Platform

For use with forklift trucks. Manufactured according to Health and Safety executive guidance note PM28 (3rd edition) December 2005. Approved to be used by 2 persons of average weight - max total load capacity 350kg. Finish: Yellow epoxy.

The Access Platform has been designed to provide easier access for your maintenance, repair and installation requirements.

Fully welded with a raised expanded metal floor, located and welded into a formed kickboard surround. Tubular handrail and rear RSA frame with wire mesh panels. Hinged entry gate with spring return to closed position a spring loaded retention bolt holds the gate in the closed position.

Platform locks onto the lift truck forks with threaded screw jacks.

Important ordering requirements

In the interests of safety, we do not specify standard fork location details. Platform must be manufactured to your forklift truck specification.

On all orders please specify:

- 1. Length of fork
- 2. Width and depth (cross section) of fork
- 3. Maximum standard distance between forks



Fork heel lock and screw jack.

Raised gate lock and slam bolt.

1925 x 1020 x 1020 1000 x 1000 1010 510 78 ASP1	Overall H x W x D mm	Platform Size W x L mm	Handrail Height: mm	Gate Width mm	Weight kg (approx.):	Order Ref
	1925 x 1020 x 1020	1000 x 1000	1010	510	78	ASP1

Optional accessories

Castors - 2 swivel, 2 fixed castors, 100mm diameter. nylon wheels. Provides for ease of movement and storage independent of forklift truck. Increases height by 125mm Ref: ASP4



Tool Tray - Welded tool tray hooks onto front guard rail. Complete with locking screws. L x W x D : 1000 x 200 x 200mm. Weight: 10kg





Loadtek

<u>j</u>D



108

108

SDL
Rolling Corners

Max Load Made in Britain

Sold in sets of 4, rolling corners allow large items to be moved with little effort. Manufactured from formed and welded sheet steel, platforms fitted with 3mm thick black ribbed rubber matting. Metalwork finished in high quality powder coating.

Wheels: 3 castors, all swivel with 50mm wheels with grey non marking rubber tyres.

IMPORTANT: Weight must be evenly distributed on the four corners.







RMD1

109

Description	Overall H x W x L mm	Platform Height mm	Capacity kg (over 4 corners)	Wheel dia mm	Weight kg (set of 4)	Order Ref
Grey Epoxy Finish	75 200 200	20	400	50	8	RMD1
Orange Epoxy Finish	75 x 300 x 300	20	600	50	10	RMD2

Roller Platforms

Unique, tough and versatile. A heavy load shifter fitted with 3 heavy duty swivel castors housing white nylon wheels 50mm diameter.

Steel deck with ribbed rubber pad.





Description	Side Lengths mm	Platform Height mm	Capacity kg (over 4 corners)	Wheel dia mm	Weight kg (set of 4)	Order Ref
Yellow Epoxy Finish	300 x 300 x 300	90	500	50	10	RMD3





Rolling Corners and Platforms



Book Trolleys

Max Load Made in 250kg Britain



Popular design for libraries, offices, classrooms, laboratories etc. Single sided with flat shelves and double sided with angled shelves Strong all steel construction finished in cream epoxy. Overall L x W: 840 x 470mm.

Fitted with 4 swivel castors 100mm, grey non-marking tyres & thread guards.









Description	Overall H x L x W mm	Platform Size L x W mm	Shelf Heights mm	Weight kg	Order Ref
Double Sided, 2 Tier Trolley	185 x 655	1000 × 600	52	35	TT21
Double Sided, 3 Tier Trolley	185 x 600 x 1020		56	46	TT22
Single Sided, 2 Tier Trolley	185 x 580		42	27	TT24
Single Sided, 3 Tier Trolley	185 x 540 x 895		46	38	TT25

Colour Options	R	В	Y	GN	
4 handle frame colours, ideal for job or location coding.					

Optional extras Total stop brakes: Ref: B052 (pair)



Max Load 250kg

Book Trolley

<u>]</u>

SDL

₋oadtek

Popular design for libraries, offices, classrooms and laboratories.

Double sided with angled shelves. Tubular steel frame with sheet steel shelves.

Fitted with 4 swivel castors 125mm, grey non-marking tyres and thread guards.





Ref: B047 (pair)



Ref: B172 (set)

111





Stacking Chair Dolly

Features a skid base design that easily facilitates stacked chairs. Sturdy and strong folded sheet steel design. Finish: Black epoxy.

Wheels: Mounted on 2 swivel braked and 2 fixed castors fitted with 100mm polyurethane tyred wheels and roller bearings.

Maximum Chair Stack: 24

	Height mm Wheel dia mm	Weight kg	Order Ref
420 × 550 × 650 790 × 500 × 500 460	100	16	PRIN-20



Universal Table Trolley

Designed to carry either folding round tables using centre open tubular support, or folded rectangular tables using the MDF board platform at both ends of trolley.

Heavy duty design manufactured from steel box section, tube and bar. Tubular support rails are covered with protective plastic sheaths. Supplied with handles removed and with easy to assemble instructions, complete with retaining bars. Finish: Black epoxy.

Wheels: Mounted on 2 swivel braked and 2 swivel castors fitted with 100mm polyurethane tyred wheels and roller bearings.



Overall H x W x D mm	Wheel dia mm	Weight kg	Order Ref
1260 x 520 x 1830	100	42	PRIN-19



112

Chair Dolly / Table Trolley

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Made in Britain

Transport Trolley



Wheels: Mounted on all swivel castors fitted with 75mm grey non-marking wheels and roller bearings.

Maximum Chair Stack: 40





Overall H x W x D mm	Height When Fully Loaded mm	Chair Overall Size H x W x D mm	Wheel dia mm	Weight kg	Order Ref
1255 x 485 x 1130	1500	820 x 450 x 550	75	11	PRIN-4

Upright Chair Truck

Designed to carry folded chairs in the vertical position. Sturdy folded sheet steel and tubular design. Supplied with handles removed and with easy to assemble instructions, complete with retaining strap. Finish: Black epoxy.

Wheels: Mounted on 2 swivel (1 braked) and 2 fixed castors fitted with 100mm polyurethane tyred wheels and roller bearings.







Overall H x W x D mm Chair Size H x W x D mm Height When Fully Loaded mm Wheel dia mm Weight kg 1100 x 520 x 1530 870 x 470 x 540 (Vertical) 1250 100 29 PRIN-14



Loadtek

Chair Trolleys

Hanging Chair Storage Trolleys

Designed to carry either folding round tables using centre open tubular support, or folded rectangular tables using the MDF board platform at both ends of trolley.

Heavy duty design manufactured from steel box section, tube and bar. Tubular support rails are covered with protective plastic sheaths. Supplied with handles removed and with easy to assemble instructions, complete with retaining bars. Finish: Black epoxy.

Wheels: Mounted on 2 swivel braked and 2 swivel castors fitted with 100mm polyurethane tyred wheels and roller bearings.



114



PRIN-L2





PRIN-L3



Tubular Hanging Rails Length: 550mm Tubular Hanging Rails Centres: 330mm

Description		Number of Rows	No. of chairs stored		Wheel dia		Order
			Padded	Plastic	mm	kg	
Low Hanging Storage Trolley	1145 x 1135 x 1250	2	36	68		40	PRIN-L2
Low Hanging Storage Trolley	1145 x 1135 x 1750	3	54	102	100	44	PRIN-L3
High Hanging Storage Trolley	1145 x 1135 x 1250	2	72	136		62	PRIN-H2
High Hanging Storage Trolley	1145 x 1135 x 1750	3	108	204		66	PRIN-H3



Chair Trolleys

N

Made in Britain

Max Load **150kg**

Chair Shifters



Wheels: 200mm diameter solid rubber or 260mm diameter pneumatic.



Description	Overall H x W x D mm	Base Pan W x D mm	Overall Frame Height mm	Wheel Type	Wheel dia mm	Weight kg	Order Ref	
Bar Handle with Sandstone epoxy finish	1300 x 590 x 380	585 x 155		Solid tyres	200	12	ST81	
Bar Handle with Sandstone epoxy finish	1300 x 590 x 420		1295	Pneumatic	260	13	ST82	
Loop Handle with Blue epoxy finish	1300 x 590 x 380		582 X 122	1295	Solid tyres	200	12	ST83
Loop Handle with Blue epoxy finish	1300 x 590 x 440			Pneumatic	260	13	ST84	

Stairclimbing Chair Shifter

The Stairclimbing Chair Shifter is fitted with a star wheel system designed to climb stairs, enabling chairs to be moved easily and efficiently from one level to another.

The wheels are fitted with solid tyres, which also helps to facilitate transportation over rough ground. Steel pan base takes the rear legs of the chairs.

Finish: Blue epoxy.





Overall H x W x D mm	Base Pan W x D mm	Overall Frame Height mm	Wheel Type	Weight kg	Order Ref
1300 x 590 x 500	585 x 155	1295	Solid tyres	18	SM31





Racking Upright Protectors

Racking end protection barriers manufactured from formed 4mm mild steel. 400mm high and brightly epoxy coated yellow finish.

Rack protection must be bolted to the floor (fixings not supplied). 'L' shaped protector gives protection to the end and front of the upright, 'U' shaped protector gives protection to the front and both sides of the upright.

Internal clearance on the 'U' shaped protector: 155mm.



Description	Overall H x W x D mm	Order Ref
U-Shape upright protector only	406 × 250 × 290	REP-1
L-Shape upright protector only	406 x 195 x 195	REP-2

Racking End Protector Kits

Specification as Racking Upright Protectors above, but supplied with formed sheet steel connection beam.



	\mathbf{X}
PEP-2/930	
REF-2/950	1



Description	Overall H x W x D mm	Kit length (internal) mm	Order Ref
U-Shape	427 × 1020 × 290	930	REP-1/930
	427 x 1220 x 290	1130	REP-1/1130
	427 x 2120 x 290	2030	REP-1/2030
	427 x 2520 x 290	2430	REP-1/2430
L-Shape	427 x 1025 x 195	930	REP-2/930
	427 x 1225 x 195	1130	REP-2/1130
	427 x 2125 x 195	2030	REP-2/2030
	427 x 2525 x 195	2430	REP-2/2430



Loadtek

117

V

Protective Posts and Bollards

Ideal for traffic areas such as loading areas, protects racking and warehouse assets from damage.

Powder coated Yellow, Black or Black & Yellow stripe.

Heavy duty fully welded design, supplied with floor fixings.





118



Description	Overall H x D mm	Order Ref
	760 x 90	PP-1/YB
Yellow / Black	915 x 115	PP-2/YB
	1100 x 150	PP-3/YB
	760 x 90	PP-1/B
Black	915 x 115	PP-2/B
	1100 x 150	PP-3/B
	760 × 90	PP-1/Y
Yellow	915 x 115	PP-2/Y
	1100 × 150	PP-3/Y



118Protective Posts and Bollards

Handrail Barrier

The barrier is manufactured from 51mm diameter heavy duty form ERW steel tube. 4mm thick sheet steel feet complete with holes for floor fixings (fixings not supplied). Brightly epoxy coated yellow finish.

Barrier Length mm	Overall Height mm	Order Ref
1000		BAR-1
1530	075	BAR-2
2060	975	BAR-3
2600		BAR-4

BAR-3

Low Level Warehouse Barriers

Ideal for protecting machinery & racking columns. Heavy duty fully welded steel box section, powder coated yellow or black with floor fixings supplied.





Description	L x H mm	Yellow Order Ref	Black Order Ref
Corner	300 x 300	LLB-4/Y	LLB-4/B
Straight	400 x 300	LLB-1/Y	LLB-1/B
Straight	800 × 300	LLB-2/Y	LLB-2/B
Straight	1200 x 300	LLB-3/Y	LLB-3/B



Loadtek

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

V

Made in Britain

N

Made in Britain



Walkway Barriers KD

Suitable for indoor use, modular design with lift out rails to allow access when required. Supplied in knock down format for easy on-site assembly. (Floor fixings not supplied)

Lift Out Barrier Rails - supplied as a pair

Gate Dimensions: H 520mm (Overall 556mm with clips) x W 785mm

Manufactured from tough mild steel box section, powder coated yellow.

BAR-2000



120







BAR-21











Description	Overall H x W mm	
End Post	1100 x 80	BAR-20
Corner Post	1100 x 80	BAR-21
Centre Post	1100 x 80	BAR-22
Modular Gate	556 x 785	BAR-23





Walkway Barriers KD

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Walkway Barriers

Walkway Barriers Fully Welded

Ideal near work areas, machinery and factory equipment. Protect staff by identifying walkways. Add mesh to increase layer of protection

Powder coated yellow, supplied with floor fixings.















Description	Overall H x L mm	Order Ref
	900 x 1200	BAR-30/90/Y
Straight Barrier	900 x 2400	BAR-31/90/Y
	1100 x 1200	BAR-30/11/Y
	1100 x 2400	BAR-31/11/Y
Corner Barrier	900 x 1200	BAR-32/90/Y
	1100 x 1200	BAR-32/11/Y
	900 x 1200	BAR-40/90/Y
Straight Darrian with Mach	900 x 2400	BAR-41/90/Y
Straight Barrier with Mesh	1100 x 1200	BAR-40/11/Y
	1100 x 2400	BAR-41/11/Y
Corner Barrier with Mesh	900 x 1200	BAR-42/90/Y
Comer barner with Mesh	1100 x 1200	BAR-42/11/Y

Description	Overall H x L mm	Order Ref
Gates without Mesh	900 x 900	BAR-33/90/Y
	900 x 1200	BAR-34/90/Y
	1100 x 900	BAR-33/11/Y
	1100 x 1200	BAR-34/11/Y
	900 x 900	BAR-43/90/Y
Color III Mark	900 x 1200	BAR-44/90/Y
Gates with Mesh	1100 x 900	BAR-43/11/Y
	1100 x 1200	BAR-44/11/Y



HSP-1

Pedestrian Snow Ploughs

This bi-directional snow plough makes it simple and easy to clear your driveway and sidewalks in half the time with half the effort needed for conventional shovelling. Manufactured from mild steel with high quality epoxy coated finish, making this a superior and hard wearing product. Product is supplied fully assembled.

Angled plough to allow snow to easily slide off the side of the blade. Simply flip the handle over to choose which side the snow is ploughed to. Narrow Model is ideal for home use where space is restricted.

Wheels: 160mm solid rubber tyred wheels and roller bearings.





Loadtek

<u>j</u>

Description	Blade H x W mm	Handle H x W mm	Wheel dia mm	Weight kg	Order Ref
Wide Blade	195 x 955	1110 × 410	160	8	HSP-1
Narrow Blade	195 x 500			7	HSP-2



'V' Blade Push Along Snow Plough

Minimises work by pushing instead of lifting and throwing with the angled plough allowing snow to easily slide off either side of the blade. Manufactured from mild steel with high quality epoxy coated finish, making this a superior and hard wearing product. Product is supplied fully assembled.

Wheels: 160mm solid rubber tyred wheels and roller bearings.



Description	Blade H x W mm	Handle H x W mm	Wheel dia mm	Weight kg	Order Ref
V Blade	165 x 900	1110 × 410	160	8	HSP-3



122

Snow Ploughs SDL

N

Made in Britain

N

Made in

Britain

Heavy Duty Push Along Snow Plough

Adjustable blade: from 0 degrees to 30 degrees of left hand sweep, allowing snow to easily slide off the blade. Easily adjustable on a 50mm pitch with 6 adjustments using fly nut and bolt. Simple trolley style design allows you to remove snow while keeping your body in an upright, walking position. Angled plough allows snow to easily slide off either side of the blade.

Manufactured from mild steel with high quality epoxy coated finish, making this a superior and hard wearing product. Product is supplied fully assembled.

Wheels: 4 x 260mm pneumatic tyred wheels and roller bearings.

Description	Overall H x W x D mm	Blade Width mm	Wheel dia mm	Weight kg	Order Ref
Wide Blade	1000 × 1000 × 1140	955	260	8	HSP-4

Heavy Duty Snow Plough

Heavy duty snow plough and yard scraper attachment to fit most fork lift trucks. Fixed left hand sweep angle of 15 degrees. Heavy duty concave blade with bolt on 12mm thick reversible rubber wear strip. When not used for snow clearing can be utilised as general purpose yard scraper. Finish: Yellow epoxy coated.

Plough fits over forks and is secured with zinc plated 'T' bar screws.



Wear Strip Thickness: 12mm Fork Centres: 800mm

Loadtek

						Rubber Wearstrip
Description	Blade Height mm	Fork Pockets H x W mm	Overall Depth mm	Weight kg	Order Ref	Order Ref
1200mm Blade Width				79	FSP-1	FSP-1RB
1500mm Blade Width	510	160 x 50	1350	98	FSP-2	FSP-2RB
2000mm Blade Width				123	FSP-3	FSP-3RB

123





Replacement



. . .

SDL ~ TRADER ~ 2025 'B'



Redditek has stood the test of time. This range of highly customisable products have been developed over forty years into one of the most respected workbench and storage brands

The storage collection includes the Euro Cabinet System, a versatile range of steel work cabinets that can be combined to form complete working layouts; and the Hazardous Storage Cabinet range in a vast choice of sizes and colours to assist in identifying the cabinets use in the work place.

The range of workbench products available is extensive. Built in a variety of designs and with a choice of worktop finishes, these workbench products come with a huge array of custom options to create the perfect work environment to aid productivity and organisation.



Recycling Bin - 2 Bay

- Manufactured from durable epoxy-coated galvanised steel
- Two inner compartments, each with a generous 80 litre capacity
- Ideal for separating recyclables and general waste in working environments, exhibition centres, hospitals and schools
- Customisable with a complementary
 range of stickers to suit your requirements

Please state your required stickers when ordering

Available in a range of 10 body colours













Step two - choose two apertures

Slot Type Description	Order Ref
Circle with Flap	REC-FLAP
Circle	REC-OPEN
Lid	REC-LID

Step three - choose two labels

Label Description	Order Ref
Mixed Self Adhesive Stickers	REC-MIXED
Paper Self Adhesive Stickers	REC-PAPER
Plastic Self Adhesive Stickers	REC-PLASTIC
General Self Adhesive Stickers	REC-GENERAL
Food Self Adhesive Stickers	REC-FOOD
Cans Self Adhesive Stickers	REC-ALU

Step four - add a bespoke logo (optional)

Description	Order Ref
Bespoke Logo	REC-LOGO/2



126 Recycling Bins

Recycling Bin - 3 Bay

- Manufactured from durable epoxy-coated galvanised steel
- Three inner compartments, each with a generous 80 litre capacity
- Ideal for separating recyclables and general waste in working environments, exhibition centres, hospitals and schools
- Customisable with a complementary
 range of stickers to suit your requirements
- Available in a range of 10 body colours



Please state your required stickers when ordering





Step one - choose the colour of your bay

Description	Overall H x W x D mm				Weight kg	Order Ref						
ecycling Bin - 3 Bay			1050	1050 x 1040 x 535				45	REC-3			
Colour Options BK	W	Y	0	RD	BL	GN	DGN	LGY	DGY			

Step two - choose three apertures

Slot Type Description	Order Ref
Circle with Flap	REC-FLAP
Circle	REC-OPEN
Lid	REC-LID

Step three - choose two labels

Label Description	Order Ref
Mixed Self Adhesive Stickers	REC-MIXED
Paper Self Adhesive Stickers	REC-PAPER
Plastic Self Adhesive Stickers	REC-PLASTIC
General Self Adhesive Stickers	REC-GENERAL
Food Self Adhesive Stickers	REC-FOOD
Cans Self Adhesive Stickers	REC-ALU

Step four - add a bespoke logo (optional)

٠Ħ

SDL

Redditek

Description	Order Ref
Bespoke Logo	REC-LOGO/3

N

Made in

Britain

Recycling Bins 127

Stainless Steel Cabinets

A range of stainless steel cabinets manufactured from 304 grade stainless. Ideal for clean and hygienic work environments.

Stainless Steel CB Cupboards are supplied complete with adjustable shelves, leverlock handle with 2 rods locking top and bottom and 2 keys.





Description	Overall H x W x D mm	Shelf Capacity kg	Ref
1 Adjustable Shelf	915 x 457 x 457		CB11SS
1 Adjustable Shelf	915 x 915 x 457	50	CB60SS
2 Adjustable Shelves	1220 x 915 x 457	50	CB65SS
3 Adjustable Shelves	1830 x 915 x 457		CB70SS

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	ES1SS
915 x 457	50	ES2SS

128 **Stainless Steel Cabinets**

Stainless Steel Hazardous Cabinets

Stainless Steel Hazardous FB Cabinets are supplied complete with punched adjsutable shelf trays, removable sump, leverlock handle with 2 rods locking top and bottom and 2 keys.





Description	Overall H x W x D mm	Shelf Capacity kg	Ref
1 Adjustable Shelf	915 x 457 x 457		FB10SS
1 Adjustable Shelf	915 x 915 x 457	50	FB20SS
2 Adjustable Shelves	1220 x 915 x 457	50	FB25SS
3 Adjustable Shelves	1830 x 915 x 457		FB30SS

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457		
915 x 457	50	ES2SS

Optional extra

Upgrade to 100kgs per shelf, maximum 400kgs for cabinet. Ref: CBHD

Redditek



Hazardous Cabinets 129

۲

۲

۲

۲

۲

۲

۲

Hazardous Cabinets - Flammable Liquids Storage

Storage cabinets for hazardous materials. Strong welded 20swg steel construction. Lever lockhandles with 2 rods locking top and bottom, 2 keys. Shelf trays have punched drain holes to allow any spillages to drain into base sump. Removable sump for convenient removal of spills. Shelf capacity 35kgs, maximum 250kgs per cabinet. Warning stickers. Powder coated finish. Flammable Cabinet: D. Grey RAL7031 or Yellow RAL1003

All cabinets meet the requirements of The Highly Flammable and Liquefied Petroleum Gases Regulations 1972 (Section 5 Part D), The Health and Safety Executive Guide HS(G)51 1990 and the Factory Inspectorate Certificate of Approval No 1 Parts 3 and 4.

The maximum volume of any flammable liquid with a flashpoint below 32°C that may be stored in a flame resistant cabinet within a workroom is 50 litres (regardless of the total capacity of the storage cabinet).



Description	Overall H x W x D mm	Sump Cap. Ltrs	Yellow Order Ref	Dark Grey Order Ref
	457 x 457 x 305	13.5		FB1G
	610 x 457 x 457	14.5		FB4G
1 Adjustable Shelf	915 x 457 x 457	14.5	FB10	FB10G
	712 x 915 x 457	27.0		FB15G
	915 x 915 x 457	27.0		FB20G
2 Adjustable Shelves	1220 x 915 x 457	27.0		FB25G
3 Adjustable Shelves	1525 x 915 x 457	27.0		FB26G
	1830 x 915 x 457	27.0		FB30G
	1800 x 1200 x 500	42.5	FB40	FB40G

Stand

Shelf Size H x W x D mm	Yellow Order Ref	Dark Grey Order Ref
460 x 915 x 457	SS11	SS11G
460 x 457 x 457	SS12	SS12G

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Order Ref
457 x 457		ES1
915 x 457	50	ES2
1200 x 500		ES5



٢

٨

Britain

Optional extra

Upgrade to 80kgs per shelf, maximum 400kgs for cabinet. **Ref: FBHD**

) Hazardous Cabinets

SDL

Hazardous Cabinets

Hazardous Cabinets - Pesticide/Chemical

Storage cabinets for hazardous materials. Strong welded 20swg steel construction. Lever lockhandles with 2 rods locking top and bottom, 2 keys. Door vents to prevent fume build-up Shelf trays have punched drain holes to allow any spillages to drain into base sump. Removable sump for convenient removal of spills. Shelf capacity 35kgs, maximum 250kgs per cabinet. Warning stickers. Powder coated finish. Pesticide / Chemical Cabinet: Red RAL3020 or Green RAL6029















٠	•
•	_و

Description	Overall H x W x D mm	Sump Cap. Ltrs	Red Order Ref	Green Order Ref
	457 x 457 x 305	13.5	PFB1	PFB1G
	610 x 457 x 457	14.5	PFB4	PFB4G
1 Adjustable Shelf	915 x 457 x 457	14.5	PFB10	PFB10G
	712 x 915 x 457	27.0	PFB15	PFB15G
	915 x 915 x 457	27.0	PFB20	PFB20G
2 Adjustable Shelves	1220 x 915 x 457	27.0	PFB25	PFB25G
	1525 x 915 x 457	27.0	PFB26	PFB26G
3 Adjustable Shelves	1830 x 915 x 457	27.0	PFB30	PFB30G
	1800 x 1200 x 500	42.5		PFB40G

Stand

Shelf Size H x W x D mm	Red Order Ref	Green Order Ref
460 x 915 x 457	PSS11	
460 x 457 x 457	PSS12	

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Order Ref
457 x 457		ES1
915 x 457	50	ES2
1200 x 500		ES5



Optional extra

Upgrade to 80kgs per shelf, maximum 400kgs for cabinet. **Ref: FBHD**

Redditek



Hazardous Cabinets - Coshh

Storage cabinets for hazardous materials. Strong welded 20swg steel construction. Lever lockhandles with 2 rods locking top and bottom, 2 keys. Shelf trays have punched drain holes to allow any spillages to drain into base sump. Removable sump for convenient removal of spills. Shelf capacity 35kgs, maximum 250kgs per cabinet. Warning stickers. Powder coated finish. Coshh Cabinet: L. Grey RAL7035







of spills. Shelf capacity 35kgs, cabinet. Warning stickers. Pow Coshh Cabinet: L. Grey RAL70	der coated finish.		
CFB1	CFB4	CFB10	CFB15
Description	Overall H x W x D mm 457 x 457 x 305	Sump Cap. Ltrs 13.5	Order Ref CFB1
	610 x 457 x 457	14.5	CFB4
1 Adjustable Shelf	915 x 457 x 457	14.5	CFB10
	712 × 915 × 457	27.0	CFB15
	915 x 915 x 457	27.0	CFB20
2 Adjustable Shelves	1220 x 915 x 457	27.0	CFB25
	1525 x 915 x 457	27.0	CFB26
3 Adjustable Shelves	1830 x 915 x 457	27.0	CFB30
	1800 × 1200 × 500	42.5	CFB40
Stand			
Shelf Size H x W x D mm		Order Ref	
460 x 915 x 457		CSS11	
460 x 457 x 457		CSS12	
Extra Shelves			
Shelf Size W x D mm	Shelf Capacity kg	Order Ref	-
457 x 457		ES1	
915 x 457	50	ES2	

Optional extra

1200 x 500

Upgrade to 80kgs per shelf, maximum 400kgs for cabinet. **Ref: FBHD**



132 Hazardous Cabinets

Made in Britain

Hazardous Cabinets - Acid

Storage cabinets for hazardous materials. Strong welded 20swg steel construction. Lever lockhandles with 2 rods locking top and bottom, 2 keys. Shelf trays have punched drain holes to allow any spillages to drain into base sump. Removable sump for convenient removal of spills. Shelf capacity 35kgs, maximum 250kgs per cabinet. Warning stickers. Powder coated finish. Acid Cabinet White RAL9003











Description	Overall H x W x D mm	Sump Cap. Ltrs	Order Ref
	457 x 457 x 305	13.5	AFB1
	610 x 457 x 457	14.5	AFB4
1 Adjustable Shelf	915 x 457 x 457	14.5	AFB10
	712 × 915 × 457	27.0	AFB15
	915 x 915 x 457	27.0	AFB20
2 Adjustable Shelves	1220 x 915 x 457	27.0	AFB25
	1525 x 915 x 457	27.0	AFB26
3 Adjustable Shelves	1830 x 915 x 457	27.0	AFB30
	1800 x 1200 x 500	42.5	AFB40

Stand

Shelf Size H x W x D mm	Order Ref	
460 x 915 x 457	ASS11	
460 x 457 x 457	ASS12	

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Order Ref
457 x 457		ES1
915 x 457	50	ES2
1200 x 500		ES5

Optional extra

Upgrade to 80kgs per shelf, maximum 400kgs for cabinet. **Ref: FBHD**

Redditek



First Aid Cabinets

Storage cabinets for First Aid supplies and equipment. Instantly recognisable with clear identification labelling. Clean, durable white powder coated finish. First Aid Cabinets White RAL9003.



Wall Fixing Cabinets

- Fixed shelf and internal drawer tray(s), lock with 2 keys
- Cabinets pre-drilled for fixing (fixings not included)

Floor Standing Cabinets

- Shelves adjustable to 25mm pitch
- Lever lock handles with 2 rods locking top and bottom, 2 keys

134



Description	Overall H x W x D mm	Shelf Capacity kg	Ref
Floor Cabinet with 1 Adjustable Shelf	915 x 457 x 457		FAC10
Floor Cabinet with 2 Adjustable Shelves	915 x 915 x 457		FAC60
Floor Cabinet with 2 Adjustable Shelves	1220 × 915 × 457		FAC65
Floor Cabinet with 3 Adjustable Shelves	1830 x 915 x 457	50	FAC70
Wall Cabinet with 1 Fixed Shelf	600 × 400 × 300		FAWC3
Wall Cabinet with 1 Fixed Shelf	600 x 500 x 300		FAWC4
Wall Cabinet with 2 Fixed Shelves	600 x 800 x 300		FAWC6

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	ES1
915 x 457	50	ES2

4 First Aid Cabinets

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

PPE Cabinets

Storage cabinets for Personal Protective equipment. Designed and manufactured to meet the requirements of The Personal Protective Equipment at Work Regulations 1994. PPE Cabinets - Cabinet Grey RAL7035 & Doors RAL5017

- Strong welded 20swg steel construction
- Shelves adjustable to 25mm pitch
- Lever lock handles with 2 rods locking top and bottom, 2 keys
- Powder coated finish
- Identification labelling



Description	Overall H x W x D mm	Shelf Capacity kg	Ref
1 Adjustable Shelf	915 x 457 x 457		PPE10
2 Adjustable Shelves	915 x 915 x 457		PPE60
2 Adjustable Shelves	1220 x 915 x 457	50	PPE65
3 Adjustable Shelves	1830 x 915 x 457		PPE70
3 Adjustable Shelves, Centre Divider and Hanging Rail	1830 x 915 x 457		PPE71

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	ES1
915 x 457	50	ES2



Redditek



Polycarbonate Door Cabinets

Strong welded 20swg steel construction with polycarbonate door panels for enclosed visibility whilst maintaining security. Body: Grey RAL7035 Powder coated finish. Blue, grey, green, yellow or red (Blue supplied if not specified).

Wall Fixing Cabinets

- Fixed shelf.
- · Lock with 2 keys.
- Cabinets pre-drilled for wall fixing
 (fixings not included).

Floor Standing Cabinets

- Shelves adjustable to 25mm pitch.
- Lever lock handles with 2 rods locking top and bottom, 2 keys.





Description	Overall H x W x D mm	Shelf Capacity kg	Ref
Floor Cabinet with 1 Adjustable Shelf	915 x 457 x 457		CBP11
Floor Cabinet with 1 Adjustable Shelf	915 x 915 x 457		CBP60
Floor Cabinet with 2 Adjustable Shelves	1220 x 915 x 457	50	CBP65
Floor Cabinet with 3 Adjustable Shelves	1830 x 915 x 457		CBP70
Wall Cabinet with 1 Fixed Shelf	600 x 1000 x 300		WCP10

Colour Options GY R B	Y GN
-----------------------	------

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	ES1
915 x 457	50	ES2



Polycarbonate Door Cabinets

136

136 Polycarbonate Door Cabinets

Mesh Door Cabinets

Strong welded construction with mesh door panels for visibility and ventilation whilst maintaining security.

- Strong welded 20swg steel construction.
- Shelves adjustable to 25mm pitch.
- · Leverlock handles with 2 rod locking top and bottom, 2 keys.
- Powder coated finish.
- Body: Grey RAL7035.
- Doors / shelves: Blue, grey, green, yellow or red (Blue supplied if not specified).





Description	Overall H x W x D mm	Shelf Capacity kg	Ref
1 Adjustable Shelf	915 x 457 x 457		CBM11
1 Adjustable Shelf	915 x 915 x 457		CBM60
2 Adjustable Shelves	1220 x 915 x 457	50	CBM65
3 Adjustable Shelves	1830 x 915 x 457		CBM70
3 Adjustable Shelves, Centre Divider and Hanging Rail	1830 x 915 x 457		CBM71

	Colour Options	GY	R	В	Y	GN
--	----------------	----	---	---	---	----

Redditek

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	ES1
915 x 457	50	ES2



Tall Cabinet System

Tall Cabinet System

A flexible range of tough steel cabinets with hinged doors and a range of accessories to create just the storage solution you need.

Fitted with tool panel reinforced doors Full width robust doors for maximum aperture Adjustable shelves - 50mm pitch - shelf capacity 45kg Leverlock handle with 2 rod locking top and bottom, 2 keys Base pre-drilled for floor fixing - recommended (fixings not supplied) Back tool or louvre panel options.





























Tall Cabinet System SDL TEL:0144677

Description			0	
No. of Shelves	No. of Drawers	Panel Back Type	Overall H x W x D mm	Order Ref
0 Shelves	0 Drawers	Frank (EC2000
4 Adjustable Shelves		Empty		EC2010
1 Adjustable Shef	8 Drawers (base)	Halfl Tool Panel Back	2000 x 1000 x 500	EC2031
1 Adjustable Shef	2 Drawers (base & 560mm)	Halfl Louvre Panel Back		EC2032
2 Adjustable Shelves	4 Drawers (base, 460, 760 & 860mm)	Halfl Tool Panel Back		EC2033
0 Shelves	0 Drawers	Full Louvre Panel Back		EC2035
0 Shelves	U Diaweis	Full Tool Panel Back		EC2036
2 Adjustable Shelves	1 Drawer (1010mm)	Quarter Louvre & Quarter Tool Panel Back		EC2037

Optional extras

Drawer unit - Internal W x D: 888 x 375mm. Front height: 95mm. Available at 50mm pitch (min 100mm between drawers) - please state height when ordering. Max 12 drawers to cabinet. Only one drawer to be opened at a time.

Ref: ECA020

Adjustable shelf. Capacity 45kg 1000mm wide shelf Ref: ECA025

Quarter rear tool panel Please state position height when ordering. Max 4 per cabinet. Ref: ECA022

Quarter rear louvre panel. Please state position height when ordering. Max 4 per cabinet. Ref: ECA023

Tool clips (set of 10) 3 single hooks, 3 double hooks, 2 snap-in hooks, 1 hammer hook, 1 pliers hook (For additional hooks see page 161) Ref: ECA009

Louvre panel doors. Replaces standard tool panel doors (factory fitted). Accepts size 2 & 3 bins (see page 103 for container bin packs) Ref: ECA021















BCL01		Bin Cabinets - Louvro	e Support	
	Made in <mark>Britain</mark>			
FEEEEEEEEEE		Robust, heavy duty steel cupbo louvre or shelf bin support syst		
		bins, or choice of units comple	te with bins. Lockable de	oors supplied with
		2 keys, finished in epoxy grey o	cabinet and blue doors.	
	BC	BCL54	BCL60	BCL126
Description		Overall H x W x D mm		Order Ref
Empty Unit				BCL01
54 Bin Unit -30 x No. 3 bins; 24 No. 4 bins				BCL54
60 Bin Unit - 60 x No. 3 bins		2000 × 1000 × 500		BCL60
78 Bin Unit - 42 x No. 2 bins; 20 No. 3 bins	; 16 No 4 bins			BCL78

126 Bin Unit - 126 x No. 2 bins



Bin Cabinets - Shelf Support

	Committee and Co	8
		and the second s
		and the second s
		mmmm
		man and a second se
		mmm
	and the second se	mmmm l
	A REAL PROPERTY AND A REAL	mmmm
	No.	mmmm
		Concerne and
		in the second se
		Chichenen -
		COCO COCO
		COMPANY AND A
		CO.CO.CO.CO.
		00000
	r	
		mmmm .
		occe l
		occe
		oces
		one l
		0000
		oppe
	August and a second sec	mmmm
	Management of the second se	Comme
		0000
		0000
		0000
	1	0000





Description		Overall H x W x D mm	Order Ref
Bins	Shelves / Drawers	Overall H X W X D IIIII	
Empty Bin Unit	4 Shelves		BCS04
Empty Bin Unit	8 Shelves		BCS08
Empty Bin Unit	10 Shelves		BCS10
Empty Bin Unit	12 Shelves	2000 × 1000 × 500	BCS12
44 Bin Unit - 44 No 4 bins.	11 shelves.	2000 x 1000 x 500	BCS48
54 Bin Unit - 24 No.2 bins, 18 x No.3 bins; 12 No. 4 bins	9 Shelves / 4 Drawers		BCS60
66 Bin Unit - 66 No.3 bins	11 shelves		BCS72
68 Bin Unit - 24 No.2 bins, 24 No.3 bins, 20 x No.4 bins	12 shelves		BCS72C

Extra shelf Ref: BCSES



140

Bin Cabinets - Louvre & Shelf Support

140 Bin Cabinets - Louvre & Shelf Support

CB Cupboards

Range of steel cabinets constructed to imperial sizes, designed to combine with existing imperial size cabinets. Lever lock handles with 2 rods locking top and bottom, 2 keys. Powder coated finish in grey as standard, blue doors on request. Shelf capacity 50kgs, maximum 250kgs per cabinet.



Description	Overall H x W x D mm	Shelf Capacity kg	Ref
1 Adjustable Shelf	915 x 457 x 457		CB11
2 Adjustable Shelves	915 x 915 x 457	50	CB60
2 Adjustable Shelves	1220 x 915 x 457		CB65
3 Adjustable Shelves	1830 x 915 x 457		CB70

Extra Shelves

Shelf Size W x D mm	Shelf Capacity kg	Ref
457 x 457	50	
915 x 457	50	ES2

Optional extra

Upgrade to 100kgs per shelf, maximum 400kgs for cabinet. **Ref: CBHD**

Redditek



CB Cupboards

Steel Bin Cabinets

All units supplied complete and fully assembled ready for immediate use.









Bin Sizes

Widths: 148mm (6 bins across) 222mm (4 bins across) 296mm (3 bins across) 445mm (2 bins across) 900mm (1 bin across)

148mm (12 bins down)

220mm (8 bins down)

293mm (6 bins down)

440mm (4 bins down)

Bin capacityShelf capacity10kg60kg12.5kg50kg15kg45kg20kg40kg30kg30kg

Bin sizes stated are internal dimensions after the aperture. Aperture = bin height - shelf profile.

Depths

Heights:

Cabinet:377, 427, 532mmInternal:305, 355, 460mmShelf:253, 304, 409mm



Shelf Profiles



"F" Flush shelves supplied unless other specified

Finish

Powder coated finish in a choice of colours:

Grey (as standard) Red Blue Green

For full range of 72 models see next page.

Cabinet heights Full height: 1820mm

Cabinet width All cabinets: 942mm



Doors are available as an option for all units. Twin steel doors, lock and 2 keys

Height: 1820mm Ref: SBC6D







SDL





Depth mm	Order Ref
305	SBC601
355	SBC602
460	SBC603



48 bins Bin size W x H: 222 x 148mm

Depth mm	Order Ref
305	SBC604
355	SBC605
460	SBC606



36 bins Bin size W x H:296 x 148mm

Depth mm	
305	
355	
460	SBC609



24 bins Bin size W x H:445 x 148mm

Depth mm	Order Ref
305	SBC610
355	SBC611
460	SBC612



48 bins Bin size w x h: 148 x 220mm

Depth mm	Order Ref
305	SBC613
355	SBC614
460	SBC615



32 bins Bin size w x h: 222 x 220mm





24 bins Bin size w x h: 296 x 220mm

Depth mm	Order Ref	Depth mm	Order Ref
305	SBC619	305	SBC622
355	SBC620	355	SBC623
460	SBC621	460	SBC624

16 bins

Bin size w x h: 445 x 220mm



36 bins Bin size w x h: 148 x 293mm



8 bins Bin size w x h: 445 x 440mm



18 bins Bin size w x h: 296 x 293mm



12 bins Bin size w x h: 445 x 293mm

Depth mm	Order Ref						
305	SBC625	305	SBC646	305	SBC631	305	SBC634
355	SBC626	355	SBC647	355	SBC632	355	SBC635
460	SBC627	460	SBC648	460	SBC633	460	SBC636

143

·

Redditek

Steel Bin Cabinets

System 'D' Drawer Cabinets

High density small parts storage system.













Steel construction throughout All cabinets 902mm wide. Cabinet depths: 334 and 488mm

Available with or without lockable doors.

Drawer dividers available for further stock separation (not available for 205 x 180mm size drawers).

Steel drawers have rear retaining lip to hold drawer in unit while contents are viewed / accessed.



1090mm high W x H
18 drawers: 135 x 75mm
6 drawers: 280 x 75mm
8 drawers: 205 x 180mm

Depth mm	Ref: Without doors
305	DCD33
460	DCD34
Depth mm	Ref: With doors
305	DCD33D
460	DCD34D



Finish: powder coated - Drawers: grey Cabinets in choice of: grey, red, blue, green or yellow (grey supplied if not specified).



Steel Drawer Cabinets

144
e in ain

Drawer W x H: 135 x 75mm Drawer W x H: 280 x 75mm Drawer W x H: 205 x 180mm Drawer D: 285 or 440mm Drawer D: 285 or 440mm Drawer D: 285 or 440mm Divider slots at 20mm centres Divider slots at 20mm centres 30 drawers - 670mm high 15 drawers - 670mm high 8 drawers - 570mm high Depth mm Without doors Depth mm Without doors Depth mm Without doors 305 305 305 460 460 460 60 drawers - 1090mm high 30 drawers - 1090mm high 20 drawers - 1090mm high

Depth mm	Without doors	Depth mm	Without doors		Depth mm	Without doors
305	DCD06	305	DCD21		305	DCD27
460	DCD07	460	DCD22		460	DCD28
Depth mm	With doors	Depth mm	With doors		Depth mm	With doors
 305	DCD06D	305	DCD21D		305	DCD27D
460	DCD07D	460	DCD22D		460	DCD28D

90 drawers -	1600mm high	45 drawers -	1600mm high	28 drawers -	1500mm high
Depth mm	Without doors	Depth mm	Without doors	Depth mm	Without doors
305	DCD09	305	DCD23	305	DCD29
460	DCD10	460	DCD24	460	DCD30
Depth mm	With doors	Depth mm	With doors	Depth mm	With doors
305	DCD09D	305	DCD23D	305	DCD29D
460	DCD10D	460	DCD24D	460	DCD30D

Packs of drawers 135mm wide x 75mm high

Steel Drawers	Depth mm	Order Ref
6 Pack	285	DCD12
6 Pack	440	DCD13
Dividers	Size mm	
50	132 x 60	

Packs of drawers	
280mm wide x 75mm high	

Steel Drawers	Depth mm	Order Ref
3 Pack	285	DCD16
3 Pack	440	DCD117
Dividers	Size mm	Order Ref
50	277 x 60	DCD18

Packs of drawers 205mm wide x 180mm high

Steel Drawers	Depth mm	Order Ref
4 Pack	285	DCD31
4 Pack	440	DCD32



Redditek

Steel Drawer Cabinets

145



amazon.co.uk amazo

Workbench Styles



Standard Fully welded steel construction



Adjustable Height Crank handle to alter worktop height



Heavy Duty
Designed for engineering / factory environments



Infinite Modular Excellent for continuous runs and double sided working

Worktop Materials



- 20mm worktop & impact resistant surface
- Plain grey laminate with mid grey plastic edging
- Great in all environments



- 20mm worktop & impact resistant surface
- Grey fleck Lino with mid grey plastic edging
- Surface reduces risk of product damage



Steel

- 20mm Galvanised Steel worktop
- Heavy duty, hard wearing and long-lasting
- Suitable for use with hot components



Stainless Steel

- 1.2mm stainless steel with 20mm worktop
- Heavy duty, hard wearing and long-lasting
- Great for wet and clean environments



- 18mm worktop
- Mid Grey plastic edging



Anti-static Laminate

- 20mm worktop with light grey plastic edging
- Plain grey static dissipative laminate
- Perfect for electric parts

Standard Workbench

Construction: Fully welded steel with 40 x 40mm legs and 50 x 25mm framework. Standard workbench height 840mm (750 & 900mm available at no extra cost), frame finished in light grey epoxy. Supplied with adjustable feet.

Optional extra

2 x swivel and 2 x swivel braked castors fitted with 100mm blue resilex tyred wheels and roller bearings. Ref: AA-MOB



Worktop Thickness

Laminate: 20mm Anti-static Laminate: 20mm MDF: 18mm



Height and Worktop Options

rieight and worktop Options				
		Standard Worktop Material	S	
Description	Overall H x W x D mm	Laminate Order Ref		MDF Order Ref
Standard Workbench	840 x 1800 x 750	SB8-LA	SB8-ALA	SB8-M

Above Workbench Accessories







Britain

148

148 Standard Workbench

SDL



Redditek



	Description	Overall	H × W ×	D mm	Order Ref
А	Full width lower shelf, laminate		1800	600	AB-LSLA
в	Full width middle shelf, laminate		1800	600	AB-MSLA
	Half width lower shelf, laminate		900	600	AB-HLSLA
	Half width middle shelf, laminate		900	600	AB-HMSLA
	Full width lower shelf, anti-static laminate		1800	600	AB-LSALA
	Full width middle shelf, anti-static laminate		1800	600	AB-MSALA
	Half width lower shelf, anti-static laminate		900	600	AB-HLSALA
	Half width middle shelf, anti-static laminate		900	600	AB-HMSALA
	Full width lower shelf, MDF		1800	600	AB-LSM
	Full width middle shelf, MDF		1800	600	AB-MSM
	Half width lower shelf, MDF		900	600	AB-HLSM
	Half width middle shelf, MDF		900	600	AB-HMSM

Drawers and Cupboards

Lockable drawer and cupboard units bolt to the underside of the workbench frame, using captive nuts fitted to every frame, so they can be fitted or changed at any time. Cupboards have one fixed steel shelf. Supplied loose for simple on-site assembly.

All above bench accessories and cupboard and drawer carcass:

Light Grey epoxy

Red

Blue

٠Ħ

SDL

Drawer fronts and doors available in choice of: (Blue supplied if none specified)

Redditek

Dark Grey

	Below bench accessory	H x W x D mm		Right fitted Order Ref
А	Single drawer	140 x 410 x 430	LA	RA
в	2 drawer unit	280 x 410 x 430	LE	RE
С	3 drawer unit	420 x 410 x 430	LH	RH
D	4 drawer unit	560 x 410 x 430	LK	RK
Е	Small cupboard	420 x 410 x 430	LC	RC
F	Large cupboard	560 x 410 x 430	LD	RD
G	Single drawer + small cpbd	560 x 410 x 430	LG	RG
	Retaining skirt	100mm high steel back	-	RS





149

Standard Workbench

149

Adjustable Height Workbench

Construction: Welded steel with 40 x 40mm and 50 x 25mm framework. Adjustable workbench height from 840mm to 1140, frame finished in light grey epoxy.

Worktop Thickness

Laminate: 20mm Anti-static Laminate: 20mm MDF: 18mm



Max Load

300kg

Made in

Britain

Height and Worktop Options

		Standard Worktop Materi	als	
Description	Overall H x W x D mm	Laminate Order Ref		MDF Order Ref
Adjustable Height Workbench	840 to 1140 x 1800 x 750	AB8-LA	AB8-ALA	AB8-M

Above Workbench Accessories

F	In .	Description	Overa	all H x W x	Dmm	Order Ref
-		A Pair of accessory outer bench posts	10.00			AB-P
-	D	A central accessory post	1260r	nm above	bench	AB-CP
		Formed sheet divider	300		300	AB-SDIV
N. N. W. N.	A	Full width tool panel	450	1800		AB-RTP
		Half width tool panel	450	900		AB-HRTP
	Concentration of the second	B Full width louvre panel	450	1800		AB-RLP
1000000000		Half width louvre panel	450	900		AB-HRLP
		Half width monitor mounting panel	450	900		AB-HMP
		Full width post mounting service due	t	1800		AB-FPSD
		Half width post mounting service du	:t	900		AB-HPSD
		C Worktop mounted service duct		1800		AB-RSD
		D Full width flush shelf c/w divider hole	s	1800	300	AB-TSS
	· · · · ·	Full width angled shelf, lipped front		1800	300	AB-ATSS
		Half width flush shelf c/w divider hole	s	900	300	AB-HTSS
		Half width angled shelf, lipped front		900	300	AB-HATSS
		E Back stop for shelf		1800		AB-BST
	F	F LED Batten to fit under shelf		1220		AB-LED
		Label printer shelf		200	300	AB-LAB
1	1 march	Monitor arm				AB-MON



150

Adjustable Height Workbench

SDL TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk



	Description	Overall	H × W ×	D mm	Order Ref
А	Full width lower shelf, laminate		1800	600	AB-LSLA
в	Full width middle shelf, laminate		1800	600	AB-MSLA
	Half width lower shelf, laminate		900	600	AB-HLSLA
	Half width middle shelf, laminate		900	600	AB-HMSLA
	Full width lower shelf, anti-static laminate		1800	600	AB-LSALA
	Full width middle shelf, anti-static laminate		1800	600	AB-MSALA
	Half width lower shelf, anti-static laminate		900	600	AB-HLSALA
	Half width middle shelf, anti-static laminate		900	600	AB-HMSALA
	Full width lower shelf, MDF		1800	600	AB-LSM
	Full width middle shelf, MDF		1800	600	AB-MSM
	Half width lower shelf, MDF		900	600	AB-HLSM
	Half width middle shelf, MDF		900	600	AB-HMSM

Drawers and Cupboards

Lockable drawer and cupboard units bolt to the underside of the workbench frame, using captive nuts fitted to every frame, so they can be fitted or changed at any time. Cupboards have one fixed steel shelf. Supplied loose for simple on-site assembly.

All above bench accessories and cupboard and drawer carcass:

Light Grey epoxy

Red

Blue

Drawer fronts and doors available in choice of: (Blue supplied if none specified)

Redditek

Dark Grey

	Below bench accessory	H x W x D mm		Right fitted Order Ref
А	Single drawer	140 x 410 x 430	LA	RA
в	2 drawer unit	280 x 410 x 430	LE	RE
С	3 drawer unit	420 x 410 x 430	LH	RH
D	4 drawer unit	560 x 410 x 430	LK	RK
Е	Small cupboard	420 x 410 x 430	LC	RC
F	Large cupboard	560 x 410 x 430	LD	RD
G	Single drawer + small cpbd	560 x 410 x 430	LG	RG
	Retaining skirt	100mm high steel back	-	RS







151

Standard Height Packing Bench

Redhill's modular packing station. Customise your packing operation and maximise your working and storage space with our new fixed height work bench.

Build to your requirements including carton dividers, wrapping dispenser bars, PC monitor panels, Electrical points and other accessories.

All powder coated finished with a choice of laminate, Anti-Static or MDF worktops.

Worktop Thickness Laminate: 20mm Anti-static Laminate: 20mm MDF: 18mm

2 x swivel and 2 x swivel braked castors fitted with 100mm blue resilex tyred wheels and roller bearings. **Ref: AA-MOB**

Optional extra

Height and Worktop Options

Description Overall H x W x D mm Laminate Order Ref Anti-static Order Ref MDF Order Ref Standard Workbench 840 x 1800 x 750 SB8-LA SB8-ALA SB8-M

Above Workbench Accessories

А

D

F G



	Description	Overall	$H\timesW\times$	D mm	Order Ref
А	Pair of accessory outer bench posts	1260mm above bench		hanch	AB-P
в	A central accessory post	1260111	n above	Dench	AB-CP
С	Formed sheet divider	300		300	AB-SDIV
	Full width tool panel	450	1800		AB-RTP
D	Half width tool panel	450	900		AB-HRTP
	Full width louvre panel	450	1800		AB-RLP
	Half width louvre panel	450	900		AB-HRLP
Е	Half width monitor mounting panel	450	900		AB-HMP
	Full width post mounting service duct		1800		AB-FPSD
F	Half width post mounting service duct		900		AB-HPSD
	Worktop mounted service duct		1800		AB-RSD
	Full width flush shelf c/w divider holes		1800	300	AB-TSS
	Full width angled shelf, lipped front		1800	300	AB-ATSS
G	Half width flush shelf c/w divider holes		900	300	AB-HTSS
н	Half width angled shelf, lipped front		900	300	AB-HATSS
	Back stop for shelf		1800		AB-BST
1	LED Batten to fit under shelf		1220		AB-LED
	Label printer shelf		200	300	AB-LAB
	Monitor arm				AB-MON

·E

Redditek





152 Standard Height Packing Bench SDL TEL:01446772614 www



scription	otion Overall H x W x D mm		Order Ref	
ll width lower shelf, laminate		1800	600	AB-LSLA
ll width middle shelf, laminate		1800	600	AB-MSLA
lf width lower shelf, laminate		900	600	AB-HLSLA
lf width middle shelf, laminate		900	600	AB-HMSLA
II width lower shelf, anti-static laminate		1800	600	AB-LSALA
II width middle shelf, anti-static laminate		1800	600	AB-MSALA
If width lower shelf, anti-static laminate		900	600	AB-HLSALA
If width middle shelf, anti-static laminate		900	600	AB-HMSALA
II width lower shelf, MDF		1800	600	AB-LSM
II width middle shelf, MDF		1800	600	AB-MSM
If width lower shelf, MDF		900	600	AB-HLSM
lf width middle shelf, MDF		900	600	AB-HMSM
nter and CPU shelf	660	410	685	AB-PCSH
derbench roll holder, full width		1800		AB-URH
derbench roll holder, half width		900		AB-HURH

Drawers and Cupboards

Lockable drawer and cupboard units bolt to the underside of the workbench frame, using captive nuts fitted to every frame, so they can be fitted or changed at any time. Cupboards have one fixed steel shelf. Supplied loose for simple on-site assembly.

All above bench accessories and cupboard and drawer carcass:

Light Grey epoxy

Red

Blue

Drawer fronts and doors available in choice of: (Blue supplied if none specified)

Dark Grey

	Below bench accessory	H x W x D mm	Left fitted Order Ref	Right fitted Order Ref
А	Single drawer	140 × 410 × 430	LA	RA
в	2 drawer unit	280 x 410 x 430	LE	RE
С	3 drawer unit	420 x 410 x 430	LH	RH
D	4 drawer unit	560 x 410 x 430	LK	RK
Е	Small cupboard	420 × 410 × 430	LC	RC
F	Large cupboard	560 x 410 x 430	LD	RD
G	Single drawer + small cpbd	560 x 410 x 430	LG	RG
	Retaining skirt	100mm high steel back	-	RS







Adjustable Height Packing Bench

Redhill's modular packing station. Customise your packing operation and maximise your working and storage space with our new adjustable height work bench.

Build to your requirements including carton dividers, wrapping dispenser bars, PC monitor panels, Electrical points and other accessories.

All powder coated finished with a choice of laminate, Anti-Static or MDF worktops.

Worktop Thickness

А

D

F G

Laminate: 20mm Anti-static Laminate: 20mm MDF: 18mm

Height and Worktop Options

		Standard Worktop Material	S	
Description	Overall H x W x D mm	Laminate Order Ref		MDF Order Ref
Adjustable Height Workbench	840 to 1140 x 1800 x 750	AB8-LA	AB8-ALA	AB8-M

Above Workbench Accessories



	Description	Overall	H x W x	D mm	Order Ref
А	Pair of accessory outer bench posts	1260mr	1260mm above bench		AB-P
В	A central accessory post			AB-CP	
С	Formed sheet divider	300		300	AB-SDIV
	Full width tool panel	450	1800		AB-RTP
D	Half width tool panel	450	900		AB-HRTP
	Full width louvre panel	450	1800		AB-RLP
	Half width louvre panel	450	900		AB-HRLP
Е	Half width monitor mounting panel	450	900		AB-HMP
	Full width post mounting service duct		1800		AB-FPSD
F	Half width post mounting service duct		900		AB-HPSD
	Worktop mounted service duct		1800		AB-RSD
	Full width flush shelf c/w divider holes		1800	300	AB-TSS
	Full width angled shelf, lipped front		1800	300	AB-ATSS
G	Half width flush shelf c/w divider holes		900	300	AB-HTSS
н	Half width angled shelf, lipped front		900	300	AB-HATSS
	Back stop for shelf		1800		AB-BST
L	LED Batten to fit under shelf		1220		AB-LED
	Label printer shelf		200	300	AB-LAB
	Monitor arm				AB-MON

·E

154 Adjustable Height Packing Bench

SDL

Redditek

154

Adjustable Height Packing Bench



Britain



	Description	Overall	H x W x	D mm	Order Ref
A	Full width lower shelf, laminate		1800	600	AB-LSLA
в	Full width middle shelf, laminate		1800	600	AB-MSLA
с	Half width lower shelf, laminate		900	600	AB-HLSLA
	Half width middle shelf, laminate		900	600	AB-HMSLA
	Full width lower shelf, anti-static laminate		1800	600	AB-LSALA
	Full width middle shelf, anti-static laminate		1800	600	AB-MSALA
	Half width lower shelf, anti-static laminate		900	600	AB-HLSALA
	Half width middle shelf, anti-static laminate		900	600	AB-HMSALA
	Full width lower shelf, MDF		1800	600	AB-LSM
	Full width middle shelf, MDF		1800	600	AB-MSM
	Half width lower shelf, MDF		900	600	AB-HLSM
	Half width middle shelf, MDF		900	600	AB-HMSM
D	Printer and CPU shelf	660	410	685	AB-PCSH
	Underbench roll holder, full width		1800		AB-URH
Е	Underbench roll holder, half width		900		AB-HURH

Drawers and Cupboards

Lockable drawer and cupboard units bolt to the underside of the workbench frame, using captive nuts fitted to every frame, so they can be fitted or changed at any time. Cupboards have one fixed steel shelf. Supplied loose for simple on-site assembly.

All above bench accessories and cupboard and drawer carcass:

Light Grey epoxy

Red

Blue

Drawer fronts and doors available in choice of: (Blue supplied if none specified)

Dark Grey

	Below bench accessory	H x W x D mm	Left fitted Order Ref	Right fitted Order Ref
А	Single drawer	140 × 410 × 430	LA	RA
в	2 drawer unit	280 x 410 x 430	LE	RE
С	3 drawer unit	420 x 410 x 430	LH	RH
D	4 drawer unit	560 x 410 x 430	LK	RK
Е	Small cupboard	420 × 410 × 430	LC	RC
F	Large cupboard	560 x 410 x 430	LD	RD
G	Single drawer + small cpbd	560 x 410 x 430	LG	RG
	Retaining skirt	100mm high steel back	-	RS





Redditek

Adjustable Height Packing Bench

Adjustable Height Packing Bench

155

Extra Heavy Duty Workbench

Extra Heavy Duty Workbench

Strong, fully welded, steel construction makes these versatile workbenches suitable for the toughest of applications. Standard height 840mm (750 & 900mm available at no extra cost). Fully welded construction. Heavy Duty: 50 x 50mm steel angle.

Finish: Dark grey RAL7031

Choice of worktops and range of accessories provides the best combination for your requirements.

Worktop Thickness

Laminate: 20mm Lino: 20mm MDF: 18mm Steel: 3mm Stainless: 20mm



H8-S

	Standard Worktop Materials					
Overall H x W x D mm	Laminate Order Ref		MDF Order Ref		Stainless Order Ref	
840 x 600 x 1200	H1-LA	H1-V	H1-M	H1-S	H1-SS	
840 x 750 x 1200	H2-LA	H2-V	H2-M	H2-S	H2-SS	
840 x 900 x 1200	H3-LA	H3-V	H3-M	H3-S	H3-SS	
840 x 600 x 1500	H4-LA	H4-V	H4-M	H4-S	H4-SS	
840 x 750 x 1500	H5-LA	H5-V	H5-M	H5-S	H5-SS	
840 x 900 x 1500	H6-LA	H6-V	H6-M	H6-S	H6-SS	
840 x 600 x 1800	H7-LA	H7-V	H7-M	H7-S	H7-SS	
840 x 750 x 1800	H8-LA	H8-V	H8-M	H8-S	H8-SS	
840 × 900 × 1800	H9-LA	H9-V	Н9-М	H9-S	H9-SS	

Extra Lower Steel Shelf

Thickness: 1.5mm

Overall H x W x D mm	Order Ref
840 × 600 × 1200	HLS1
840 x 750 x 1200	HLS2
840 × 900 × 1200	HLS3
840 × 600 × 1500	HLS4
840 x 750 x 1500	HLS5
840 x 900 x 1500	HLS6
840 x 600 x 1800	HLS7
840 x 750 x 1800	HLS8
840 × 900 × 1800	HLS9
	11200

Easy Order Workbenches

E7 workbench complete with 1 drawer and 1 cupboard.

E11 workbench complete with 3 side retaining skirt, lower shelf, 2 drawer unit and 1 cupboard



Max Load

750kg

Made in

Britain

Overall H x W x D mm	MDF Worktop Order Ref	
840 x 750 x 1200	E7H4	E11H4
840 x 750 x 1500	E7H5	E11H5
840 x 750 x 1800	E7H6	E11H6



156 Extra Heavy Duty Workbench

Extra Heavy Duty Workbench Accessories

Choose your selection of accessories for extra heavy duty workbenches. Add the reference numbers to that of your selected bench. All accessories are factory fitted, so must be ordered with workbench (no retro fit)

Above Workbench



ΕV



RS3



Description	Size mm	Left Fitting Order Ref
	1200	RSD-4
Rear service duct with 2 x 13amp sockets	1500	RSD-5
	1800	RSD-6
Rear Only Retaining Skirt		RS1
3 Sided Retaining Skirt		RS3
Vice plate	3 x 230 x 230	VP
100mm engineering vice c/w vice plate and bolts		EV

Below Workbench



Description	Overall H x W x D mm	Left Fitting Order Ref	Right Fitting Order Ref
1 Drawer	140 × 410 × 430	LH-11	RH-11
2 Drawers	280 x 410 x 430	LH-13	RH-13
3 Drawers	420 × 410 × 430	LH-14	RH-14
1 Cupboard	600 x 410 x 430	LH-12	RH-12
1 Drawer and 1 Cupboard	560 × 410 × 430	LH-15	RH-15



Redditek

Extra Heavy Duty Workbench 157 TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Infinite Modular Workbench System

Heavy duty modular design. Unit accessible from both sides for two people working together. Framework is constructed from fabricated steel section with welded leg supports and bolt in multi-position cross rails which can be assembled in a variety of combinations to suit individual applications. Max Load Made in 1000kg Britain

Adjustable height from 840 - 940mm in 25mm increments Choice of MDF, Lino and Laminate worktop options. Worktop Thickness: 25mm Base shelf supplied in 18mm plain cut MDF irrespective of finish of top shelf



Use starter and extension method to mix and match depths

Description	Overall H x W x D mm	Standard Worktop Materials		
Description		MDF Order Ref		Lino Order Ref
Starter	940 x 700 x 2000	IM1-M	IM1-LA	IM1-V
Starter and base	940 x 700 x 2000	IM1-MBS	IM1-LABS	IM1-VBS
Starter	940 x 1200 x 2000	IM2-M	IM2-LA	IM2-V
Starter and base	940 x 1200 x 2000	IM2-MBS	IM2-LABS	IM2-VBS
Starter	940 x 1400 x 2000	ІМЗ-М	IM3-LA	IM3-V
Starter and base	940 x 1400 x 2000	IM3-MBS	IM3-LABS	IM3-VBS
Starter	940 x 700 x 3000	IM4-M	IM4-LA	IM4-V
Starter and base	940 x 700 x 3000	IM4-MBS	IM4-LABS	IM4-VBS
Starter	940 x 1200 x 3000	IM5-M	IM5-LA	IM5-V
Starter and base	940 x 1200 x 3000	IM5-MBS	IM5-LABS	IM5-VBS
Starter	940 x 1400 x 3000	IM6-M	IM6-LA	IM6-V
Starter and base	940 x 1400 x 3000	IM6-MBS	IM6-LABS	IM6-VBS
Add-on	0407002000	IM7-M	IM7-LA	IM7-V
Add-on and base	940 x 700 x 2000	IM7-MBS	IM7-LABS	IM7-VBS
Add-on	040 x 1200 x 2000	IM8-M	IM8-LA	IM8-V
Add-on and base	940 x 1200 x 2000	IM8-MBS	IM8-LABS	IM8-VBS
Add-on	940 x 1400 x 2000	IM9-M	IM9-LA	IM9-V
Add-on and base	940 x 1400 x 2000	IM9-MBS	IM9-LABS	IM9-VBS



150

Infinite Modular Workbench System

158 Infinite Modular Workbench System

159

Extension Benches

Then use add on workbenches as required to create a run with infinite combinations. Each extension has an MDF Worktop

We can modify a standard model or custom build to your own specifications - please call for details.

size benches to form combinations



Description	Overall H x W x D mm	Order Ref
3 Drawers, 1 Cupboard with Base Shelf and Leg Socket	940 × 700 × 2000	IM-EOB1
Combined Cabinet & Drawer Unit with Base Shelf	940 x 1200 x 3000	IM-EOB2
Top Shelf		IM5-M
Top Shelf and Base Shelf		IM5-MBS

Combine with easy to add bench accessories

Description	Order Ref
Cupboard Unit	RC / LC
Single Drawer	RA / LA
Two Drawer	RE / LE
Three Draw	RH / LH
Cupboard / Drawer	RG / LG
2000mm Upper Shelf	US2000
3000mm Upper Shelf	US3000
2000mm Service Duct	RSD20
3000mm Service Duct	RSD30

Optional extras 13 Amp Socket Ref: SRDSO





Workbench Accessories



Data Sockets & Cable Outlets

Data Sockets

Double or quadruple CAT 5e data sockets fitted to relevant rear service duct. Please state position required.

Brush Cable Outlets

Single or double width brush cable outlets to allow continuous cables to be wired through the rear service duct. Brush design stops debris getting into the ducting. Fitted to the relevant service duct. Please state position required.

Through Desk Cable Tidy

Grey plastic through desk cable tidy. Please state position required.

Description	Ref
Single Data Socket	RSD-CAT2
Double Data Socket	RSD-CAT4
Single Width Brush Cable Outlets	RSD-BR2
Double Width Brush Cable Outlets	RSD-BR4
Through Desk Cable Tidy	CA-DTID









Rear Service Duct Optional Extra's

Single Phase Blue Socket

Single phase 16 amp blue socket fitted to the relevant rear service duct. Please state position required.

Circuit Breaker

25 amp type AC residual current circuit breaker fitted to the relevant rear service duct. Please state position required.

Double Safety Socket

Double 13 amp safety socket. 30mA trip current. Replaces one of the current double sockets supplied with the rear

Additional Double Socket

Factory fitted to rear service duct. Position required with order.

USB Socket

USB socket, factory fitted to rear service duct. Position required with order.

Description	Ref
Single Phase Blue Socket	RSD-SPB
Circuit Breaker	RSD-RCD
Double Safety Socket	RSD-SS
Additional Double Socket	RSD-DS
USB Socket	SD-USB



0 Workbench Accessories

SDL

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

Tool Hooks

Range of tool hooks and holders for use with tool panels (tools not included).















CP11

CP3

CP7



Description	Size: Length mm	Ref
	30	CP1-30
Single Hook	60	CP1-60
	90	CP1-90
Double Hook	30	CP2-30
	60	CP2-60
Single Angled Lleek	30	CP3-30
Single Angled Hook	60	CP3-60
Pliers Holder	17	CP4-17
	20	CP4-20

Description	Size: Diameter mm	Ref
	12	CP5-12
Spring Clip	18	CP5-18
	24	CP5-24
Pipe Holder	30	CP6-30
Pipe Holdel	50	CP6-50
Drill Bit Holder (22 bit capacity)		CP7-22
Drill Holder (2 hook pack)		CP8-02
Spanner Holder (8 slot) Can Holder	N/A	CP9-08
	IV/A	CP10-01
Angle Grinder Holder		CP11-01
Hammer Holder		CP12-01

Redditek

·E

SDL

Workbench Accessories

161

TEL:01446772614 www.storage-design.ltd.uk info@storage-design.ltd.uk

CP4

CP8

CP12

Workbench Accessories

Product Index

Product	Page No.
Access Equipment	
British Standard Steps	6-14
Mobile steps	8-24
Narrow Steps	9, 21
Premier Commercial Steps	10, 22
Static steps	15-16
Stainless Steel Steps	18
Step Tray Trolleys	26-27
Access Platform	108
Acid Storage Cabinets	133
Balance Wheel Trucks	106
Bar and Pipe	
Racking & trolleys	52-55
Barriers	119-121
Beam Trolley	52
Bin Cabinets	
Steel	142-143
Bins	
Hazardous	129-133
Bin Cabinets	140-143
Skip bins	88
Recycling bins	126-127
Book Trolleys – Library & Office	111
British Standard Safety Steps	6-14
Cage Construction	
Trucks and trolleys	38-43
Trailers	76-78
Chairshifters	115
Chemical Storage Cabinets	129-133
Container Trucks	106-107
Containers	
Attached lid	102
Euro	102
Louvre	103
Coshh Cabinets	132
Cupboards	
Bin - shelf and louvre	140
СВ	141
Euro system	138-139
First aid	134
Louvre	138-140
Mesh door	137
Polycarbonate door	136
PPE	135
Stainless steel	128-129
Wall	134, 136
Workshop	138-139

Product	Page No.
Cylinder Handling	
(Cradles, racks, stands	64-73
and trolleys)	
Dollies	
Chair	112
Drum	60
Euro	102
Drawer Cabinets	
Static	142-145
Drum Handling	
(Clamps, dollies, levers, lifters,	56-63
pallets, trucks, racking, stands,	
tines, sump systems)	
Electric Sack Trucks	
Euro	
Containers	102
Cabinets	138-139
First Aid Cabinets	134
Flammable Storage Cabinets	129-130
GoodsMan Sack Trucks	80-87
Hazardous Storage	0007
Acid	133
Chemical	129-133
Flammable	129-130
Pesticide	131
Keg Trolley	68
Library Equipment	00
Book trolleys	111
Steps	8-27
Long Load Equipment	0-27
(Buggies, platform trucks,	52-55
beam trolley and trailers)	52-55
Louvre Panels - mobile and wall	103-104
Mesh Door Cabinets	137
Mesh Panel Platform Trucks	44, 46, 49-51
Mobile Steps	8-24
Mobile Tray Racks	97-100
Multi-Trip Containers and Trolleys	105
Order Picking	105
Step tray trolleys	23-24, 26-27
Oxygen Trolleys	23-24, 20-27 71
Pallets	71
Drum	57, 61
Parcel Trucks	36
Parcel Trucks Pesticide Storage Cabinets	36 131
Platform	131
Trucks	4451
Trailers	74-79
Access Platform	108

SDL ~ TRADER ~ 2025 'B'

Product	Page No.
Plastic Container Systems	97-107
Polycarbonate Door Cabinets	136
Racking Protection	117
Racks	117
Bar, pipe and plate	52-54
Drum	56-63
Tray mobile racks	97-100
Recycling Bins	126-127
Rolling Corners	109
Sack Trucks	100
Electric	80-87
Stainless steel	88
3 Position	90
Rough Terrain	91
Splay Back	92
Stairclimbers	93
Telescopic	94-95
Shelf Trucks	38-39
Sheet Handling	
Trucks and racks	52-54
Skip	96
Small Parts	
Racks and containers	97-98
Bin cabinets	140, 142-145
Drawer cabinets	144-145
Snow Ploughs	122-123
Stainless Steel	
Steps	18
Trucks	49
Cylinder	64
Cupboards	128-129
Sack trucks	88
Stairclimbing Chair Shifter	115
Stairclimber Sack Truck	95
Stanchion Truck	36
Step Tray Trolleys	26-27
Steps – Static and Mobile	8-24
Handlock anchorage	11, 14, 24
Storage Cages	
Trolleys	38-43
Cylinder	73
Trailers	74-79
Straps – Load Retaining	89, 93
Sumps	64.60
Drums	61-63
Hazardous cabinets	129-133
Tables – Mobile	00.00
Tray Trolleys	89-92
Heavy duty and workshop	148, 152
Tall Cabinet System	138-139
Tool Panels	27
Trolley Cabinets	37 138-139
Cabinets Tool Hooks	138-139
Trailers	101
Turntable Trailers	74-77
Mesh sides	77-78
Ackerman	77-78
Towing Trailers	78
Tray Trolleys and Trucks	30-35
hay noncys and nucks	00 00

Product	Page No.
Trolleys	
Low Cost	31
Cupboard	35
Industrial	33
Stainless steel	49
Keg	68
Folding Box Trolley	80
Book	111
Wall Cupboards	134, 136
Workbenches	
Standard	148, 152
Height Adjustable	150, 154
Heavy Duty	156-157
Infinite Modular	158-159
Accessories	160-161
Waste Management	
Skip Bin	96
Recycling Bins	126-127
Workshop Equipment	
Cylinder racks and stands	64-66
Welder's trolley	68
Store and distributor trolleys	105
Table trucks – heavy duty	34
Tray trolleys – heavy duty	32-33
Zinc	
Picking Trolley	40-41
Platform Truck	51

Mobile Steps	6 - 29
Trucks & Trolleys	30 - 51
Plate & Sheet Handling & Storage	52 - 55
Drum Storage & Handling	56 - 63
Cylinder Storage & Handling	64 - 73
Trailers	74 - 79
Sack Trucks & Stairclimbers	80 - 96
Plastic Container Systems	97 - 107
Access Platform & Roller Platforms	108 - 109
Book Trolleys & Chair Handling	110 - 115
Racking Protection & Warehouse Barriers	116 - 121
Snow Ploughs	122 - 123
Recycling Bins	124 - 127
Cabinets / Drawer Systems & Shelving Units	128 - 145
Workbenches & Accessories	146 - 161





We reserve the right to alter designs and specifications without prior notice. All technical data, dimensions, weights etc. stated in this catalogue serve only as a guide. The seller cannot accept any liability which may be attributed in any way to the use of this information. All goods are sold strictly in accordance with our terms and conditions of sale, details are available on request.

Storage Design Limited