

CAMBRIDGE

INDOOR




4214  
STORMY




4204  
WOODBINE




4205  
PRAIRIE



4213  
SEQUOIA



4203  
MUSLIN



4212  
IRON




4202  
FOG



4201  
NAVAJO



4207  
CALIENTE




4210  
CAVE




4209  
WAYLAN



4206  
BASIL



4208  
BRIDLE



4211  
BISON

**CHARACTERISTICS****INDOOR**

Composition:	Topcoat : 72,3% PVC, 6,7% PU
Backing:	21% Polyester
Weight:	760 gr/m <sup>2</sup>
Roll Width:	min. 137 cm
Roll Length:	+/- 30 m
Abrasion:	>100.000 cycles (MARTINDALE)
Accelerated-ageing tests:	(Tropical test ISO 1419): week 7: No cracking, peeling, or delamination
Light fastness:	>6 EN ISO 105B02 (Blue Wool Scale)
Colour fastness to	
Rubbing (dry):	4-5 EN ISO 105X12:2002 (Blue Wool Scale)
Rubbing (wet):	4-5 EN ISO 105X12:2002 (Blue Wool Scale)
Flame retardancy*:	US UFAC Class 1 US NFPA 260 US CAL TB 117-2013, Section 1: PASS US ASTM E1353-08ae1: PASS class 1

\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behaviour of this or any other material under actual fire conditions.

**SUSTAINABILITY**

REACH | RoHS

**CARE AND CLEANING**

For optimum care and cleaning please read the following instructions and recommendations.

**Disinfectant Use**

For leather surface, use 1:250 mix of 84(NaClO) and water.

Rinse the area with clean water, then dry with a clean, lint-free cloth after using any disinfectants and cleaners.

**Cleaning after Disinfection:**

The coated fabric should be cleaned periodically in order to maintain its appearance and prevent build-up of dirt and contaminants. Any stain, spills, or soiling should be cleaned up immediately to prevent the possibility of permanent staining.

Use a mixture of 1:1 liquid soap (neutral pH) and water or our approved cleaning products for coated fabrics to remove stains on the surface of the material. Completely remove excess cleaner with a white, clean, damp cloth; and dry the surfaces afterwards. Lacquers, strong cleaners, detergents, bleach, xylene-based solutions, acetone, or ketone (MEK) cause immediate damage and contribute to the deterioration of the material. The use of such cleaners is at the owner's risk.

**Cleaning methods to remove tougher stains**

**Step 1:** Coffee, juice, red wine, sauces, chocolate, grease, crayon and suntan lotion. Remove excess spill with a damp cloth. Clean with a 1:1 mix of neutral liquid soap and water. Next, rinse with clean water and dry.

**Step 2:** Make-up. Use a straight application of neutral PH soap. Wipe with a clean white cloth or soft brush, rinse with clean water, and dry.

**Step 3:** Blood, urine, faeces and all other tough stains. Use a 1:10 mix of Isopropyl alcohol and water. Rinse thoroughly with clean water and dry.

For cleaning: use a soft white cotton cloth saturated with the recommended cleaning agent and rub the stain in random circles, ten times or more. Pat dry with another soft white cotton cloth and check the results. Do not use steel bristle brushes, abrasive scouring pads or metal, these cause permanent damage to the fabric. Methods 2 & 3 are not recommended for everyday cleaning! After cleaning, rinse the area with clean water, then dry with a clean, lint-free cloth. Failure to remove chemical residue will cause discolouration of the coated fabric surface to manifest itself earlier in the life cycle of the product.

**SAMPLES AND ENQUIRES**

samples: [samples@vyvafabrics.nl](mailto:samples@vyvafabrics.nl) | orders: [info@vyvafabrics.nl](mailto:info@vyvafabrics.nl)

**VYVA**  
FABRICS



FLAME  
RETARDANT



HARD  
WEARING



WATER  
RESISTANT



SOFT



REACH  
COMPLIANT



INDOOR

[INFO@VYVAFABRICS.NL](mailto:INFO@VYVAFABRICS.NL)

[WWW.VYVAFABRICS.NL](http://WWW.VYVAFABRICS.NL)

TEL +31 (0)20 6599523