

# TIP SHEET

for the installation of a play structure with poured concrete anchoring and in bulk protective surfacing material.

- 1** Check the condition of pallets on receipt: pre-identify your products through the packaging film. Unpack products gradually as the job progresses.
- 2** Using the layout plans, mark out the future play area.  
*(The play area)*
- 3** Lay out the play area using stakes, string lines or spray paint.
- 4** Excavate to the depth indicated on the plan, and level the bottom of the play area. *(Make sure your site is well drained to ensure the product's longevity.)*
- 5** If you install the peripheral borders at this stage, plan to leave a section open to still be able to bring heavy materials to the play area.
- 6** Working in accordance with the plan, after orienting it correctly, mark the position of each post and its corresponding number on the bottom of the play area.
- 7** Excavate the holes for the posts, usually using an auger. Lay out the geotextile membrane and cut it at each post hole.
- 8** Place the numbered posts in the holes you made in the ground, following their position and orientation.
- 9** Place the platforms on the posts, following the assembly plan and using the proper hardware provided. Do not over-tighten, as the final tightening will take place at the very end.  
*(Small tip for the hardware: you can sort it by size into individual boxes and write down the size on each box. Once labelled, fewer mistakes are possible.)*
- 10** Continue assembling the play components according to plans, such as fences, railings, roofs, etc.
- 11** Once the play structure is assembled, check that the final positioning is correct and make any necessary adjustments. At the same time, check your protective surfacing zones. *(Around the play structure, from another play structure, slide exit, etc.)*
- 12** If everything is in accordance with the plan, you can now proceed with the final tightening. Try to do this one section at a time, so as not to forget anything. Ideally, have another of your teammates carry out a second tightening check.
- 13** You can now proceed to pour the concrete.
- 14** Before laying down the protective surfacing material, make sure the perimeter of borders is correctly positioned and complete.
- 15** A clean and tidy jobsite can prevent many falls and injuries. Sort and collect waste as you go. Sort properly depending on materials to be recycled.

## Important

The hardware is counted and sorted for each play structure.

