

GEL

READY-TO-USE & NON-SPILLABLE




TECHNOLOGY

The **GEL** range is engineered to deliver maximum performance and safety. **Ready-to-use** straight from the box, these batteries require **no acid handling, initial preparation, or maintenance.**

Thanks to their non-spillable VRLA design and **high-performance** capabilities, GEL batteries are the perfect choice for all powersports applications, combining reliability, convenience, and peace of mind for every rider.

FEATURES

- » **Ready-to-use:** factory activated for immediate use
- » **100% maintenance-free:** no refilling required
- » **Non-spillable (VRLA):** safe to ship and handle
- » **Multi-positional fitment:** up to 90°
- » **Extended service life:** designed for long-lasting reliability



COMPATIBLE CHARGERS

- » **Fulload 1000:** battery capacity up to 20Ah
- » **Fulload F4:** battery capacity up to 80Ah
- » **Fulload F10:** battery capacity up to 200Ah
- » **Fulbank F2:** battery capacity up to 40Ah

DESIGNATION	P/N	VOLTAGE (V)	CAPACITY Ah (10hr)	CAPACITY Ah (20hr)	CCA (A)	DIMENSIONS (+/- 2 mm)			POLARITY	TERMINAL
						L	W	H		
6N4-2A/A-4	550959	6	4	4.2	25	71	71	93		-
6N6-3B/B-1	550960	6	6	6.3	50	95	55	117		
B49-6	550961	6	10	10.5	80	91	83	159		
B38-6A	550962	6	13	13.7	105	119	83	161		
6N11A-1B/3A	550957	6	11	11.6	90	121	58	130		
6N11A-4A	550958	6	11	11.6	90	121	58	130		
12N5.5-3B	550980	12	5.5	5.8	70	135	60	130		
12N5.5-4A/4B	550981	12	5.5	5.8	70	135	60	130		
FB3L-A/B	550842	12	3	3.2	35	98	56	110		
FB4L-B	550916	12	5	5.3	50	120	70	92		
FB5L-B	550991	12	5	5.3	65	120	60	130		
FB7-A	550992	12	8	8.4	120	135	75	133		
FB7C-A	550989	12	8	8.4	85	129	89	114		
FB7L-B/B2	550995	12	8	8.4	100	136	76	130		
FB9-B (12N9-4B-1)	550925	12	9	9.5	115	135	75	139		
FB10L-A2/B2	550956	12	11	11.6	120	133	90	145		
FB12A-A/B (12N12A-4A-1)	550947	12	12	12.6	155	134	80	161		
FB12AL-A2	550926	12	12	12.6	150	134	80	161		
FB14A-A2	550971	12	14	14.7	200	134	88	176		
FB16AL-A2	550948	12	16	16.8	210	205	70	162		
FT4B-BS	550949	12	2.3	2.4	40	113	38	85		
FTR4A-BS	550950	12	2.3	2.4	45	113	48	85		
FTX4L-BS/FTZ5S	550671	12	5	5.3	70	113	70	85		
FTX5L-BS/FTZ6S	550919	12	5	5.3	90	113	70	105		
FTX6.5L-BS	550963	12	6.5	6.8	85	147	73	112		
FTX7L-BS	550920	12	6	6.3	100	113	70	130		
FTX7A-BS	550915	12	6	6.3	90	150	87	93		
FTX9-BS	550921	12	8	8.4	135	150	87	105		
FT12A-BS	550679	12	10	10.5	175	150	88	105		
FTX12-BS	550922	12	10	10.5	180	150	87	130		
FTX14-BS	550923	12	12	12.6	200	150	87	145		
FTX14L-BS	550990	12	12	12.6	200	150	87	145		
FTX14AH-BS/FB14-A2/B2 (12N14-4A)	550946	12	14	14.7	210	135	90	167		
FTX14AHL-BS/FB14L-A2/B2 (12N14-3A)	550927	12	14	14.7	210	135	90	167		
FTX16	550763	12	14	14.7	230	150	87	161		
FTX20-BS	550993	12	18	18.9	310	175	87	155		
FTX20A-BS	550994	12	18	18.9	270	150	87	161		
FTX20HL-BS	550924	12	18	18.9	310	175	87	155		
FTX24HL-BS/F50-N18L-A/A2/A3 (12N18-3A)	550982	12	21	22.1	350	205	87	162		
FIX30L-BS	550943	12	30	31.6	400	165	125	175		
FTZ7S	550635	12	6	6.3	130	113	70	105		
FT7B-4	550641	12	6.5	6.8	110	150	65	93		
FTZ7V	550998	12	6.5	6.8	105	113	70	121		
FTZ8V	550918	12	7	7.4	120	113	70	130		
FT9B-4	550642	12	8	8.4	120	150	68	105		
FTZ10S	550636	12	8.6	9.1	190	150	88	93		
FTZ12S	550637	12	11	11.6	210	150	88	110		
FT12-10Z	550999	12	10	10.5	180	194	59	112		
FT12B-4	550643	12	10	10.5	210	150	69	130		
FTZ14S	550638	12	11.2	11.8	230	150	88	110		
FT14B-4	550644	12	12	12.6	210	150	69	145		
NH12-20 (BMW)	550917	12	20	21.1	250	186	82	171		
53030 (F60-N30L-A)	550945	12	30	31.6	325	184	124	170		
53034 (F60-N30-A)	550843	12	30	31.6	325	184	124	170		

HIGH PERFORMANCE & VIBRATION RESISTANCE




TECHNOLOGY

The **GEL FitHD** range features high-capacity batteries designed for **heavy-duty** applications. With Harley-Davidson compatible terminals and a **reinforced battery case**, these batteries deliver superior vibration resistance and **enhanced starting power**, ensuring reliable performance even in the most demanding conditions.

FEATURES

- » **Ready-to-use:** factory activated for immediate use
- » **100% maintenance-free:** no refilling required
- » **Non-spillable (VRLA):** safe to ship and handle
- » **Multi-positional fitment:** up to 90°
- » **HD specific terminals:** designed for perfect fit on Harley and other heavy-duty bikes
- » **Reinforced case:** extra durability for extreme conditions
- » **Extended service life:** designed for long-lasting reliability



COMPATIBLE CHARGERS

- » **Fulload 1000:** battery capacity up to 20Ah
- » **Fulload F4:** battery capacity up to 80Ah
- » **Fulload F10:** battery capacity up to 200Ah
- » **Fulbank F2:** battery capacity up to 40Ah

DESIGNATION	P/N	VOLTAGE (V)	CAPACITY Ah (10hr)	CAPACITY Ah (20hr)	CCA (A)	DIMENSIONS (+/- 2 mm)			POLARITY	TERMINAL
						L	W	H		
FHD14HL-BS	550880	12	14	14.7	220	150	87	145		
FHD20HL-BS	550881	12	20	21.1	310	175	87	155		
FHD32HL-BS	550874	12	32	33.6	445	165	130	175		

HIGH CYCLING CAPABILITY & RELIABLE BACK-UP POWER




TECHNOLOGY

The **AUXILIARY** range is specifically engineered for **Start-Stop** automotive applications. Featuring a non-spillable, maintenance-free AGM design, these batteries deliver **enhanced cycling capability** and provide the reliable power needed to run onboard electronics and vehicle management systems efficiently and safely.

FEATURES

- » **AGM technology:** advanced design for reliable performance
- » **Ready-to-use:** factory activated for immediate use
- » **100% maintenance-free:** worry-free operation
- » **Non-spillable (VRLA):** safe to ship and handle
- » **Extended service life:** higher cycle resistance, up to 3x longer



COMPATIBLE CHARGERS

- » **Fulload 1000:** battery capacity up to 20Ah
- » **Fulload F4:** battery capacity up to 80Ah
- » **Fulbank F2:** battery capacity up to 40Ah

DESIGNATION	P/N	VOLTAGE (V)	CAPACITY Ah (10hr)	CAPACITY Ah (20hr)	CCA (A)	DIMENSIONS (+/- 2 mm)			POLARITY	TERMINAL
						L	W	H		
AUX9	550983	12	8	8.4	135	150	87	105		
AUX12	550984	12	10	10.5	180	150	87	130		
AUX14	550985	12	12	12.6	200	150	87	145		
AUX14J	550986	12	12	12.6	200	150	130	145		

UPGRADE CROSS REFERENCE CHART



BATTERY MODEL EQUIVALENTS

DRY	MF	GEL	LITHIUM
6N4-2A - 6N4-2A-4		6N4-2A/A-4	
6N6-3B - 6N6-3B-1		6N6-3B/B-1	
B49-6		B49-6	
B38-6A		B38-6A	
6N11A-1B - 6N11A-3A		6N11A-1B/3A	
12N5.5-3B		12N5.5-3B	
12N5.5-4A		12N5.5-4A/4B	
FB3L-A - FB3L-B		FB3L-A/B	
FB4L-B		FB4L-B	FLTX4L/5L/7L - FLTZ5S/6S/7S
FB5L-B - 12N5-3B		FB5L-B GEL	
12N7-4A - FB7-A		FB7-A	
FB7C-A		FB7C-A	
FB7L-B - FB7L-B2 - 12N7-3B		FB7L-B/B2	FLTX4L/5L/7L - FLTZ5S/6S/7S
FB9-B - 12N9-4B1	FT9A-BS	FB9-B	
FB10L-A2 - FB10L-B2 - 12N10-3A/B		FB10L-A2/B2	
FB12AL-A/A2		FB12AL-A2	
FB12A-A - FB12A-B - 12N12A-4A-1		FB12A-A/B	
FB14A-A1 - FB14A-A2		FB14A-A2	
FB16AL-A2		FB16AL-A2	
FB16CL-B		FB16CL-B	FLTX20HL
	FT4B-BS	FT4B-BS	
	FTR4A-BS	FTR4A-BS	
	FTX4L-BS/FTZ5S	FTX4L-BS/FTZ5S	FLTX4L/5L/7L - FLTZ5S/6S/7S
	FTX5L-BS	FTX5L-BS/FTZ6S	FLTX4L/5L/7L - FLTZ5S/6S/7S
	FTX7A-BS	FTX7A-BS	FLT7A/9 - FLTZ10S
	FTX7L-BS	FTX7L-BS	FLTX4L/5L/7L - FLTZ5S/6S/7S
	FTX9-BS	FTX9-BS	FLT7A/9 - FLTZ10S
	FT12A-BS	FT12A-BS	FLT12/14 - FLTZ12S/14S
	FTX12-BS	FTX12-BS	FLT12/14 - FLTZ12S/14S
	FTX14-BS	FTX14-BS	FLT12/14 - FLTZ12S/14S
	FTX14L-BS	FTX14L-BS GEL - FHD14HL-BS	
FB14-A2 - FB14-B2 - 12N14-4A	FTX14AH-BS	FTX14AH-BS / FB14-A2	
FB14L-A2 - FB14L-B2 - 12N14-3A	FTX14AHL-BS	FTX14AHL-BS / FB14L-A2	
	FTX16-BS	FTX16	FLT12/14 - FLTZ12S/14S
FB16-B	FTX20-BS	FTX20-BS	FLT20H
	FTX20A-BS	FTX20A-BS	FLT12/14 - FLTZ12S/14S
FB16L-B - FB18L-A	FTX20L-BS	FTX20HL-BS GEL - FHD20HL-BS	FLTX20HL
F50-N18L-A/A2 / 12N18-3A - F50-N18L-A3	FTX24HL-BS	FTX24HL-BS / F50-N18L-A/A2/A3	
FB30L-B	FIX30L-BS	FIX30L-BS GEL - FHD32HL-BS	FLTX30HL
		FTZ7V	FLTX4L/5L/7L - FLTZ5S/6S/7S
		FTZ7S GEL - FTZ8V	FLTX4L/5L/7L - FLTZ5S/6S/7S
		FT7B-4	FLT7B/9B
		FT9B-4	FLT7B/9B
		FTZ10S	FLT7A/9 - FLTZ10S
		FTZ12S	FLT12/14 - FLTZ12S/14S
		FT12B-4	FLT12B/14B
		FTZ14S	FLT12/14 - FLTZ12S/14S
		FT14B-4	FLT12B/14B
51814 - 51913		NH12-20	
F60-N30L-A - 53030		53030	FLTX30HL
F60-N30-A - 53034		53034	

Important: Before upgrading to Lithium, verify that the bike's voltage regulator limits output to 15V or less.

LITHIUM

Ready to use
High CCA performance
Ultra lightweight



GEL

Ready to use
100% maintenance free
Non-spillable



MF

100% maintenance free
Acid Pack included
Unlimited shelf life



DRY

DRY charged construction
Acid Pack included
Unlimited shelf life

