

# SELECT PRO WELD-IN DEADLOCK

## Specification Sheet **SWD**

### FEATURES

- Enhanced security: Stainless steel deadbolt extends 30mm into the gate post for secure hold.
- Precise fit: Adjustable deadbolt length ensures accurate on-site fitting.
- Maximum strength: Welding the lock into the gate offers the most secure installation method.
- Convenient access: Keyed on both sides for easy operation.
- Durable construction: Made with a 2.5mm steel lock case for long-lasting reliability.

### PRODUCT DETAILS

Product code	Description
SWD1630	For 30mm (1-1/8") wide gate frames
SWD1640	For 40mm (1-5/8") wide gate frames
SWD1650	For 50mm (2") wide gate frames
SWD1660	For 60mm (2-3/8") wide gate frames



### INCLUDED IN THE BOX

- 1x3mm hex key
- M5 fixing bolts
- Deadbolt
- Keep plate (self-drilling fasteners)
- A set of keys (3)

### INSTALLATION

1. Disassemble the lock by removing the 3 screws from the face plate of the lock, remove the face plate, and then remove the euro cylinder (twist the key 15 degrees clockwise or anti-clockwise to release). The insides of the lock will then slide out.
2. Weld the lockcase to the gate and galvanise or paint as part of the gate.
3. Fit the lock and eurocylinder into the lockcase and secure with screws.

**MAINTENANCE:** Every two months, lubricate the latchbolt with light oil. Annually, dismantle lock and spray the mechanism inside with light oil.

