

# HYOSUNG

# MX8200LV

## The Future of Enhanced Function, Recycling ATMs is Here.

The **MX8200LV** is a flexible, scalable recycling solution that is focused on creating differentiated branding and attainment programs for the financial institution. The **MX8200LV** offers customers more transaction types versus a traditional ATM: includes loan payments, streamlines branch transactions, and delivers quick and secure autonomously or with the assistance of branch staff. The **MX8200LV** was designed as an easy-to-use, reliable, and secure solution with the customer experience incorporated from the beginning.

## Features

---

### Highest Availability

Flexible support for delivering transactions through self-service or with the support of video. A footprint that enables placement in the area/space currently inhabited by a traditional ATM. A user interface specifically adapted to accommodate the full range of branch banking needs. Leverage a large 32" touchscreen format for elite marketing and an exception video banking experience. Availability is over 99%.

### Service

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment, and reduced downtime.

### Capacity

High capacity cash recycler capability and the ability to support multi-check function.

### Functionality

The **MX8200LV** provides for the delivery of an unparalleled range of transactions when deployed in conjunction with Hyosung's innovative integrated software approaches and powerful video assistance solutions. The hardware is enabled for supporting a wide range of transactions typically delivered in the branch.



## Specifications

### Dimensions (CEN-I base)

- Height: 1981mm (78")
- Width: 686mm (27")
- Depth: 1016mm (40")
- Weight: 704kg (1,552lbs)

### Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 25% – 85%

### System Platform

- Microsoft Windows® 10

### Customer Interface

- 32" customer interface monitor
- Input method – IR touch screen
- PIN pad – PCI complaint
- ADA audio guidance – earphone jack
- Card reader – EMV compliant, anti-skimming and anti-shimming included
- Contactless – Integrated reader (via card, smartphone or smartwatch)

### Media Handling

- **Cash Dispenser**
  - 4 Recycling + 1 Deposit cassette
  - Recycle up to 4 denominations with 2,850 notes per recycling cassette, and 2,000 notes in the deposit cassette
- **Cash & Check In Module (CCIM)**
  - 10 check insertion
  - Total check capacity - 350 checks\*

### Security

- Safe – UL291 Level-1
- Alarm – Seismic + Heat
- Locking Device – KABA Mas Cencon
- Sensor – Safety door sensor
- Security – Terminal block (external I/F)
- Camera
  - IP-camera 1st (face)
  - CCD camera 2nd (hand)

### Printer

- 3.1" graphical thermal receipt printer

### Servicing

- Rear access
- State of health indicators for all modules
- LCD supervisor panel

### Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

### Additional Features

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.