### **HYOSUNG**

# Cajera CR-E

### Cajera CR-E

Hyosung's latest TCR (Teller Cash Recycler) in the Cajera CR-E series is designed as the entry-level TCR model for Retailers seeking the most reliable and proven cash recycling technology while maximizing return on investment. The Cajera CR-E streamlines cashier productivity with TCR functionality previously unavailable in its class, leveraging the latest in TCR technology including stacked cassettes, high speed, capacity, and Windows 10 security.

#### **Features**

The 'Cajera' series, Spanish for 'cashier', embodies Hyosung's latest and most transformational TCR series designed for teller cash optimization and customer delight.

The Cajera CR-E is the entry-level cash recycler that provides cash automation efficiency to Retail locations that were previously seen as unfit for more expensive, higher-end cash recycling products.

- Designed for lower volume locations, such as Retail, where great customer service and experience are key.
- Priced economically while driving the core value proposition of improved cash automation puts the Cajera CR-E within reach of every Retail location.
- Delivers industry leading technology based on the proven and reliable MS500 technology, such as Win10 Core, 100% stacking cassette technology, speed of 8 notes per second, and 8,500 note total capacity.
- Leverage Cajera CR-E technology alone when cash volumes are low or pair with Hyosung's higher capacity MS500 when multiple cash recycling points of different capacities are needed.



## **HYOSUNG**

## Cajera CR-E

#### Standard Features

#### **Dimensions**

• Height: 695.00mm (27.4") under desk

Width: 428.0mm (16.85")Depth: 1,176.3mm (46.3")Weight: 420.1kg (926lbs)

#### **Environmental Conditions**

• Temperature 32F ~ 95F (5°C ~ 35°C)

• Humidity 25% - 85%

#### **System Platform**

Microsoft Windows 10°

#### **Customer Interface**

- 7" wide LCD with touch screen
- Display unit status, note counting and guidance messages
- · Error and jamming point display

#### **Media Handling**

- Individual deposit, dispense, and reject slots
  - Deposit and withdrawal up to 200 banknotes maximum
  - 30 note reject slot
- · Cash handling speed
  - Deposit 8 notes per second
  - Dispense 8 notes per second
  - Note counting only 8 notes per second
- 6 recycling cassettes plus 1 overflow/reject cassette
  - 6 small size recycling cassettes (1,000 nominal capacity)\*
  - 1 large overflow/reject cassette (2,850 nominal capacity)\*

#### Security

• Safe - UL291 Level-1

#### Servicing

Front access

#### **Power Supply**

• AC 100V~240V=10% 50/60Hz

#### **Additional Features**

- Communication TCP/1P
- In-use Button
- Counting Feature
- With note validation
- Without note validation
- Note serial number recognition
- Fitness sorting
- · Multi-channel communications

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



<sup>\*</sup>Subject to note quality and other variables