



JST

Other Connectors
(Including Headers)

MIH connector

1mm pitch

[Type]
Compression connector

[Current rating]
0.5A

[Voltage rating]
20V




Compression type connector developed for compact equipment such as mobile phone. *Compact Projected area is only 2.0 x 2.8mm, with 1.8mm height. *High contact pressure Despite its smallness, the contact provides contact pressure of 0.7N per circuit thanks to curled spring design, giving stable contact performance even under conditions of vibration.

BC header

2mm pitch

[Type]
Header



Headers for direct board-to-board connection, having 0.5mm square posts. *Available in two types, top entry type and side entry type.


2.5SB header

2.5mm pitch

[Type]
Header

[Current rating]
3A

[Voltage rating]
250V



Having 0.64mm square posts, the 2.5SB header can be used to connect any 2.5mm receptacles to PC boards. They can also be used to directly connect PC boards. *Available in two types, top entry type and side entry type.

TB header

2.5mm pitch

[Type]
Header

[Current rating]
3A

[Voltage rating]
250V



Having 0.64mm square posts, the TB header can be used to connect any 2.5mm receptacles to PC boards. They can also be used to directly connect PC boards. *Available in two types, top entry type and side entry type.


2.54SB header

2.54mm pitch

[Type]
Header

[Current rating]
3A

[Voltage rating]
250V



Having 0.64mm square posts, the 2.54SB header can be used to connect any 2.54mm receptacles to PC boards. They can also be used to directly connect PC boards. *Available in two types, top entry type and side entry type


JM connector

2.54mm pitch

[Type]
Jumper connector

[Current rating]
3A

[Voltage rating]
250V




Two-circuit jumper connector suited for changing or switching circuits on PC boards without using DIP switches. *This connector is stackable in both directions.

VS header

3.96mm pitch

[Type]
Header




Having 1.14mm square posts, the VS header can mate with a receptacle or as a connector for the direct interconnection of PC boards.*Available in two types, top entry type and side entry type.

BTT connector

[Type]
For a battery, Compression connector

[Current rating]
2A

[Voltage rating]
20V




Connector for batteries used in the compact mobile equipment such as mobile phones. The battery can be set with Off set 0mm.

BTT connector CM type

[Type]
For a battery, Compression connector

[Current rating]
2A


[Voltage rating]
20V



Connector for batteries used in the compact mobile equipment such as mobile router. The battery can be set with Off set 0mm.

PB connector

[Type]
Socket for a button battery



Connector for button batteries used in the compact mobile equipment such as mobile phones.