



PERIMETER PROTECTION IN ALL WEATHERS

Performance Series Thermal Bullet Cameras

KEY FEATURES



Video Content Analytics
with deep learning
algorithms to reduce false
alarms



Temperature exception alarm
with visualized smart warning



Vigilant smoking detection
helps to detect smoking
behaviors in the first place



Picture-in-picture preview
saves efforts on switching
between optical and thermal
channels

APPLICATION SCENARIOS



Villas



Communities



Car Dealerships



Factories



Parking Lots



Entrances



Warehouses



Substations

PARAMETERS



DS-2TD2117-3/V1
DS-2TD2117-6/V1

Performance Series Thermal Bullet Cameras

- Resolution:
 - Thermal: 160 x 120 @ 25 fps, 17 μ m (the resolution of the output image is 320 x 240)
 - Optical: 1920 x 1080 (DS-2TD2617 series only)
- Focal length:
 - Thermal: 3 mm / 6 mm
 - Optical: 4 mm / 6 mm (DS-2TD2617 series only)
- Hikvision sensor, NETD < 40 mk
- Video content analytics: Line crossing / Intrusion detection / Region entrance / Region exiting
- Temperature exception alarm (temperature measuring range: -20° to 150° C, accuracy: \pm 8° C)
- Smoking detection
- Supports bi-spectrum image fusion, picture-in-picture preview (DS-2TD2617 series only)
- Working temperature: -40° to 65° C (-40° to 149° F)
- IP67 ingress protection



DS-2TD2617-3/V1
DS-2TD2617-6/V1

Performance Series Thermal Bi-spectrum Bullet Camera



Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

